

Internet Engineering Task Force (IETF)
Request for Comments: 6945
Category: Standards Track
ISSN: 2070-1721

R. Bush
Internet Initiative Japan
B. Wijnen
RIPE NCC
K. Patel
Cisco Systems
M. Baer
SPARTA
May 2013

Definitions of Managed Objects for the
Resource Public Key Infrastructure (RPKI) to Router Protocol

Abstract

This document defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects used for monitoring the Resource Public Key Infrastructure (RPKI) to Router Protocol.

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc6945>.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	2
1.1. Requirements Language	2
2. The Internet-Standard Management Framework	2
3. Overview	3
4. Definitions	3
5. IANA Considerations	22
6. Security Considerations	22
7. References	23
7.1. Normative References	23
7.2. Informative References	24

1. Introduction

This document defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it defines objects used for monitoring the RPKI-Router Protocol [RFC6810].

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410]. Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB.

MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIv2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579], and STD 58, RFC 2580 [RFC2580].

3. Overview

The objects defined in this document are used to monitor the RPKI-Router Protocol [RFC6810]. The MIB module defined here is broken into these tables: the RPKI-Router Cache Server (Connection) Table, the RPKI-Router Cache Server Errors Table, and the RPKI-Router Prefix Origin Table.

The RPKI-Router Cache Server Table contains information about the state and current activity of connections with the RPKI-router cache servers. It also contains counters for the number of messages received and sent, plus the number of announcements, withdrawals, and active records. The RPKI-Router Cache Server Errors Table contains counters of occurrences of errors on the connections (if any). The RPKI-Router Prefix Origin Table contains IP prefixes with their minimum and maximum prefix lengths and the Origin Autonomous System (AS). This data is the collective set of information received from all RPKI cache servers that the router is connected with. The cache servers are running the RPKI-Router Protocol.

Two notifications have been defined to inform a Network Management Station (NMS) or operators about changes in the connection state of the connections listed in the RPKI-Router Cache Server (Connection) Table.

4. Definitions

The following MIB module imports definitions from [RFC2578], [RFC2579], [RFC2580], [RFC4001], and [RFC2287]. That means we have a normative reference to each of those documents.

The MIB module also has a normative reference to the RPKI-Router Protocol [RFC6810]. Furthermore, for background and informative information, the MIB module refers to [RFC1982], [RFC4252], [RFC5246], and [RFC5925].

```
RPKI-ROUTER-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,  
Integer32, Unsigned32, mib-2, Gauge32, Counter32  
    FROM SNMPv2-SMI -- RFC 2578
```

```
InetAddressType, InetAddress, InetPortNumber,  
InetAddressPrefixLength, InetAutonomousSystemNumber  
    FROM INET-ADDRESS-MIB -- RFC 4001
```

```
TEXTUAL-CONVENTION, TimeStamp  
    FROM SNMPv2-TC -- RFC 2579
```

```
MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP  
    FROM SNMPv2-CONF -- RFC 2580
```

```
LongUtf8String FROM SYSAPPL-MIB -- RFC 2287
```

```
;
```

```
rpkiRtrMIB MODULE-IDENTITY  
    LAST-UPDATED "201305010000Z"  
    ORGANIZATION "IETF Secure Inter-Domain Routing (SIDR)  
        Working Group  
    "  
    CONTACT-INFO "Working Group Email: sidr@ietf.org
```

```
        Randy Bush  
        Internet Initiative Japan  
        5147 Crystal Springs  
        Bainbridge Island, WA 98110  
        USA  
        Email: randy@psg.com
```

```
        Bert Wijnen  
        RIPE NCC  
        Schagen 33  
        3461 GL Linschoten  
        Netherlands  
        Email: bertietf@bwijnen.net
```

```
        Keyur Patel  
        Cisco Systems  
        170 W. Tasman Drive  
        San Jose, CA 95134  
        USA
```

Email: keyupate@cisco.com

Michael Baer
 SPARTA
 P.O. Box 72682
 Davis, CA 95617
 USA
 Email: baerm@tislabs.com

"

DESCRIPTION "This MIB module contains management objects to support monitoring of the Resource Public Key Infrastructure (RPKI) protocol on routers.

Copyright (c) 2013 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this MIB module is part of RFC 6945; see the RFC itself for full legal notices."

REVISION "201305010000Z"

DESCRIPTION "Initial version, published as RFC 6945."
 ::= { mib-2 218 }

rpkiRtrNotifications OBJECT IDENTIFIER ::= { rpkiRtrMIB 0 }
 rpkiRtrObjects OBJECT IDENTIFIER ::= { rpkiRtrMIB 1 }
 rpkiRtrConformance OBJECT IDENTIFIER ::= { rpkiRtrMIB 2 }

-- =====
 -- Textual Conventions used in this MIB module
 -- =====

RpkiRtrConnectionType ::= TEXTUAL-CONVENTION
 STATUS current
 DESCRIPTION "The connection type used between a router (as a client) and a cache server."

The following types have been defined in RFC 6810:

- ssh(1) - Section 7.1; see also RFC 4252.
- tls(2) - Section 7.2; see also RFC 5246.
- tcpMD5(3) - Section 7.3; see also RFC 2385.
- tcpAO(4) - Section 7.4; see also RFC 5925.
- tcp(5) - Section 7.
- ipsec(6) - Section 7; see also RFC 4301.
- other(7) - none of the above."

REFERENCE "The RPKI-Router Protocol, RFC 6810, Section 7"

SYNTAX INTEGER {
 ssh(1),
 tls(2),
 tcpMD5(3),
 tcpAO(4),
 tcp(5),
 ipsec(6),
 other(7)
 }

-- =====
 -- Scalar objects
 -- =====

rpkiRtrDiscontinuityTimer OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION "This timer represents the timestamp (value
 of sysUpTime) at which time any of the
 Counter32 objects in this MIB module
 encountered a discontinuity.

For objects that use rpkiRtrDiscontinuityTimer to
 indicate discontinuity, only values received since
 the time indicated by rpkiRtrDiscontinuityTimer are
 comparable to each other. A manager should take the
 possibility of rollover into account when
 calculating difference values.

In principle, that should only happen if the
 SNMP agent or the instrumentation for this
 MIB module starts or restarts."

::= { rpkiRtrObjects 1 }

-- =====
 -- RPKI-Router Cache Server Connection Table
 -- =====

```

rpkiRtrCacheServerTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RpkiRtrCacheServerTableEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "This table lists the RPKI cache servers
                known to this router/system."
    ::= { rpkiRtrObjects 2 }

rpkiRtrCacheServerTableEntry OBJECT-TYPE
    SYNTAX      RpkiRtrCacheServerTableEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "An entry in the rpkiRtrCacheServerTable.
                It holds management attributes associated
                with one connection to a RPKI cache server.

                Implementers should be aware that if the
                rpkiRtrCacheServerRemoteAddress object exceeds 114
                octets, the index values will exceed the 128
                sub-identifier limit and cannot be accessed using
                SNMPv1, SNMPv2c, or SNMPv3."

    INDEX      { rpkiRtrCacheServerRemoteAddressType,
                rpkiRtrCacheServerRemoteAddress,
                rpkiRtrCacheServerRemotePort
                }
    ::= { rpkiRtrCacheServerTable 1 }

RpkiRtrCacheServerTableEntry ::= SEQUENCE {
    rpkiRtrCacheServerRemoteAddressType  InetAddressType,
    rpkiRtrCacheServerRemoteAddress      InetAddress,
    rpkiRtrCacheServerRemotePort         InetPortNumber,
    rpkiRtrCacheServerLocalAddressType   InetAddressType,
    rpkiRtrCacheServerLocalAddress       InetAddress,
    rpkiRtrCacheServerLocalPort          InetPortNumber,
    rpkiRtrCacheServerPreference         Unsigned32,
    rpkiRtrCacheServerConnectionType     RpkiRtrConnectionType,
    rpkiRtrCacheServerConnectionStatus   INTEGER,
    rpkiRtrCacheServerDescription        LongUtf8String,
    rpkiRtrCacheServerMsgsReceived        Counter32,
    rpkiRtrCacheServerMsgsSent           Counter32,
    rpkiRtrCacheServerV4ActiveRecords     Gauge32,
    rpkiRtrCacheServerV4Announcements     Counter32,
    rpkiRtrCacheServerV4Withdrawals       Counter32,
    rpkiRtrCacheServerV6ActiveRecords     Gauge32,
    rpkiRtrCacheServerV6Announcements     Counter32,
    rpkiRtrCacheServerV6Withdrawals       Counter32,
    rpkiRtrCacheServerLatestSerial        Unsigned32,

```

```

rpkiRtrCacheServerSessionID      Unsigned32,
rpkiRtrCacheServerRefreshTimer   Unsigned32,
rpkiRtrCacheServerTimeToRefresh  Integer32,
rpkiRtrCacheServerId             Unsigned32
}

```

rpkiRtrCacheServerRemoteAddressType OBJECT-TYPE

```

SYNTAX      InetAddressType
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION "The network address type of the connection
            to this RPKI cache server.

```

Note: Only IPv4, IPv6, and DNS support are required for read-only compliance with RFC 6945."

```
 ::= { rpkiRtrCacheServerTableEntry 1 }
```

rpkiRtrCacheServerRemoteAddress OBJECT-TYPE

```

SYNTAX      InetAddress
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION "The remote network address for this connection
            to this RPKI cache server.

```

The format of the address is defined by the value of the corresponding instance of rpkiRtrCacheServerRemoteAddressType.

This object matches the address type used within the local router configuration. If the address is of type dns (fqdn), then the router will resolve it at the time it connects to the cache server."

```
 ::= { rpkiRtrCacheServerTableEntry 2 }
```

rpkiRtrCacheServerRemotePort OBJECT-TYPE

```

SYNTAX      InetPortNumber (1..65535)
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION "The remote port number for this connection
            to this RPKI cache server."

```

```
 ::= { rpkiRtrCacheServerTableEntry 3 }
```

rpkiRtrCacheServerLocalAddressType OBJECT-TYPE

```

SYNTAX      InetAddressType
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION "The network address type of the connection
            to this RPKI cache server.

```

Note: Only IPv4, IPv6, and DNS support are required for read-only compliance with RFC 6945."

```
 ::= { rpkiRtrCacheServerTableEntry 4 }
```

rpkiRtrCacheServerLocalAddress OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The local network address for this connection to this RPKI cache server.

The format of the address is defined by the value of the corresponding instance of rpkiRtrCacheServerLocalAddressType.

This object matches the address type used within the local router configuration. If the address is of type dns (fqdn), then the router will resolve it at the time it connects to the cache server."

```
 ::= { rpkiRtrCacheServerTableEntry 5 }
```

rpkiRtrCacheServerLocalPort OBJECT-TYPE

SYNTAX InetPortNumber (1..65535)

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The local port number for this connection to this RPKI cache server."

```
 ::= { rpkiRtrCacheServerTableEntry 6 }
```

rpkiRtrCacheServerPreference OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The routers' preference for this RPKI cache server.

A lower value means more preferred. If two entries have the same preference, then the order is arbitrary.

In two cases, the maximum value for an Unsigned32 object should be returned for this object:

- If no order is specified in the RPKI-Router configuration.
- If a preference value is configured that is larger than the max value for an Unsigned32 object."

REFERENCE "The RPKI-Router Protocol, RFC 6810, Section 8."

```
DEFVAL      { 4294967295 }
 ::= { rpkiRtrCacheServerTableEntry 7 }
```

```
rpkiRtrCacheServerConnectionType OBJECT-TYPE
 SYNTAX      RpkiRtrConnectionType
 MAX-ACCESS  read-only
 STATUS      current
 DESCRIPTION "The connection type or transport security suite
             in use for this RPKI cache server."
 ::= { rpkiRtrCacheServerTableEntry 8 }
```

```
rpkiRtrCacheServerConnectionStatus OBJECT-TYPE
 SYNTAX      INTEGER { up(1), down(2) }
 MAX-ACCESS  read-only
 STATUS      current
 DESCRIPTION "The connection status for this entry
             (connection to this RPKI cache server)."
 ::= { rpkiRtrCacheServerTableEntry 9 }
```

```
rpkiRtrCacheServerDescription OBJECT-TYPE
 SYNTAX      LongUtf8String
 MAX-ACCESS  read-only
 STATUS      current
 DESCRIPTION "Free form description/information for this
             connection to this RPKI cache server."
 ::= { rpkiRtrCacheServerTableEntry 10 }
```

```
rpkiRtrCacheServerMsgsReceived OBJECT-TYPE
 SYNTAX      Counter32
 MAX-ACCESS  read-only
 STATUS      current
 DESCRIPTION "Number of messages received from this
             RPKI cache server via this connection.

             Discontinuities are indicated by the value
             of rpkiRtrDiscontinuityTimer."
 ::= { rpkiRtrCacheServerTableEntry 11 }
```

```
rpkiRtrCacheServerMsgsSent OBJECT-TYPE
 SYNTAX      Counter32
 MAX-ACCESS  read-only
 STATUS      current
 DESCRIPTION "Number of messages sent to this
             RPKI cache server via this connection.

             Discontinuities are indicated by the value
             of rpkiRtrDiscontinuityTimer."
 ::= { rpkiRtrCacheServerTableEntry 12 }
```

```
rpkiRtrCacheServerV4ActiveRecords OBJECT-TYPE
    SYNTAX      Gauge32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "Number of active IPv4 records received from
                this RPKI cache server via this connection."
    ::= { rpkiRtrCacheServerTableEntry 13 }

rpkiRtrCacheServerV4Announcements OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "The number of IPv4 records announced by the
                RPKI cache server via this connection.

                Discontinuities are indicated by the value
                of rpkiRtrDiscontinuityTimer."
    ::= { rpkiRtrCacheServerTableEntry 14 }

rpkiRtrCacheServerV4Withdrawals OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "The number of IPv4 records withdrawn by the
                RPKI cache server via this connection.

                Discontinuities are indicated by the value
                of rpkiRtrDiscontinuityTimer."
    ::= { rpkiRtrCacheServerTableEntry 15 }

rpkiRtrCacheServerV6ActiveRecords OBJECT-TYPE
    SYNTAX      Gauge32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "Number of active IPv6 records received from
                this RPKI cache server via this connection."
    ::= { rpkiRtrCacheServerTableEntry 16 }

rpkiRtrCacheServerV6Announcements OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "The number of IPv6 records announced by the
                RPKI cache server via this connection.

                Discontinuities are indicated by the value
                of rpkiRtrDiscontinuityTimer."
    ::= { rpkiRtrCacheServerTableEntry 17 }
```

```

rpkiRtrCacheServerV6Withdrawals OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "The number of IPv6 records withdrawn by the
                RPKI cache server via this connection.

                Discontinuities are indicated by the value
                of rpkiRtrDiscontinuityTimer."
    ::= { rpkiRtrCacheServerTableEntry 18 }

rpkiRtrCacheServerLatestSerial OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "The latest serial number of data received from
                this RPKI server on this connection.

                Note: this value wraps back to zero when it
                reaches its maximum value."
    REFERENCE   "RFC 1982 and RFC 6810, Section 2"
    ::= { rpkiRtrCacheServerTableEntry 19 }

rpkiRtrCacheServerSessionID OBJECT-TYPE
    SYNTAX      Unsigned32 (0..65535)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "The Session ID associated with the RPKI cache
                server at the other end of this connection."
    REFERENCE   "RFC 6810, Section 2"
    ::= { rpkiRtrCacheServerTableEntry 20 }

rpkiRtrCacheServerRefreshTimer OBJECT-TYPE
    SYNTAX      Unsigned32 (60..7200)
    UNITS       "seconds"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "The number of seconds configured for the refresh
                timer for this connection to this RPKI cache
                server."
    REFERENCE   "RFC 6810, Sections 6.1 and 8"
    ::= { rpkiRtrCacheServerTableEntry 21 }

rpkiRtrCacheServerTimeToRefresh OBJECT-TYPE
    SYNTAX      Integer32
    UNITS       "seconds"
    MAX-ACCESS  read-only
    STATUS      current

```

DESCRIPTION "The number of seconds remaining before a new refresh is performed via a Serial Query to this cache server over this connection.

A negative value means that the refresh time has passed this many seconds and the refresh has not yet been completed. It will stop decrementing at the maximum negative value.

Upon a completed refresh (i.e., a successful and complete response to a Serial Query) the value of this attribute will be reinitialized with the value of the corresponding rpkiRtrCacheServerRefreshTimer attribute."

REFERENCE "RFC 6810, Section 8"
 ::= { rpkiRtrCacheServerTableEntry 22 }

rpkiRtrCacheServerId OBJECT-TYPE

SYNTAX Unsigned32 (1..4294967295)

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The unique ID for this connection.

An implementation must make sure this ID is unique within this table. It is this ID that can be used to find entries in the rpkiRtrPrefixOriginTable that were created by announcements received on this connection from this cache server."

REFERENCE "RFC 6810, Section 4"
 ::= { rpkiRtrCacheServerTableEntry 23 }

-- =====
 -- Errors Table
 -- =====

rpkiRtrCacheServerErrorsTable OBJECT-TYPE

SYNTAX SEQUENCE OF RPKIRTRCacheServerErrorsTableEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION "This table provides statistics on errors per RPKI peer connection. These can be used for debugging."

::= { rpkiRtrObjects 3 }

rpkiRtrCacheServerErrorsTableEntry OBJECT-TYPE

SYNTAX RPKIRTRCacheServerErrorsTableEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION "An entry in the rpkiCacheServerErrorTable. It holds management objects associated with error codes that were received on the specified connection to a specific cache server."

REFERENCE "RFC 6810, Section 10"

AUGMENTS { rpkiRtrCacheServerTableEntry }
 ::= { rpkiRtrCacheServerErrorsTable 1 }

```
RpkiRtrCacheServerErrorsTableEntry ::= SEQUENCE {
  rpkiRtrCacheServerErrorsCorruptData      Counter32,
  rpkiRtrCacheServerErrorsInternalError    Counter32,
  rpkiRtrCacheServerErrorsNoData          Counter32,
  rpkiRtrCacheServerErrorsInvalidRequest   Counter32,
  rpkiRtrCacheServerErrorsUnsupportedVersion Counter32,
  rpkiRtrCacheServerErrorsUnsupportedPdu   Counter32,
  rpkiRtrCacheServerErrorsWithdrawalUnknown Counter32,
  rpkiRtrCacheServerErrorsDuplicateAnnounce Counter32
}
```

rpkiRtrCacheServerErrorsCorruptData OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The number of 'Corrupt Data' errors received from the RPKI cache server at the other end of this connection.

Discontinuities are indicated by the value of rpkiRtrDiscontinuityTimer."

::= { rpkiRtrCacheServerErrorsTableEntry 1 }

rpkiRtrCacheServerErrorsInternalError OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The number of 'Internal Error' errors received from the RPKI cache server at the other end of this connection.

Discontinuities are indicated by the value of rpkiRtrDiscontinuityTimer."

::= { rpkiRtrCacheServerErrorsTableEntry 2 }

rpkiRtrCacheServerErrorsNoData OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The number of 'No Data Available' errors received

from the RPKI cache server at the other end of this connection.

Discontinuities are indicated by the value of rpkIRtrDiscontinuityTimer."

```
::= { rpkIRtrCacheServerErrorsTableEntry 3 }
```

rpkIRtrCacheServerErrorsInvalidRequest OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The number of 'Invalid Request' errors received from the RPKI cache server at the other end of this connection.

Discontinuities are indicated by the value of rpkIRtrDiscontinuityTimer."

```
::= { rpkIRtrCacheServerErrorsTableEntry 4 }
```

rpkIRtrCacheServerErrorsUnsupportedVersion OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The number of 'Unsupported Protocol Version' errors received from the RPKI cache server at the other end of this connection.

Discontinuities are indicated by the value of rpkIRtrDiscontinuityTimer."

```
::= { rpkIRtrCacheServerErrorsTableEntry 5 }
```

rpkIRtrCacheServerErrorsUnsupportedPdu OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The number of 'Unsupported PDU Type' errors received from the RPKI cache server at the other end of this connection.

Discontinuities are indicated by the value of rpkIRtrDiscontinuityTimer."

```
::= { rpkIRtrCacheServerErrorsTableEntry 6 }
```

rpkIRtrCacheServerErrorsWithdrawalUnknown OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The number of 'Withdrawal of Unknown Record'

errors received from the RPKI cache server at the other end of this connection.

Discontinuities are indicated by the value of rpkIRtrDiscontinuityTimer."

```
::= { rpkIRtrCacheServerErrorsTableEntry 7 }
```

rpkIRtrCacheServerErrorsDuplicateAnnounce OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION "The number of 'Duplicate Announcement Received' errors received from the RPKI cache server at the other end of this connection.

Discontinuities are indicated by the value of rpkIRtrDiscontinuityTimer."

```
::= { rpkIRtrCacheServerErrorsTableEntry 8 }
```

```
-- =====
-- The rpkIRtrPrefixOriginTable
-- =====
```

rpkIRtrPrefixOriginTable OBJECT-TYPE

SYNTAX SEQUENCE OF RpkIRtrPrefixOriginTableEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION "This table lists the prefixes that were announced by RPKI cache servers to this system. That is the prefixes and their Origin Autonomous System Number (ASN) as received by announcements via the RPKI-Router Protocol."

```
::= { rpkIRtrObjects 4 }
```

rpkIRtrPrefixOriginTableEntry OBJECT-TYPE

SYNTAX RpkIRtrPrefixOriginTableEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION "An entry in the rpkIRtrPrefixOriginTable. This represents one announced prefix. If a cache server is removed from the local configuration, any table rows associated with that server (indicated by rpkIRtrPrefixOriginCacheServerId) are also removed from this table.

Implementers should be aware that if the rpkIRtrPrefixOriginAddress object exceeds 111 octets, the index values will exceed the 128

sub-identifier limit and cannot be accessed using SNMPv1, SNMPv2c, or SNMPv3."

```
INDEX      { rpkiRtrPrefixOriginAddressType,
             rpkiRtrPrefixOriginAddress,
             rpkiRtrPrefixOriginMinLength,
             rpkiRtrPrefixOriginMaxLength,
             rpkiRtrPrefixOriginASN,
             rpkiRtrPrefixOriginCacheServerId
           }
 ::= { rpkiRtrPrefixOriginTable 1 }
```

```
RpkiRtrPrefixOriginTableEntry ::= SEQUENCE {
  rpkiRtrPrefixOriginAddressType  InetAddressType,
  rpkiRtrPrefixOriginAddress      InetAddress,
  rpkiRtrPrefixOriginMinLength    InetAddressPrefixLength,
  rpkiRtrPrefixOriginMaxLength    InetAddressPrefixLength,
  rpkiRtrPrefixOriginASN          InetAutonomousSystemNumber,
  rpkiRtrPrefixOriginCacheServerId Unsigned32
}
```

rpkiRtrPrefixOriginAddressType OBJECT-TYPE

```
SYNTAX      InetAddressType
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION "The network address type for this prefix.
```

Note: Only IPv4 and IPv6 support are required for read-only compliance with RFC 6945."

```
::= { rpkiRtrPrefixOriginTableEntry 1 }
```

rpkiRtrPrefixOriginAddress OBJECT-TYPE

```
SYNTAX      InetAddress
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION "The network address for this prefix.
```

The format of the address is defined by the value of the corresponding instance of rpkiRtrPrefixOriginAddressType."

```
::= { rpkiRtrPrefixOriginTableEntry 2 }
```

rpkiRtrPrefixOriginMinLength OBJECT-TYPE

```
SYNTAX      InetAddressPrefixLength
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION "The minimum prefix length allowed for this prefix."
 ::= { rpkiRtrPrefixOriginTableEntry 3 }
```

```

rpkiRtrPrefixOriginMaxLength OBJECT-TYPE
    SYNTAX      InetAddressPrefixLength
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "The maximum prefix length allowed for this prefix.

                Note, this value must be greater or equal to the
                value of rpkiRtrPrefixOriginMinLength."
    ::= { rpkiRtrPrefixOriginTableEntry 4 }

rpkiRtrPrefixOriginASN OBJECT-TYPE
    SYNTAX      InetAutonomousSystemNumber (0..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "The ASN that is authorized to announce the
                prefix or sub-prefixes covered by this entry."
    ::= { rpkiRtrPrefixOriginTableEntry 5 }

rpkiRtrPrefixOriginCacheServerId OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "The unique ID of the connection to the cache
                server from which this announcement was received.
                That connection is identified/found by a matching
                value in attribute rpkiRtrCacheServerId."
    ::= { rpkiRtrPrefixOriginTableEntry 6 }

-- =====
-- Notifications
-- =====

rpkiRtrCacheServerConnectionStateChange NOTIFICATION-TYPE
    OBJECTS      { rpkiRtrCacheServerConnectionStatus,
                  rpkiRtrCacheServerLatestSerial,
                  rpkiRtrCacheServerSessionID
                }
    STATUS      current
    DESCRIPTION "This notification signals a change in the status
                of an rpkiRtrCacheServerConnection.

                The management agent MUST throttle the generation of
                consecutive rpkiRtrCacheServerConnectionStateChange
                notifications such that there is at least a 5 second
                gap between them.

                If more than one notification has occurred locally
                during that time, the most recent notification is

```

sent at the end of the 5 second gap and the others
are discarded."

```
::= { rpkiRtrNotifications 1 }
```

```
rpkiRtrCacheServerConnectionToGoStale NOTIFICATION-TYPE
```

```
OBJECTS      { rpkiRtrCacheServerV4ActiveRecords,
                rpkiRtrCacheServerV6ActiveRecords,
                rpkiRtrCacheServerLatestSerial,
                rpkiRtrCacheServerSessionID,
                rpkiRtrCacheServerRefreshTimer,
                rpkiRtrCacheServerTimeToRefresh
              }
```

```
STATUS      current
```

```
DESCRIPTION "This notification signals that an RPKI cache
             server connection is about to go stale.
             It is suggested that this notification is
             generated when the value of the
             rpkiRtrCacheServerTimeToRefresh attribute
             goes below 60 seconds.
```

```
             The SNMP agent MUST throttle the generation of
             consecutive rpkiRtrCacheServerConnectionToGoStale
             notifications such that there is at least a
             5 second gap between them.
```

```
"
```

```
::= { rpkiRtrNotifications 2 }
```

```
-- =====
-- Module Compliance information
-- =====
```

```
rpkiRtrCompliances OBJECT IDENTIFIER ::=
                    {rpkiRtrConformance 1}
rpkiRtrGroups      OBJECT IDENTIFIER ::=
                    {rpkiRtrConformance 2}
```

```
rpkiRtrRFC6945ReadOnlyCompliance MODULE-COMPLIANCE
```

```
STATUS      current
```

```
DESCRIPTION
```

```
"The compliance statement for the rpkiRtrMIB module. There
are only read-only objects in this MIB module, so the
'ReadOnly' in the name of this compliance statement is there
only for clarity and truth in advertising.
```

```
There are a number of INDEX objects that cannot be
represented in the form of OBJECT clauses in SMIV2, but for
which there are compliance requirements. Those requirements
and similar requirements for related objects are expressed
```

below, in pseudo-OBJECT clause form, in this description:

```
-- OBJECT rpkiRtrCacheServerRemoteAddressType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2), dns(16) }
-- DESCRIPTION
--   The MIB requires support for the IPv4, IPv6, and DNS
--   InetAddressTypes for this object.

-- OBJECT rpkiRtrCacheServerLocalAddressType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2), dns(16) }
-- DESCRIPTION
--   The MIB requires support for the IPv4, IPv6, and DNS
--   InetAddressTypes for this object.

-- OBJECT rpkiRtrPrefixOriginAddressType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
-- DESCRIPTION
--   The MIB requires support for the IPv4, and IPv6
--   InetAddressTypes for this object.
"
```

```
MODULE      -- This module
```

```
MANDATORY-GROUPS { rpkiRtrCacheServerGroup,
                    rpkiRtrPrefixOriginGroup,
                    rpkiRtrNotificationsGroup
                  }
```

```
GROUP      rpkiRtrCacheServerErrorsGroup
DESCRIPTION "Implementation of this group is optional and
            would be useful for debugging."
```

```
::= { rpkiRtrCompliances 1 }
```

```
rpkiRtrCacheServerGroup OBJECT-GROUP
```

```
OBJECTS    {
            rpkiRtrDiscontinuityTimer,
            rpkiRtrCacheServerLocalAddressType,
            rpkiRtrCacheServerLocalAddress,
            rpkiRtrCacheServerLocalPort,
            rpkiRtrCacheServerPreference,
            rpkiRtrCacheServerConnectionType,
            rpkiRtrCacheServerConnectionStatus,
            rpkiRtrCacheServerDescription,
            rpkiRtrCacheServerMsgsReceived,
            rpkiRtrCacheServerMsgsSent,
            rpkiRtrCacheServerV4ActiveRecords,
            rpkiRtrCacheServerV4Announcements,
            rpkiRtrCacheServerV4Withdrawals,
```

```

        rpkiRtrCacheServerV6ActiveRecords,
        rpkiRtrCacheServerV6Announcements,
        rpkiRtrCacheServerV6Withdrawals,
        rpkiRtrCacheServerLatestSerial,
        rpkiRtrCacheServerSessionID,
        rpkiRtrCacheServerRefreshTimer,
        rpkiRtrCacheServerTimeToRefresh,
        rpkiRtrCacheServerId
    }
    STATUS          current
    DESCRIPTION    "The collection of objects to monitor the RPKI peer
        connections."
    ::= { rpkiRtrGroups 1 }

rpkiRtrCacheServerErrorsGroup OBJECT-GROUP
    OBJECTS        {
        rpkiRtrCacheServerErrorsCorruptData,
        rpkiRtrCacheServerErrorsInternalError,
        rpkiRtrCacheServerErrorsNoData,
        rpkiRtrCacheServerErrorsInvalidRequest,
        rpkiRtrCacheServerErrorsUnsupportedVersion,
        rpkiRtrCacheServerErrorsUnsupportedPdu,
        rpkiRtrCacheServerErrorsWithdrawalUnknown,
        rpkiRtrCacheServerErrorsDuplicateAnnounce
    }
    STATUS          current
    DESCRIPTION    "The collection of objects that may help in
        debugging the communication between RPKI
        clients and cache servers."
    ::= { rpkiRtrGroups 2 }

rpkiRtrPrefixOriginGroup OBJECT-GROUP
    OBJECTS        {
        rpkiRtrPrefixOriginCacheServerId
    }
    STATUS          current
    DESCRIPTION    "The collection of objects that represent
        the prefix(es) and their validated Origin
        ASes."
    ::= { rpkiRtrGroups 3 }

```

```

rpkiRtrNotificationsGroup NOTIFICATION-GROUP
  NOTIFICATIONS { rpkiRtrCacheServerConnectionStateChange,
                  rpkiRtrCacheServerConnectionToGoStale
                  }
  STATUS          current
  DESCRIPTION     "The set of notifications to alert an NMS of change
                  in connections to RPKI cache servers."
  ::= { rpkiRtrGroups 4 }

```

END

5. IANA Considerations

IANA has assigned the MIB module in this document the following OBJECT IDENTIFIER within the SMI Numbers registry.

Descriptor	OBJECT IDENTIFIER value
-----	-----
rpkiRtrMIB	{ mib-2 218 }

6. Security Considerations

There are no management objects defined in this MIB module that have a MAX-ACCESS clause of read-write and/or read-create. So, if this MIB module is implemented correctly, then there is no risk that an intruder can alter or create any management objects of this MIB module via direct SNMP SET operations.

Most of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. They are vulnerable in the sense that when an intruder sees the information in this MIB module, then it might help him/her to set up an attack on the router or cache server. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

Implementations MUST provide the security features described by the SNMPv3 framework (see [RFC3410]), including full support for authentication and privacy via the User-based Security Model (USM) [RFC3414] with the AES cipher algorithm [RFC3826]. Implementations

MAY also provide support for the Transport Security Model (TSM) [RFC5591] in combination with a secure transport such as SSH [RFC5592] or TLS/DTLS [RFC6353].

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2287] Krupczak, C. and J. Saperia, "Definitions of System-Level Managed Objects for Applications", RFC 2287, February 1998.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, RFC 2579, April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, RFC 2580, April 1999.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", RFC 4001, February 2005.
- [RFC6810] Bush, R. and R. Austein, "The Resource Public Key Infrastructure (RPKI) to Router Protocol", RFC 6810, January 2013.

7.2. Informative References

- [RFC1982] Elz, R. and R. Bush, "Serial Number Arithmetic", RFC 1982, August 1996.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, December 2002.
- [RFC3414] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", STD 62, RFC 3414, December 2002.
- [RFC3826] Blumenthal, U., Maino, F., and K. McCloghrie, "The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model", RFC 3826, June 2004.
- [RFC4252] Ylonen, T. and C. Lonvick, "The Secure Shell (SSH) Authentication Protocol", RFC 4252, January 2006.
- [RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", RFC 5246, August 2008.
- [RFC5591] Harrington, D. and W. Hardaker, "Transport Security Model for the Simple Network Management Protocol (SNMP)", RFC 5591, June 2009.
- [RFC5592] Harrington, D., Salowey, J., and W. Hardaker, "Secure Shell Transport Model for the Simple Network Management Protocol (SNMP)", RFC 5592, June 2009.
- [RFC5925] Touch, J., Mankin, A., and R. Bonica, "The TCP Authentication Option", RFC 5925, June 2010.
- [RFC6353] Hardaker, W., "Transport Layer Security (TLS) Transport Model for the Simple Network Management Protocol (SNMP)", RFC 6353, July 2011.

Authors' Addresses

Randy Bush
Internet Initiative Japan
5147 Crystal Springs
Bainbridge Island, WA 98110
US

E-Mail: randy@psg.com

Bert Wijnen
RIPE NCC
Schagen 33
3461 GL Linschoten
Netherlands

E-Mail: berttietf@bwijnen.net

Keyur Patel
Cisco Systems
170 W. Tasman Drive
San Jose, CA 95134
USA

E-Mail: keyupate@cisco.com

Michael Baer
SPARTA
P.O. Box 72682
Davis, CA 95617
USA

E-Mail: baerm@tislabs.com

