

Network Working Group  
Requests for Comment: 2896  
Category: Informational

A. Bierman  
C. Bucci  
Cisco Systems, Inc.  
R. Iddon  
3Com, Inc.  
August 2000

## Remote Network Monitoring MIB Protocol Identifier Macros

### Status of this Memo

This memo provides information for the Internet community. It does not specify an Internet standard of any kind. Distribution of this memo is unlimited.

### Copyright Notice

Copyright (C) The Internet Society (2000). All Rights Reserved.

### Abstract

This memo contains various protocol identifier examples, which can be used to produce valid protocolDirTable INDEX encodings, as defined by the Remote Network Monitoring MIB (Management Information Base) Version 2 [RFC2021] and the RMON Protocol Identifier Reference [RFC2895].

This document contains protocol identifier macros for well-known protocols. A conformant implementation of the RMON-2 MIB [RFC2021] can be accomplished without the use of these protocol identifiers, and accordingly, this document does not specify any IETF standard. It is published to encourage better interoperability between RMON-2 agent implementations, by providing a great deal of RMON related protocol information in one document.

The first version of the RMON Protocol Identifiers Document [RFC2074] has been split into a standards-track Reference portion [RFC2895], and an "RMON Protocol Identifier Macros", document (this document) which contains the non-normative portion of that specification.

### Table of Contents

1 The SNMP Network Management Framework .....	2
2 Overview .....	3
2.1 Terms .....	3
2.2 Relationship to the Remote Network Monitoring MIB .....	4
2.3 Relationship to the RMON Protocol Identifier Reference .....	4

2.4 Relationship to Other MIBs .....	4
3 Protocol Identifier Macros .....	4
3.1 Protocol Stacks And Single-Vendor Applications .....	5
3.1.1 The TCP/IP protocol stack .....	5
3.1.2 Novell IPX Stack .....	44
3.1.3 The XEROX Protocol Stack .....	49
3.1.4 AppleTalk Protocol Stack .....	51
3.1.5 Banyon Vines Protocol Stack .....	56
3.1.6 The DECNet Protocol Stack .....	61
3.1.7 The IBM SNA Protocol Stack. ....	65
3.1.8 The NetBEUI/NetBIOS Family .....	66
3.2 Multi-stack protocols .....	70
4 Intellectual Property .....	72
5 Acknowledgements .....	72
6 References .....	73
7 Security Considerations .....	82
8 Authors' Addresses .....	83
9 Full Copyright Statement .....	84

## 1. The SNMP Network Management Framework

The SNMP Management Framework presently consists of five major components:

- o An overall architecture, described in RFC 2571 [RFC2571].
- o Mechanisms for describing and naming objects and events for the purpose of management. The first version of this Structure of Management Information (SMI) is called SMIv1 and described in STD 16, RFC 1155 [RFC1155], STD 16, RFC 1212 [RFC1212] and RFC 1215 [RFC1215]. The second version, called SMIv2, is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].
- o Message protocols for transferring management information. The first version of the SNMP message protocol is called SNMPv1 and described in STD 15, RFC 1157 [RFC1157]. A second version of the SNMP message protocol, which is not an Internet standards track protocol, is called SNMPv2c and described in RFC 1901 [RFC1901] and RFC 1906 [RFC1906]. The third version of the message protocol is called SNMPv3 and described in RFC 1906 [RFC1906], RFC 2572 [RFC2572] and RFC 2574 [RFC2574].
- o Protocol operations for accessing management information. The first set of protocol operations and associated PDU formats is described in STD 15, RFC 1157 [RFC1157]. A second set of protocol operations and associated PDU formats is described in RFC 1905 [RFC1905].

- o A set of fundamental applications described in RFC 2573 [RFC2573] and the view-based access control mechanism described in RFC 2575 [RFC2575].

A more detailed introduction to the current SNMP Management Framework can be found in RFC 2570 [RFC2570].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. Objects in the MIB are defined using the mechanisms defined in the SMI.

This memo does not specify a MIB module.

## 2. Overview

The RMON-2 MIB [RFC2021] uses hierarchically formatted OCTET STRINGS to globally identify individual protocol encapsulations in the protocolDirTable.

This guide contains examples of protocol identifier encapsulations, which can be used to describe valid protocolDirTable entries. The syntax of the protocol identifier descriptor is defined in the RMON Protocol Identifier Reference [RFC2895].

This document is not intended to be an authoritative reference on the protocols described herein. Refer to the Official Internet Standards document [RFC2600], the Assigned Numbers document [RFC1700], or other appropriate RFCs, IEEE documents, etc. for complete and authoritative protocol information.

This is the second revision of this document, and is intended to replace Section 5 of the first RMON-2 Protocol Identifiers document [RFC2074].

The RMONMIB working group has decided to discontinue maintenance of this Protocol Identifier Macro repository document, due to a lack of contributions from the RMON vendor community. This document is published as an aid in implementation of the protocolDirTable.

### 2.1. Terms

Refer to the RMON Protocol Identifier Reference [RFC2895] for definitions of terms used to describe the Protocol Identifier Macro and aspects of protocolDirTable INDEX encoding.

## 2.2. Relationship to the Remote Network Monitoring MIB

This document is intended to describe some protocol identifier macros, which can be converted to valid protocolDirTable INDEX values, using the mapping rules defined in the RMON Protocol Identifier Reference [RFC2895].

This document is not intended to limit the protocols that may be identified for counting in the RMON-2 MIB. Many protocol encapsulations, not explicitly identified in this document, may be present in an actual implementation of the protocolDirTable. Also, implementations of the protocolDirTable may not include all the protocols identified in the example section below.

## 2.3. Relationship to the RMON Protocol Identifier Reference

This document is intentionally separated from the normative reference document defining protocolDirTable INDEX encoding rules and the protocol identifier macro syntax [RFC2895]. This allows frequent updates to this document without any republication of MIB objects or protocolDirTable INDEX encoding rules. Note that the base layer and IANA assigned protocol identifier macros are located in Reference document, since these encoding values are defined by the RMONMIB WG.

Protocol Identifier macros submitted from the RMON working group and community at large (to the RMONMIB WG mailing list at '[rmonmib@cisco.com](mailto:rmonmib@cisco.com)') will be collected and added to this document.

Macros submissions will be collected in the IANA's MIB files under the directory "[ftp://ftp.isi.edu/mib/rmonmib/rmon2\\_pi\\_macros/](ftp://ftp.isi.edu/mib/rmonmib/rmon2_pi_macros/)" and in the RMONMIB working group mailing list message archive file "<ftp://ftpeng.cisco.com/ftp/rmonmib/rmonmib>".

## 2.4. Relationship to Other MIBs

The RMON Protocol Identifier Macros document is intended for use with the RMON Protocol Identifier Reference [RFC2895] and the RMON-2 MIB protocolDirTable [RFC2021]. It is not relevant to any other MIB, or intended for use with any other MIB.

## 3. Protocol Identifier Macros

This section contains protocol identifier macros for some well-known protocols, although some of them may no longer be in use. These macros reference the base layer identifiers found in section 4 of the RMON Protocol Identifier Reference [RFC2895]. These identifiers are listed below:

```

ether2
llc
snap
vsnap
ianaAssigned
802-1Q

```

Refer to the RMON Protocol Identifier Reference [RFC2895] for the protocol identifier macro definitions for these protocols.

### 3.1. Protocol Stacks And Single-Vendor Applications

Network layer protocol identifier macros contain additional information about the network layer, and is found immediately following a base layer-identifier in a protocol identifier.

The ProtocolDirParameters supported at the network layer are 'countsFragments(0)', and 'tracksSessions(1)'. An agent may choose to implement a subset of these parameters.

The protocol-name should be used for the ProtocolDirDescr field. The ProtocolDirType ATTRIBUTES used at the network layer are 'hasChildren(0)' and 'addressRecognitionCapable(1)'. Agents may choose to implement a subset of these attributes for each protocol, and therefore limit which tables the indicated protocol can be present (e.g. protocol distribution, host, and matrix tables).

The following protocol-identifier macro declarations are given for example purposes only. They are not intended to constitute an exhaustive list or an authoritative source for any of the protocol information given. However, any protocol that can encapsulate other protocols must be documented here in order to encode the children identifiers into protocolDirID strings. Leaf protocols should be documented as well, but an implementation can identify a leaf protocol even if it isn't listed here (as long as the parent is documented).

#### 3.1.1. The TCP/IP protocol stack

```

arp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "An Address Resolution Protocol message (request or response).
  This protocol does not include Reverse ARP (RARP) packets, which
  are counted separately."
REFERENCE
  "RFC 826 [RFC826] defines the Address Resolution Protocol."

```

```

 ::= {
 ether2 0x806, -- [ 0.0.8.6 ]
 snap 0x806,
 802-1Q 0x806 -- [ 0.0.8.6 ]
}

ip PROTOCOL-IDENTIFIER
PARAMETERS {
    countsFragments(0) -- This parameter applies to all child
                         -- protocols.
}
ATTRIBUTES {
    hasChildren(0),
    addressRecognitionCapable(1)
}
DESCRIPTION
"The protocol identifiers for the Internet Protocol (IP). Note
that IP may be encapsulated within itself, so more than one of
the following identifiers may be present in a particular
protocolDirID string."
CHILDREN
"Children of 'ip' are selected by the value in the Protocol field
(one octet), as defined in the PROTOCOL NUMBERS table within the
Assigned Numbers Document.

The value of the Protocol field is encoded in an octet string as
[ 0.0.0.a ], where 'a' is the protocol field .

Children of 'ip' are encoded as [ 0.0.0.a ], and named as 'ip a'
where 'a' is the protocol field value. For example, a
protocolDirID-fragment value of:
 0.0.0.1.0.0.8.0.0.0.0.1

defines an encapsulation of ICMP (ether2.ip.icmp)"

ADDRESS-FORMAT
"4 octets of the IP address, in network byte order. Each ip
packet contains two addresses, the source address and the
destination address."

DECODING
>Note: ether2.ip.ipip4 udp is a different protocolDirID than
ether2.ip.udp, as identified in the protocolDirTable. As such,
two different local protocol index values will be assigned by the
agent. E.g. (full INDEX values shown):
ether2.ip.ipip4.udp =
 16.0.0.0.1.0.0.8.0.0.0.0.0.4.0.0.0.0.17.4.0.0.0.0
ether2.ip.udp =
 12.0.0.0.1.0.0.8.0.0.0.0.0.0.17.3.0.0.0"

REFERENCE

```

"RFC 791 [RFC791] defines the Internet Protocol; The following URL defines the authoritative repository for the PROTOCOL NUMBERS Table:

```

ftp://ftp.isi.edu/in-notes/iana/assignments/protocol-numbers"
::= {
  ether2      0x0800,
  llc         0x06,
  snap        0x0800,
  -- ip          4,           ** represented by the ipip4 macro
  -- ip          94,          ** represented by the ipip macro
  802-1Q      0x0800,       -- [0.0.8.0]
  802-1Q      0x02000006   -- 1Q-LLC [2.0.0.6]
}

-- *****
-- Children of IP
--

icmp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Internet Message Control Protocol"
REFERENCE
  "RFC 792 [RFC792] defines the Internet Control Message Protocol."
::= {
  ip 1,
  ipip4 1,
  ipip 1
}

igmp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Internet Group Management Protocol; IGMP is used by IP hosts to
  report their host group memberships to any immediately-
  neighboring multicast routers."
REFERENCE
  "Appendix A of Host Extensions for IP Multicasting [RFC1112]
  defines the Internet Group Management Protocol."
::= {
  ip 2,
  ipip4 2,
  ipip 2
}

```

```

}

ggp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Gateway-to-Gateway Protocol; DARPA Internet Gateway
  (historical)"
REFERENCE
  "RFC 823 [RFC823] defines the Gateway-to-Gateway Protocol."
 ::= {
  ip 3,
  ipip4 3,
  ipip 3
}

ipip4 PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES {
  hasChildren(0),
  addressRecognitionCapable(1)
}
DESCRIPTION
  "IP in IP Tunneling"
CHILDREN
  "Children of 'ipip4' are selected and encoded in the same manner
  as children of IP."
ADDRESS-FORMAT
  "The 'ipip4' address format is the same as the IP address
  format."
DECODING
  "Note: ether2.ip.ipip4.udp is a different protocolDirID than
  ether2.ip.udp, as identified in the protocolDirTable. As such,
  two different local protocol index values will be assigned by the
  agent. E.g. (full INDEX values shown):
  ether2.ip.ipip4.udp =
    16.0.0.0.1.0.0.8.0.0.0.0.4.0.0.0.17.4.0.0.0.0
  ether2.ip.udp =
    12.0.0.0.1.0.0.8.0.0.0.0.17.3.0.0.0"
REFERENCE
  "RFC 1853 [RFC1853] defines IP in IP over Protocol 4."
 ::= {
  ip 4,
  ipip4 4,
  ipip 4
}

st PROTOCOL-IDENTIFIER

```

```

PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Internet Stream Protocol Version 2 (ST2); (historical) ST2 is an
  experimental resource reservation protocol intended to provide
  end-to-end real-time guarantees over an internet."
REFERENCE
  "RFC 1819 [RFC1819] defines version 2 of the Internet Stream
  Protocol."
 ::= {
  ip 5,
  ipip4 5,
  ipip 5
}

tcp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES {
  hasChildren(0)
}
DESCRIPTION
  "Transmission Control Protocol"
CHILDREN
  "Children of TCP are identified by the 16 bit Source or
  Destination Port value as specified in RFC 793. They are encoded
  as [ 0.0.a.b], where 'a' is the MSB and 'b' is the LSB of the
  port value. Both bytes are encoded in network byte order. For
  example, a protocolDirId-fragment of:
  0.0.0.1.0.0.8.0.0.0.0.6.0.0.0.23

  identifies an encapsulation of the telnet protocol
  (ether2.ip.tcp.telnet)"
REFERENCE
  "RFC 793 [RFC793] defines the Transmission Control Protocol.

  The following URL defines the authoritative repository for
  reserved and registered TCP port values:

  ftp://ftp.isi.edu/in-notes/iana/assignments/port-numbers"
 ::= {
  ip 6,
  ipip4 6,
  ipip 6
}

egp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }

```

```
DESCRIPTION
    "Exterior Gateway Protocol (historical)"
REFERENCE
    "RFC 904 [RFC904] defines the Exterior Gateway Protocol."
 ::= {
 ip 8,
 ipip4 8,
 ipip 8
}

igp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "Any private interior gateway."
REFERENCE
    "[RFC1700]"
 ::= {
 ip 9,
 ipip4 9,
 ipip 9
}

nvp2 PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "NVP-II; Network Voice Protocol"
REFERENCE
    "RFC 741 [RFC741] defines the Network Voice Protocol"
 ::= {
 ip 11,
 ipip4 11,
 ipip 11
}

pup PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "PUP Protocol"
REFERENCE
    "Xerox"
 ::= {
 ip 12,
 ipip4 12,
 ipip 12
}
```

```

xnet PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Cross Net Debugger (historical)"
REFERENCE
  "[IEN158]"
 ::= {
  ip 15,
  ipip4 15,
  ipip 15
}

chaos PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "CHAOS Protocol; historical"
REFERENCE
  "J. Noel Chiappa <JNC@XX.LCS.MIT.EDU>"
 ::= {
  ip 16,
  ipip4 16,
  ipip 16
}

udp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES {
  hasChildren(0)
}
DESCRIPTION
  "User Datagram Protocol"
CHILDREN
  "Children of UDP are identified by the 16 bit Source or
  Destination Port value as specified in RFC 768. They are encoded
  as [ 0.0.a.b ], where 'a' is the MSB and 'b' is the LSB of the
  port value. Both bytes are encoded in network byte order. For
  example, a protocolDirId-fragment of:
    0.0.0.1.0.0.8.0.0.0.0.17.0.0.0.161

  identifies an encapsulation of SNMP (ether2.ip.udp.snmp)"
REFERENCE
  "RFC 768 [RFC768] defines the User Datagram Protocol.

  The following URL defines the authoritative repository for
  reserved and registered UDP port values:

```

```
ftp://ftp.isi.edu/in-notes/iana/assignments/port-numbers"
 ::= {
 ip 17,
 ipip4 17,
 ipip 17
 }

mux PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
 "Multiplexing Protocol (historical)"
REFERENCE
 "IEN-90 [IEN-90] defines the Multiplexing Protocol"
 ::= {
 ip 18,
 ipip4 18,
 ipip 18
 }

hmp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
 "Host Monitoring Protocol; historical"
REFERENCE
 "RFC 869 [RFC869] defines the Host Monitoring Protocol"
 ::= {
 ip 20,
 ipip4 20,
 ipip 20
 }

xns-idp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
 "XEROX NS IDP"
REFERENCE
 "Xerox Corporation"
 ::= {
 ip 22,
 ipip4 22,
 ipip 22
 }

rdp PROTOCOL-IDENTIFIER
PARAMETERS { }
```

```
ATTRIBUTES { }
DESCRIPTION
  "Reliable Data Protocol"
REFERENCE
  "RFC 908 [RFC908] defines the original protocol; RFC 1151
  [RFC1151] defines version 2 of the Reliable Data Protocol."
 ::= {
  ip 27,
  ipip4 27,
  ipip 27
}

irtp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Internet Reliable Transaction Protocol"
REFERENCE
  "RFC 938 [RFC938] defines the Internet Reliable Transaction
  Protocol functional and interface specification."
 ::= {
  ip 28,
  ipip4 28,
  ipip 28
}

iso-tp4 PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "ISO Transport Protocol Specification"
REFERENCE
  "RFC 905 [RFC905] defines the ISO Transport Protocol
  Specification; ISO DP 8073"
 ::= {
  ip 29,
  ipip4 29,
  ipip 29
}

netblt PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Bulk Data Transfer Protocol; historical"
REFERENCE
  "RFC 998 [RFC998] defines NETBLT: A Bulk Data Transfer Protocol."
 ::= {
```

```
ip 30,
ipip4 30,
ipip 30
}

mfe-nsp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "MFE Network Services Protocol; historical"
REFERENCE
  "Shuttleworth, B., 'A Documentary of MFENet, a National Computer
   Network', UCRL-52317, Lawrence Livermore Labs, Livermore,
   California, June 1977."
 ::= {
  ip 31,
  ipip4 31,
  ipip 31
}

idpr PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Inter-Domain Policy Routing Protocol"
REFERENCE
  "RFC 1479 [RFC1479] defines Version 1 of the Inter-Domain Policy
   Routing Protocol."
 ::= {
  ip 35,
  ipip4 35,
  ipip 35
}

idpr-cmtp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "IDPR Control Message Transport Protocol"
REFERENCE
  "RFC 1479 [RFC1479] defines Version 1 of the Inter-Domain Policy
   Routing Protocol."
 ::= {
  ip 38,
  ipip4 38,
  ipip 38
}
```

```
sdrp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Source Demand Routing Protocol"
REFERENCE
  "RFC 1940 [RFC1940] defines version 1 of the Source Demand
  Routing: Packet Format and Forwarding Specification"
 ::= {
  ip 42,
  ipip4 42,
  ipip 42
}

idrp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Inter-Domain Routing Protocol"
REFERENCE
  "RFC 1745 [RFC1745] defines BGP4/IDRP for IP."
 ::= {
  ip 45,
  ipip4 45,
  ipip 45
}

rsvp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Resource Reservation Setup Protocol"
REFERENCE
  "Resource ReSerVation Protocol (RSVP); Version 1 Functional
  Specification [RFC2205]."
 ::= {
  ip 46,
  ipip4 46,
  ipip 46
}

gre PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "General Routing Encapsulation"
REFERENCE
  "RFC 1701 [RFC1701] defines Generic Routing Encapsulation (GRE);
```

```
RFC 1702 [RFC1702] defines Generic Routing Encapsulation over
IPv4 networks"
 ::= {
 ip 47,
 ipip4 47,
 ipip 47
}

nhrp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
 "NBMA Next Hop Resolution Protocol (NHRP)"
REFERENCE
 "RFC 2332 [RFC2332] defines the Next Hop Resolution Protocol."
 ::= {
 ip 54,
 ipip4 54,
 ipip 54
}

priv-host PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
 "Pseudo-protocol reserved for any internal host protocol."
REFERENCE
 "[RFC1700]"
 ::= {
 ip 61,
 ipip4 61,
 ipip 61
}

priv-net PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
 "Pseudo-protocol reserved for any local network protocol."
REFERENCE
 "[RFC1700]"
 ::= {
 ip 63,
 ipip4 63,
 ipip 63
}

priv-distfile PROTOCOL-IDENTIFIER
```

```
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "Pseudo-protocol reserved for any distributed file system."
REFERENCE
    "[RFC1700]"
:= {
    ip 68,
    ipip4 68,
    ipip 68
}

dgp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "Dissimilar Gateway Protocol"
REFERENCE
    "M/A-COM Government Systems, 'Dissimilar Gateway Protocol
     Specification, Draft Version', Contract no. CS901145, November
     16, 1987."
:= {
    ip 86,
    ipip4 86,
    ipip 86
}

igrp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "IGRP; Cisco routing protocol"
REFERENCE
    "Cisco Systems, Inc."
:= {
    ip 88,
    ipip4 88,
    ipip 88
}

ospf PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "Open Shortest Path First Interior GW Protocol (OSPFIGP)."
REFERENCE
    "RFC 1583 [RFC1583] defines version 2 of the OSPF protocol."
:= {
```

```

ip 89,
ipip4 89,
ipip 89
}

mtp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "Multicast Transport Protocol"
REFERENCE
    "RFC 1301 [RFC1301] defines the Multicast Transport Protocol."
::= {
    ip 92,
    ipip4 92,
    ipip 92
}

ax-25 PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "AX.25 Frame Encapsulation"
REFERENCE
    "RFC 1226 [RFC1226] defines Internet Protocol Encapsulation of
     AX.25 Frames."
::= {
    ip 93,
    ipip4 93,
    ipip 93
}

ipip PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES {
    hasChildren(0),
    addressRecognitionCapable(1)
}
DESCRIPTION
    "IP-within-IP Encapsulation Protocol"
CHILDREN
    "Children of 'ipip' are selected and encoded in the same manner
     as children of IP."
ADDRESS-FORMAT
    "The 'ipip' address format is the same as the IP address format."
DECODING
    "Note: ether2.ip.ipip.udp is a different protocolDirID than
     ether2.ip.udp, as identified in the protocolDirTable. As such,

```

two different local protocol index values will be assigned by the agent. E.g. (full INDEX values shown):

```
ether2.ip.ipip.udp =
    16.0.0.0.1.0.0.8.0.0.0.0.94.0.0.0.17.4.0.0.0.0
ether2.ip.udp =
    12.0.0.0.1.0.0.8.0.0.0.0.17.3.0.0.0 "
```

**REFERENCE**

"RFC 2003 [RFC2003] defines IP Encapsulation within IP."

```
::= {
  ip 94,
  ipip4 94,
  ipip 94
}
```

**encap PROTOCOL-IDENTIFIER**

**PARAMETERS { }**

**ATTRIBUTES { }**

**DESCRIPTION**

"Encapsulation Header; A Scheme for an Internet Encapsulation Protocol: Version 1"

**REFERENCE**

"RFC 1241 [RFC1241] defines version 1 of the ENCAP Protocol."

```
::= {
  ip 98,
  ipip4 98,
  ipip 98
}
```

**priv-encrypt PROTOCOL-IDENTIFIER**

**PARAMETERS { }**

**ATTRIBUTES { }**

**DESCRIPTION**

"Pseudo-protocol reserved for any private encryption scheme."

**REFERENCE**

"[RFC1700]"

```
::= {
  ip 99,
  ipip4 99,
  ipip 99
}
```

```
-- ****
-- 
--          Children of UDP and TCP
-- 
-- ****
```

**tcpmux PROTOCOL-IDENTIFIER**

```
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "TCP Port Service Multiplexer Port."
REFERENCE
  "RFC 1078 [RFC1078] defines the TCP Port Service Multiplexer
Protocol."
 ::= { tcp 1 }

rje PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Remote Job Entry Protocol; RJE Logger Port; (historical)."
REFERENCE
  "RFC 407 [RFC407] defines the Remote Job Entry Protocol."
 ::= { tcp 5 }

echo PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Echo Protocol for debugging TCP and UDP transports."
REFERENCE
  "RFC 862 [RFC862] defines the Echo Protocol."
 ::= {
    tcp 7,
    udp 7  }

discard PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Discard Protocol for debugging TCP and UDP transports."
REFERENCE
  "RFC 863 [RFC863] defines the Discard Protocol."
 ::= {
    tcp 9,
    udp 9  }

systat PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Retrieve the Active Users list; a debugging tool for TCP and UDP
transports."
REFERENCE
  "RFC 866 [RFC866] defines the Active Users Protocol."
```

```
: := {
  tcp 11,
  udp 11  }

daytime PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Retrieve the current time of day; a debugging tool for TCP and
  UDP transports."
REFERENCE
  "RFC 867 [RFC867] defines the Daytime Protocol."
: := {
  tcp 13,
  udp 13  }

qotd PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Quote of the Day Protocol; retrieve a short message (up to 512
  bytes); a debugging tool for TCP and UDP transports."
REFERENCE
  "RFC 865 [RFC865] defines the Quote of the Day Protocol."
: := {
  tcp 17,
  udp 17  }

msp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Message Send Protocol"
REFERENCE
  "RFC 1312 [RFC1312] defines the Message Send Protocol."
: := {
  tcp 18,
  udp 18  }

chargen PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Character Generator Protocol; a debugging tool for TCP and UDP
  transports."
REFERENCE
  "RFC 864 [RFC864] defines the Character Generator Protocol."
```

```
: := {  
    tcp 19,  
    udp 19  }  
  
ftp-data PROTOCOL-IDENTIFIER  
PARAMETERS { }  
ATTRIBUTES { }  
DESCRIPTION  
    "The File Transfer Protocol Data Port; the FTP Server process  
    default data-connection port. "  
REFERENCE  
    "RFC 959 [RFC959] defines the File Transfer Protocol. Refer to  
    section 3.2 of [RFC959] for details on FTP data connections."  
: := { tcp 20 }  
  
ftp PROTOCOL-IDENTIFIER  
PARAMETERS { }  
ATTRIBUTES { }  
DESCRIPTION  
    "The File Transfer Protocol Control Port; An FTP client initiates  
    an FTP control connection by sending FTP commands from user port  
    (U) to this port."  
REFERENCE  
    "RFC 959 [RFC959] defines the File Transfer Protocol."  
: := { tcp 21 }  
  
telnet PROTOCOL-IDENTIFIER  
PARAMETERS { }  
ATTRIBUTES { }  
DESCRIPTION  
    "The Telnet Protocol; The purpose of the TELNET Protocol is to  
    provide a fairly general, bi-directional, eight-bit byte oriented  
    communications facility. Its primary goal is to allow a standard  
    method of interfacing terminal devices and terminal-oriented  
    processes to each other. "  
REFERENCE  
    "RFC 854 [RFC854] defines the basic Telnet Protocol."  
: := { tcp 23 }  
  
priv-mail PROTOCOL-IDENTIFIER  
PARAMETERS { }  
ATTRIBUTES { }  
DESCRIPTION  
    "Pseudo-protocol reserved for any private mail system."  
REFERENCE  
    "[RFC1700]"  
: := { tcp 24,  
      udp 24 }
```

```
smtp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "The Simple Mail Transfer Protocol; SMTP control and data
  messages are sent on this port."
REFERENCE
  "RFC 821 [RFC821] defines the basic Simple Mail Transfer
  Protocol."
 ::= { tcp 25 }

priv-print PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Pseudo-protocol reserved for any private printer server."
REFERENCE
  "[RFC1700]"
 ::= { tcp 35,
      udp 35 }

time PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Time Protocol"
REFERENCE
  "RFC 868 [RFC868] defines the Time Protocol."
 ::= { tcp 37,
      udp 37 }

rap PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Route Access Protocol"
REFERENCE
  "RFC 1476 [RFC1476] defines the Internet Route Access Protocol."
 ::= { tcp 38 }

rlp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Resource Location Protocol"
REFERENCE
  "RFC 887 [RFC887] defines the Resource Location Protocol."
 ::= { udp 39 }
```

```
graphics PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Graphics Protocol"
REFERENCE
  "RFC 493 [RFC493] defines the Graphics Protocol."
 ::= { tcp 41,
       udp 41 }

nameserver PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Host Name Server Protocol"
REFERENCE
  "IEN 116 [IEN116] defines the Internet Name Server."
 ::= { udp 42 }

nicname PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "NICNAME/WHOIS Protocol"
REFERENCE
  "RFC 954 [RFC954] defines the NICNAME/Who Is Protocol."
 ::= { tcp 43 }

mpm-flags PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "MPM FLAGS Protocol; (historical)."
REFERENCE
  "RFC 759 [RFC759] defines the Message Processing Module."
 ::= { tcp 44 }

mpm PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Message Processing Module -- Receiver; (historical)."
REFERENCE
  "RFC 759 [RFC759] defines the Message Processing Module."
 ::= { tcp 45 }

mpm-snd PROTOCOL-IDENTIFIER
PARAMETERS { }
```

```
ATTRIBUTES { }
DESCRIPTION
  "Message Processing Module -- Default Send; (historical)."
REFERENCE
  "RFC 759 [RFC759] defines the Message Processing Module."
 ::= { tcp 46 }

tacacs  PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Login Host Protocol (TACACS)"
REFERENCE
  "An Access Control Protocol, Sometimes Called TACACS [RFC1492]."
 ::= { tcp 49 }

re-mail-ck  PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Remote Mail Checking Protocol"
REFERENCE
  "RFC 1339 [RFC1339] defines the Remote Mail Checking Protocol."
 ::= { udp 50 }

xns-time  PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "XNS Time Protocol"
REFERENCE
  "Xerox Corporation"
 ::= { tcp 52,
      udp 52 }

domain PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Domain Name Service Protocol; DNS may be transported by either
  UDP [RFC768] or TCP [RFC793].  If the transport is UDP, DNS
  requests restricted to 512 bytes in length may be sent to this
  port."
REFERENCE
  "RFC 1035 [RFC1035] defines the Bootstrap Protocol."
 ::= { udp 53,
      tcp 53 }
```

```
xns-ch PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "XNS Clearinghouse"
REFERENCE
  "Xerox Corporation"
 ::= { tcp 54,
      udp 54 }

xns-auth PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "XNS Authentication Protocol"
REFERENCE
  "Xerox Corporation"
 ::= { tcp 56,
      udp 56 }

priv-term PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Pseudo-protocol reserved for any private terminal access
 protocol."
REFERENCE
  "[RFC1700]"
 ::= { tcp 57,
      udp 57 }

xns-mail PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "XNS Mil Protocol"
REFERENCE
  "Xerox Corporation"
 ::= { tcp 58,
      udp 58 }

priv-file PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Pseudo-protocol reserved for any private file service."
REFERENCE
  "[RFC1700]"
```

```
: := { tcp 59,
      udp 59 }

tacacs-ds PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Default Server Port; TACACS Access Control Protocol Database
   Service."
REFERENCE
  "RFC 1492 [RFC1492] defines the TACACS Protocol."
: := { tcp 65 }

sqlnet PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Oracle SQL*NET"
REFERENCE
  "Oracle Corporation"
: := { tcp 66 }

bootps PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Bootstrap Protocol Server Protocol; BOOTP Clients send requests
   (usually broadcast) to the bootps port."
REFERENCE
  "RFC 951 [RFC951] defines the Bootstrap Protocol."
: := { udp 67 }

bootpc PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Bootstrap Protocol Client Protocol; BOOTP Server replies are
   sent to the BOOTP Client using this destination port."
REFERENCE
  "RFC 951 [RFC951] defines the Bootstrap Protocol."
: := { udp 68 }

tftp PROTOCOL-IDENTIFIER
PARAMETERS {
  tracksSessions(1)
}
ATTRIBUTES { }
DESCRIPTION
```

"Trivial File Transfer Protocol; Only the first packet of each TFTP transaction will be sent to port 69. If the tracksSessions attribute is set, then packets for each TFTP transaction will be attributed to tftp, instead of the unregistered port numbers that will be encoded in subsequent packets."

**REFERENCE**

"RFC 1350 [RFC1350] defines the TFTP Protocol (revision 2);  
RFC 1782 [RFC1782] defines TFTP Option Extensions;  
RFC 1783 [RFC1783] defines the TFTP Blocksize Option;  
RFC 1784 [RFC1784] defines TFTP Timeout Interval and Transfer  
Size Options."  
 ::= { udp 69 }

**gopher PROTOCOL-IDENTIFIER**

PARAMETERS { }  
ATTRIBUTES { }  
DESCRIPTION

"Internet Gopher Protocol"

**REFERENCE**

"RFC 1436 [RFC1436] defines the Gopher Protocol."  
 ::= { tcp 70 }

**netrjs-1 PROTOCOL-IDENTIFIER**

PARAMETERS { }  
ATTRIBUTES { }  
DESCRIPTION

"Remote Job Service Protocol; (historical)."

**REFERENCE**

"RFC 740 [RFC740] defines the NETRJS Protocol."  
 ::= { tcp 71 }

**netrjs-2 PROTOCOL-IDENTIFIER**

PARAMETERS { }  
ATTRIBUTES { }  
DESCRIPTION

"Remote Job Service Protocol; (historical)."

**REFERENCE**

"RFC 740 [RFC740] defines the NETRJS Protocol."  
 ::= { tcp 72 }

**netrjs-3 PROTOCOL-IDENTIFIER**

PARAMETERS { }  
ATTRIBUTES { }  
DESCRIPTION

"Remote Job Service Protocol; (historical)."

**REFERENCE**

"RFC 740 [RFC740] defines the NETRJS Protocol."  
 ::= { tcp 73 }

```
netrjs-4 PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Remote Job Service Protocol; (historical)."
REFERENCE
  "RFC 740 [RFC740] defines the NETRJS Protocol."
 ::= { tcp 74 }

priv-dialout PROTOCOL-IDENTIFIER

PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Pseudo-protocol reserved for any private dial out service."
REFERENCE
  "[RFC1700]"
 ::= { tcp 75,
      udp 75 }

priv-rje PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Pseudo-protocol reserved for any private remote job entry
service."
REFERENCE
  "[RFC1700]"
 ::= { tcp 77,
      udp 77 }

finger PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Finger User Information Protocol"
REFERENCE
  "RFC 1288 [RFC1288] defines the finger protocol."
 ::= { tcp 79 }

www-http PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Hypertext Transfer Protocol"
REFERENCE
  "RFC 1945 [RFC1945] defines the Hypertext Transfer Protocol
(HTTP/1.0).
```

RFC 2068 [RFC2068] defines the Hypertext Transfer Protocol (HTTP/1.1).  
RFC 2069 [RFC2069] defines an Extension to HTTP: Digest Access Authentication.  
RFC 2109 [RFC2109] defines the HTTP State Management Mechanism.  
RFC 2145 [RFC2145] defines the use and interpretation of HTTP version numbers."  
 ::= { tcp 80 }

**priv-terminal PROTOCOL-IDENTIFIER**

PARAMETERS { }  
ATTRIBUTES { }  
DESCRIPTION  
 "Pseudo-protocol reserved for any private terminal link protocol."  
REFERENCE  
 "[RFC1700]"  
 ::= { tcp 87,  
 udp 87 }

**kerberos PROTOCOL-IDENTIFIER**

PARAMETERS { }  
ATTRIBUTES { }  
DESCRIPTION  
 "The Kerberos Network Authentication Service (V5)"  
REFERENCE  
 "RFC 1510 [RFC1510] defines the Kerberos protocol."  
 ::= { udp 88 }

**supdup PROTOCOL-IDENTIFIER**

PARAMETERS { }  
ATTRIBUTES { }  
DESCRIPTION  
 "SUPDUP Display; (historical)"  
REFERENCE  
 "RFC 734 [RFC734] defines the SUPDUP Protocol."  
 ::= { tcp 95 }

**dixie PROTOCOL-IDENTIFIER**

PARAMETERS { }  
ATTRIBUTES { }  
DESCRIPTION  
 "DIXIE Directory Service"  
REFERENCE  
 "RFC 1249 [RFC1249] defines the DIXIE Protocol."  
 ::= { tcp 96,  
 udp 96 }

```
hostname PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "NIC Internet Hostname Server Protocol; (historical)"
REFERENCE
  "RFC 953 [RFC953] defines the Hostname Server Protocol."
 ::= { tcp 101 }

3com-tsmux PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "3COM-TSMUX"
REFERENCE
  "3Com, Inc."
 ::= { tcp 106,
      udp 106 }

rtelnet PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Remote User Telnet Protocol; (historical)."
REFERENCE
  "RFC 818 [RFC818] defines the Remote User Telnet Service."
 ::= { tcp 107 }

pop2 PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Post Office Protocol -- Version 2. Clients establish connections
   with POP2 servers by using this destination port number.
   Historical."
REFERENCE
  "RFC 937 [RFC937] defines Version 2 of the Post Office Protocol."
 ::= { tcp 109 }

pop3 PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Post Office Protocol -- Version 3. Clients establish connections
   with POP3 servers by using this destination port number."
REFERENCE
  "RFC 1725 [RFC1725] defines Version 3 of the Post Office
   Protocol."
```

```
::= { tcp 110,
      udp 110 }      -- RFC defines tcp use
```

#### sunrpc PROTOCOL-IDENTIFIER

```
PARAMETERS {
    tracksSessions(1) -- learn port mapping of programs
}
```

```
ATTRIBUTES {
    hasChildren(0) -- port mapper function numbers
}
```

#### DESCRIPTION

"SUN Remote Procedure Call Protocol. Port mapper function requests are sent to this destination port."

#### CHILDREN

"Specific RPC functions are represented as children of the sunrpc protocol. Each 'RPC function protocol' is identified by its function number assignment. RPC function number assignments are defined by different naming authorities, depending on the function identifier value.

From [RFC1831]:

Program numbers are given out in groups of hexadecimal 20000000 (decimal 536870912) according to the following chart:

0 - 1fffffff	defined by rpc@sun.com
20000000 - 3fffffff	defined by user
40000000 - 5fffffff	transient
60000000 - 7fffffff	reserved
80000000 - 9fffffff	reserved
a0000000 - bfffffff	reserved
c0000000 - dfffffff	reserved
e0000000 - ffffffff	reserved

Children of 'sunrpc' are encoded as [ 0.0.0.111], the protocol identifier component for 'sunrpc', followed by [ a.b.c.d ], where a.b.c.d is the 32 bit binary RPC program number encoded in network byte order. For example, a protocolDirID-fragment value of:

0.0.0.111.0.1.134.163

defines the NFS function (and protocol).

Children are named as 'sunrpc' followed by the RPC function number in base 10 format. For example, NFS would be named:

'sunrpc 100003'."

#### DECODING

"The first packet of many SUNRPC transactions is sent to the

port-mapper program, and therefore decoded statically by monitoring RFC portmap requests [RFC1831]. Any subsequent packets must be decoded and correctly identified by 'remembering' the port assignments used in each RPC function call (as identified according to the procedures in the RPC Specification Version 2 [RFC1831]).

In some cases the port mapping for a particular protocol is well known and hard coded into the requesting client. In these cases the client will not send portmap requests; instead it will send the SUNRPC request directly to the well known port. These cases are rare and are being eliminated over time. NFS is the most significant SUNRPC program of this class. Such programs should still be declared as children of SUNRPC as described under CHILDREN above. How an implementation detects this behaviour and handles it is beyond the scope of this document.

The 'tracksSessions(1)' PARAMETER bit is used to indicate whether the probe can (and should) monitor portmapper activity to correctly track SUNRPC connections."

#### REFERENCE

"RFC 1831 [RFC1831] defines the Remote Procedure Call Protocol Version 2. The authoritative list of RPC Functions is identified by the URL:

ftp://ftp.isi.edu/in-notes/iana/assignments/sun-rpc-numbers"

```
::= { tcp 111,
      udp 111 }
```

#### auth PROTOCOL-IDENTIFIER

PARAMETERS { }

ATTRIBUTES { }

#### DESCRIPTION

"Authentication Service; Identification Protocol."

#### REFERENCE

"RFC 1413 [RFC1413] defines the Identification Protocol."

```
::= { tcp 113 }
```

#### sftp PROTOCOL-IDENTIFIER

PARAMETERS { }

ATTRIBUTES { }

#### DESCRIPTION

"Simple File Transfer Protocol; (historical)."

#### REFERENCE

"RFC 913 [RFC913] defines the Simple File Transfer Protocol."

```
::= { tcp 115 }
```

#### uucp-path PROTOCOL-IDENTIFIER

```
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "UUCP Path Service"
REFERENCE
  "RFC 915 [RFC915] defines the Network Mail Path Service."
 ::= { tcp 117 }

nntp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Network News Transfer Protocol"
REFERENCE
  "RFC 977 [RFC977] defines the Network News Transfer Protocol."
 ::= { tcp 119 }

cfdptkt PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "CFDPTKT; Coherent File Distribution Protocol"
REFERENCE
  "RFC 1235 [RFC1235] defines the Coherent File Distribution
Protocol."
 ::= { udp 120 }

ntp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Network Time Protocol"
REFERENCE
  "RFC 1305 [RFC1305] defines version 3 of the Network Time
Protocol."
 ::= { udp 123 }

pwdgen PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Password Generator Protocol"
REFERENCE
  "RFC 972 [RFC972] defines the Password Generator Protocol."
 ::= { tcp 129,
      udp 129 }

cisco-fna PROTOCOL-IDENTIFIER
```

```
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "cisco FNATIVE"
REFERENCE
  "Cisco Systems, Inc."
 ::= { tcp 130,
      udp 130 }

cisco-tna  PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "cisco TNATIVE"
REFERENCE
  "Cisco Systems, Inc."
 ::= { tcp 131,
      udp 131 }

cisco-sys  PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "cisco SYSMAINT"
REFERENCE
  "Cisco Systems, Inc."
 ::= { tcp 132,
      udp 132 }

statsrv  PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Statistics Server; (historical)."
REFERENCE
  "RFC 996 [RFC996] defines the Statistics Server Protocol."
 ::= { tcp 133,
      udp 133 }

-- defined as nbt-name in IPX section
-- netbios-ns      137/tcp     NETBIOS Name Service
-- netbios-ns      137/udp     NETBIOS Name Service
-- defined as nbt-data in IPX section
-- netbios-dgm    138/tcp     NETBIOS Datagram Service
-- netbios-dgm    138/udp     NETBIOS Datagram Service

-- defined as nbt-session in IPX section
-- netbios-ssn    139/tcp     NETBIOS Session Service
```

```
-- netbios-ssn      139/udp      NETBIOS Session Service

imap2  PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Interactive Mail Access Protocol v2;
   Internet Message Access Protocol v4 (IMAP4) also uses this
   server port."
REFERENCE
  "RFC 1064 [RFC1064] defines Version 2 of the Interactive Mail
   Access
   Protocol.
  RFC 1730 [RFC1730] defines Version 4 of the Internet Message
   Access
   Protocol."
::= { tcp 143 }

iso-tp0  PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "ISO-TP0; ISO-TP0 bridge between TCP and X.25"
REFERENCE
  "RFC 1086 [RFC1086] defines the ISO-TP0 protocol."
::= { tcp 146,
      udp 146 }

iso-ip  PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "ISO-IP; Use of the Internet as a Subnetwork for Experimentation
   with the OSI Network Layer"
REFERENCE
  "RFC 1070 [RFC1070] defines the ISO-IP Protocol."
::= { tcp 147,
      udp 147 }

hems  PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "HEMS; High Level Entity Management System; (historical)."
REFERENCE
  "RFC 1021 [RFC1021] defines HEMS."
::= { tcp 151 }
```

```
bftp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Background File Transfer Program"
REFERENCE
  "RFC 1068 [RFC1068] defines the Background File Transfer
  Program."
 ::= { tcp 152 }

sgmp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Simple Gateway Monitoring Protocol; (historical)."
REFERENCE
  "RFC 1028 [RFC1028] defines the Simple Gateway Monitoring
  Protocol."
 ::= { udp 153 }

pcmail-srv PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "PCMail Server; Distributed Mail System Protocol (DMSP)"
REFERENCE
  "RFC 1056 [RFC1056] defines the PCMAIL Protocol."
 ::= { tcp 158 }

sgmp-traps PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Simple Gateway Monitoring Protocol Traps; (historical)."
REFERENCE
  "RFC 1028 [RFC1028] defines the Simple Gateway Monitoring
  Protocol."
 ::= { udp 160 }

-- snmp and snmptrap found in the Protocol-Independent section
-- snmp          161/udp    SNMP
-- snmptrap      162/udp    SNMPTRAP

cmip-man PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
```

```
"CMIP/TCP (CMOT) Manager; (historical)."
REFERENCE
  "RFC 1095 [RFC1095] defines the Common Management Information
  Services and Protocol over TCP/IP."
  ::= { tcp 163,
        udp 163 }

cmip-agent PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "CMIP/TCP (CMOT) Agent; (historical)."
REFERENCE
  "RFC 1095 [RFC1095] defines the Common Management Information
  Services and Protocol over TCP/IP."
  ::= { tcp 164,
        udp 164 }

xdmcp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "X Display Manager Control Protocol"
REFERENCE
  "X11 Consortium"
  ::= { udp 177 }

bgp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Border Gateway Protocol"
REFERENCE
  "RFC 1267 [RFC1267] defines version 3 of the Border Gateway
  Protocol."
  ::= { tcp 179 }

remote-kis PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Remote-Knowbot Information Service (KIS)"
REFERENCE
  "RFC 1739 [RFC1739] describes the KNOWBOT Protocol."
  ::= { tcp 185,
        udp 185 }
```

```

kis PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Knowbot Information Service (KIS)"
REFERENCE
  "RFC 1739 [RFC1739] describes the KNOWBOT Protocol."
 ::= { tcp 186,
       udp 186 }

irc PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Internet Relay Chat Protocol"
REFERENCE
  "RFC 1459 [RFC1459] defines the Internet Relay Chat Protocol."
 ::= { tcp 194,
       udp 194 }

smux PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "SMUX; SNMP MUX Protocol and MIB; (historical)."
REFERENCE
  "RFC 1227 [RFC1227] defines the SMUX Protocol."
 ::= { tcp 199 }

-- AppleTalk applications are defined in the AppleTalk Stack section
--
-- at-rtmp      201/tcp    AppleTalk Routing Maintenance
-- at-rtmp      201/udp    AppleTalk Routing Maintenance
-- at-nbp       202/tcp    AppleTalk Name Binding
-- at-nbp       202/udp    AppleTalk Name Binding
-- at-3         203/tcp    AppleTalk Unused
-- at-3         203/udp    AppleTalk Unused
-- at-echo      204/tcp    AppleTalk Echo
-- at-echo      204/udp    AppleTalk Echo
-- at-5          205/tcp    AppleTalk Unused
-- at-5          205/udp    AppleTalk Unused
-- at-zis       206/tcp    AppleTalk Zone Information
-- at-zis       206/udp    AppleTalk Zone Information
-- at-7          207/tcp    AppleTalk Unused
-- at-7          207/udp    AppleTalk Unused
-- at-8          208/tcp    AppleTalk Unused
-- at-8          208/udp    AppleTalk Unused

```

```
z39-50 PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "ANSI Z39.50"
REFERENCE
  "RFC 1729 [RFC1729] describes the Z39.50 Protocol."
::= { tcp 210 }

ipx-tunnel PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Tunneling IPX Traffic through IP Networks"
REFERENCE
  "RFC 1234 [RFC1234] defines the IPX Tunnel Protocol."
::= { udp 213 }

mpp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Netix Message Posting Protocol"
REFERENCE
  "RFC 1204 [RFC1204] defines the Message Posting Protocol."
::= { tcp 218 }

imap3 PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Interactive Mail Access Protocol v3; (historical)."
REFERENCE
  "RFC 1203 [RFC1203] defines version 3 of the Interactive Mail
Access Protocol."
::= { tcp 220 }

ldap PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Lightweight Directory Access Protocol"
REFERENCE
  "RFC 1777 [RFC1777] defines Lightweight Directory Access
Protocol; RFC 1798 [RFC1798] defines Connection-less Lightweight
X.500 Directory Access Protocol"
::= { tcp 389,          -- RFC 1777
      udp 389 }         -- RFC 1798
```

```
mobileip-agent PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "IP Mobility Support"
REFERENCE
  "RFC 2002 [RFC2002] defines the IP Mobility Support protocol."
::= { udp 434 }

https PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Secure HTTP; HTTP over TLS/SSL"
REFERENCE
  "Netscape; http://home.netscape.com/eng/ssl3/"
::= { tcp 443 }

smtps PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "SMTP protocol over TLS/SSL"
REFERENCE
  "Netscape; http://home.netscape.com/eng/ssl3/"
::= { tcp 465 }

isakmp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Internet Security Association and Key Management Protocol
  (ISAKMP)"
REFERENCE
  "RFC 2408 [RFC2408]"
::= { udp 500 }

login PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "BSD Rlogin; remote login a la telnet"
REFERENCE
  "RFC 1282 [RFC1282] defines the BSD Rlogin Protocol."
::= { tcp 513 }

syslog PROTOCOL-IDENTIFIER
PARAMETERS { }
```

```
ATTRIBUTES { }
DESCRIPTION
  "syslog"
REFERENCE
  "[RFC1700]"
 ::= { udp 514 }

uucp  PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Unix-to-Unix copy protocol"
REFERENCE
  "[RFC1700]"
 ::= { tcp 540 }

doom  PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "DOOM Game;"
REFERENCE
  " Id Software"
 ::= { tcp 666 }

radius  PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Remote Authentication Dial In User Service (RADIUS)"
REFERENCE
  "RFC 2138 [RFC2138] defines the Radius protocol."
 ::= { udp 1812 }

radiusacct  PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "RADIUS Accounting Protocol"
REFERENCE
  "RFC 2139 [RFC2139] defines the Radius Accounting protocol."
 ::= { udp 1813 }

-- Portmapper Functions; Children of sunrpc
--

portmapper PROTOCOL-IDENTIFIER
```

```
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "SUNRPC PORTMAPPER program. This is the SUNRPC program which is
  used to locate the UDP/TCP ports on which other SUNRPC programs
  can be found."
REFERENCE
  "Appendix A of RFC 1057 [RFC1057] describes the portmapper
  operation."
 ::= { sunrpc 100000 }

nfs PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Sun Network File System (NFS);"
DECODING
  "NFS is a SUNRPC program which may or may not use the port mapper
  SUNRPC program to connect clients and servers. In many cases the
  NFS server program runs over UDP/TCP port 2049, but an
  implementation is encouraged to perform further analysis before
  assuming that a packet to/from this port is a SUNRPC/NFS packet.
  Likewise an implementation is encouraged to track port mapper
  activity to spot cases where it is used to locate the SUNRPC/NFS
  program as this is more robust."
REFERENCE
  "The NFS Version 3 Protocol Specification is defined in RFC 1813
  [RFC1813]."
 ::= {
  sunrpc 100003      -- [0.1.134.163]
}

xwin PROTOCOL-IDENTIFIER
PARAMETERS {
  tracksSessions(1)
}
ATTRIBUTES { }
DESCRIPTION
  "X Windows Protocol"
DECODING
  "The X Windows Protocol when run over UDP/TCP normally runs over
  the well known port 6000. It can run over any port in the range
  6000 to 6063, however. If the tracksSessions(1) parameter bit is
  set the agent can and should detect such X Window sessions and
  report them as the X protocol."
REFERENCE
  "The X Windows Protocol is defined by TBD"
 ::= {
```

```

tcp 6000,
udp 6000
-- lat ?
}

```

### 3.1.2. Novell IPX Stack

ipx PROTOCOL-IDENTIFIER

PARAMETERS { }

ATTRIBUTES {

```

hasChildren(0),
addressRecognitionCapable(1)
}
```

DESCRIPTION

"Novell IPX"

CHILDREN

"Children of IPX are defined by the 8 bit packet type field. The value is encoded into an octet string as [ 0.0.0.a ], where 'a' is the single octet of the packet type field.

Notice that in many implementations of IPX usage of the packet type field is inconsistent with the specification and implementations are encouraged to use other techniques to map inconsistent values to the correct value (which in these cases is typically the Packet Exchange Protocol). It is beyond the scope of this document to describe these techniques in more detail.

Children of IPX are encoded as [ 0.0.0.a ], and named as 'ipx a' where a is the packet type value. The novell echo protocol is referred to as 'ipx nov-echo' OR 'ipx 2'."

ADDRESS-FORMAT

"4 bytes of Network number followed by the 6 bytes Host address each in network byte order."

REFERENCE

"The IPX protocol is defined by the Novell Corporation

A complete description of IPX may be secured at the following address:

Novell, Inc.  
 122 East 1700 South  
 P. O. Box 5900  
 Provo, Utah 84601 USA  
 800 526 5463  
 Novell Part # 883-000780-001"

```
 ::= {
ether2      0x8137,      -- [0.0.129.55]
snap        0x8137,      -- [0.0.129.55]
```

```

        ianaAssigned 1,          -- [ 0.0.0.1 ]  (ipxOverRaw8023)
    llc      224,           -- [ 0.0.0.224 ]
    802-1Q   0x8137,        -- [ 0.0.129.55 ]
    802-1Q   0x020000e0,    -- 1Q-LLC [ 2.0.0.224 ]
    802-1Q   0x05000001    -- 1Q-IANA [ 5.0.0.1 ]
                                -- (ipxOverRaw8023)
}

nov-rip PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "Novell Routing Information Protocol"
REFERENCE
    "Novell Corporation"
:= {
    ipx 0x01,      -- when reached by IPX packet type
    nov-pep 0x0453 -- when reached by IPX socket number
}

nov-echo PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "Novell Echo Protocol"
REFERENCE
    "Novell Corporation"
:= { ipx 0x02 }

nov-error PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "Novell Error-handler Protocol"
REFERENCE
    "Novell Corporation"
:= { ipx 0x03 }

nov-pep PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES {
    hasChildren(0)
}
DESCRIPTION
    "Novell Packet Exchange Protocol. This is really a null protocol
     layer as all IPX packets contain the relevant fields for this
     protocol. This protocol is defined so that socket-based decoding
     has a point of attachment in the decode tree while still allowing

```

packet type based decoding also."

**CHILDREN**

"Children of PEP are defined by the 16 bit socket values. The value is encoded into an octet string as [ 0.0.a.b ], where 'a' and 'b' are the network byte order encodings of the MSB and LSB of the socket value.

Each IPX/PEP packet contains two sockets, source and destination. How these are mapped onto the single well-known socket value used to identify its children is beyond the scope of this document."

**REFERENCE**

```
"Novell Corporation"
 ::= {
   -- ipx 0x00      ** Many third party IPX's use this value always
   ipx 0x04        -- Xerox assigned for PEP
   -- ipx 0x11      ** Novell use this for PEP packets, often
 }
```

**nov-spx PROTOCOL-IDENTIFIER**

```
PARAMETERS {
ATTRIBUTES {
hasChildren(0)
}
```

**DESCRIPTION**

"Novell Sequenced Packet Exchange Protocol. This protocol is an extension of IPX/PEP as it shares a common header."

**CHILDREN**

"Children of SPX are defined by the 16 bit socket values. The value is encoded into an octet string as [ 0.0.a.b ], where 'a' and 'b' are the network byte order encodings of the MSB and LSB of the socket value.

Each IPX/SPX packet contains two sockets, source and destination. How these are mapped onto the single well-known socket value used to identify its children is beyond the scope of this document."

**REFERENCE**

```
"Novell Corporation"
 ::= {
   ipx 0x05 -- Xerox assigned for SPX
 }
```

**nov-sap PROTOCOL-IDENTIFIER**

```
PARAMETERS {
  tracksSessions(1)
}
ATTRIBUTES {
  hasChildren(0)
}
```

**DESCRIPTION**

"Novell Service Advertising Protocol. This protocol binds applications on a particular host to an IPX/PEP or IPX/SPX socket number. Although it never truly acts as a transport protocol itself it is used to establish sessions between clients and servers and barring well-known sockets is the only reliable way to determine the protocol running over a given socket on a given machine."

**CHILDREN**

"Children of SAP are identified by a 16 bit service type. They are encoded as [ 0.0.a.b ], where 'a' is the MSB and 'b' is the LSB of the service type.

Children of SAP are named as 'nov-sap a' where 'a' is the service type in hexadecimal notation. The novell NCP protocol is referred to as 'nov-sap ncp' OR 'nov-sap 0x0004'."

**DECODING**

"The first packet of any session for a SAP based application (almost all IPX/PEP and IPX/SPX based applications utilize SAP) is sent to the SAP server(s) to map the service type into a port number for the host(s) on which the SAP server(s) is(are) running. These initial packets are SAP packets and not application packets and must be decoded accordingly.

Having established the mapping, clients will then send application packets to the newly discovered socket number. These must be decoded by 'remembering' the socket assignments transmitted in the SAP packets.

In some cases the port mapping for a particular protocol is well known and SAP will always return the same socket number for that application.

Such programs should still be declared as children of nov-sap as described under CHILDREN above. How an implementation detects a client which is bypassing the SAP server to contact a well-known application is beyond the scope of this document.

The 'tracksSessions(1)' PARAMETER bit is used to indicate whether the probe can (and should) monitor nov-sap activity to correctly track SAP-based connections."

**REFERENCE**

"A list of SAP service types can be found at  
<ftp://ftp.isi.edu/in-notes/iana/assignments/novell-sap-numbers>"  
 ::= { nov-pep 0x0452 }

ncp PROTOCOL-IDENTIFIER

```

PARAMETERS {
  tracksSessions(1)
}
ATTRIBUTES {
  hasChildren(0)
}
DESCRIPTION
  "Netware Core Protocol"
CHILDREN
  "Children of NCP are identified by the 8 bit command type field.
  They are encoded as [ 0.0.0.a ] where 'a' is the command type
  value.

  Children of NCP are named as 'ncp a' where 'a' is the command
  type in decimal notation.  The NDS sub-protocol is referred to as
  'ncp nds' OR 'ncp 104'."

DECODING
  "Only the NCP request frames carry the command type field.  How
  the implementation infers the command type of a response frame is
  an implementation specific matter and beyond the scope of this
  document.

The tracksSessions(1) PARAMETERS bit indicates whether the probe
can (and should) perform command type inference."
REFERENCE
  "Novell Corporation"
 ::= { nov-sap 0x0004,
       nov-pep 0x0451 }

nds PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "The Netware Directory Services sub-protocol."
REFERENCE
  "Novell Corporation"
 ::= { ncp 104 }

nov-diag PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Novell's diagnostic Protocol"
REFERENCE
  "Novell Corporation"
 ::= {
   nov-sap 0x0017,    -- [ed., this is the right one]
   nov-pep 0x0456
}

```

```

}

nov-sec PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Novell security - serialization - copy protection protocol."
REFERENCE
  "Novell Corporation"
::= { nov-pep 0x0457 }

nov-watchdog PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Novell watchdog protocol."
REFERENCE
  "Novell Corporation"
::= { nov-pep 0x4004 }

nov-bcast PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Novell broadcast protocol."
REFERENCE
  "Novell Corporation"
::= { nov-pep 0x4005 }

```

### 3.1.3. The XEROX Protocol Stack

```

idp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES {
  hasChildren(0),
  addressRecognitionCapable(1)
}
DESCRIPTION
  "Xerox IDP"
CHILDREN
  "Children of IDP are defined by the 8 bit value of the Packet
  type field. The value is encoded into an octet string as [
  0.0.0.a ], where 'a' is the value of the packet type field in
  network byte order.

  Children of IDP are encoded as [ 0.0.0.a ], and named as 'idp a'
  where a is the packet type value. The XNS SPP protocol is
  referred to as 'idp xns-spp' OR 'idp 2'."

```

```
ADDRESS-FORMAT
  "4 bytes of Network number followed by the 6 bytes Host address
   each in network byte order."
REFERENCE
  "Xerox Corporation, Document XNSS 028112, 1981"
 ::= {
  ether2 0x600,      -- [ 0.0.6.0 ]
  snap    0x600,
  802-1Q 0x600      -- [ 0.0.6.0 ]
}

xns-rip PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Routing Information Protocol."
REFERENCE
  "Xerox Corporation"
 ::= { idp 1 }

xns-echo PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "XNS echo protocol."
REFERENCE
  "Xerox Corporation"
 ::= { idp 2 }

xns-error PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "XNS error-handler protocol."
REFERENCE
  "Xerox Corporation"
 ::= { idp 3 }

xns-pep PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES {
  hasChildren(0)
}
DESCRIPTION
  "XNS Packet Exchange Protocol."
CHILDREN
  "Children of PEP are defined by the 16 bit socket values.  The
```

value is encoded into an octet string as [ 0.0.a.b ], where 'a' and 'b' are the network byte order encodings of the MSB and LSB of the socket value.

Each XNS/PEP packet contains two sockets, source and destination. How these are mapped onto the single well-known socket value used to identify its children is beyond the scope of this document."

#### REFERENCE

"Xerox Corporation"  
::= { idp 4 }

### xns-spp PROTOCOL-IDENTIFIER

PARAMETERS { }  
ATTRIBUTES {  
hasChildren(0)  
}

#### DESCRIPTION

"Sequenced Packet Protocol."

#### CHILDREN

"Children of SPP are defined by the 16 bit socket values. The value is encoded into an octet string as [ 0.0.a.b ], where 'a' and 'b' are the network byte order encodings of the MSB and LSB of the socket value.

Each XNS/SPP packet contains two sockets, source and destination. How these are mapped onto the single well-known socket value used to identify its children is beyond the scope of this document."

#### REFERENCE

"Xerox Corporation"  
::= { idp 5 }

### 3.1.4. AppleTalk Protocol Stack

### apple-oui PROTOCOL-IDENTIFIER

PARAMETERS { }  
ATTRIBUTES { }  
DESCRIPTION

"Pseudo-protocol which binds Apple's protocols to vsnap."

#### CHILDREN

"Children of apple-oui are identified by the ether2 type field value that the child uses when encapsulated in ether2. The value is encoded into an octet string as [ 0.0.a.b ], where 'a' and 'b' are the MSB and LSB of the 16-bit ether type value in network byte order."

#### REFERENCE

"AppleTalk Phase 2 Protocol Specification, document ADPA  
#C0144LL/A."  
::= {

```
vsnap    0x080007,      -- [ 0.8.0.7 ]
802-1Q   0x04080007      -- 1Q-VSNAP [ 4.8.0.7 ]
}

aarp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "AppleTalk Address Resolution Protocol."
REFERENCE
  "AppleTalk Phase 2 Protocol Specification, document ADPA
  #C0144LL/A."
 ::= {
ether2    0x80f3,          -- [ 0.0.128.243 ]
snap      0x80f3,
apple-oui 0x80f3,
802-1Q   0x80f3          -- [ 0.0.128.243 ]
}

atalk PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES {
  hasChildren(0),
  addressRecognitionCapable(1)
}
DESCRIPTION
  "AppleTalk Protocol."
CHILDREN
  "Children of ATALK are defined by the 8 bit value of the DDP type
  field. The value is encoded into an octet string as [ 0.0.0.a ],
  where 'a' is the value of the DDP type field in network byte
  order."
ADDRESS-FORMAT
  "2 bytes of Network number followed by 1 byte of node id each in
  network byte order."
REFERENCE
  "AppleTalk Phase 2 Protocol Specification, document ADPA
  #C0144LL/A."
 ::= {
ether2    0x809b,  -- [ 0.0.128.155 ]
apple-oui 0x809b,
802-1Q   0x809b  -- [ 0.0.128.155 ]
}

rtmp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
```

```
"AppleTalk Routing Table Maintenance Protocol."
REFERENCE
    "Apple Computer"
:= {
    atalk 0x01,      -- responses
    atalk 0x05      -- requests
}

aep PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "AppleTalk Echo Protocol."
REFERENCE
    "Apple Computer"
:= { atalk 0x04 }

nbp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "AppleTalk Name Binding Protocol."
DECODING
    "In order to correctly identify the application protocol running
     over atm NBP packets must be analyzed. The mechanism by which
     this is achieved is beyond the scope of this document."
REFERENCE
    "Apple Computer"
:= { atalk 0x02 }

zip PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "AppleTalk Zone Information Protocol."
REFERENCE
    "Apple Computer"
:= {
    atalk 0x06,
    atm    3
}

atp PROTOCOL-IDENTIFIER
PARAMETERS {
    tracksSessions(1)
}
ATTRIBUTES {
    hasChildren(0)
```

```
}
```

DESCRIPTION  
"AppleTalk Transaction Protocol."

CHILDREN  
"Children of atp are identified by the following (32 bit)  
enumeration:  
1 asp (AppleTalk Session Protocol)  
2 pap (Printer Access Protocol)  
3 zip (Zone Information Protocol)  
Children of atp are encoded as [ a.b.c.d ] where 'a', 'b', 'c'  
and 'd' are the four octets of the enumerated value in network  
order (i.e. 'a' is the MSB and 'd' is the LSB).

The ZIP protocol is referred to as 'atp zip' OR 'atp 3'."  
DECODING

"An implementation is encouraged to examine both the socket  
fields in the associated DDP header as well as the contents of  
prior NBP packets in order to determine which (if any) child is  
present. A full description of this algorithm is beyond the  
scope of this document. The tracksSessions(1) PARAMETER  
indicates whether the probe can (and should) perform this  
analysis."

REFERENCE

"Apple Computer"  
:= { atalk 0x03 }

adsp PROTOCOL-IDENTIFIER

PARAMETERS {  
tracksSessions(1)  
}

ATTRIBUTES {  
hasChildren(0)  
}

DESCRIPTION

"AppleTalk Data Stream Protocol."

CHILDREN

"Children of adsp are identified by enumeration. At this time  
none are known."

DECODING

"An implementation is encouraged to examine the socket numbers in  
the associated DDP header as well as the contents of prior NBP  
packets in order to determine which (if any) child of ADSP is  
present.

The mechanism by which this is achieved is beyond the scope of  
this document.

The tracksSessions(1) PARAMETER indicates whether the probe can

```

        (and should) perform this analysis."
REFERENCE
    "Apple Computer"
::= { atalk 0x07 }

asp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES {
hasChildren(0)
}
DESCRIPTION
    "AppleTalk Session Protocol."
CHILDREN
    "Children of asp are identified by the following (32 bit)
enumeration:
    1   afp (AppleTalk Filing Protocol)
Children of asp are encoded as [ a.b.c.d ] where 'a', 'b', 'c'
and 'd' are the four octets of the enumerated value in network
order (i.e. 'a' is the MSB and 'd' is the LSB).

The AFP protocol is referred to as 'asp afp' OR 'asp 1'."
```

**DECODING**

```

    "ASP is a helper layer to assist in building client/server
protocols. It cooperates with ATP to achieve this; the
mechanisms used when decoding ATP apply equally here (i.e.
checking DDP socket numbers and tracking NBP packets).
```

Hence the tracksSessions(1) PARAMETER of atm applies to this protocol also."

**REFERENCE**

```

    "Apple Computer"
::= { atm 1 }
```

afp PROTOCOL-IDENTIFIER

```

PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "AppleTalk Filing Protocol."
```

**REFERENCE**

```

    "Apple Computer"
::= { asp 1 }
```

pap PROTOCOL-IDENTIFIER

```

PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "AppleTalk Printer Access Protocol."
```

**REFERENCE**

```
"Apple Computer"
 ::= { atp 2 }
```

### 3.1.5. Banyan Vines Protocol Stack

```
vtr PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES {
  hasChildren(0)
}
DESCRIPTION
  "Banyan Vines Token Ring Protocol Header."
CHILDREN
  "Children of vines-tr are identified by the 8 bit packet type
   field. Children are encoded as [ 0.0.0.a ] where 'a' is the
   packet type value.

  The vines-ip protocol is referred to as 'vines-tr vip' OR 'vines-
   tr 0xba'."

REFERENCE
  "See vip."
 ::= {
  llc          0xBC,      -- declared as any LLC, but really TR only.
  802-1Q       0x020000BC  -- 1Q-LLC [2.0.0.188]
}

vecho PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Banyan Vines data link level echo protocol."
REFERENCE
  "See vip."
 ::= {
  ether2        0x0BAF,     -- [0.0.11.175]
  snap          0x0BAF,
  -- vfrp        0x0BAF,
  vtr           0xBB,       -- [ed. yuck!]
  802-1Q        0x0BAF     -- [0.0.11.175]
}

vip PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES {
  hasChildren(0),
  addressRecognitionCapable(1)
}
DESCRIPTION
```

"Banyan Vines Internet Protocol."

**CHILDREN**

"Children of vip are selected by the one-byte 'protocol type' field located at offset 5 in the vip header. The value is encoded as [ 0.0.0.a ], where a is the 'protocol type.' For example, a protocolDirId fragment of:

```
0.0.0.1.0.0.11.173.0.0.0.1
```

identifies an encapsulation of vipc (ether2.vip.vipc)."

**ADDRESS-FORMAT**

"vip packets have 6-byte source and destination addresses. The destination address is located at offset 6 in the vip header, and the source address at offset 12. These are encoded in network byte order."

**REFERENCE**

"Vines Protocol Definition - part# 092093-001, order# 003673

```
BANYAN,
120 Flanders Road,
Westboro, MA 01581 USA"
 ::= {
ether2 0x0BAD,
snap    0x0BAD,
-- vfrp 0x0BAD,
vtr     0xBA,      -- [ed. yuck!]
802-1Q  0x0BAD      -- [0.0.11.173]
}
```

**varp PROTOCOL-IDENTIFIER**

**PARAMETERS { }**

**ATTRIBUTES { }**

**DESCRIPTION**

"Banyan Vines Address Resolution Protocol."

**REFERENCE**

"BANYAN"

```
 ::= { vip 0x04 }
```

**vipc PROTOCOL-IDENTIFIER**

**PARAMETERS { }**

**ATTRIBUTES { }**

**hasChildren(0)**

**}**

**DESCRIPTION**

"Banyan Vines Interprocess Communications Protocol."

**CHILDREN**

"Children of Vines IPC are identified by the packet type field at offset 4 in the vipc header."

These are encoded as [ 0.0.0.a ] where 'a' is the packet type value. Children of vipc are defined as 'vipc a' where 'a' is the packet type value in hexadecimal notation.

The Vines Reliable Data Transport protocol is referred to as 'vipc vipc-rdp' OR 'vipc 0x01'."

#### DECODING

"Children of vipc are deemed to start at the first byte after the packet type field (i.e. at offset 5 in the vipc header)."

#### REFERENCE

"BANYAN"

```
::= { vip 0x01 }
```

```
-- Banyan treats vipc, vipc-dgp and vipc-rdp as one protocol, IPC.
-- Vines IPC really comes in two flavours. The first is used to
-- send unreliable datagrams (vipc packet type 0x00). The second
-- used to send reliable datagrams (vipc packet type 0x01),
-- consisting of up to four actual packets.
-- In order to distinguish between these we need two 'virtual'
-- protocols to identify which is which.
```

#### vipc-dgp PROTOCOL-IDENTIFIER

```
PARAMETERS { }
```

```
ATTRIBUTES {
  hasChildren(0)
}
```

#### DESCRIPTION

"Vines Unreliable Datagram Protocol."

#### CHILDREN

"Children of vipc-dgp are identified by the 16 bit port numbers contained in the vipc (this protocol's parent protocol) header.

These are encoded as [ 0.0.a.b ] where 'a' is the MSB and 'b' is the MSB of the port number in network byte order.

Children of vipc-dgp are defined as 'vipc-dgp a' where 'a' is the port number in hexadecimal notation.

The StreetTalk protocol running over vipc-dgp would be referred to as 'vipc-dgp streettalk' OR 'vipc-dgp 0x00F'.

The mechanism by which an implementation selects which of the source and destination ports to use in determining which child protocol is present is implementation specific and beyond the scope of this document."

#### DECODING

"Children of vipc-dgp are deemed to start after the single padding byte found in the vipc header. In the case of vipc-dgp

the vipc header is a so called 'short' header, total length 6 bytes (including the final padding byte)."

REFERENCE

"BANYAN"

`::= { vipc 0x00 }`

**vipc-rdp PROTOCOL-IDENTIFIER**

PARAMETERS {  
 countsFragments(0)  
}

ATTRIBUTES {  
 hasChildren(0)  
}

DESCRIPTION

"Vines Reliable Datagram Protocol."

CHILDREN

"Children of vipc-rdp are identified by the 16 bit port numbers contained in the vipc (this protocol's parent protocol) header.

These are encoded as [ 0.0.a.b ] where 'a' is the MSB and 'b' is the MSB of the port number in network byte order.

Children of vipc-dgp are defined as 'vipc-rdp a' where 'a' is the port number in hexadecimal notation.

The StreetTalk protocol running over vipc-rdp would be referred to as 'vipc-rdp streettalk' OR 'vipc-rdp 0x000F'.

The mechanism by which an implementation selects which of the source and destination ports to use in determining which child protocol is present is implementation specific and beyond the scope of this document."

DECODING

"Children of vipc-rdp are deemed to start after the error/length field at the end of the vipc header. For vipc-rdp the vipc header is a so called 'long' header, total 16 bytes (including the final error/length field).

vipec-rdp includes a high level fragmentation scheme which allows up to four vipec packets to be sent as a single atomic PDU. The countsFragments(0) PARAMETERS bit indicates whether the probe can (and should) identify the child protocol in all fragments or only the leading one."

REFERENCE

"BANYAN"

`::= { vipc 0x01 }`

**vspp PROTOCOL-IDENTIFIER**

```

PARAMETERS { }
ATTRIBUTES {
  hasChildren(0)
}
DESCRIPTION
  "Banyan Vines Sequenced Packet Protocol."
CHILDREN
  "Children of vspp are identified by the 16 bit port numbers
  contained in the vspp header.

These are encoded as [ 0.0.a.b ] where 'a' is the MSB and 'b' is
the MSB of the port number in network byte order.

Children of vspp are defined as 'vspp a' where 'a' is the port
number in hexadecimal notation.

The StreetTalk protocol running over vspp would be referred to as
'vspp streettalk' OR 'vspp 0x000F'.

The mechanism by which an implementation selects which of the
source and destination ports to use in determining which child
protocol is present is implementation specific and beyond the
scope of this document."
DECODING
  "The implementation must ensure only those vspp packets which
  contain application data are decoded and passed on to children.
  Although it is suggested that the packet type and control fields
  should be used to determine this fact it is beyond the scope of
  this document to fully define the algorithm used."
REFERENCE
  "BANYAN"
::= { vip 0x02 }

vrtp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Banyan Vines Routing Update Protocol."
REFERENCE
  "BANYAN"
::= { vip 0x05 }

vicp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Banyan Vines Internet Control Protocol."
REFERENCE

```

```

    "BANYAN"
 ::= { vip 0x06 }

3.1.6. The DECNet Protocol Stack

dec PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "DEC"
REFERENCE
    "Digital Corporation"
 ::= {
ether2 0x6000,
802-1Q 0x6000      -- [0.0.96.0]
}

lat PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "DEC Local Area Transport Protocol."
REFERENCE
    "Digital Corporation"
 ::= {
ether2 0x6004,
802-1Q 0x6004      -- [0.0.96.4]
}

mop PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "DEC Maintenance Operations Protocol."
REFERENCE
    "Digital Corporation"
 ::= {
ether2 0x6001,      -- mop dump/load
ether2 0x6002,      -- mop remote console
802-1Q 0x6001,     -- [0.0.96.1] VLAN + mop dump/load
802-1Q 0x6002      -- [0.0.96.2] VLAN + mop remote console
}

dec-diag PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "DEC Diagnostic Protocol."

```

```
REFERENCE
    "Digital Corporation"
 ::= {
 ether2 0x6005,
 802-1Q 0x6005      -- [0.0.96.5]
 }

lavc PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "DEC Local Area VAX Cluster Protocol."
REFERENCE
    "Digital Corporation"
 ::= {
 ether2 0x6007,
 802-1Q 0x6007      -- [0.0.96.7]
 }

drp PROTOCOL-IDENTIFIER
PARAMETERS {
 countsFragments(1)
}
ATTRIBUTES {
 hasChildren(0),
 addressRecognitionCapable(1)
}
DESCRIPTION
    "DEC Routing Protocol."

CHILDREN
    "There is only one child of DRP, NSP. This is encoded as [
 0.0.0.1 ]."
ADDRESS-FORMAT
    "There are three address formats used in DRP packets, 2-byte
 (short data packet and all control except ethernet endnode &
 router hello messages), 6-byte (ethernet router & endnode hello
 messages) and 8-byte (long data packet). All of these contain
 the 2-byte format address in the last 2 bytes with the remaining
 bytes being unimportant for the purposes of system
 identification. It is beyond the scope of this document to
 define the algorithms used to identify packet types and hence
 address formats.

The 2-byte address format is the concatenation of a 6-bit area
and a 10-bit node number. In all cases this is placed in little
 endian format (i.e. LSB, MSB). The probe, however, will return
them in network order (MSB, LSB). Regardless of the address
```

format in the packet, the probe will always use the 2-byte format.

For example area=13 (001101) and node=311 (0100110111) gives:  
0011 0101 0011 0111 = 0x3537 in network order (the order the probe should return the address in).

In packets this same value would appear as (hex):

```
2-byte 37 35
6-byte AA 00 04 00 37 35
8-byte 00 00 AA 00 04 00 37 35
```

Notice that the AA 00 04 00 prefix is defined in the specification but is unimportant and should not be parsed.

Notice that control messages only have a source address in the header and so they can never be added into the conversation based tables."

#### DECODING

"NSP runs over DRP data packets; all other packet types are DRP control packets of one sort or another and do not carry any higher layer protocol.

NSP packets are deemed to start at the beginning of the DRP data area.

Data packets may be fragmented over multiple DRP data packets. The countsFragments(1) parameter indicates whether a probe can (and should) attribute non-leading fragments to the child protocol (above NSP in this case) or not.

Recognition of DRP data packets and fragments is beyond the scope of this document."

#### REFERENCE

```
"DECnet Digital Network Architecture
Phase IV
Routing Layer Functional Specification
Order# AA-X435A-TK
Digital Equipment Corporation, Maynard, Massachusetts, USA"
::= {
ether2 0x6003,
snap    0x6003,
802-1Q 0x6003      -- [0.0.96.3]
}
```

```
nsp PROTOCOL-IDENTIFIER
PARAMETERS {
```

```
tracksSessions(1)
}
ATTRIBUTES {
  hasChildren(0)
}
DESCRIPTION
  "DEC Network Services Protocol."
CHILDREN
  "Children of NSP are identified by the SCP 8-bit object type.
  Notice that the object type is included only in the session
  establishment messages (connect initiate, retransmitted connect
  initiate)."

Children of NSP are encoded [ 0.0.0.a ] where 'a' is the SCP
object type. Children of NSP are named as 'nsp' followed by the
SCP object type in decimal. CTERM is referred to as 'nsp cterm'
OR 'nsp 42'."

DECODING
  "An implementation is encouraged to examine SCP headers included
  in NSP control messages in order to determine which child
  protocol is present over a given session. It is beyond the scope
  of this document to define the algorithm used to do this.

The tracksSessions(1) flag indicates whether the probe can (and
should) perform this analysis."
REFERENCE
  "DECnet Digital Network Architecture
  Phase IV
  NSP Functional Specification
  Order# AA-X439A-TK
  Digital Equipment Corporation, Maynard, Massachusetts, USA"
::= { drp 1 }

dap-v1 PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "DEC Data Access Protocol version 1."
REFERENCE
  "Digital Corporation"
::= { nsp 1 }

dap-v4 PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "DEC Data Access Protocol versions 4 and above."
REFERENCE
```

```

    "Digital Corporation"
 ::= { nsp 17 }

nice PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "DEC Network Information and Control Exchange protocol."
REFERENCE
    "Digital Corporation"
 ::= { nsp 19 }

dec-loop PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "DEC Loopback Protocol."
REFERENCE
    "Digital Corporation"
 ::= { nsp 25 }

dec-event PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "DEC Event Protocol."
REFERENCE
    "Digital Corporation"
 ::= { nsp 26 }

cterm PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "DEC CTERM Protocol."
REFERENCE
    "Digital Corporation"
 ::= { nsp 42 }

```

### 3.1.7. The IBM SNA Protocol Stack.

```

sna-th PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "IBM's SNA TH protocol."
REFERENCE
    "IBM Systems Network Architecture"

```

Format and Protocol  
 Reference Manual: Architectural Logic

SC30-3112-2

IBM System Communications Division,  
 Publications Development,  
 Department E02,  
 PO Box 12195,  
 Research Triangle Park,  
 North Carolina 27709."

```
: ::= {
  llc      0x04,          -- [ 0.0.0.4 ]
  llc      0x08,          -- [ 0.0.0.8 ]
  llc      0x0c,          -- [ 0.0.0.12 ]
  ether2   0x80d5,        -- [ 0.0.128.213 ]
  802-1Q   0x02000004,    -- 1Q-LLC [ 2.0.0.4 ]
  802-1Q   0x02000008,    -- 1Q-LLC [ 2.0.0.8 ]
  802-1Q   0x0200000c,    -- 1Q-LLC [ 2.0.0.12 ]
  802-1Q   0x80d5         -- [ 0.0.128.213 ]
}
```

### 3.1.8. The NetBEUI/NetBIOS Family

```
-- CHILDREN OF NETBIOS
-- The NetBIOS/NetBEUI functions are implemented over a wide variety of
-- transports. Despite varying implementations they all share two
-- features. First, all sessions are established by connecting to
-- locally named services. Second, all sessions transport application
-- data between the client and the named service. In all cases the
-- identification of the application protocol carried within the data
-- packets is beyond the scope of this document.]
--
-- Children of NetBIOS/NetBEUI are identified by the following (32 bit)
-- enumeration
--
--     1    smb (Microsoft's Server Message Block Protocol)
--     2    notes (Lotus' Notes Protocol)
--     3    cc-mail (Lotus' CC Mail Protocol)
--
-- Children of NetBIOS/NetBEUI are encoded as [ a.b.c.d ] where 'a', 'b',
-- 'c' and 'd' are the four octets of the enumerated value in network
-- order (i.e. 'a' is the MSB and 'd' is the LSB).
--
-- For example notes over NetBEUI is declared as
--     'notes ::= { netbeui 2 }'
-- but is referred to as
--     'netbeui notes' OR 'netbeui 2'.
```

```
netbeui PROTOCOL-IDENTIFIER
PARAMETERS {
  tracksSessions(1)
}
ATTRIBUTES {
  hasChildren(0)
}
DESCRIPTION
  "Lan Manager NetBEUI protocol."

CHILDREN
  "See 'CHILDREN OF NETBIOS'"
DECODING
  "NETBEUI provides a named service lookup function. This function
  allows clients to locate a service by (locally assigned) name.
  An implementation is encouraged to follow lookups and session
  establishments and having determined the child protocol, track
  them.

How the child protocol is determined and how the sessions are
tracked is an implementation specific matter and is beyond the
scope of this document."
REFERENCE
  "IBM"
 ::= {
  llc      0xF0,          -- [0.0.0.240]
  802-1Q   0x020000F0    -- 1Q-LLC [2.0.0.240]
}

nbt-name PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "NetBIOS-over-TCP name protocol."
REFERENCE
  "RFC 1001 [RFC1001] defines the 'PROTOCOL STANDARD FOR A NetBIOS
  SERVICE ON A TCP/UDP TRANSPORT: CONCEPTS AND METHODS.' RFC 1002
  [RFC1002] defines the 'PROTOCOL STANDARD FOR A NetBIOS SERVICE ON
  A TCP/UDP TRANSPORT: DETAILED SPECIFICATIONS'."
 ::= {
  udp      137,
  tcp      137
}

nbt-session PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
```

```
"NetBIOS-over-TCP session protocol."
REFERENCE
  "RFC 1001 [RFC1001] defines the 'PROTOCOL STANDARD FOR A NetBIOS
  SERVICE ON A TCP/UDP TRANSPORT: CONCEPTS AND METHODS.' RFC 1002
  [RFC1002] defines the 'PROTOCOL STANDARD FOR A NetBIOS SERVICE ON
  A TCP/UDP TRANSPORT: DETAILED SPECIFICATIONS'.""
::= {
  udp      139,
  tcp      139
}

nbt-data PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES {
  hasChildren(0)
}
DESCRIPTION
  "NetBIOS-over-TCP datagram protocol."
CHILDREN
  "See 'CHILDREN OF NETBIOS'"
REFERENCE
  "RFC 1001 [RFC1001] defines the 'PROTOCOL STANDARD FOR A NetBIOS
  SERVICE ON A TCP/UDP TRANSPORT: CONCEPTS AND METHODS.' RFC 1002
  [RFC1002] defines the 'PROTOCOL STANDARD FOR A NetBIOS SERVICE ON
  A TCP/UDP TRANSPORT: DETAILED SPECIFICATIONS'.""
::= {
  udp      138,
  tcp      138
}

netbios-3com PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES {
  hasChildren(0)
}
DESCRIPTION
  "3COM NetBIOS protocol."
CHILDREN
  "See 'CHILDREN OF NETBIOS'"
REFERENCE
  "3Com Corporation"
::= {
  ether2  0x3C00,
  ether2  0x3C01,
  ether2  0x3C02,
  ether2  0x3C03,
  ether2  0x3C04,
```

```
ether2 0x3C05,
ether2 0x3C06,
ether2 0x3C07,
ether2 0x3C08,
ether2 0x3C09,
ether2 0x3C0A,
ether2 0x3C0B,
ether2 0x3C0C,
ether2 0x3C0D,
802-1Q 0x3C00,
802-1Q 0x3C01,
802-1Q 0x3C02,
802-1Q 0x3C03,
802-1Q 0x3C04,
802-1Q 0x3C05,
802-1Q 0x3C06,
802-1Q 0x3C07,
802-1Q 0x3C08,
802-1Q 0x3C09,
802-1Q 0x3C0A,
802-1Q 0x3C0B,
802-1Q 0x3C0C,
802-1Q 0x3C0D
}

nov-netbios PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES {
  hasChildren(0)
}
DESCRIPTION
  "Novell's version of the NetBIOS protocol."
CHILDREN
  "See 'CHILDREN OF NETBIOS'"
REFERENCE
  "Novell Corporation"
 ::= {
  nov-sap 0x0020, -- preferred encapsulation to use, even though
                   -- the following are typically used also
  -- ipx 0x14,      -- when reached by IPX packet type
  -- nov-pep 0x0455 -- when reached by socket number
}

burst PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Novell burst-mode transfer"
```

## REFERENCE

```
"Novell Corporation"
 ::= { nov-pep 0x0d05 }
```

## 3.2. Multi-stack protocols

```
smb PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "Microsoft Server Message Block Protocol."
REFERENCE
    "Microsoft Corporation"
 ::= {
    netbeui      1,
    netbios-3com 1,
    nov-netbios  1,
    nbt-data     1,
    nbt-session  1,
    nov-pep      0x550,
    nov-pep      0x552
}

notes PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
    "Lotus Notes Protocol."
REFERENCE
    "Lotus Development"
 ::= {
    netbeui      2,
    netbios-3com 2,
    nov-netbios  2,
    nbt-data     2,
    tcp          1352,
    udp          1352,
    nov-sap      0x039b
}

ccmail PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }

DESCRIPTION
    "Lotus CC-mail Protocol."
REFERENCE
```

```
"Lotus Development"
 ::= {
 netbeui      3,
 netbios-3com 3,
 nov-netbios  3,
 nbt-data     3,
 tcp          3264,
 udp          3264
}

snmp PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Simple Network Management Protocol. Includes SNMPv1 and SNMPv2
   protocol versions. Does not include SNMP trap packets."
REFERENCE
  "The SNMP SMI is defined in RFC 1902 [RFC1902]. Version 1 of the
   SNMP protocol is defined in RFC 1905 [RFC1905]. Transport
   mappings are defined in RFC 1906 [RFC1906]; RFC 1420 (SNMP over
   IPX) [RFC1420]; RFC 1419 (SNMP over AppleTalk) [RFC1419]."
 ::= {
  udp 161,
  nov-pep 0x900f,    -- [ 0.0.144.15 ]
  atalk 8,
  tcp 161
}

snmptrap PROTOCOL-IDENTIFIER
PARAMETERS { }
ATTRIBUTES { }
DESCRIPTION
  "Simple Network Management Protocol Trap Port."
REFERENCE
  "The SNMP SMI is defined in RFC 1902 [RFC1902]. The SNMP
   protocol is defined in RFC 1905 [RFC1905]. Transport mappings
   are defined in RFC 1906 [RFC1906]; RFC 1420 (SNMP over IPX)
   [RFC1420]; RFC 1419 (SNMP over AppleTalk) [RFC1419]."
 ::= {
  udp 162,
  nov-pep 0x9010,
  atalk 9,
  tcp 162
}

-- END
```

#### 4. Intellectual Property

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in BCP-11. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification can be obtained from the IETF Secretariat."

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

#### 5. Acknowledgements

This document was produced by the IETF RMONMIB Working Group.

The authors wish to thank the following people for their contributions to this document:

Anil Singhal  
Frontier Software Development, Inc.

Jeanne Haney  
Bay Networks

Dan Hansen  
Network General Corp.

Special thanks are in order to the following people for writing RMON PI macro compilers, and improving the specification of the PI macro language:

David Perkins  
DeskTalk Systems, Inc.

Skip Koppenhaver  
Technically Elite, Inc.

## 6. References

- [IEN158] J. Haverty, "XNET Formats for Internet Protocol Version 4", IEN 158, October 1980.
- [RFC407] Bressler, R., Guida. R. and A. McKenzie, "Remote Job Entry Protocol", RFC 407, October 1972.
- [RFC493] Michener, J., Cotton, I., Kelley, K., Liddle, D. and E. Meyer, "E.W., Jr Graphics Protocol", RFC 493, April 1973.
- [RFC734] Crispin, M., "SUPDUP Protocol", RFC 734, October 1977.
- [RFC740] Braden, R., "NETRJS Protocol", RFC 740, November 1977.
- [RFC741] Cohen, D., "Specifications for the Network Voice Protocol", RFC 741, ISI/RR 7539, March 1976.
- [RFC759] Postel, J., "Internet Message Protocol", RFC 759, August 1980.
- [RFC768] Postel, J., "User Datagram Protocol", STD 6, RFC 768, August 1980.
- [RFC791] Postel, J., "Internet Protocol - DARPA Internet Program Protocol Specification", STD 5, RFC 791, September 1981.
- [RFC792] Postel, J., "Internet Control Message Protocol - DARPA Internet Program Protocol Specification", STD 5, RFC 792, September 1981.
- [RFC793] Postel, J., "Transmission Control Protocol - DARPA Internet Program Protocol Specification", STD 5, RFC 793, September 1981.
- [RFC818] Postel, J., "Remote User Telnet service", RFC 818, November 1982.
- [RFC821] Postel, J., "Simple Mail Transfer Protocol", STD 10, RFC 821, August 1982.
- [RFC823] Hinden, R. and A. Sheltzer, "The DARPA Internet Gateway", RFC 823, September 1982.
- [RFC826] Plummer, D., "An Ethernet Address Resolution Protocol or Converting Network Protocol Addresses to 48-bit Ethernet Addresses for Transmission on Ethernet Hardware", STD 37, RFC 826, November 1982.

- [RFC854] Postel, J. and J. Reynolds, "Telnet Protocol Specification", STD 8, RFC 854, May 1983.
- [RFC862] Postel, J., "Echo Protocol", STD 20, RFC 862, May 1983.
- [RFC863] Postel, J., "Discard Protocol", STD 21, RFC 863, May 1983.
- [RFC864] Postel, J., "Character Generator Protocol", STD 22, RFC 864, May 1983.
- [RFC865] Postel, J., "Quote of the Day Protocol", STD 23, RFC 865, May 1983.
- [RFC866] Postel, J., "Active Users", STD 26, RFC 866, May 1983.
- [RFC867] Postel, J., "Daytime Protocol", STD 25, RFC 867, May 1983.
- [RFC868] Postel, J., "Time Protocol", STD 26, RFC 868, May 1983.
- [RFC869] Hinden, R., "A Host Monitoring Protocol", RFC 869, December 1983.
- [RFC887] Accetta, M., "Resource Location Protocol", RFC 887, December 1983.
- [RFC904] International Telegraph and Telephone Co., D. Mills, "Exterior Gateway Protocol Formal Specification", STD 18, RFC 904, April 1984.
- [RFC905] McKenzie, A., "ISO Transport Protocol Specification - ISO DP 8073", RFC 905, April 1984.
- [RFC908] Veltén, D., Hinden, R., and J. Sax, "Reliable Data Protocol", RFC 908, July 1984.
- [RFC913] Lottor, M., "Simple File Transfer Protocol", RFC 913, September 1984.
- [RFC915] Elvy, M. and R. Nedved, "Network mail path service", RFC 915, December 1984.
- [RFC937] Butler, M., Chase, D., Goldberger, J., Postel, J., and J. Reynolds, "Post Office Protocol - version 2", RFC 937, February 1985.
- [RFC938] Miller, T., "Internet Reliable Transaction Protocol", RFC 938, February 1985.

- [RFC951] Croft, W. and J. Gilmore, "BOOTSTRAP Protocol (BOOTP)", RFC 951, September 1985.
- [RFC953] Feinler, E., Harrenstien, K. and M. Stahl, "Hostname Server", RFC 953, October 1985.
- [RFC954] Feinler, E., Harrenstien, K. and M. Stahl, "NICNAME/WHOIS", RFC 954, October 1985.
- [RFC959] Postel, J., and J. Reynolds, "File Transfer Protocol", STD 9, RFC 959, October 1985.
- [RFC972] Wancho, F., "Password Generator Protocol", RFC 972, January 1986.
- [RFC977] Kantor, B. and P. Lapsley, "Network News Transfer Protocol: A Proposed Standard for the Stream-Based Transmission of News", RFC 977, February 1986.
- [RFC996] Mills, D., "Statistics server", RFC 996, February 1987.
- [RFC998] Clark, D., Lambert, M. and L. Zhang, "NETBLT: A Bulk Data Transfer Protocol", RFC 998, March 1987.
- [RFC1001] NetBIOS Working Group in the Defense Advanced Research Projects Agency, Internet Activities Board, End-to-End Services Task Force. "Protocol standard for a NetBIOS service on a TCP/UDP transport: Concepts and methods", STD 19, RFC 1001, March 1987.
- [RFC1002] NetBIOS Working Group in the Defense Advanced Research Projects Agency, Internet Activities Board, End-to-End Services Task Force. "Protocol standard for a NetBIOS service on a TCP/UDP transport: Detailed specifications.", STD 19, RFC 1002, March 1987.
- [RFC1021] Partridge, C. and G. Trewitt, "High-level Entity Management System HEMS", RFC 1021, October 1987.
- [RFC1028] Case, J., Davin, J., Fedor, M. and M. Schoffstall, "Simple Gateway Monitoring Protocol", RFC 1028, November 1987.
- [RFC1035] Mockapetris, P., "Domain Names - Implementation and Specification", STD 13, RFC 1035, November 1987.
- [RFC1056] Lambert, M., "PCMAIL: A distributed mail system for personal computers", RFC 1056, June 1988.

- [RFC1057] Sun Microsystems, Inc, "RPC: Remote Procedure Call Protocol Specification version 2", RFC 1057, June 1988.
- [RFC1064] Crispin, M., "Interactive Mail Access Protocol: Version 2", RFC 1064, July 1988.
- [RFC1068] DeSchon, A. and R. Braden, "Background File Transfer Program BFTP", RFC 1068, August 1988.
- [RFC1070] Hagens, R., Hall, N. and M. Rose, "Use of the Internet as a subnetwork for experimentation with the OSI network layer", RFC 1070, February 1989.
- [RFC1078] Lottor, M., "TCP port service Multiplexer TCPMUX", RFC 1078, November, 1988.
- [RFC1086] Onions, J. and M. Rose, "ISO-TP0 bridge between TCP and X.25", RFC 1086, December 1988.
- [RFC1095] Warrier, U. and L. Besaw, "Common Management Information Services and Protocol over TCP/IP (CMOT)", RFC 1095, April 1989.
- [RFC1112] Deering, S., "Host Extensions for IP Multicasting", STD 5, RFC 1112, August 1989.
- [RFC1155] Rose, M. and K. McCloghrie, "Structure and Identification of Management Information for TCP/IP-based Internets", STD 16, RFC 1155, May 1990.
- [RFC1157] Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.
- [RFC1203] Rice, J., "Interactive Mail Access Protocol - Version 3", RFC 1203, February 1991.
- [RFC1204] Lee, D. and S. Yeh, "Message Posting Protocol (MPP)", RFC 1204, February 1991.
- [RFC1212] Rose, M. and K. McCloghrie, "Concise MIB Definitions", STD 16, RFC 1212, March 1991.
- [RFC1213] McCloghrie, K. and M. Rose, "Management Information Base for Network Management of TCP/IP-based internets: MIB-II", STD 17, RFC 1213, March 1991.
- [RFC1215] Rose, M., "A Convention for Defining Traps for use with the SNMP", RFC 1215, March 1991.

- [RFC1226] Kantor, B., "Internet Protocol Encapsulation of AX.25 Frames", RFC 1226, May 1991.
- [RFC1227] Rose, M., "SNMP MUX Protocol and MIB", RFC 1227, May 1991.
- [RFC1234] Provan, D., "Tunneling IPX Traffic through IP Networks", RFC 1234, June 1991.
- [RFC1235] Ioannidis, J. and G. Maguire, Jr., "The Coherent File Distribution Protocol", RFC 1235, June 1991.
- [RFC1241] Mills, D. and R. Woodburn, "A Scheme for an Internet Encapsulation Protocol: Version 1", RFC 1241, July 1991.
- [RFC1249] Howes, T., Smith, M. and B. Beecher, "DIXIE Protocol Specification", RFC 1249, August 1991.
- [RFC1267] Lougheed, K. and Y. Rekhter, "A Border Gateway Protocol 3 (BGP-3)", RFC 1267, October 1991.
- [RFC1282] Kantor, B., "BSD Rlogin", RFC 1282, December 1991.
- [RFC1288] Zimmerman, D., "The Finger User Information Protocol", RFC 1288, December 1991.
- [RFC1301] Amstrong, S., Freier, A. and K. Marzullo, "Multicast Transport Protocol", RFC 1301, February 1992.
- [RFC1305] Mills, D., "Network Time Protocol (v3)", RFC 1305, April 1992.
- [RFC1312] Nelson, R. and G. Arnold, "Message Send Protocol", RFC 1312, April 1992.
- [RFC1339] Dorner, S. and P. Resnick, "Remote Mail Checking Protocol", RFC 1339, June 1992.
- [RFC1350] Sollins, K., "TFTP Protocol (revision 2)", RFC 1350, July 1992.
- [RFC1413] St. Johns, M., "Identification Protocol", RFC 1413, February 1993.
- [RFC1419] Minshall, G. and M. Ritter, "SNMP over AppleTalk", RFC 1419, March 1993.
- [RFC1420] Bostock, S., "SNMP over IPX", RFC 1420, March 1993.

- [RFC1436] Anklesaria, F., McCahill, M., Lindner, P., Johnson, D., John, D., Torrey, D. and B. Alberti, "The Internet Gopher Protocol (a distributed document search and retrieval protocol)", RFC 1436, March 1993.
- [RFC1459] Oikarinen, J. and D. Reed, "Internet Relay Chat Protocol", RFC 1459, May 1993.
- [RFC1476] Ullmann, R., "RAP: Internet Route Access Protocol", RFC 1476, June 1993.
- [RFC1479] Steenstrup, M., "Inter-Domain Policy Routing Protocol Specification: Version 1", RFC 1479, July 1993.
- [RFC1483] Heinanen, J., "Multiprotocol Encapsulation over ATM Adaptation Layer 5", RFC 1483, July 1993.
- [RFC1492] Finseth, C., "An Access Control Protocol, Sometimes Called TACACS", RFC 1492, July 1993.
- [RFC1510] Kohl, J. and B. Neuman, "The Kerberos Network Authentication Service (V5)", RFC 1510, September 1993.
- [RFC1583] Moy, J., "OSPF Version 2", RFC 1583, March 1994.
- [RFC1700] Reynolds, J. and J. Postel, "Assigned Numbers", STD 2, RFC 1700, October 1994.
- [RFC1701] Hanks, S., Li, T., Farinacci, D. and P. Traina, "Generic Routing Encapsulation (GRE)", RFC 1701, October 1994.
- [RFC1702] Hanks, S., Li, T., Farinacci, D. and P. Traina, "Generic Routing Encapsulation over IPv4 networks", RFC 1702, October 1994.
- [RFC1725] Myers, J. and M. Rose, "Post Office Protocol - Version 3", RFC 1725, November 1994.
- [RFC1729] Lynch, C., "Using the Z39.50 Information Retrieval Protocol in the Internet Environment", RFC 1729, December 1994.
- [RFC1730] Crispin, M., "Internet Message Access Protocol - Version 4", RFC 1730, December 1994.
- [RFC1739] Kessler, G. and S. Shepard, "A Primer On Internet and TCP/IP Tools", RFC 1739, December 1994.

- [RFC1745] Varadhan, K., Hares, S. and Y. Rekhter, "BGP4/IDRP for IP---OSPF Interaction", RFC 1745, December 1994.
- [RFC1757] Waldbusser, S., "Remote Network Monitoring MIB", RFC 1757, February 1995.
- [RFC1777] Yeong, W., Howes, T. and S. Kille, "Lightweight Directory Access Protocol", RFC 1777, March 1995.
- [RFC1782] Malkin, G. and A. Harkin, "TFTP Option Extension", RFC 1782, March 1995.
- [RFC1783] Malkin, G. and A. Harkin, "TFTP BlockOption Option", RFC 1783, March 1995.
- [RFC1784] Malkin, G. and A. Harkin, "TFTP Timeout Interval and Transfer Size Options", RFC 1784, March 1995.
- [RFC1798] Young, A., "Connection-less Lightweight Directory Access Protocol", RFC 1798, June 1995.
- [RFC1813] Callaghan, B., Pawlowski, B. and P. Staubach, "NFS Version 3 Protocol Specification", RFC 1813, June 1995.
- [RFC1819] Delgrossi, L. and L. Berger, "Internet Stream Protocol Version 2 (ST2)", RFC 1819, August 1995.
- [RFC1831] Srinivasan, R., "Remote Procedure Call Protocol Version 2", RFC 1831, August 1995.
- [RFC1853] Simpson, W., "IP in IP Tunneling", RFC 1853, October 1995.
- [RFC1901] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Introduction to Community-based SNMPv2", RFC 1901, January 1996.
- [RFC1902] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Structure of Management Information for version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1902, January 1996.
- [RFC1903] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Textual Conventions for version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1903, January 1996.

- [RFC1904] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Conformance Statements for version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1904, January 1996.
- [RFC1905] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Protocol Operations for Version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1905, January 1996.
- [RFC1906] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Transport Mappings for Version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1906, January 1996.
- [RFC1940] Estrin, D., Li, T., Rekhter, Y., Varadhan, K. and D. Zappala, "Source Demand Routing: Packet Format and Forwarding Specification (Version 1)", RFC 1940, May 1996.
- [RFC1945] Berners-Lee, T. and R. Fielding, "Hypertext Transfer Protocol -- HTTP/1.0", RFC 1945, November 1995.
- [RFC2002] Perkins, C., "IP Mobility Support", RFC 2002, October 1996.
- [RFC2003] Perkins, C., "IP Encapsulation within IP", RFC 2003, October 1996.
- [RFC2021] Waldbusser, S., "Remote Network Monitoring MIB (RMON-2)", RFC 2021, January 1997.
- [RFC2037] McCloghrie, K. and A. Bierman, "Entity MIB using SMIv2", RFC 2037, October 1996.
- [RFC2068] Fielding, R., Gettys, J., Mogul, J., Frystyk, H. and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2068, January 1997.
- [RFC2069] Franks, J., Hallam-Baker, P., Hostetler, J., Luotonen, P. A. and E. L. Stewart, "An Extension to HTTP: Digest Access Authentication", RFC 2069, January 1997.
- [RFC2074] Bierman, A. and R. Iddon, "Remote Network Monitoring MIB Protocol Identifiers", RFC 2074, January 1997.
- [RFC2109] Kristol, D. and L. Montulli, "HTTP State Management Mechanism", RFC 2109, February 1997.

- [RFC2138] Rigney, C., Rubens, A., Simpson, W. and W. Willens, "Remote Authentication Dial In User Service (RADIUS)", RFC 2138, April 1997.
- [RFC2139] Rigney, C., "RADIUS Accounting", RFC 2139, April 1997.
- [RFC2145] Mogul, J., Fielding, R., Gettys, J. and H. Frystyk, "Use and interpretation of HTTP version numbers", RFC 2145, May 1997.
- [RFC2205] Braden, R., Zhang, L., Berson, S., Herzog, S. and S. Jamin, "Resource ReSerVation Protocol (RSVP) -- Version 1 Functional Specification", RFC 2205, September, 1997.
- [RFC2233] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB Using SMIv2", RFC 2233, November, 1997.
- [RFC2271] Harrington, D., Presuhn, R. and B. Wijnen, "An Architecture for Describing SNMP Management Frameworks", RFC 2271, January 1998.
- [RFC2272] Case, J., Harrington D., Presuhn R. and B. Wijnen, "Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)", RFC 2272, January 1998.
- [RFC2273] Levi, D., Meyer, P. and B. Stewart, "SNMPv3 Applications", RFC 2273, January 1998.
- [RFC2274] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", RFC 2274, January 1998.
- [RFC2275] Wijnen, B., Presuhn, R. and K. McCloghrie, "View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)", RFC 2275, January 1998.
- [RFC2332] Luciani, J., Katz, D., Piscitello, D., Cole, B. and N. Doraswamy, "NBMA Next Hop Resolution Protocol (NHRP)", RFC 2332, April 1998.
- [RFC2408] Maughan, D., Schertler, M., Schneider, M. and J. Turner, RFC 2408, November 1998.
- [RFC2570] Case, J., Mundy, R., Partain, D. and B. Stewart, "Introduction to Version 3 of the Internet-standard Network Management Framework", RFC 2570, April 1999.

- [RFC2571] Harrington, D., Presuhn, R. and B. Wijnen, "An Architecture for Describing SNMP Management Frameworks", RFC 2571, April 1999.
- [RFC2572] Case, J., Harrington D., Presuhn R. and B. Wijnen, "Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)", RFC 2572, April 1999.
- [RFC2573] Levi, D., Meyer, P. and B. Stewart, "SNMPv3 Applications", RFC 2573, April 1999.
- [RFC2574] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", RFC 2574, April 1999.
- [RFC2575] Wijnen, B., Presuhn, R. and K. McCloghrie, "View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)", RFC 2575, April 1999.
- [RFC2578] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Structure of Management Information Version 2 (SMIV2)", STD 58, RFC 2578, April 1999.
- [RFC2579] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Textual Conventions for SMIV2", STD 58, RFC 2579, April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Conformance Statements for SMIV2", STD 58, RFC 2580, April 1999.
- [RFC2600] Reynolds, J. and R. Braden, "Internet Official Protocol Standards", STD 1, RFC 2600, March 2000.
- [RFC2895] Bierman, A., Bucci, C. and R. Iddon, "RMON Protocol Identifier Reference", RFC 2895, August 2000.

## 7. Security Considerations

This document contains textual descriptions of well-known networking protocols, not the definition of any networking behavior. As such, no security considerations are raised by its publication.

## 8. Authors' Addresses

Andy Bierman  
Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA USA 95134

Phone: +1 408-527-3711  
EMail: abierman@cisco.com

Chris Bucci  
Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA USA 95134

Phone: +1 408-527-5337  
EMail: cbucci@cisco.com

Robin Iddon  
c/o 3Com Inc.  
Blackfriars House  
40/50 Blackfriars Street  
Edinburgh, EH1 1NE, UK

Phone: +44 131.558.3888  
EMail: None

## 9. Full Copyright Statement

Copyright (C) The Internet Society (2000). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.

