Network Working Group Request for Comment: 619 NIC 21990 W. Naylor H. Opderbeck UCLA-NMC March 7, 1974

Mean Round-Trip Times in the ARPANET

In one of our current measurement projects we are interested in the average values of important network parameters. For this purpose we collect data on the network activity over seven consecutive days. This data collection is only interrupted by down-time or maintenance of either the net or our collecting facility (the "late" Sigma-7 or, in future, the 360/91 at CCN).

The insight gained from the analysis of this data has been reported in Network Measurement Group Note 18 (NIC 20793):

L. Kleinrock and W. Naylor "On Measured Behavior of the ARPA Network"

This paper will be presented at the NCC '74 in Chicago.

In this RFC we want to report the mean round-trip times (or delays) that were observed during these week-long measurements since we think these figures are of general interest to the ARPA community. Let us first define the term "round trip time" as it is used by the statistics gathering program in the IMPs. When a message is sent from a source HOST to a destination HOST, the following events, among others, can be distinguished (T(i) is the time of event i):

- $\ensuremath{\mathtt{T}}(1)\xspace$ T(1): The message is passed from the user program to the NCP in the source HOST
- T(2): The proper entry is made in the pending packet table (PPT) for single packet messages or the pending leader table (PLT) for multiple packet messages after the first packet is received by the source IMP
- T(3): The first packet of the message is put on the proper output queue in the source IMP (at this time the input of the second packet is initiated)
- T(4): The message is put on the HOST-output queue in the destination IMP (at this time the reassembly of the message is complete)
- T(5): The RFNM is sent from the destination IMP to the source IMP

Naylor & Opderbeck

[Page 1]

T(6): The RFNM arrives at the source IMP

T(7): The RFNM is accepted by the source HOST

The time intervals T(i)-T(i-1) are mainly due to the following delays and waiting times:

T(2)-T(1): -HOST processing delay

- -HOST-IMP transmission delay for the 32-bit leader
 -Waiting time for a message number to become free (only four messages can simultaneously be transmitted between any pair of source IMP destination IMP)
 -Waiting time for a buffer to become free (there must be more than three buffers on the "free buffer list")
 -HOST-IMP transmission delay for the first packet
 -Waiting time for an entry in the PPT or PLT to become available (there are eight entries in the PPT and twelve in the PLT table)
- T(3)-T(2): -Waiting time for a store-and-forward (S/F) buffer to become free (the maximum number of S/F-buffers is 20).
 -Waiting time for a logical ACK-channel to become free (there are 8 logical ACK-channels for each physical channel).
 -For multiple packet messages, waiting time until the ALLOCATE is received (unless an allocation from a previous multiple-packet message still exists; such an allocation is returned in the RFNM and expires after 125 msec)
- T(4)-T(3): -Queuing delay, transmission delay, and propagation delay in all the IMPs and lines in the path from source IMP to destination IMP -Possibly retransmission delay due to transmission errors or lack of buffer space (for multiple packet messages the delays for the individual packets overlap)
- T(5)-T(4): -Queuing delay in the destination IMP -IMP-HOST transmission delay for the first packet -For multiple-packet messages, waiting time for reassembly buffers to become free to piggy-back an ALLOCATE on the RFNM (if this waiting time exceeds one second then the RFNM is sent without the ALLOCATE)
- T(6)-T(5): -Queuing delay, transmission delay, and propagation delay for the RFNM in all the IMPs and lines in the path from destination IMP to source IMP

Naylor & Opderbeck

[Page 2]

T(7)-T(6): -Queuing delay for the RFNM in the source IMP -IMP-HOST transmission delay for the RFNM

IMP processing delays are not included in this table since they are usually very small. Also, some of the abovementioned waiting times reduce to zero in many cases, e.g. the waiting time for a message number to become available and the waiting time for a buffer to become free.

If the source and destination HOSTs are attached to the same IMP, this table can be simplified as follows:

T(2)-T(1):	as before
T(3)-T(2):	for multiple packet messages: waiting time until
	reassembly space becomes available (there are up to 66
	reassembly buffers)
T(4)-T(3):	for multiple packet messages: HOST-IMP transmission delay
	for packets 2,3,
T(5)-T(4):	as before
т(б)-т(5):	0
т(7)-т(б):	as before

Up to now we have neglected the possibility that a single packet message is rejected at the destination IMP because of lack of reassembly space. If this occurs, the single packet message is treated as a request for buffer space allocation and the time interval T(3)-T(2) increased by the waiting time until the corresponding "ALLOCATE" is received.

The round trip time (RTT) is now defined as the time interval T(6)-T(2). Note that the RTT for multiple packet messages does include the waiting time until the ALLOCATE is received. It does, however, not include the source HOST processing delay (i.e. delays in the NCP), the HOST-IMP transmission delay, and the waiting time until a message number becomes available. Note also, that the RFNM is sent after the first packet of a multiple packet message has been received by the destination HOST.

Let us now turn to the presentation of the average round trip times as they were measured during continuous seven-day periods in August and December '73. In August, an average number of 2935 messages/minute were entering the ARPANET. The overall mean round trip delay for all these messages was 93 milliseconds (msec). The corresponding numbers for December were 2226 messages/minute and 200 msec. An obvious question that immediately arises is: why did the average round trip delay more than double while the rate of incoming messages decreased? The answer to this question can be found in the large round trip delays for the status reports that are sent from each IMP to the NCC. Each IMP sends, on the average, 2.29 status reports per minute to the NCC. Since there

Naylor & Opderbeck

RFC 619

[Page 3]

were 45 sites connected to the net in December, a total of 103.05 status reports per minute were sent to the NCC. Thus 4.63 percent of all messages that entered the net were status reports.

The average round trip delay for all these status reports in December was 1.66 sec. This number is five to ten times larger than the average round-trip delay for status reports we observed in August. It is not yet clear what change in the collection of status reports caused this increase. One reason appears to be that the number of these reports was doubled between August and December. Since the large round-trip delays of these status reports distort the overall picture somewhat, we are going to present the December data - wherever appropriate - with and without the effect of these delays. (We should point out here that the traffic/delay picture is distorted by the accumulated statistics messages which were collected to produce this data. We have, however, ignored this effect since these measurement messages represent less than 0.3% of the total traffic.) The overall mean round trip delay without the status reports in December is 132 msec. This value is still more than 35 msec larger than the corresponding value for August. However, before we shall attempt to explain this difference we will first present the measured data.

Table 1 shows the mean round trip delay as a function of the number of hops over the minimum-hop path. This minimum number of hops was calculated from the (static) topology of the net as it existed in August and December of last year. The actual number of hops over which any given message travels may, of course, be larger due to network congestion, line failures or IMP failures. In fact, for August we observed a minimum mean path length of 3.24 while the actual measured mean path length was 3.30; in December we observed 4.02 and 4.40, respectively. (See Network Measurement Group Note #18 for an explanation of the computation of actual mean path length.) As expected we observe a sharp increase of the mean round trip delay as the minimum number of hops is increased. Note, however, that the mean round trip delay is not a strictly increasing function of the minimum number of hops.

Table 2 gives the mean round trip delay for messages from a given site. The December data is presented with and without the large delays incurred by the sending of status reports to the NCC. Table 3 shows the mean round trip delay for messages to a given site. The largest round trip delays, in December, were incurred by messages sent to the NCC-TIP since these messages include all the status reports.

Table 4, finally, gives for each site the mean round trip delays to those three destination IMP/TIP's to which the most messages were sent during the seven-day measurement period in December. Let us first say few words about the traffic distribution which is dealt with in more

Naylor & Opderbeck

[Page 4]

detail in Network Measurement Group Note #18. There are several sites which like to use their IMP as a kind of local multiplexer (UTAH, MIT, HARV, CMU, USCT, CCAT, XROX, HAWT, MIT2). For these sites the most favorite destination site is the source IMP itself. For several other sites the most favorite destination site is just one hop away (BBN, AMES, AMST, NCCT, RUTT). Nobody will be surprised that for many sites ISI (ILL, MTRT, ETAT, SDAT, ARPT, RMLT, LONT) or SRI (UCSB, RADT, NBST) is the most favorite site. There are several other sites (SDC, LL, CASE, DOCT, BELV, ABRD, FNWT, LBL, NSAT, TYMT, MOFF, WPAT) which were rather inactive in terms of generating traffic during the seven-day measurement period in December. Most of their messages were status reports sent to the NCC. (Those IMPs, for which the frequency of messages to the NCC-TIP is less than 2.2 messages per minute, were down for some time during the measurement period).

Let us now attempt to give a few explanations for the overall increase in the mean round trip delay between August and December. These explanations may also help to understand the differences in the mean round trip delays for any given source IMP-destination IMP pair as observed in Table 4.

- 1. Frequency of routing messages. Routing messages are the major source of queuing delay in a very lightly loaded net. In August, a routing message was sent every 640 msec. Since a routing message is 1160 bits long, 3.625 percent of the bandwidth of a 50 kbs circuit was used for the sending of routing messages. For randomly arriving packets this corresponds to a mean queuing delay of 0.42 msec per hop. Between August and December the frequency of sending routing messages was made dependent on line speed and line utilization. As a result, routing messages are now sent on a 50 kbs circuit with zero load every 128 msec. This corresponds to a line utilization of 18.125 percent and a mean queuing delay of 2.10 msec. The queuing delay due to routing messages in a very lightly loaded net in December was therefore five times as large as it was in August.
- Traffic matrix. The overall mean round trip delay depends on the traffic matrix. If most of the messages are sent over distances of 0 or 1 hop the overall round trip delay will be small. The heavy traffic between AMES and AMST over a high-speed circuit in August contributed to the small overall mean round trip delay.
- 3. Network topology. The mean round trip delay depends on the number of hops between source-IMP and destination-IMP and therefore on the network topology. Disregarding line or IMP failures, the mean number of hops for a message in August and December was, respectively, 3.24 and 4.02.

Naylor & Opderbeck

[Page 5]

- 4. Averaging. The network load, given in number or messages per minute, represents an average over a seven-day period. Even though this number may be small, considerable queuing delays could have been incurred during bursts of traffic.
- 5. Host delays. The round trip delay includes the transmission delay of the first packet from the destination-IMP to the destination-HOST; therefore, the mean round trip delay may be influenced by HOST delays that are independent of the network load.

[Page 6]

Table 1 Mean Round Trip Delay as a Function of the Number of Hops

	#MESSAGES	S/MINUTE	#SITE	PAIRS	MEAN	ROUND TRI	P DELAY
HOPS	AUG	DEC	AUG	DEC	AUG	DEC WITH STAT	DEC W/OUT STAT
0	646.9	378.3	39	45	27	44 RP15	41
1	487.6	288.7	86	100	25	65	50
2	191.0	143.1	118	138	70	119	80
3	380.7	226.9	148	168	95	131	112
4	218.5	274.1	176	196	102	167	119
5	276.3	185.6	204	228	109	217	134
6	183.8	136.3	210	258	175	355	167
7	333.6	212.7	218	256	178	301	240
8	156.7	161.1	160	234	222	365	241
9	59.0	160.3	102	208	270	308	218
10	0.6	29.9	40	124	331	939	410
11	1.0	18.9	20	46	344	998	699
12	-	10.2	-	20	-	992	655
13	-	0.01	-	4	-	809	809

Naylor & Opderbeck

[Page 7]

RFC 619

Table 2 Mean Round Trip Delays for Messages from a Given Site

		#MESSAGE	CS/MINUTE	MEAN	ROUND TRIP	DELAY
	SITE	AUGUST	DECEMBER	AUGUST	DECEMBER	DECEMBER
					WITH	WITHOUT
					STATUS	STATUS
					REPORTS	REPORTS
1	UCLA	50.7	40.3	130	282	165
2	SRI	377.3	147.9	45	189	174
3	UCSB	80.2	70.3	120	221	161
4	UTAH	27.0	46.2	136	247	169
5	BBN	120.4	128.3	110	133	133
б	MIT	120.6	96.9	126	160	150
7	RAND	29.3	34.2	127	323	208
8	SDC	1.7	2.4	521	2068	131
9	HARV	50.3	96.0	105	88	72
10	LL	4.4	6.7	201	602	187
11	STAN	49.7	39.7	173	300	191
12	ILL	26.8	53.4	158	216	165
13	CASE	57.6	2.5	138	1592	335
14	CMU	61.1	59.5	153	220	170
15	AMES	242 4	114 1	43	120	81
16	AMST	304 0	163 0	39	94	67
17	MTRT	89 5	60 0	126	199	142
18	RADT	27 7	29 1	145	273	160
19	NBST	98.4	48 2	118	213	152
20	ETAT	24 1	20 6	119	280	119
21	T.T.T.	_	6.8	-	721	169
22	TST	372 0	304 4	110	147	142
22	IISCT	298 1	210 3	60	92	70
24	GWCT	10 5	14 1	144	381	102
25		55	7 0	236	791	171
26	TT TT T	14 7	22 9	164	322	177
27	BFLV	1 3	22.5	243	1469	466
29		57 9	64 3	84	150	93
20	V B B D	1 3	2 4	183	1402	554
30	RENT	40.8	10 0	75	372	124
31	ССЛТ	10.0	86 7	83	147	115
33	VPOY	56 8	71 7	79	136	78
22	FNWT	23	35	347	1466	174
34	T.RT.	1 2	2.5	384	1653	621
25	חפח	11 0	10.2	227	112	205
35	บเรา นาณา	27 5	19.3 5 0	657	569	205
20		27.5	12 0	122	202	470
57 40		10.4	13.U 50 2		30/ 110	/ د ۲۵
40 /11	NCCI	- 0 6	2.5	1022	1070	97 1056
4 J		0.0	3.4 20 0	LUZZ	TOIN	010
4⊿ ∕\?		-	∠∪.ŏ 2 7	-	770 1950	848 157
чэ	TIMT	-	5.1	-	TSDZ	1 C L

Naylor & Opderbeck

[Page 8]

RFC	619	Mean 1	Round-Trip	Times in	the ARPANET	March 1974
44	MIT2	-	5.6	-	720	100
45	MOFF	-	2.4	-	1982	447
46	RUTT	-	22.4	-	271	153
47	WPAT	-	2.7	-	1399	380

[Page 9]

	Table	3	Mean Rou	und Trip Del	lay for Mess	ages to a Give	en Site
	C T T E		#MESSAGE	DECEMPED	MEAN ROUND	DECEMPED	
1			AUGUSI	A2 E	124	DECEMBER 200	
⊥ 2	CLA		292 2	43.5	154	209	
2	JICCP		502.5	EQ 1	117	120	
2 1			01.1	59.1	128	150	
т 5	BBN		160 8	149 2	185	110	
5	ырыл Мтт		150.0	107 1	116	130	
7			22 6	25 0	95	161	
8	SDC		1 7	23.0	149	174	
g	HARV		593	983	101	70	
10	T.T.		4 6	5 2	195	202	
11			65 3	40 G	135	162	
12	TT.T.		29 1	69.8	156	149	
13	CASE		52 6	4 0	127	262	
14	CMII		74 8	68 9	135	165	
15	AMES		210 3	117 2	40	75	
16	AMST		316 7	135 0	38	86	
17	MTRT		77 7	51 7	130	151	
18	RADT		23 4	23 9	142	202	
19	NBST		92.2	39 5	125	169	
20	ETAT		25 4	22.8	110	111	
21	T.T.T.		_	3.7	-	185	
22	ISI		361.9	299.2	107	130	
23	USCT		298.1	190.6	60	68	
24	GWCT		10.5	7.3	144	122	
25	DOCT		5.5	4.2	236	187	
26	SDAT		13.3	19.7	149	177	
27	BELV		0.9	0.9	196	285	
28	ARPT		55.4	58.3	78	95	
29	ABRD		1.3	0.7	183	271	
30	BBNT		40.8	6.4	75	159	
31	CCAT		177.7	76.3	83	119	
32	XROX		56.8	75.3	79	69	
33	FNWT		2.3	1.4	347	165	
34	LBL		1.2	0.9	384	305	
35	UCSD		11.9	24.0	237	157	
36	HAWT		27.5	5.0	654	458	
37	RMLT		10.4	11.0	122	97	
40	NCCT		-	140.1	-	1263	
41	NSAT		0.6	1.6	1022	918	
42	LONT		-	17.3	-	855	
43	TYMT		-	1.6	-	160	
44	MIT2		-	3.9	-	83	
45	MOFF		-	0.2	-	219	
46	RUTT		-	14.7	-	153	
47	WPAT		-	0.5	-	282	

[Page 10]

Table 4 Mean Round Trip Delay to the Three Most Favorite Sites

			#MESSAG	ES/MINUTE	MEAN RO	UND TRIP DELAY
FROM SIT	TE TO	SITE	AUGUST	DECEMBER	AUGUST	DECEMBER
1 UCLA	1	RAND	10.8	9.4	57	92
	26	SDAT	5.6	5.9	157	191
	2.2	TST	3.1	3.1	99	146
		101	5.1	5.1		110
2 SRI	12	RADT	16.6	19.5	142	163
	17	MTRT	21.9	18.7	140	161
	2	SRI	266.1	17.5	14	69
3 UCSB	2	SRT	8 1	178	72	68
0 0002	22	TST	18 1	17 0	75	86
	1/	CMII	16 6	11 0	140	152
	TI	CMO	10.0	11.0	140	TJZ
4 UTAH	4	UTAH	3.5	13.5	136	27
	22	ISI	3.7	4.8	131	165
	5	BBN	4.2	4.1	168	204
5 BBN	40	NCCT	_	81 4	_	105
5 DDR	-0	BBN	12 5	19 7	102	37
	5		12.5	19.7	102	27
	9	HARV	0.5	9.2	22	57
6 MIT	6	MIT	40.6	24.0	81	85
	23	USCT	9.8	13.9	150	173
	9	HARV	1.7	12.0	63	88
סאגם 7	1	TICT.A	12 5	10 4	54	96
/ ICAND	16		12.5	2 6	00	100
	10	AMSI	0.0	2.0	99	1041
	40	NCCI	-	2.5	_	1941
8 SDC	40	NCCT	-	2.2	-	2217
	1	UCLA	0.2	0.2	110	136
	8	SDC	0.01	0.01	93	13
ο υλου	0	117 D77	76	50 F	10	21
9 HARV	9 0		1.0	11 0	49 60	21
	ے ح	MII	1.0	11.9	62	20
	5	BBN	1.6	9.5	50	37
10 LL	40	NCCT	-	2.2	-	1420
	10	LL	1.5	1.8	238	135
	24	GWCT	0.04	0.6	146	80
11 פידא אז	1 4	CMIT	3 0	7 0	215	207
TT OTAN	1		0.2	,.0 5 5	117	117
	4	UIAD	0.4	5.5	10 <i>6</i>	
	6	I¶I⊥⊥	0.5	5.0	T 0 0	440

Naylor & Opderbeck

[Page 11]

RFC 619	Mean Rou	nd-Trip Times	in the A	ARPANET		March	1974
12 ILL	22 ISI 15 AMES 35 UCSD	13.3 0.8 6.7	20.3 14.6 6.5	146 109 192	142 135 269		
13 CASE	40 NCCT 1 UCLA 2 SRI	- 0.2 7.1	2.2 0.2 0.01	- 296 163	1744 400 316		
14 CMU	14 CMU 3 UCSB 11 STAN	13.8 13.8 3.2	23.4 9.2 5.1	129 153 193	94 166 209		
15 AMES	16 AMST 12 ILL 31 CCAT	205.0 1.2 3.2	65.8 19.6 4.6	15 115 174	34 120 230		
16 AMST	15 AMES 22 ISI 32 XROX	176.8 63.6 13.3	74.3 33.2 17.4	13 50 41	28 69 60		
17 MTRT	22 ISI 2 SRI 5 BBN	26.3 23.8 3.5	27.5 20.3 4.2	115 137 179	118 155 133		
18 RADT	2 SRI 1 UCLA 40 NCCT	17.7 0.4 -	21.7 2.3 2.3	139 265 -	156 181 1618		
19 NBST	2 SRI 22 ISI 5 BBN	14.1 29.6 21.6	12.1 11.8 9.6	132 100 71	163 117 97		
20 ETAT	22 ISI 24 GWCT 40 NCCT	11.9 5.0 -	11.3 5.9 2.2	106 99 -	107 107 1602		
21 LLL	5 BBN 40 NCCT 4 UTAH	- -	2.9 2.2 0.5	- - -	183 1847 71		
22 ISI	28 ARPT 23 USCT 16 AMST	26.0 69.0 62.0	38.3 32.7 28.5	106 80 53	104 92 87		
23 USCT	23 USCT 22 ISI 6 MIT	160.9 69.2 12.9	119.2 34.1 19.6	19 78 135	23 91 150		

[Page 12]

RFC 619	Mean Round	-Trip Times	in the A	ARPANET	March 1974
24 GWCT	20 ETAT	6.6	10.8	93	91
	40 NCCT	-	2.1	- 1	978
	10 LL	0.03	0.5	359	115
25 DOCT	40 NCCT	-	2.3	- 2	091
	22 ISI	1.0	1.6	220	118
	15 AMES	1.9	1.2	167	198
26 SDAT	22 ISI	2.9	8.7	154	138
	1 UCLA	5.9	6.0	169	209
	2 SRI	1.0	4.4	182	184
27 BELV	40 NCCT	-	2.2	- 1	553
	1 UCLA	0.1	0.2	405	517
	22 ISI	-	0.01	-	325
28 ARPT	22 ISI	27.4	41.6	106	101
	28 ARPT	19.2	13.7	20	35
	2 SRI	3.3	3.3	139	157
29 ABRD	40 NCCT	-	2.2	- 1	461
	1 UCLA	0.2	0.2	439	562
	9 HARV	-	0.01	-	112
30 BBNT	5 BBN	24.2	5.1	36	64
	40 NCCT	-	2.1	- 1	327
	22 ISI	4.2	1.1	170	217
31 CCAT	31 CCAT	81.9	28.2	15	31
	22 ISI	31.3	23.3	156	171
	5 BBN	7.8	7.3	45	42
32 XROX	32 XROX	20.2	36.4	19	15
	16 AMST	10.5	13.3	69	93
	14 CMU	2.5	3.0	193	251
33 FNWT	40 NCCT9 HARV7 RAND	- 0.01 0.3	2.2 0.3 0.3	- 2 208 96	210 194 171
34 LBL	40 NCCT	-	2.4	- 1	814
	41 NSAT	-	0.2	- 1	674
	1 UCLA	0.1	0.2	295	478
35 UCSD	12 ILL	6.0	7.5	220	260
	16 AMST	1.7	4.9	120	172
	40 NCCT	-	2.0	- 2	183

[Page 13]

RFC 619	Mean Round	-Trip Times	in the	ARPANET	
36 HAWT	36 HAWT 22 ISI 15 AMES	0.04 5.1 2.5	1.6 1.0 0.8	17 600 551	26 623 590
37 RMLT	22 ISI 40 NCCT 28 ARPT	7.5 - -	9.0 2.2 1.0	68 - -	67 1918 63
40 NCCT	5 BBN 40 NCCT 22 ISI		41.2 6.6 3.2	- - -	33 433 151
41 NSAT	40 NCCT 2 SRI 3 UCSB	- 0.01 0.01	2.2 0.4 0.2	_ 1046 1169	2308 1002 1018
42 LONT	22 ISI 2 SRI 4 UTAH		6.1 3.7 2.2	- - -	837 884 921
43 TYMT	40 NCCT 2 SRI 3 UCSB		2.6 0.5 0.2	- - -	1859 79 74
44 MIT2	44 MIT2 40 NCCT 1 UCLA		2.8 2.3 0.2	- - -	18 1664 589
46 MOFF	40 NCCT 1 UCLA	-	2.2 0.2	- -	2091 447
46 RUTT	9 HARV 5 BBN 22 ISI		4.3 3.5 2.9	- - -	38 93 172
47 WPAT	40 NCCT 3 UCSB 1 UCLA	- -	2.2 0.2 0.2	- - -	1643 301 671

[This RFC was put into machine readable form for entry] [into the online RFC archives by Alex McKenzie with] [support from GTE, formerly BBN Corp. 12/99]

Naylor & Opderbeck

[Page 14]