Internet Engineering Task Force (IETF)

Request for Comments: 6302

BCP: 162

Category: Best Current Practice

ISSN: 2070-1721

A. Durand
Juniper Networks
I. Gashinsky
Yahoo! Inc.
D. Lee
Facebook, Inc.
S. Sheppard
ATT Labs
June 2011

Logging Recommendations for Internet-Facing Servers

Abstract

In the wake of IPv4 exhaustion and deployment of IP address sharing techniques, this document recommends that Internet-facing servers log port number and accurate timestamps in addition to the incoming IP address.

Status of This Memo

This memo documents an Internet Best Current Practice.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on BCPs is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at http://www.rfc-editor.org/info/rfc6302.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Durand, et al.

Best Current Practice

[Page 1]

Table of Contents

1.	Int	roduct	ion .															2
2.	Rec	ommenda	ations															3
3.	ISP	Consid	derati	ons														4
4.	Sec	urity (Consid	era	tic	ons												4
5.	Ref	erence	s															4
	5.1.	Norma	tive r	efe	rer	ıce	S											4
	5.2.	Infor	mative	re	fei	cen	ce	S										4

1. Introduction

The global IPv4 address free pool at IANA was exhausted in February 2011. Service providers will now have a hard time finding enough IPv4 global addresses to sustain product and subscriber growth. Due to the huge existing global infrastructure, both hardware and software, vendors, and service providers must continue to support IPv4 technologies for the foreseeable future. As legacy applications and hardware are retired, the reliance on IPv4 will diminish; however, this is a process that will take years, perhaps decades.

To maintain legacy IPv4 address support, service providers will have little choice but to share IPv4 global addresses among multiple customers. Techniques to do so are outside of the scope of this document. All include some form of address translation/address sharing, being NAT44 [RFC3022], NAT64 [RFC6146] or DS-Lite [DS-LITE].

The effects on the Internet of the introduction of those address sharing techniques have been documented in [RFC6269].

Address sharing techniques come with their own logging infrastructure to track the relation between which original IP address and source port(s) were associated with which user and external IPv4 address at any given point in time. In the past, to support abuse mitigation or public safety requests, the knowledge of the external global IP address was enough to identify a subscriber of interest. With address sharing technologies, only providing information about the external public address associated with a session to a service provider is no longer sufficient information to unambiguously identify customers.

Note: This document provides recommendations for Internet-facing servers logging incoming connections. It does not provide any recommendations about logging on carrier-grade NAT or other address sharing tools.

Durand, et al.

Best Current Practice

[Page 2]

2. Recommendations

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

It is RECOMMENDED as best current practice that Internet-facing servers logging incoming IP addresses from inbound IP traffic also log:

- o The source port number.
- o A timestamp, RECOMMENDED in UTC, accurate to the second, from a traceable time source (e.g., NTP [RFC5905]).
- o The transport protocol (usually TCP or UDP) and destination port number, when the server application is defined to use multiple transports or multiple ports.

Discussion: Carrier-grade NATs may have different policies to recycle ports; some implementations may decide to reuse ports almost immediately, some may wait several minutes before marking the port ready for reuse. As a result, servers have no idea how fast the ports will be reused and, thus, should log timestamps using a reasonably accurate clock. At this point, the RECOMMENDED accuracy for timestamps is to the second or better. Representation of timestamps in UTC is preferred to local time with UTC-offset or time zone, as this extra information can be lost in the reporting chain.

Examples of Internet-facing servers include, but are not limited to, web servers and email servers.

Although the deployment of address sharing techniques is not foreseen in IPv6, the above recommendations apply to both IPv4 and IPv6, if only for consistency and code simplification reasons.

Discussions about data-retention policies are out of scope for this document. Server security and transport security are important for the protection of logs for Internet-facing systems. The operator of the Internet-facing server must consider the risks, including the data and services on the server, to determine the appropriate measures. The protection of logs is critical in incident investigations. If logs are tampered with, evidence could be destroyed.

The above recommendations also apply to devices such as load-balancers logging incoming connections on behalf of actual servers.

Durand, et al.

Best Current Practice

[Page 3]

The above recommendations apply to current logging practices. They do not require any changes in the way logging is performed; e.g., which packets are examined and logged.

3. ISP Considerations

ISP deploying IP address sharing techniques should also deploy a corresponding logging architecture to maintain records of the relation between a customer's identity and IP/port resources utilized. However, recommendations on this topic are out of scope for this document.

4. Security Considerations

In the absence of the source port number and accurate timestamp information, operators deploying any address sharing techniques will not be able to identify unambiguously customers when dealing with abuse or public safety queries.

5. References

5.1. Normative references

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

5.2. Informative references

- [DS-LITE] Durand, A., Droms, R., Woodyatt, J., and Y. Lee, "Dual-Stack Lite Broadband Deployments Following IPv4 Exhaustion", Work in Progress, May 2011.
- [RFC5905] Mills, D., Martin, J., Burbank, J., and W. Kasch, "Network Time Protocol Version 4: Protocol and Algorithms Specification", RFC 5905, June 2010.
- [RFC6146] Bagnulo, M., Matthews, P., and I. van Beijnum, "Stateful NAT64: Network Address and Protocol Translation from IPv6 Clients to IPv4 Servers", RFC 6146, April 2011.
- [RFC6269] Ford, M., Ed., Boucadair, M., Durand, A., Levis, P., and P. Roberts, "Issues with IP Address Sharing", RFC 6269, June 2011.

Durand, et al. Best Current Practice [Page 4]

Authors' Addresses

Alain Durand Juniper Networks 1194 North Mathilda Avenue Sunnyvale, CA 94089-1206 USA

EMail: adurand@juniper.net

Igor Gashinsky Yahoo! Inc. 45 West 18th St. New York, NY 10011 USA

EMail: igor@yahoo-inc.com

Donn Lee Facebook, Inc. 1601 S. California Ave. Palo Alto, CA 94304 USA

EMail: donn@fb.com

Scott Sheppard ATT Labs 575 Morosgo Ave, 4d57 Atlanta, GA 30324 USA

EMail: Scott.Sheppard@att.com