Internet Engineering Task Force (IETF) Request for Comments: 7128 Category: Informational ISSN: 2070-1721 R. Bush Internet Initiative Japan R. Austein Dragon Research Labs K. Patel Cisco Systems H. Gredler Juniper Networks, Inc. M. Waehlisch FU Berlin February 2014

Resource Public Key Infrastructure (RPKI) Router Implementation Report

## Abstract

This document is an implementation report for the Resource Public Key Infrastructure (RPKI) Router protocol as defined in RFC 6810. The authors did not verify the accuracy of the information provided by respondents. The respondents are experts with the implementations they reported on, and their responses are considered authoritative for the implementations for which their responses represent. The respondents were asked to only use the "YES" answer if the feature had at least been tested in the lab.

Status of This Memo

This document is not an Internet Standards Track specification; it is published for informational purposes.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Not all documents approved by the IESG are a candidate for any level of Internet Standard; see Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at http://www.rfc-editor.org/info/rfc7128.

Bush, et al.

Informational

[Page 1]

## Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction
2.	Implementation Forms
3.	Protocol Data Units
4.	Protocol Sequence
5.	Protocol Transport
6.	Error Codes
7.	Incremental Updates Support
8.	Session ID Support
9.	Incremental Session Startup Support
10.	Interoperable Implementations
1(	).1. Cisco Implementation
10	).2. Juniper Implementation
10	0.3. rpki.net Implementation
1(	0.4. RIPE NCC Implementation
10	0.5. RTRlib Implementation
10	).6. BBN RPSTIR Implementation
11.	Security Considerations
12.	Acknowledgements
13.	Normative References

Bush, et al.

Informational

[Page 2]

# 1. Introduction

In order to formally validate the origin Autonomous Systems (ASes) of BGP announcements, routers need a simple but reliable mechanism to receive Resource Public Key Infrastructure (RPKI) [RFC6810] prefix origin data from a trusted cache. The RPKI Router protocol defined in [RFC6810] provides a mechanism to deliver validated prefix origin data to routers.

This document provides an implementation report for the RPKI Router protocol as defined in RFC 6810 [RFC6810].

The authors did not verify the accuracy of the information provided by respondents or by any alternative means. The respondents are experts with the implementations they reported on, and their responses are considered authoritative for the implementations for which their responses represent. Respondents were asked to only use the "YES" answer if the feature had at least been tested in the lab.

### 2. Implementation Forms

Contact and implementation information for person filling out this form:

#### TOS

Name: Keyur Patel Email: keyupate@cisco.com Vendor: Cisco Systems, Inc. Release: IOS Protocol Role: Client

#### XR

Name: Forhad Ahmed Email:foahmed@cisco.com Vendor: Cisco Systems, Inc. Release: IOS-XR Protocol Role: Client

### JUNOS

Name: Hannes Gredler Email: hannes@juniper.net Vendor: Juniper Networks, Inc. Release: JUNOS Protocol Role: Client

Bush, et al.

Informational

[Page 3]

rpki.net Name: Rob Austein Email: sra@hactrn.net Vendor: rpki.net project Release: <http://subvert-rpki.hactrn.net/trunk/> Protocol Role: Client, Server NCC Name: Tim Bruijnzeels Email: tim@ripe.net Vendor: RIPE NCC Release: RIPE NCC validator-app 2.0.0 <https://github.com/RIPE-NCC /rpki-validator> Protocol Role: Server RTRlib Name: Fabian Holler, Matthias Waehlisch Email: waehlisch@ieee.org Vendor: HAW Hamburg, FU Berlin, RTRlib project Release: RTRlib 0.2 <http://rpki.realmv6.org/> Protocol Role: Client BBN Name: David Mandelberg, Andrew Chi Email: dmandelb@bbn.com Vendor: Raytheon/BBN Technologies Release: RPSTIR 0.2 <http://sourceforge.net/projects/rpstir/> Protocol Role: Server 3. Protocol Data Units Does the implementation support Protocol Data Units (PDUs) as described in Section 5 of [RFC6810]? P0: Serial Notify P1: Serial Query P2: Reset Query P3: Cache Response P4: IPv4 Prefix P6: IPv6 Prefix P7: End of Data

Bush, et al.

Informational

[Page 4]

P8: Cache Reset

P10: Error Report

_		L					L	L	L	1
		IOS	XR	JUNOS	rpki .net clnt	rpki .net srvr	NCC   	RTR-	BBN	
-	Rcv.P0	   YES		YES	 YES			   YES		+
	Snd.P0					YES	YES		YES	İ
	Rcv.P1					YES	YES		YES	İ
	Snd.P1	YES	YES	YES	YES		j	YES		İ
	Rcv.P2					YES	YES		YES	İ
	Snd.P2	YES	YES	YES	YES			YES		İ
	Rcv.P3	YES	YES	YES	YES			YES		İ
	Snd.P3					YES	YES		YES	ĺ
	Rcv.P4	YES	YES	YES	YES			YES		ĺ
	Snd.P4					YES	YES		YES	
	Rcv.P6	YES	YES	YES	YES			YES		
	Snd.P6					YES	YES		YES	
	Rcv.P7	YES	YES	YES	YES			YES		
	Snd.P7					YES	YES		YES	
	Rcv.P8	YES	YES	YES	YES			YES		
	Snd.P8					YES	YES		YES	
	Rcv.P10	YES	YES	NO~1	YES	YES	YES	YES	YES	
	Snd.P10	YES	NO	NO	YES	YES	YES	YES	YES	
+		+	+		+	+	+	+	+	÷

Note 1: No, Error PDU gets silently ignored.

Bush, et al. Informational

[Page 5]

4. Protocol Sequence

Does the RPKI Router protocol implementation follow the four protocol sequences as outlined in Section 6 of [RFC6810]?

- S1: Start or Restart
- S2: Typical Exchange
- S3: No Incremental Update Available

S4: Cache Has No Data Available

	IOS	XR	JUNOS	rpki .net clnt	rpki .net srvr	NCC	RTRlib	BBN
S1	YES	YES	YES	YES	YES	YES	YES	YES
S2	YES	YES	YES	YES	YES	NO~1	YES	YES
S3	YES	YES	YES	YES	YES	YES	YES	YES
S4	YES	YES	YES	YES	YES	YES	YES	YES~2

- Note 1: Does not implement Serial Query, thus Incremental Update is never available, so responds to Serial Query with Cache Reset as described in Section 6.3 of [RFC6810]
- Note 2: Sends Cache Reset in response to Serial Query when no data; sends Error Report PDU in response to Reset Query when no data.

Bush, et al.

Informational

[Page 6]

## 5. Protocol Transport

Does the RPKI Router protocol implementation support the different protocol transport mechanisms outlined in Section 7 of [RFC6810]?

+	IOS	+   XR   	JUNOS	rpki .net clnt	rpki .net srvr	NCC	RTRlib	BBN
SSH   TLS   TCP   TCP-MD5   TCP-AO   IPsec	NO NO YES NO NO NO	YES NO YES NO NO	NO NO YES NO NO	YES NO YES NO NO	YES NO YES NO NO NO	NO NO YES NO NO	YES NO YES NO NO	YES NO YES NO NO NO

## 6. Error Codes

Does the RPKI Router protocol implementation support the different protocol error codes outlined in Section 10 of [RFC6810]?

	IOS	XR	JUNOS	rpki .net clnt	rpki .net srvr	NCC   	RTRlib	++   BBN   
Rcv.0	YES	YES	NO	YES	YES	YES	YES	YES
Snd.0	YES	YES	NO	YES	YES	YES	YES	YES
Rcv.1	YES	YES	NO	YES	YES	YES	YES	YES
Snd.1	YES	YES	NO	YES	YES	YES	YES	YES
Rcv.2	YES	YES	NO	YES			YES	
Snd.2					YES	YES		YES
Rcv.3	YES	YES	NO	YES			YES	
Snd.3					YES	YES		YES
Rcv.4	YES	YES	NO	YES	YES	YES	YES	YES
Snd.4	YES	YES	NO	YES	YES	YES	YES	YES
Rcv.5	YES	YES	NO	YES	YES	YES	YES	YES
Snd.5	YES	YES	NO	YES	YES	YES	YES	YES
Rcv.6					YES	YES~1		YES
Snd.6	YES	YES	NO	NO			YES	
Rcv.7					YES	YES~1		YES
Snd.7	YES	YES +	NO +	NO	 +	 +	YES +	 ++

Note 1: YES, but... fatal, so connection is dropped, but cache does not conclude it's inconsistent.

Bush, et al.

Informational

[Page 7]

# 7. Incremental Updates Support

Does the RPKI Router implementation support Incremental Updates as defined in Section 4 of [RFC6810]?

IOS   	+ XR   	JUNOS	rpki.net clnt	rpki.net srvr	NCC	+   RTRlib 	++   BBN   
++-	NO   +	YES	YES	 YES 	NO	+   YES +	++   YES   ++

### 8. Session ID Support

Session ID is used to indicate that the cache server may have restarted and that the incremental restart may not be possible.

Does the RPKI Router protocol implementation support the Session ID procedures outlined in Section 5.1 of [RFC6810]?

+   IOS 	+   XR 	+   JUNOS 	rpki.net clnt	rpki.net srvr	+   NCC 	RTRlib	+   BBN   
+   YES +	   YES +	   YES	YES	YES	NO~1	   YES	YES

Note 1: NO, using random, but will FIX

9. Incremental Session Startup Support

Does the RPKI Router protocol implementation support Incremental session startups with Serial Number and Session ID as defined in Section 5.3 of [RFC6810]?

+	IOS	XR	JUNOS	rpki.net clnt	rpki.net srvr	NCC	RTRlib	+   BBN   
	YES	YES	YES	YES	YES	NO	YES	YES

Bush, et al.

Informational

[Page 8]

#### 10. Interoperable Implementations

List other implementations with which you have tested the interoperability of the RPKI Router implementation.

10.1. Cisco Implementation

Cisco: The Cisco IOS and IOS-XR implementation should be interoperable with other vendor RPKI Router Protocol implementations. In particular, we have tested our interoperability with rpki.net's RPKI Router implementation.

#### 10.2. Juniper Implementation

Juniper: The Juniper Networks, Inc. JUNOS implementation should be interoperable with other vendor RPKI Router Protocol implementations. In particular, we have tested our interoperability with rpki.net's and NCC's RPKI Router Cache implementation.

10.3. rpki.net Implementation

rpki.net: The rpki.net implementation should operate with other rpkirtr implementations. In particular, we have tested our rpki-rtr server's interoperability with Cisco IOS, Cisco IOS-XR, and Juniper.

#### 10.4. RIPE NCC Implementation

RIPE NCC: The RIPE NCC validator has been tested by us with other rpki-rtr implementations. In particular, we have tested with RTRlib and CISCO IOS. We received positive feedback from close contacts who tested our validator with JUNOS and Quagga.

### 10.5. RTRlib Implementation

RTRlib: The RTRlib has been tested by us with other rpki-rtr implementations. In particular, we have tested with rtr-origin from rpki.net and RIPE NCC Validator.

10.6. BBN RPSTIR Implementation

BBN RPSTIR: We have not yet tested with any other implementations.

### 11. Security Considerations

No new security issues are introduced to the RPKI Router protocol defined in [RFC6810].

Bush, et al.

Informational

[Page 9]

# 12. Acknowledgements

The authors would like to thank Andrew Chi, David Mandelberg, Fabian Holler, Forhad Ahmed, and Tim Bruijnzeels for their contributions to this document.

- 13. Normative References
  - [RFC6810] Bush, R. and R. Austein, "The Resource Public Key Infrastructure (RPKI) to Router Protocol", RFC 6810, January 2013.

Bush, et al.

Informational

[Page 10]

Authors' Addresses Randy Bush Internet Initiative Japan 5147 Crystal Springs Bainbridge Island, Washington 98110 US EMail: randy@psg.com Rob Austein Dragon Research Labs EMail: sra@hactrn.net Keyur Patel Cisco Systems 170 West Tasman Drive San Jose, California 95134 US EMail: keyupate@cisco.com Hannes Gredler Juniper Networks, Inc. 1194 N. Mathilda Ave. Sunnyvale, California 94089 US EMail: hannes@juniper.net Matthias Waehlisch FU Berlin Takustr. 9 Berlin 14195 Germany EMail: waehlisch@ieee.org URI: http://www.inf.fu-berlin.de/~waehl

Bush, et al.

Informational

[Page 11]