

Network Working Group
Request for Comments: 3055
Category: Standards Track

M. Krishnaswamy
Photuris, Inc.
D. Romascanu
Avaya Communication
February 2001

Management Information Base for the PINT Services Architecture

Status of this Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Copyright Notice

Copyright (C) The Internet Society (2001). All Rights Reserved.

Abstract

This memo describes a proposed Management Information Base (MIB) for the PSTN/Internet Interworking (PINT) Services Architecture.

Table of Contents

1. Introduction	2
2. The SNMP Management Framework	2
3. The need for PINT Services monitoring MIB	3
4. PINT MIB Overview	4
5. Definitions	5
6. Acknowledgements	17
7. Security Considerations	17
8. IANA Considerations	18
9. Intellectual Property	18
10. References	18
11. Authors' Addresses	20
12. Full Copyright Statement	21

1. Introduction

PINT services are an emerging set of new Internet based applications where voice (and fax) requests to the PSTN (Public Switched Telephone Network) are carried over the Internet. RFC 2458 [1] gives a good introduction to the (pre-standard) PINT architecture and services. It also has examples of some of the early implementations of pre-PINT.

This document defines a MIB which contains the elements for monitoring the performance of a PINT based service. The MIB consists of details of the four basic PINT services and their performance statistics measured under various criteria.

It is not the purpose of this MIB to enable management of the PINT networking elements. We are concerned only with the PINT specific performance parameters. While it is understood that PINT service performance is closely related to host and network performance, they are not addressed here.

2. The SNMP Management Framework

The SNMP Management Framework presently consists of five major components:

- o An overall architecture, described in RFC 2571 [2].
- o Mechanisms for describing and naming objects and events for the purpose of management. The first version of this Structure of Management Information (SMI) is called SMIV1 and described in STD 16, RFC 1155 [3], STD 16, RFC 1212 [4] and RFC 1215 [5]. The second version, called SMIV2, is described in STD 58, RFC 2578 [6], RFC 2579 [7] and RFC 2580 [8].
- o Message protocols for transferring management information. The first version of the SNMP message protocol is called SNMPv1 and described in STD 15, RFC 1157 [9]. A second version of the SNMP message protocol, which is not an Internet standards track protocol, is called SNMPv2c and described in RFC 1901 [10] and RFC 1906 [11]. The third version of the message protocol is called SNMPv3 and described in RFC 1906 [11], RFC 2572 [12] and RFC 2574 [13].
- o Protocol operations for accessing management information. The first set of protocol operations and associated PDU formats is described in STD 15, RFC 1157 [9]. A second set of protocol operations and associated PDU formats is described in RFC 1905 [14].

- o A set of fundamental applications described in RFC 2573 [15] and the view-based access control mechanism described in RFC 2575 [16].

A more detailed introduction to the current SNMP Management Framework can be found in RFC 2570 [17].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. Objects in the MIB are defined using the mechanisms defined in the SMI.

This memo specifies a MIB module that is compliant to the SMIV2. A MIB conforming to the SMIV1 can be produced through the appropriate translations. The resulting translated MIB must be semantically equivalent, except where objects or events are omitted because no translation is possible (use of Counter64). Some machine-readable information in SMIV2 will be converted into textual descriptions in SMIV1 during the translation process. However, this loss of machine readable information is not considered to change the semantics of the MIB.

3. The need for PINT services monitoring MIB

Traditionally voice (and fax) requests originate and terminate inside a PSTN network. This network is well known for robust handling of the requests, in terms of availability and security. However when the requests originate from the Internet there is a concern both on the part of the user as well as the provider about issues like reliable forwarding of the call requests to the PINT gateway under various network conditions, user/host authentication, secure handling of the user information etc. Performance and security management becomes all the more important where PINT services cross multiple administrative domains (or providers).

This MIB is an attempt to list the parameters that need to be monitored on an user, PINT client, PINT server and PINT gateway basis.

(PINT services, their invocation methods/protocols and security issues associated with the PINT architecture are discussed in detail in [18]).

4. PINT MIB - Overview

Following is a list of some explanations on the MIB definitions that we have chosen to construct.

- o The basic purpose of this MIB is to monitor the access to PINT services both from the performance and security point of view. Information may pertain to a certain user or his/her system (PINT client) or the system providing the PINT services (PINT server) or the PINT gateway that forwards the call to the PSTN network.
- o We chose to build the configuration table as an extension of the Application MIB - RFC 2287 [19] using the augments construct. Server location and contact might be retrieved from the standard MIB-II sysLocation and sysContact objects. There is no need to replicate this information in the PINT MIB. However, the PINT administrator may be a different person than the sysadmin with global responsibilities, thus a pintSysContact object is defined.
- o We chose to monitor the gateway connections from the PINT server. While the agent runs in the PINT servers, the connections to the gateways might need to be monitored in order to understand what goes on. We placed them in a separate MIB group, and by using MODULE-COMPLIANCE clauses, agents that cannot implement this stuff will not be mandated to do it.
- o There is no traps definition in this MIB module. Note that thresholding on counters is always possible by using a standard mechanism defined by the Remote Monitoring MIB, that can be referenced here. Some events that may be defined by using this mechanisms:
 - * continuous login/authentication failure or refusal from a particular client or user
 - * nuisance call - repeated calls (within a specified period) to a number originating from the same user
- o The client performance and user performance tables may be rather resource demanding for an agent implementation. In some MIBs, like the Remote Monitoring (RMON) MIBs, control mechanisms were built in order to activate those statistics on demand. If needed, a sorting ('topN') mechanism can be designed, so that a sorted view of clients or users is presented for the high level debugging.

- o We built a time-distribution trying to cover both short-lived, as well as longer sessions (1-10 secs, 10 secs - 1 min., 1-15 min., 15 mins-24 hours, longer).
- o PintServerClientAddress is defined as a SnmpAdminString. It may include an IpAddress and/or name, but we preferred to minimize the number of indices at this stage, and keep a human-readable format at the same time.
- o We define pintServerUserName as the UserId. This UserId needs to be unique across multiple PINT servers and gateways (depending on the architecture) and is mapped to the SessionId. One way to achieve this uniqueness is by appending clientId to the UserId string before sending to the PINT server. The SessionId could then be a combination of this new UserId and a timestamp.

5. Definitions

PINT-MIB DEFINITIONS ::= BEGIN

```

IMPORTS
    OBJECT-TYPE, Counter32, MODULE-IDENTITY, mib-2
FROM    SNMPv2-SMI
TEXTUAL-CONVENTION
FROM    SNMPv2-TC
MODULE-COMPLIANCE, OBJECT-GROUP
FROM    SNMPv2-CONF
sysApplInstallPkgEntry
FROM    SYSAPPL-MIB
SnmpAdminString
FROM    SNMP-FRAMEWORK-MIB; -- RFC 2571 [2]

pintMib MODULE-IDENTITY
LAST-UPDATED "200102010000Z" -- 1 Feb 2001

```

ORGANIZATION "IETF PINT Working Group"

CONTACT-INFO "

Chairs: Steve Bellovin
E-mail: smb@research.att.com

Igor Faynberg
E-mail: faynberg@lucent.com

Authors: Murali Krishnaswamy
Postal: 20 Corporate Place South
Piscataway, NJ 08854
Tel: +1 (732)465-1000

E-mail: murali@photuris.com

Dan Romascanu
 Postal: Atidim Technology Park, Bldg 3
 Tel Aviv, Israel
 Tel: +972 3 6458414
 E-mail: dromasca@avaya.com

General Discussion: pint@lists.bell-labs.com
 To Subscribe: pint-request@lists.bell-labs.com
 In Body: subscribe your-email-address
 Archive: <http://www.bell-labs.com/mailing-lists/pint/>
 "

DESCRIPTION

"This MIB defines the objects necessary to monitor
 PINT Services"

-- Revision history

REVISION "200102010000Z" -- 1 Feb 2001

DESCRIPTION

"Initial version, published as RFC 3055."

::= { mib-2 93 }

PintServiceType ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"This TC describes the type of a PINT service."

SYNTAX INTEGER {
 r2C(1), -- Request-to-Talk
 r2F(2), -- Request-to-Fax
 r2FB(3), -- Request-to-Fax-Back
 r2HC(4) -- Request-to-Hear-Content
 }

PintPerfStatPeriod ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"This TC describes the statistics period of time.

Note that the values of the counters indexed with a value
 SinceReboot(4) can be potentially affected by a counter rollover.
 It is the responsibility of the application using this object to
 take into account that the counter has been zeroed each time it
 reached a value of (2**32-1)."

SYNTAX INTEGER {
 last30sec(1), -- Performance Statics for the last 30 sec

```

last15min(2),  -- 15 min
last24Hr(3),  -- 24 Hour
sinceReboot(4) -- Since the time the pint server was
-- last rebooted
}

```

```

pintServerConfig      OBJECT IDENTIFIER ::= { pintMib 1 }
pintServerMonitor     OBJECT IDENTIFIER ::= { pintMib 2 }
pintMibConformance   OBJECT IDENTIFIER ::= { pintMib 3 }

```

```
-- pintServerConfig - PINT configuration MIB variables
```

```

pintReleaseNumber OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "An indication of version of the PINT protocol supported
        by this agent."
    ::= { pintServerConfig 1 }

```

```

pintSysContact      OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "Contact information related to the administration of the PINT
        services."
    ::= { pintServerConfig 2 }

```

```

pintApplInstallPkgTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PintApplInstallPkgEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Table describing the PINT applications that are installed."
    ::= { pintServerConfig 3 }

```

```

pintApplInstallPkgEntry OBJECT-TYPE
    SYNTAX      PintApplInstallPkgEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Entries per PINT Application."
    AUGMENTS { sysApplInstallPkgEntry }
    ::= { pintApplInstallPkgTable 1 }

```

```
PintApplInstallPkgEntry ::= SEQUENCE {
```

```

pintApplInstallPkgDescription      SnmpAdminString
}

pintApplInstallPkgDescription OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Textual description of the installed PINT application."
    ::= { pintApplInstallPkgEntry 1 }

pintRegisteredGatewayTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PintRegisteredGatewayEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Table describing the registered gateway applications."
    ::= { pintServerConfig 4 }

pintRegisteredGatewayEntry OBJECT-TYPE
    SYNTAX      PintRegisteredGatewayEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Entries per Registered Gateway Application."
    AUGMENTS { sysApplInstallPkgEntry }
    ::= { pintRegisteredGatewayTable 1 }

PintRegisteredGatewayEntry ::= SEQUENCE {
    pintRegisteredGatewayName      SnmpAdminString,
    pintRegisteredGatewayDescription SnmpAdminString
}

pintRegisteredGatewayName OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Name of the registered gateway."
    ::= { pintRegisteredGatewayEntry 1 }

pintRegisteredGatewayDescription OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Textual description of the registered gateway."
    ::= { pintRegisteredGatewayEntry 2 }

```


-- pintServerMonitor - PINT monitoring statistics MIB variables

```
pintServerGlobalPerf      OBJECT IDENTIFIER ::= {pintServerMonitor 1 }
pintServerClientPerf     OBJECT IDENTIFIER ::= {pintServerMonitor 2 }
pintServerUserIdPerf     OBJECT IDENTIFIER ::= {pintServerMonitor 3 }
pintServerGatewayPerf    OBJECT IDENTIFIER ::= {pintServerMonitor 4 }
```

```
pintServerGlobalStatsTable      OBJECT-TYPE
    SYNTAX          SEQUENCE OF PintServerGlobalStatsEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "Table displaying the monitored global server statistics."
    ::= { pintServerGlobalPerf 1 }
```

```
pintServerGlobalStatsEntry OBJECT-TYPE
    SYNTAX          PintServerGlobalStatsEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "Entries in the global statistics table.
         One entry is defined for each monitored service type and
         performance statistics collection period."
    INDEX {pintServerServiceTypeIndex, pintServerPerfStatPeriodIndex}
    ::= { pintServerGlobalStatsTable 1 }
```

```
PintServerGlobalStatsEntry      ::= SEQUENCE {
pintServerServiceTypeIndex      PintServiceType,
pintServerPerfStatPeriodIndex   PintPerfStatPeriod,
pintServerGlobalCallsReceived   Counter32,
pintServerGlobalSuccessfulCalls Counter32,
pintServerGlobalDisconnectedCalls Counter32,
pintServerGlobalDisCUAutFCalls  Counter32,
pintServerGlobalDisServProbCalls Counter32,
pintServerGlobalDisGatProbCalls Counter32
}
```

```
pintServerServiceTypeIndex OBJECT-TYPE
    SYNTAX          PintServiceType
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "The unique identifier of the monitored service."
    ::= { pintServerGlobalStatsEntry 1 }
```

```
pintServerPerfStatPeriodIndex OBJECT-TYPE
    SYNTAX          PintPerfStatPeriod
    MAX-ACCESS      not-accessible
```

```
STATUS      current
DESCRIPTION
  "Time period for which the performance statistics are requested
  from the pint server."
 ::= { pintServerGlobalStatsEntry 2 }

pintServerGlobalCallsReceived OBJECT-TYPE
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
  "Number of received global calls."
 ::= { pintServerGlobalStatsEntry 3 }

pintServerGlobalSuccessfulCalls OBJECT-TYPE
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
  "Number of global successful calls."
 ::= { pintServerGlobalStatsEntry 4 }

pintServerGlobalDisconnectedCalls OBJECT-TYPE
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
  "Number of global disconnected (failed) calls."
 ::= { pintServerGlobalStatsEntry 5 }

pintServerGlobalDisCUAutFCalls
OBJECT-TYPE
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
  "Number of global calls that were disconnected because of client
  or user authorization failure."
 ::= { pintServerGlobalStatsEntry 6 }

pintServerGlobalDisServProbCalls OBJECT-TYPE
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
  "Number of global calls that were disconnected because of
  server problems."
 ::= { pintServerGlobalStatsEntry 7 }
```

```

pintServerGlobalDisGatProbCalls OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of global calls that were disconnected because of
        gateway problems."
    ::= { pintServerGlobalStatsEntry 8 }

pintServerClientStatsTable      OBJECT-TYPE
    SYNTAX      SEQUENCE OF PintServerClientStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Table displaying the monitored server client statistics."
    ::= { pintServerClientPerf 1 }

pintServerClientStatsEntry OBJECT-TYPE
    SYNTAX      PintServerClientStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Entries in the client server statistics table.
        One entry is defined for each client identified by name,
        monitored service type and performance statistics collection
        period."
    INDEX {pintServerClientAddress, pintServerServiceTypeIndex,
    pintServerPerfStatPeriodIndex}
    ::= { pintServerClientStatsTable 1 }

PintServerClientStatsEntry      ::= SEQUENCE {
pintServerClientAddress          SnmpAdminString,
pintServerClientCallsReceived   Counter32,
pintServerClientSuccessfulCalls Counter32,
pintServerClientDisconnectedCalls Counter32,
pintServerClientDisCAutFCalls   Counter32,
pintServerClientDisEFProbCalls  Counter32
}

pintServerClientAddress OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The unique identifier of the monitored client
        identified by its address represented as as a string."
    ::= { pintServerClientStatsEntry 1 }

```

```

pintServerClientCallsReceived OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of calls received from the specific client."
    ::= { pintServerClientStatsEntry 2 }

pintServerClientSuccessfulCalls OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of calls from the client successfully completed."
    ::= { pintServerClientStatsEntry 3 }

pintServerClientDisconnectedCalls OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of calls received from the client, and that were
        disconnected (failed)."
    ::= { pintServerClientStatsEntry 4 }

pintServerClientDisCAutFCalls
OBJECT-TYPE
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "Number of calls from the client that were disconnected because of
    client authorization failure."
::= { pintServerClientStatsEntry 5 }

pintServerClientDisEFProbCalls OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of calls from the client that were disconnected because
        of egress facility problems."
    ::= { pintServerClientStatsEntry 6 }

pintServerUserIdStatsTable      OBJECT-TYPE
    SYNTAX      SEQUENCE OF PintServerUserIdStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current

```

DESCRIPTION

"Table displaying the monitored Pint service user statistics."
 ::= { pintServerUserIdPerf 1 }

pintServerUserIdStatsEntry OBJECT-TYPE

SYNTAX PintServerUserIdStatsEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Entries in the user statistics table.

One entry is defined for each user identified by name,
 each monitored service type and performance statistics collection
 period.

It is assumed that the capabilities of the pint server
 are enough to accommodate the number of entries in this table.

It is a local server implementation issue if an aging mechanism

is implemented in order to avoid scalability problems."

INDEX {pintServerUserIdName, pintServerServiceTypeIndex,
 pintServerPerfStatPeriodIndex}

::= { pintServerUserIdStatsTable 1 }

```
PintServerUserIdStatsEntry      ::= SEQUENCE {
pintServerUserIdName            SnmpAdminString,
pintServerUserIdCallsReceived   Counter32,
pintServerUserIdSuccessfulCalls Counter32,
pintServerUserIdDisconnectedCalls Counter32,
pintServerUserIdDiscUIdAFailCalls Counter32,
pintServerUserIdEFProbCalls     Counter32
}
```

pintServerUserIdName OBJECT-TYPE

SYNTAX SnmpAdminString (SIZE(0..64))

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The unique identifier of the monitored user
 identified by its name."

::= { pintServerUserIdStatsEntry 1 }

pintServerUserIdCallsReceived OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Number of calls received from the specific user."

::= { pintServerUserIdStatsEntry 2 }

```

pintServerUserIdSuccessfulCalls OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of calls from the user successfully completed."
    ::= { pintServerUserIdStatsEntry 3 }

pintServerUserIdDisconnectedCalls OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of calls received from the user that were
        disconnected (failed)."
    ::= { pintServerUserIdStatsEntry 4 }

pintServerUserIdDiscUIIdAFailCalls
OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of calls from the user that were disconnected because of
        user authorization failure."
    ::= { pintServerUserIdStatsEntry 5 }

pintServerUserIdEFProbCalls OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of calls from the user that were disconnected because of
        egress facility problems."
    ::= { pintServerUserIdStatsEntry 6 }

pintServerGatewayStatsTable      OBJECT-TYPE
    SYNTAX      SEQUENCE OF PintServerGatewayStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Table displaying the monitored gateway statistics."
    ::= { pintServerGatewayPerf 1 }

pintServerGatewayStatsEntry OBJECT-TYPE
    SYNTAX      PintServerGatewayStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current

```

DESCRIPTION

"Entries in the gateway table.
One entry is defined for each gateway identified by name,
each monitored service type and performance statistics collection
period."

INDEX { pintRegisteredGatewayName, pintServerServiceTypeIndex,
pintServerPerfStatPeriodIndex }
 ::= { pintServerGatewayStatsTable 1 }

PintServerGatewayStatsEntry ::= SEQUENCE {
pintServerGatewayCallsReceived Counter32,
pintServerGatewaySuccessfulCalls Counter32,
pintServerGatewayDisconnectedCalls Counter32
}

pintServerGatewayCallsReceived OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Number of calls received at the specified gateway."
 ::= { pintServerGatewayStatsEntry 1 }

pintServerGatewaySuccessfulCalls OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Number of calls successfully completed at the specified gateway."
 ::= { pintServerGatewayStatsEntry 2 }

pintServerGatewayDisconnectedCalls OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Number of calls that were disconnected (failed) at the specified
gateway."
 ::= { pintServerGatewayStatsEntry 3 }

--
-- Notifications Section
-- (none defined)
--

--
-- Conformance Section

```

--

pintMibCompliances OBJECT IDENTIFIER ::= { pintMibConformance 1 }
pintMibGroups      OBJECT IDENTIFIER ::= { pintMibConformance 2 }

pintMibCompliance MODULE-COMPLIANCE
STATUS current
DESCRIPTION
    "Describes the requirements for conformance to the
    PINT MIB."
MODULE -- this module
MANDATORY-GROUPS { pintMibConfigGroup, pintMibMonitorGroup }
 ::= { pintMibCompliances 1 }

pintMibConfigGroup OBJECT-GROUP
OBJECTS {
pintReleaseNumber,
pintSysContact,
pintApplInstallPkgDescription,
pintRegisteredGatewayName,
pintRegisteredGatewayDescription
}
STATUS current
DESCRIPTION
    "A collection of objects providing configuration
    information
    for a PINT Server."
 ::= { pintMibGroups 1 }

pintMibMonitorGroup OBJECT-GROUP
OBJECTS {
pintServerGlobalCallsReceived,
pintServerGlobalSuccessfulCalls,
pintServerGlobalDisconnectedCalls,
pintServerGlobalDisCUAutFCalls,
pintServerGlobalDisServProbCalls,
pintServerGlobalDisGatProbCalls,
pintServerClientCallsReceived,
pintServerClientSuccessfulCalls,
pintServerClientDisconnectedCalls,
pintServerClientDisCAutFCalls,
pintServerClientDisEFProbCalls,
--pintServerUserIdName,
pintServerUserIdCallsReceived,
pintServerUserIdSuccessfulCalls,
pintServerUserIdDisconnectedCalls,
pintServerUserIdDiscUIAFailCalls,
pintServerUserIdEFProbCalls,

```



```
pintServerGatewayCallsReceived,  
pintServerGatewaySuccessfulCalls,  
pintServerGatewayDisconnectedCalls  
}  
STATUS current  
DESCRIPTION  
    "A collection of objects providing monitoring  
    information  
    for a PINT Server."  
 ::= { pintMibGroups 2 }  
  
END
```

6. Acknowledgements

The authors would like to thank Igor Faynberg for his encouragement to produce this work.

7. Security Considerations

There is only one management object defined in this MIB that has a MAX-ACCESS clause of read-write (pintSysContact). There are no read-create objects. This read-write object may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

There are a number of managed objects in this MIB that may contain information that may be sensitive from a business perspective. One could be the customer identification (UserIdName). Also information on PINT services performance might itself be need to be guarded. It is thus important to control even GET access to these objects and possibly to even encrypt the values of these object when sending them over the network via SNMP. Not all versions of SNMP provide features for such a secure environment.

SNMPv1 by itself is not a secure environment. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB.

It is recommended that the implementers consider the security features as provided by the SNMPv3 framework. Specifically, the use of the User-based Security Model RFC 2574 [13] and the View-based Access Control Model RFC 2575 [16] is recommended.

It is then a customer/user responsibility to ensure that the SNMP entity giving access to an instance of this MIB, is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

8. IANA Considerations

All extensions to the values listed in this MIB must be done through Standards Action processes as defined in RFC 2434 [20].

9. Intellectual Property

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in BCP-11. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

10. References

- [1] Lu, H., Conroy, L., Bellovin, S., Krishnaswamy, M., Burg, F., DeSimone, A., Tewani, K., Davidson, P., Schulzrinne, H. and K. Vishwanathan, "Toward the PSTN/Internet Inter-Networking -- Pre-PINT Implementations", RFC 2458, November 1998.
- [2] Wijnen, B., Harrington, D. and R. Presuhn, "An Architecture for Describing SNMP Management Frameworks", RFC 2571, April 1999.
- [3] Rose, M. and K. McCloghrie, "Structure and Identification of Management Information for TCP/IP-based Internets", STD 16, RFC 1155, May 1990.

- [4] Rose, M. and K. McCloghrie, "Concise MIB Definitions", STD 16, RFC 1212, March 1991.
- [5] Rose, M., "A Convention for Defining Traps for use with the SNMP", RFC 1215, March 1991.
- [6] McCloghrie, K., Perkins, D. and J. Schoenwaelder, "Structure of Management Information Version 2 (SMIV2)", STD 58, RFC 2578, April 1999.
- [7] McCloghrie, K., Perkins, D. and J. Schoenwaelder, "Textual Conventions for SMIV2", STD 58, RFC 2579, April 1999.
- [8] McCloghrie, K., Perkins, D. and J. Schoenwaelder, "Conformance Statements for SMIV2", STD 58, RFC 2580, April 1999.
- [9] Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.
- [10] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Introduction to Community-based SNMPv2", RFC 1901, January 1996.
- [11] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Transport Mappings for Version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1906, January 1996.
- [12] Case, J., Harrington D., Presuhn R. and B. Wijnen, "Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)", RFC 2572, April 1999.
- [13] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", RFC 2574, April 1999.
- [14] Case, J., McCloghrie, K., Rose, M. and Waldbusser, "Protocol Operations for Version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1905, January 1996.
- [15] Levi, D., Meyer, P. and B. Stewart, "SNMPv3 Applications", RFC 2573, April 1999.
- [16] Wijnen, B., Presuhn, R. and K. McCloghrie, "View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)", RFC 2575, April 1999.

- [17] Case, J., Mundy, R., Partain, D. and B. Stewart, "Introduction to Version 3 of the Internet-standard Network Management Framework", RFC 2570, April 1999.
- [18] Petrack, S. and L. Conroy, "The PINT Service Protocol: Extensions to SIP and SDP for IP Access to Telephone Call Services", RFC 2848, June 2000.
- [19] Krupczak, C. and J. Saperia, "Definitions of System-Level Managed Objects for Applications", RFC 2287, February 1998.
- [20] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", BCP 26, RFC 2434, October 1998.

11. Authors' Addresses

Murali Krishnaswamy
Lucent Technologies
3C-512, 101 Crawfords Corner Rd.
Holmdel, NJ 07733

Phone: +1 (732)949-3611
Fax: +1 (732)949-3210
EMail: murali@lucent.com

Dan Romascanu
Avaya Communication
Atidim Technology Park, Bldg 3
Tel Aviv, Israel

Phone: +972 3 6458414
EMail: dromasca@avaya.com

12. Full Copyright Statement

Copyright (C) The Internet Society (2001). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.

