Internet Engineering Task Force (IETF)

Request for Comments: 7330 Category: Standards Track

ISSN: 2070-1721

T. Nadeau Brocade Z. Ali N. Akiya Cisco Systems August 2014

[Page 1]

Definitions of Textual Conventions (TCs) for Bidirectional Forwarding Detection (BFD) Management

Abstract

This document defines two Management Information Base (MIB) modules that contain Textual Conventions to represent commonly used Bidirectional Forwarding Detection (BFD) management information. The intent is that these TEXTUAL CONVENTIONS (TCs) will be imported and used in BFD-related MIB modules that would otherwise define their own representations.

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at http://www.rfc-editor.org/info/rfc7330.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	. 2
	1.1. Requirements Language	. 2
2.	The Internet-Standard Management Framework	. 2
	BFD Textual Conventions MIB Definitions	
	Security Considerations	
	IANA Considerations	
6.	Acknowledgments	10
	References	
	7.1. Normative References	10
	7.2. Informative References	11

1. Introduction

This document defines two MIB modules that contain Textual Conventions for Bidirectional Forwarding Detection (BFD) protocols. These Textual Conventions should be imported by MIB modules that manage BFD protocols.

Note that names of Textual Conventions defined in this document are prefixed with either "Bfd" or "IANA" to make it obvious to readers that some are specific to BFD modules, whereas others are IANA maintained.

For an introduction to the concepts of BFD, see [RFC5880], [RFC5881], [RFC5883], [RFC6428], and [RFC7130].

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14, RFC 2119 [RFC2119].

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB

module that is compliant to the SMIv2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

3. BFD Textual Conventions MIB Definitions

This MIB module makes references to the following documents: [RFC2578], [RFC2579], [RFC5880], [RFC5881], [RFC5883], [RFC6428], and [RFC7130].

BFD-TC-STD-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY, mib-2, Unsigned32 FROM SNMPv2-SMI

TEXTUAL-CONVENTION

FROM SNMPv2-TC;

-- RFC 2579

-- RFC 2578

bfdTCStdMib MODULE-IDENTITY

LAST-UPDATED

"201408120000Z" -- 12 August 2014 00:00:00 GMT

ORGANIZATION "IETF Bidirectional Forwarding Detection Working Group"

CONTACT-INFO

"Thomas D. Nadeau

Brocade

Email: tnadeau@lucidvision.com

Zafar Ali

Cisco Systems, Inc. Email: zali@cisco.com

Nobo Akiya

Cisco Systems, Inc. Email: nobo@cisco.com

Comments about this document should be emailed directly to the BFD working group mailing list at rtg-bfd@ietf.org"

DESCRIPTION

"Copyright (c) 2014 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject

Nadeau, et al.

Standards Track

[Page 3]

```
to the license terms contained in, the Simplified BSD License
       set forth in Section 4.c of the IETF Trust's Legal Provisions
       Relating to IETF Documents
       (http://trustee.ietf.org/license-info)."
    REVISION "201408120000Z" -- 12 August 2014 00:00:00 GMT
   DESCRIPTION
      "Initial version. Published as RFC 7330."
::= \{ mib-2 223 \}
BfdSessIndexTC ::= TEXTUAL-CONVENTION
DISPLAY-HINT "d"
STATUS
             current
DESCRIPTION
    "An index used to uniquely identify BFD sessions."
SYNTAX Unsigned32 (1..4294967295)
BfdIntervalTC ::= TEXTUAL-CONVENTION
DISPLAY-HINT "d"
STATUS
             current
DESCRIPTION
    "The BFD interval in microseconds."
SYNTAX Unsigned32 (0..4294967295)
BfdMultiplierTC ::= TEXTUAL-CONVENTION
DISPLAY-HINT "d"
STATUS
               current
DESCRIPTION
    "The BFD failure detection multiplier."
SYNTAX Unsigned32 (1..255)
BfdCtrlDestPortNumberTC ::= TEXTUAL-CONVENTION
                        "d"
DISPLAY-HINT
STATUS
                       current
DESCRIPTION
    "UDP destination port number of BFD control packets.
    3784 represents single-hop BFD session.
     4784 represents multi-hop BFD session.
     6784 represents BFD on Link Aggregation Group (LAG) session.
    However, syntax is left open to wider range of values
    purposely for two reasons:
     1. Implementation uses non-compliant port number for
       valid proprietary reason.
     2. Potential future extension documents.
```

The value of 0 is a special, reserved value used to indicate special conditions and should not be considered a valid port number."

REFERENCE

"Use of port 3784 from Katz, D. and D. Ward, Bidirectional Forwarding Detection (BFD) for IPv4 and IPv6 (Single Hop), RFC 5881, June 2010.

Use of port 4784 from Katz, D. and D. Ward, Bidirectional Forwarding Detection (BFD) for Multihop Paths, RFC 5883, June 2010.

Use of port 6784 from Bhatia, M., Chen, M., Boutros, S., Binderberger, M., and J. Haas, Bidirectional Forwarding Detection (BFD) on Link Aggregation Group (LAG) Interfaces, RFC 7130, February 2014."

SYNTAX Unsigned32 (0..65535)

BfdCtrlSourcePortNumberTC ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"
STATUS current

DESCRIPTION

"UDP source port number of BFD control packets. However, syntax is left open to wider range of values purposely for two reasons:

- 1. Implementation uses non-compliant port number for valid proprietary reason.
- 2. Potential future extension documents.

The value of 0 is a special, reserved value used to indicate special conditions and should not be considered a valid port number."

REFERENCE

"Port 49152..65535 from RFC5881"

SYNTAX Unsigned32 (0..65535)

END

IANA-BFD-TC-STD-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY, mib-2 FROM SNMPv2-SMI

-- RFC 2578

TEXTUAL-CONVENTION FROM SNMPv2-TC;

-- RFC 2579

Nadeau, et al.

Standards Track

[Page 5]

ianaBfdTCStdMib MODULE-IDENTITY LAST-UPDATED "201408120000Z" -- 12 August 2014 00:00:00 GMT ORGANIZATION "IANA" CONTACT-INFO "Internet Assigned Numbers Authority Postal: 12025 Waterfront Drive, Suite 300 Los Angeles, CA 90094-2536 +1 310 301 5800 Tel: EMail: iana@iana.org" DESCRIPTION "Copyright (c) 2014 IETF Trust and the persons identified as authors of the code. All rights reserved. Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info)." REVISION "201408120000Z" -- 12 August 2014 00:00:00 GMT DESCRIPTION "Initial version. Published as RFC 7330." $::= \{ mib-2 224 \}$ IANAbfdDiagTC ::= TEXTUAL-CONVENTION STATUS current DESCRIPTION

"A common BFD diagnostic code."

"Katz, D. and D. Ward, Bidirectional Forwarding Detection (BFD), RFC 5880, June 2010.

Allan, D., Swallow, G., and Drake, J., Proactive Connectivity Verification, Continuity Check, and Remote Defect Indication for the MPLS Transport Profile, RFC 6428, November 2011."

SYNTAX INTEGER { noDiagnostic(0), controlDetectionTimeExpired(1), echoFunctionFailed(2),

```
neighborSignaledSessionDown(3),
    forwardingPlaneReset(4),
   pathDown(5),
    concatenatedPathDown(6),
   administrativelyDown(7),
   reverseConcatenatedPathDown(8),
   misConnectivityDefect(9)
IANAbfdSessTypeTC ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
    "BFD session type"
REFERENCE
    "Katz, D. and D. Ward, Bidirectional Forwarding
    Detection (BFD), RFC 5880, June 2010.
    Katz, D. and D. Ward, Bidirectional Forwarding
    Detection (BFD) for IPv4 and IPv6 (Single Hop),
    RFC 5881, June 2010.
    Katz, D. and D. Ward, Bidirectional Forwarding
    Detection (BFD) for Multihop Paths, RFC 5883,
    June 2010."
SYNTAX INTEGER {
    singleHop(1),
    multiHopTotallyArbitraryPaths(2),
   multiHopOutOfBandSignaling(3),
   multiHopUnidirectionalLinks(4)
IANAbfdSessOperModeTC ::= TEXTUAL-CONVENTION
STATUS
                current
DESCRIPTION
    "BFD session operating mode"
REFERENCE
    "Katz, D. and D. Ward, Bidirectional Forwarding
    Detection (BFD), RFC 5880, June 2010."
SYNTAX INTEGER {
   asyncModeWEchoFunction(1),
    asynchModeWOEchoFunction(2),
    demandModeWEchoFunction(3),
    demandModeWOEchoFunction(4)
}
IANAbfdSessStateTC ::= TEXTUAL-CONVENTION
STATUS
             current
DESCRIPTION
```

"BFD session state. State failing(5) is only applicable if

```
corresponding session is running in BFD version 0."
REFERENCE
    "Katz, D. and D. Ward, Bidirectional Forwarding
    Detection (BFD), RFC 5880, June 2010."
SYNTAX INTEGER {
   adminDown(1),
   down(2),
    init(3),
   up(4),
    failing(5)
}
IANAbfdSessAuthenticationTypeTC ::= TEXTUAL-CONVENTION
                            current
DESCRIPTION
    "BFD authentication type"
REFERENCE
    "Sections 4.2 - 4.4 from Katz, D. and D. Ward,
    Bidirectional Forwarding Detection (BFD),
    RFC 5880, June 2010."
SYNTAX INTEGER {
   noAuthentication(-1),
    reserved(0),
    simplePassword(1),
   keyedMD5(2),
   meticulousKeyedMD5(3),
   keyedSHA1(4),
   meticulousKeyedSHA1(5)
}
IANAbfdSessAuthenticationKeyTC ::= TEXTUAL-CONVENTION
                              "1x "
DISPLAY-HINT
STATUS
                              current
DESCRIPTION
    "BFD authentication key type.
    An IANAbfdSessAuthenticationKeyTC is always interpreted
    within the context of an IANAbfdSessAuthenticationTypeTC
    value. Every usage of the IANAbfdSessAuthenticationTypeTC
     textual convention is required to specify the
     IANAbfdSessAuthenticationKeyTC object that provides the
    context. It is suggested that the
     IANAbfdSessAuthenticationKeyTC object be logically registered
```

IANAbfdSessAuthenticationKeyTC textual convention, if they

[Page 8]

before the object(s) that use the

appear in the same logical row.

The value of an IANAbfdSessAuthenticationKeyTC must always be consistent with the value of the associated IANAbfdSessAuthenticationTypeTC object. Attempts to set an IANAbfdSessAuthenticationKeyTC object to a value inconsistent with the associated IANAbfdSessAuthenticationTypeTC must fail with an inconsistentValue error.

The following size constraints for an IANAbfdSessAuthenticationKeyTC object are defined for the associated IANAbfdSessAuthenticationTypeTC values show below:

noAuthentication(-1): SIZE(0)
reserved(0): SIZE(0)
simplePassword(1): SIZE(1..16)
keyedMD5(2): SIZE(16)
meticulousKeyedMD5(3): SIZE(16)
keyedSHA1(4): SIZE(20)
meticulousKeyedSHA1(5): SIZE(20)

When this textual convention is used as the syntax of an index object, there may be issues with the limit of 128 sub-identifiers specified in SMIv2, STD 58. In this case, the object definition MUST include a 'SIZE' clause to limit the number of potential instance sub-identifiers; otherwise, the applicable constraints MUST be stated in the appropriate conceptual row DESCRIPTION clauses, or in the surrounding documentation if there is no single DESCRIPTION clause that is appropriate."

REFERENCE

"Sections 4.2 - 4.4 from Katz, D. and D. Ward, Bidirectional Forwarding Detection (BFD), RFC 5880, June 2010."

SYNTAX OCTET STRING(SIZE(0..252))

END

4. Security Considerations

This module does not define any management objects. Instead, it defines a set of textual conventions which may be used by other BFD MIB modules to define management objects.

Meaningful security considerations can only be written in the MIB modules that define management objects. This document has therefore no impact on the security of the Internet.

5. IANA Considerations

This document provides the base definition of the IANA-BFD-TC-STD-MIB module. This MIB module is under the direct control of IANA. See Section 3 for the initial contents. See the most updated version of this MIB at http://www.iana.org/assignments/ianabfdtcstd-mib. Assignments of IANA-BFD-TC-STD-MIB are via IETF Review [RFC5226].

This MIB makes reference to the following documents: [RFC2578], [RFC2579], [RFC5880], [RFC5881] and [RFC5883], [RFC6428], and [RFC7130].

IANA assigned an OID to the BFD-TC-STD-MIB module specified in this document as $\{ \text{ mib-2 223 } \}$.

IANA assigned an OID to the IANA-BFD-TC-STD-MIB module specified in this document as $\{ \text{ mib-2 224 } \}$.

6. Acknowledgments

The authors would like to thank Adrian Farrel and Jeffrey Haas for performing thorough reviews and providing a number of suggestions. The authors would also like to thank David Ward and Christer Holmberg for their comments and suggestions.

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, RFC 2579, April 1999.
- [RFC5880] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD)", RFC 5880, June 2010.

- [RFC5883] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD) for Multihop Paths", RFC 5883, June 2010.
- [RFC6428] Allan, D., Swallow Ed., G., and J. Drake Ed., "Proactive Connectivity Verification, Continuity Check, and Remote Defect Indication for the MPLS Transport Profile", RFC 6428, November 2011.
- [RFC7130] Bhatia, M., Chen, M., Boutros, S., Binderberger, M., and
 J. Haas, "Bidirectional Forwarding Detection (BFD) on Link
 Aggregation Group (LAG) Interfaces", RFC 7130, February
 2014.

7.2. Informative References

Authors' Addresses

Thomas D. Nadeau Brocade

EMail: tnadeau@lucidvision.com

Zafar Ali Cisco Systems

EMail: zali@cisco.com

Nobo Akiya Cisco Systems

EMail: nobo@cisco.com