

Internet Engineering Task Force (IETF)
Request for Comments: 7870
Category: Standards Track
ISSN: 2070-1721

Y. Fu
CNNIC
S. Jiang
Huawei Technologies Co., Ltd
J. Dong
Y. Chen
Tsinghua University
June 2016

Dual-Stack Lite (DS-Lite) Management Information Base (MIB) for
Address Family Transition Routers (AFTRs)

Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it defines managed objects for Address Family Transition Routers (AFTRs) of Dual-Stack Lite (DS-Lite).

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 7841.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc7870>.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	2
2. Requirements Language	2
3. The Internet-Standard Management Framework	3
4. Relationship to the IF-MIB	3
5. Difference from the IP Tunnel MIB and NATV2-MIB	3
6. Structure of the MIB Module	4
6.1. The Object Group	5
6.1.1. The dsliteTunnel Subtree	5
6.1.2. The dsliteNAT Subtree	5
6.1.3. The dsliteInfo Subtree	5
6.2. The Notification Group	5
6.3. The Conformance Group	5
7. MIB Modules Required for IMPORTS	5
8. Definitions	6
9. Security Considerations	22
10. IANA Considerations	24
11. References	24
11.1. Normative References	24
11.2. Informative References	26
Acknowledgements	27
Authors' Addresses	27

1. Introduction

Dual-Stack Lite [RFC6333] is a solution that offers both IPv4 and IPv6 connectivity to customers crossing an IPv6-only infrastructure. One of its key components is an IPv4-over-IPv6 tunnel, which is used to provide IPv4 connectivity across a service provider's IPv6 network. Another key component is a carrier-grade IPv4-IPv4 Network Address Translation (NAT) to share service provider IPv4 addresses among customers.

This document defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. This MIB module may be used for configuration and monitoring of Address Family Transition Routers (AFTRs) in a Dual-Stack Lite scenario.

2. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14, RFC 2119 [RFC2119]. When these words are not in ALL CAPS (such as "should" or "Should"), they have their usual English meanings and are not to be interpreted as [RFC2119] key words.

3. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIv2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579], and STD 58, RFC 2580 [RFC2580].

4. Relationship to the IF-MIB

The Interfaces MIB [RFC2863] defines generic managed objects for managing interfaces. Each logical interface (physical or virtual) has an ifEntry. Tunnels are handled by creating a logical interface (ifEntry) for each tunnel. Each DS-Lite tunnel endpoint also acts as a virtual interface that has a corresponding entry in the IP Tunnel MIB and Interface MIB. Those corresponding entries are indexed by ifIndex.

The ifOperStatus in ifTable is used to represent whether the DS-Lite tunnel function has been triggered. The ifInUcastPkts defined in ifTable will represent the number of IPv4 packets that have been encapsulated into IPv6 packets sent to a Basic Bridging BroadBand (B4). The ifOutUcastPkts defined in ifTable contains the number of IPv6 packets that can be decapsulated to IPv4 in the virtual interface. Also, the IF-MIB defines ifMtu for the MTU of this tunnel interface, so the DS-Lite MIB does not need to define the MTU for the tunnel.

5. Difference from the IP Tunnel MIB and NATV2-MIB

The key technologies for DS-Lite are IP-in-IP (IPv4-in-IPv6) tunnels and NAT (IPv4-to-IPv4 translation).

Notes: According to Section 5.2 of [RFC6333], DS-Lite only defines IPv4 in IPv6 tunnels at this moment, but other types of encapsulation could be defined in the future. So, the DS-Lite MIB only supports IP-in-IP encapsulation. If another RFC defines other tunnel types in the future, the DS-Lite MIB will be updated then.

The NATV2-MIB [RFC7659] is designed to carry translation from any address family to any address family; therefore, it supports IPv4-to-IPv4 translation.

The IP Tunnel MIB [RFC4087] is designed to manage tunnels of any type over IPv4 and IPv6 networks; therefore, it already supports IP-in-IP tunnels. But in a DS-Lite scenario, the tunnel type is point-to-multipoint IP-in-IP tunnels. The direct(2) defined in the IP Tunnel MIB only supports point-to-point tunnels. So, it needs to define a new tunnel type for DS-Lite.

However, the NATV2-MIB and IP Tunnel MIB together are not sufficient to support DS-Lite. This document describes the specific features for the DS-Lite MIB, as below.

In the DS-Lite scenario, the Address Family Transition Router (AFTR) is not only the tunnel-end concentrator, but also an IPv4-to-IPv4 NAT. So, as defined in [RFC6333], when the IPv4 packets come back from the Internet to the AFTR, it knows how to reconstruct the IPv6 encapsulation by doing a reverse lookup in the extended IPv4 NAT binding table (Section 6.6 of [RFC6333]). The NAT binding table in the AFTR is extended to include the IPv6 address of the tunnel initiator. However, the NAT binding information defined in the NATV2-MIB as natv2PortMapTable is indexed by the NAT instance, protocol, and external realm and address. Because the tunnelIfTable defined in the TUNNEL-MIB [RFC4087] is indexed by the ifIndex, the DS-Lite MIB needs to define the tunnel objects to extend the NAT binding entry by interface. Therefore, a combined MIB is necessary.

An implementation of the IP Tunnel MIB is required for DS-Lite. As the tunnel is not point-to-point in DS-Lite, it needs to define a new tunnel type for DS-Lite. The tunnelIfEncapsMethod in the tunnelIfEntry should be set to dsLite(17), and a corresponding entry in the DS-Lite module will exist for every tunnelIfEntry with this tunnelIfEncapsMethod. The tunnelIfRemoteInetAddress must be set to ":::".

6. Structure of the MIB Module

The DS-Lite MIB provides a way to monitor and manage the devices (AFTRs) in a DS-Lite scenario through SNMP.

The DS-Lite MIB is configurable on a per-interface basis. It depends on several parts of the IF-MIB [RFC2863], IP Tunnel MIB [RFC4087], and NATV2-MIB [RFC7659].

6.1. The Object Group

This group defines objects that are needed for the DS-Lite MIB.

6.1.1. The dsliteTunnel Subtree

The dsliteTunnel subtree describes managed objects used for managing tunnels in the DS-Lite scenario. Because the tunnelInetConfigLocalAddress and the tunnelInetConfigRemoteAddress defined in the IP Tunnel MIB are not readable, a few new objects are defined in the DS-Lite MIB.

6.1.2. The dsliteNAT Subtree

The dsliteNAT subtree describes managed objects used for configuration and monitoring of an AFTR that is capable of a NAT function. Because the NATV2-MIB supports the NAT management function in DS-Lite, we may reuse it in the DS-Lite MIB. The dsliteNAT subtree also provides the mapping information between the tunnel entry (dsliteTunnelEntry) and the NAT entry (dsliteNATBindEntry) by adding the IPv6 address of the B4 to the natv2PortMapEntry in the NATV2-MIB. The mapping behavior, filtering behavior, and pooling behavior described in this subtree are all defined in [RFC4787].

6.1.3. The dsliteInfo Subtree

The dsliteInfo subtree provides statistical information for DS-Lite.

6.2. The Notification Group

This group defines some notification objects for a DS-Lite scenario.

6.3. The Conformance Group

The dsliteConformance subtree provides conformance information of MIB objects.

7. MIB Modules Required for IMPORTS

This MIB module IMPORTs objects from [RFC2578], [RFC2580], [RFC2863], [RFC3411], [RFC4001], and [RFC7659].

8. Definitions

```
DSLite-MIB DEFINITIONS ::= BEGIN

    IMPORTS
        MODULE-IDENTITY, OBJECT-TYPE, mib-2,
        NOTIFICATION-TYPE, Integer32,
        Counter64, Unsigned32
            FROM SNMPv2-SMI

        OBJECT-GROUP, MODULE-COMPLIANCE,
        NOTIFICATION-GROUP
            FROM SNMPv2-CONF

        SnmpAdminString
            FROM SNMP-FRAMEWORK-MIB

        ifIndex
            FROM IF-MIB

        InetAddress, InetAddressType, InetAddressPrefixLength,
        InetPortNumber
            FROM INET-ADDRESS-MIB

        ProtocolNumber, Natv2InstanceIndex, Natv2SubscriberIndex
            FROM NATV2-MIB;

    dsliteMIB MODULE-IDENTITY
        LAST-UPDATED "201605110000Z"           -- May 11, 2016
        ORGANIZATION "IETF Softwire Working Group"
        CONTACT-INFO
            "Yu Fu
             CNNIC
             No.4 South 4th Street, Zhongguancun
             Hai-Dian District, Beijing 100090
             China
             Email: fuyu@cnnic.cn

             Sheng Jiang
             Huawei Technologies Co., Ltd
             Huawei Building, 156 Beiqing Rd.
             Hai-Dian District, Beijing 100095
             China
             Email: jiangsheng@huawei.com
```

Jiang Dong
 Tsinghua University
 Department of Computer Science, Tsinghua University
 Beijing 100084
 China
 Email: knight.dongjiang@gmail.com

Yuchi Chen
 Tsinghua University
 Department of Computer Science, Tsinghua University
 Beijing 100084
 China
 Email: flashfoxmx@gmail.com "

DESCRIPTION

"The MIB module is defined for management of objects in the DS-Lite scenario.

Copyright (c) 2016 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

REVISION "201605110000Z"

DESCRIPTION

"Initial version. Published as RFC 7870."
 ::= { mib-2 240 }

--Top-level components of this MIB module

dsliteMIBObjects OBJECT IDENTIFIER
 ::= { dsliteMIB 1 }

dsliteTunnel OBJECT IDENTIFIER
 ::= { dsliteMIBObjects 1 }

dsliteNAT OBJECT IDENTIFIER
 ::= { dsliteMIBObjects 2 }

dsliteInfo OBJECT IDENTIFIER
 ::= { dsliteMIBObjects 3 }

--Notifications section

```
dsliteNotifications OBJECT IDENTIFIER
 ::= { dsliteMIB 0 }
```

```
--dsliteTunnel
```

```
--dsliteTunnelTable
```

```
dsliteTunnelTable OBJECT-TYPE
 SYNTAX      SEQUENCE OF DsliteTunnelEntry
 MAX-ACCESS  not-accessible
 STATUS      current
 DESCRIPTION
  "The (conceptual) table containing information on
  configured tunnels. This table can be used to map
  a B4 address to the associated AFTR address. It can
  also be used for row creation."
 REFERENCE
  "B4, AFTR: RFC 6333."
 ::= { dsliteTunnel 1 }
```

```
dsliteTunnelEntry OBJECT-TYPE
 SYNTAX      DsliteTunnelEntry
 MAX-ACCESS  not-accessible
 STATUS      current
 DESCRIPTION
  "Each entry in this table contains the information on a
  particular configured tunnel."
 INDEX       { dsliteTunnelAddressType,
              dsliteTunnelStartAddress,
              dsliteTunnelEndAddress,
              ifIndex }
 ::= { dsliteTunnelTable 1 }
```

```
DsliteTunnelEntry ::=
 SEQUENCE {
  dsliteTunnelAddressType      InetAddressType,
  dsliteTunnelStartAddress     InetAddress,
  dsliteTunnelEndAddress       InetAddress,
  dsliteTunnelStartAddPreLen   InetAddressPrefixLength
 }
```

```
dsliteTunnelAddressType OBJECT-TYPE
 SYNTAX      InetAddressType
 MAX-ACCESS  not-accessible
 STATUS      current
 DESCRIPTION
  "This object MUST be set to the value of ipv6(2).
```


It describes the address type of the IPv4-in-IPv6 tunnel initiator and endpoint."

REFERENCE

"ipv6(2): RFC 4001."
 ::= { dsliteTunnelEntry 1 }

dsliteTunnelStartAddress OBJECT-TYPE

SYNTAX InetAddress (SIZE (0..16))

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The IPv6 address of the initiator of the tunnel.

The address type is given by dsliteTunnelAddressType."

::= { dsliteTunnelEntry 2 }

dsliteTunnelEndAddress OBJECT-TYPE

SYNTAX InetAddress (SIZE (0..16))

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The IPv6 address of the endpoint of the tunnel.

The address type is given by dsliteTunnelAddressType."

::= { dsliteTunnelEntry 3 }

dsliteTunnelStartAddPreLen OBJECT-TYPE

SYNTAX InetAddressPrefixLength

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The IPv6 prefix length of the IP address for the

initiator of the tunnel(dsliteTunnelStartAddress)."

::= { dsliteTunnelEntry 4 }

--dsliteNATBindTable(according to the NAPT scheme)

dsliteNATBindTable OBJECT-TYPE

SYNTAX SEQUENCE OF DsliteNATBindEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains information about currently

active NAT binds in the NAT of the AFTR. This table

adds the IPv6 address of a B4 to the natv2PortMapTable

defined in NATV2-MIB (RFC 7659)."

REFERENCE

"NATV2-MIB: Section 4 of RFC 7659."

::= { dsliteNAT 1 }

```

dsliteNATBindEntry OBJECT-TYPE
    SYNTAX      DsliteNATBindEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The entry in this table holds the mapping relationship
        between tunnel information and NAT bind information.
        Each entry in this table not only needs to match a
        corresponding entry in the natv2PortMapTable, but
        also a corresponding entry in the dsliteTunnelTable.
        So, the INDEX of the entry needs to match a corresponding
        value in the natv2PortMapTable INDEX and a corresponding
        value in the dsliteTunnelTable INDEX.  These entries are
        lost upon agent restart."
    REFERENCE
        "natv2PortMapTable: Section 4 of RFC 7659."
    INDEX      { dsliteNATBindMappingInstanceIndex,
                dsliteNATBindMappingProto,
                dsliteNATBindMappingExtRealm,
                dsliteNATBindMappingExtAddressType,
                dsliteNATBindMappingExtAddress,
                dsliteNATBindMappingExtPort,
                ifIndex,
                dsliteTunnelStartAddress }
    ::=      { dsliteNATBindTable 1 }

DsliteNATBindEntry ::=
    SEQUENCE {
        dsliteNATBindMappingInstanceIndex  Natv2InstanceIndex,
        dsliteNATBindMappingProto          ProtocolNumber,
        dsliteNATBindMappingExtRealm       SnmpAdminString,
        dsliteNATBindMappingExtAddressType InetAddressType,
        dsliteNATBindMappingExtAddress     InetAddress,
        dsliteNATBindMappingExtPort        InetPortNumber,
        dsliteNATBindMappingIntRealm       SnmpAdminString,
        dsliteNATBindMappingIntAddressType InetAddressType,
        dsliteNATBindMappingIntAddress     InetAddress,
        dsliteNATBindMappingIntPort        InetPortNumber,
        dsliteNATBindMappingPool           Unsigned32,
        dsliteNATBindMappingMapBehavior    INTEGER,
        dsliteNATBindMappingFilterBehavior INTEGER,
        dsliteNATBindMappingAddressPooling INTEGER
    }

dsliteNATBindMappingInstanceIndex OBJECT-TYPE
    SYNTAX  Natv2InstanceIndex
    MAX-ACCESS  not-accessible
    STATUS  current

```

DESCRIPTION

"Index of the NAT instance that created this port map entry."

::= { dsliteNATBindEntry 1 }

dsliteNATBindMappingProto OBJECT-TYPE

SYNTAX ProtocolNumber

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This object specifies the mapping's transport protocol number."

::= { dsliteNATBindEntry 2 }

dsliteNATBindMappingExtRealm OBJECT-TYPE

SYNTAX SnmpAdminString (SIZE(0..32))

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The realm to which dsliteNATBindMappingExtAddress belongs."

::= { dsliteNATBindEntry 3 }

dsliteNATBindMappingExtAddressType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Address type for the mapping's external address. This object MUST be set to the value of ipv4(1). The values of ipv6(2), ipv4z(3), and ipv6z(4) are not allowed."

REFERENCE

"ipv4(1), ipv6(2), ipv4z(3), and ipv6z(4): RFC 4001."

::= { dsliteNATBindEntry 4 }

dsliteNATBindMappingExtAddress OBJECT-TYPE

SYNTAX InetAddress (SIZE (0..4))

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The mapping's external address. This is the source address for translated outgoing packets. The address type is given by dsliteNATBindMappingExtAddressType."

::= { dsliteNATBindEntry 5 }

dsliteNATBindMappingExtPort OBJECT-TYPE

SYNTAX InetPortNumber

```

MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
  "The mapping's assigned external port number.
  This is the source port for translated outgoing
  packets. This MUST be a non-zero value."
 ::= { dsliteNATBindEntry 6 }

```

```

dsliteNATBindMappingIntRealm OBJECT-TYPE
SYNTAX SnmpAdminString (SIZE(0..32))
MAX-ACCESS read-only
STATUS current
DESCRIPTION
  "The realm to which natMappingIntAddress belongs. This
  realm defines the IPv6 address space from which the
  tunnel source address is taken. The realm of the
  encapsulated IPv4 address is restricted in scope to
  the tunnel, so there is no point in identifying it
  separately."
 ::= { dsliteNATBindEntry 7 }

```

```

dsliteNATBindMappingIntAddressType OBJECT-TYPE
SYNTAX InetAddressType
MAX-ACCESS read-only
STATUS current
DESCRIPTION
  "Address type of the mapping's internal address.
  This object MUST be set to the value of ipv4z(3).
  The values of ipv4(1), ipv6(2), and ipv6z(4) are
  not allowed."
REFERENCE
  "ipv4(1), ipv6(2), ipv4z(3), and ipv6z(4): RFC 4001."
 ::= { dsliteNATBindEntry 8 }

```

```

dsliteNATBindMappingIntAddress OBJECT-TYPE
SYNTAX InetAddress
MAX-ACCESS read-only
STATUS current
DESCRIPTION
  "The mapping's internal address. It is the IPv6 tunnel
  source address. The address type is given by
  dsliteNATBindMappingIntAddressType."
 ::= { dsliteNATBindEntry 9 }

```

```

dsliteNATBindMappingIntPort OBJECT-TYPE
SYNTAX InetPortNumber
MAX-ACCESS read-only
STATUS current

```

DESCRIPTION

"The mapping's internal port number. This MUST be a non-zero value."

```
::= { dsliteNATBindEntry 10 }
```

dsliteNATBindMappingPool OBJECT-TYPE

SYNTAX Unsigned32 (0|1..4294967295)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Index of the pool that contains this mapping's external address and port. If zero, no pool is associated with this mapping."

```
::= { dsliteNATBindEntry 11 }
```

dsliteNATBindMappingMapBehavior OBJECT-TYPE

SYNTAX INTEGER{

endpointIndependent (0),

addressDependent(1),

addressAndPortDependent (2)

}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mapping behavior as described in Section 4.1 of RFC 4787.

endpointIndependent(0), the behavior REQUIRED by RFC 4787, REQ-1 maps the source address and port to the same external address and port for all destination address and port combinations reached through the same external realm and using the given protocol.

addressDependent(1) maps to the same external address and port for all destination ports at the same destination address reached through the same external realm and using the given protocol.

addressAndPortDependent(2) maps to a separate external address and port combination for each different destination address and port combination reached through the same external realm.

For the DS-Lite scenario, it must be addressAndPortDependent(2)."

REFERENCE

"Mapping behavior: Section 4.1 of RFC 4787.

DS-Lite: RFC 6333."

```
::= { dsliteNATBindEntry 12 }
```

dsliteNATBindMappingFilterBehavior OBJECT-TYPE

```
SYNTAX INTEGER{
  endpointIndependent (0),
  addressDependent(1),
  addressAndPortDependent (2)
}
```

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Filtering behavior as described in Section 5 of RFC 4787.

endpointIndependent(0) accepts for translation packets from all combinations of remote address and port destined to the mapped external address and port via the given external realm and using the given protocol.

addressDependent(1) accepts for translation packets from all remote ports from the same remote source address destined to the mapped external address and port via the given external realm and using the given protocol.

addressAndPortDependent(2) accepts for translation only those packets with the same remote source address, port, and protocol incoming from the same external realm as identified when the applicable port map entry was created.

RFC 4787, REQ-8 recommends either endpointIndependent(0) or addressDependent(1) filtering behavior, depending on whether application friendliness or security takes priority.

For the DS-Lite scenario, it must be addressAndPortDependent(2)."

REFERENCE

"Filtering behavior: Section 5 of RFC 4787.

DS-Lite: RFC 6333."

```
::= { dsliteNATBindEntry 13 }
```

dsliteNATBindMappingAddressPooling OBJECT-TYPE

```
SYNTAX INTEGER{
  arbitrary (0),
  paired (1)
}
```

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Type of address pooling behavior that was used to create this mapping.

arbitrary(0) pooling behavior means that the NAT instance may create the new port mapping using any address in the pool that has a free port for the protocol concerned.

paired(1) pooling behavior, the behavior RECOMMENDED by RFC 4787, REQ-2 means that once a given internal address has been mapped to a particular address in a particular pool, further mappings of the same internal address to that pool will reuse the previously assigned pool member address."

REFERENCE

"Pooling behavior: Section 4.1 of RFC 4787."
 ::= { dsliteNATBindEntry 14 }

--dsliteInfo

dsliteAFTRAlarmScalar OBJECT IDENTIFIER ::= { dsliteInfo 1 }

dsliteAFTRAlarmB4AddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS accessible-for-notify

STATUS current

DESCRIPTION

"This object indicates the address type of the B4, which will send an alarm."

::= { dsliteAFTRAlarmScalar 1 }

dsliteAFTRAlarmB4Addr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS accessible-for-notify

STATUS current

DESCRIPTION

"This object indicates the IP address of B4, which will send an alarm. The address type is given by dsliteAFTRAlarmB4AddrType."

::= { dsliteAFTRAlarmScalar 2 }

dsliteAFTRAlarmProtocolType OBJECT-TYPE

SYNTAX INTEGER{

tcp (0),

udp (1),

icmp (2),

total (3)

}

MAX-ACCESS accessible-for-notify
 STATUS current
 DESCRIPTION
 "This object indicates the transport protocol type of alarm.

tcp (0) means that the transport protocol type of alarm is tcp.

udp (1) means that the transport protocol type of alarm is udp.

icmp (2) means that the transport protocol type of alarm is icmp.

total (3) means that the transport protocol type of alarm is total."

```
::= { dsliteAFTRAlarmScalar 3 }
```

dsliteAFTRAlarmSpecificIPAddrType OBJECT-TYPE
 SYNTAX InetAddressType
 MAX-ACCESS accessible-for-notify
 STATUS current
 DESCRIPTION
 "This object indicates the address type of the IP address whose port usage has reached the threshold."

```
::= { dsliteAFTRAlarmScalar 4 }
```

dsliteAFTRAlarmSpecificIP OBJECT-TYPE
 SYNTAX InetAddress
 MAX-ACCESS accessible-for-notify
 STATUS current
 DESCRIPTION
 "This object indicates the IP address whose port usage has reached the threshold. The address type is given by dsliteAFTRAlarmSpecificIPAddrType."

```
::= { dsliteAFTRAlarmScalar 5 }
```

dsliteAFTRAlarmConnectNumber OBJECT-TYPE
 SYNTAX Integer32 (60..90)
 MAX-ACCESS read-write
 STATUS current
 DESCRIPTION
 "This object indicates the notification threshold of the DS-Lite tunnels that is active in the AFTR device."
 REFERENCE
 "AFTR: Section 6 of RFC 6333."


```

DEFVAL
  { 60 }
 ::= { dsliteAFTRAlarmScalar 6 }

```

```

dsliteAFTRAlarmSessionNumber OBJECT-TYPE
  SYNTAX Integer32
  MAX-ACCESS read-write
  STATUS current
  DESCRIPTION
    "This object indicates the notification threshold of
    the IPv4 session for the user."
  REFERENCE
    "AFTR: Section 6 of RFC 6333
    B4: Section 5 of RFC 6333."
  DEFVAL
    { -1 }
  ::= { dsliteAFTRAlarmScalar 7 }

```

```

dsliteAFTRAlarmPortNumber OBJECT-TYPE
  SYNTAX Integer32
  MAX-ACCESS read-write
  STATUS current
  DESCRIPTION
    "This object indicates the notification threshold of the NAT
    ports that have been used by the user."
  DEFVAL
    { -1 }
  ::= { dsliteAFTRAlarmScalar 8 }

```

```

dsliteStatisticsTable OBJECT-TYPE
  SYNTAX SEQUENCE OF DsliteStatisticsEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "This table provides statistical information
    about DS-Lite."
  ::= { dsliteInfo 2 }

```

```

dsliteStatisticsEntry OBJECT-TYPE
  SYNTAX DsliteStatisticsEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "Each entry in this table provides statistical information
    about DS-Lite."
  INDEX { dsliteStatisticsSubscriberIndex }
  ::= { dsliteStatisticsTable 1 }

```

```

DsliteStatisticsEntry ::=
    SEQUENCE {
        dsliteStatisticsSubscriberIndex      Natv2SubscriberIndex,
        dsliteStatisticsDiscards             Counter64,
        dsliteStatisticsSends                Counter64,
        dsliteStatisticsReceives             Counter64,
        dsliteStatisticsIpv4Session          Counter64,
        dsliteStatisticsIpv6Session          Counter64
    }

```

```

dsliteStatisticsSubscriberIndex OBJECT-TYPE
    SYNTAX Natv2SubscriberIndex
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Index of the subscriber or host.  A unique value,
        greater than zero, for each subscriber in the
        managed system."
    ::= { dsliteStatisticsEntry 1 }

```

```

dsliteStatisticsDiscards OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "This object indicates the number of packets
        discarded from this subscriber."
    ::= { dsliteStatisticsEntry 2 }

```

```

dsliteStatisticsSends OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "This object indicates the number of packets that is
        sent to this subscriber."
    ::= { dsliteStatisticsEntry 3 }

```

```

dsliteStatisticsReceives OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "This object indicates the number of packets that is
        received from this subscriber."
    ::= { dsliteStatisticsEntry 4 }

```

```

dsliteStatisticsIpv4Session OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "This object indicates the number of the
        current IPv4 Sessions."
    REFERENCE
        "Session: Paragraph 2 in Section 11 of RFC 6333.
        (The AFTR should have the capability to log the
        tunnel-id, protocol, ports/IP addresses, and
        the creation time of the NAT binding to uniquely
        identify the user sessions)."
```

```
 ::= { dsliteStatisticsEntry 5 }
```

```

dsliteStatisticsIpv6Session OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "This object indicates the number of the
        current IPv6 session. Because the AFTR is
        also a dual-stack device, it will also
        forward normal IPv6 packets for the
        inbound and outbound direction."
    REFERENCE
        "Session: Paragraph 2 in Section 11 of RFC 6333.
        (The AFTR should have the capability to log the
        tunnel-id, protocol, ports/IP addresses, and
        the creation time of the NAT binding to uniquely
        identify the user sessions)."
```

```
 ::= { dsliteStatisticsEntry 6 }
```

---dslite Notifications

```

dsliteTunnelNumAlarm NOTIFICATION-TYPE
    OBJECTS { dsliteAFTRAlarmProtocolType,
              dsliteAFTRAlarmB4AddrType,
              dsliteAFTRAlarmB4Addr }
    STATUS current
    DESCRIPTION
        "This trap is triggered when the number of
        current DS-Lite tunnels exceeds the value of
        the dsliteAFTRAlarmConnectNumber."
    ::= { dsliteNotifications 1 }
```

```

dsliteAFTRUserSessionNumAlarm NOTIFICATION-TYPE
  OBJECTS { dsliteAFTRAlarmProtocolType,
            dsliteAFTRAlarmB4AddrType,
            dsliteAFTRAlarmB4Addr }
  STATUS current
  DESCRIPTION
    "This trap is triggered when user sessions
    reach the threshold. The threshold
    is specified by the dsliteAFTRAlarmSessionNumber."
  REFERENCE
    "Session: Paragraph 2 in Section 11 of RFC 6333.
    (The AFTR should have the capability to log the
    tunnel-id, protocol, ports/IP addresses, and
    the creation time of the NAT binding to uniquely
    identify the user sessions)."
  ::= { dsliteNotifications 2 }

```

```

dsliteAFTRPortUsageOfSpecificIpAlarm NOTIFICATION-TYPE
  OBJECTS { dsliteAFTRAlarmSpecificIPAddrType,
            dsliteAFTRAlarmSpecificIP }
  STATUS current
  DESCRIPTION
    "This trap is triggered when the used NAT
    ports of map address reach the threshold.
    The threshold is specified by the
    dsliteAFTRAlarmPortNumber."
  ::= { dsliteNotifications 3 }

```

--Module Conformance statement

```

dsliteConformance OBJECT IDENTIFIER
  ::= { dsliteMIB 2 }

```

```

dsliteCompliances OBJECT IDENTIFIER ::= { dsliteConformance 1 }

```

```

dsliteGroups OBJECT IDENTIFIER ::= { dsliteConformance 2 }

```

-- compliance statements

```

dsliteCompliance MODULE-COMPLIANCE
  STATUS current
  DESCRIPTION
    "Describes the minimal requirements for conformance
    to the DS-Lite MIB."
  MODULE -- this module
    MANDATORY-GROUPS { dsliteNATBindGroup,
                      dsliteTunnelGroup,
                      dsliteStatisticsGroup,

```

```

        dsliteNotificationsGroup,
        dsliteAFTRAlarmScalarGroup }
 ::= { dsliteCompliances 1 }

dsliteNATBindGroup OBJECT-GROUP
OBJECTS {
    dsliteNATBindMappingIntRealm,
    dsliteNATBindMappingIntAddressType,
    dsliteNATBindMappingIntAddress,
    dsliteNATBindMappingIntPort,
    dsliteNATBindMappingPool,
    dsliteNATBindMappingMapBehavior,
    dsliteNATBindMappingFilterBehavior,
    dsliteNATBindMappingAddressPooling }
STATUS current
DESCRIPTION
    "A collection of objects to support basic
    management of NAT binds in the NAT of the AFTR."
 ::= { dsliteGroups 1 }

dsliteTunnelGroup OBJECT-GROUP
OBJECTS { dsliteTunnelStartAddPreLen }
STATUS current
DESCRIPTION
    "A collection of objects to support management
    of DS-Lite tunnels."
 ::= { dsliteGroups 2 }

dsliteStatisticsGroup OBJECT-GROUP
OBJECTS { dsliteStatisticsDiscards,
          dsliteStatisticsSends,
          dsliteStatisticsReceives,
          dsliteStatisticsIpv4Session,
          dsliteStatisticsIpv6Session }
STATUS current
DESCRIPTION
    " A collection of objects to support management
    of statistical information for AFTR devices."
 ::= { dsliteGroups 3 }

dsliteNotificationsGroup NOTIFICATION-GROUP
NOTIFICATIONS { dsliteTunnelNumAlarm,
                dsliteAFTRUserSessionNumAlarm,
                dsliteAFTRPortUsageOfSpecificIpAlarm }
STATUS current
DESCRIPTION
    "A collection of objects to support management
    of trap information for AFTR devices."

```

```

 ::= { dsliteGroups 4 }

dsliteAFTRAlarmScalarGroup OBJECT-GROUP
  OBJECTS { dsliteAFTRAlarmB4AddrType,
            dsliteAFTRAlarmB4Addr,
            dsliteAFTRAlarmProtocolType,
            dsliteAFTRAlarmSpecificIPAddrType,
            dsliteAFTRAlarmSpecificIP,
            dsliteAFTRAlarmConnectNumber,
            dsliteAFTRAlarmSessionNumber,
            dsliteAFTRAlarmPortNumber}
  STATUS current
  DESCRIPTION
    "A collection of objects to support management of
    the information about the AFTR alarming scalar."
 ::= { dsliteGroups 5 }

END

```

9. Security Considerations

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection opens devices to attack. These are the tables and objects and their sensitivity/vulnerability:

dsliteAFTRAlarmConnectNumber

dsliteAFTRAlarmSessionNumber

dsliteAFTRAlarmPortNumber

Notification thresholds: An attacker setting an arbitrarily low threshold can cause many useless notifications to be generated. Setting an arbitrarily high threshold can effectively disable notifications, which could be used to hide another attack.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

entries in dsliteTunnelTable

entries in dsliteNATBindTable

Objects that reveal host identities: Various objects can reveal the identity of private hosts that are engaged in a session with external end nodes. A curious outsider could monitor these to assess the number of private hosts being supported by the AFTR device. Further, a disgruntled former employee of an enterprise could use the information to break into specific private hosts by intercepting the existing sessions or originating new sessions into the host. If nothing else, unauthorized monitoring of these objects will violate individual subscribers' privacy.

Unauthorized read access to the dsliteTunnelTable would reveal information about the tunnel topology.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

Implementations SHOULD provide the security features described by the SNMPv3 framework (see [RFC3410]), and implementations claiming compliance to the SNMPv3 standard MUST include full support for authentication and privacy via the User-based Security Model (USM) [RFC3414] with the AES cipher algorithm [RFC3826]. Implementations MAY also provide support for the Transport Security Model (TSM) [RFC5591] in combination with a secure transport such as SSH [RFC5592] or TLS/DTLS [RFC6353].

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

10. IANA Considerations

IANA has allocated the following OBJECT IDENTIFIER value and recorded it in the SMI Numbers registry in the subregistry called "SMI Network Management MGMT Codes Internet-standard MIB" under the mib-2 branch (1.3.6.1.2.1):

Descriptor	OBJECT IDENTIFIER value
-----	-----
DSLite-MIB	{ mib-2 240 }

IANA has recorded the following IANAtunnelType Textual Convention within the IANAifType-MIB:

```

IANAtunnelType ::= TEXTUAL-CONVENTION
    SYNTAX          INTEGER {
                    dsLite(17)          -- DS-Lite tunnel
                    }

```

11. References

11.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIV2)", STD 58, RFC 2578, DOI 10.17487/RFC2578, April 1999, <<http://www.rfc-editor.org/info/rfc2578>>.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIV2", STD 58, RFC 2579, DOI 10.17487/RFC2579, April 1999, <<http://www.rfc-editor.org/info/rfc2579>>.
- [RFC2580] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Conformance Statements for SMIV2", STD 58, RFC 2580, DOI 10.17487/RFC2580, April 1999, <<http://www.rfc-editor.org/info/rfc2580>>.
- [RFC2863] McCloghrie, K. and F. Kastenholtz, "The Interfaces Group MIB", RFC 2863, DOI 10.17487/RFC2863, June 2000, <<http://www.rfc-editor.org/info/rfc2863>>.

- [RFC3411] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", STD 62, RFC 3411, DOI 10.17487/RFC3411, December 2002, <<http://www.rfc-editor.org/info/rfc3411>>.
- [RFC3414] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", STD 62, RFC 3414, DOI 10.17487/RFC3414, December 2002, <<http://www.rfc-editor.org/info/rfc3414>>.
- [RFC3826] Blumenthal, U., Maino, F., and K. McCloghrie, "The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model", RFC 3826, DOI 10.17487/RFC3826, June 2004, <<http://www.rfc-editor.org/info/rfc3826>>.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", RFC 4001, DOI 10.17487/RFC4001, February 2005, <<http://www.rfc-editor.org/info/rfc4001>>.
- [RFC4087] Thaler, D., "IP Tunnel MIB", RFC 4087, DOI 10.17487/RFC4087, June 2005, <<http://www.rfc-editor.org/info/rfc4087>>.
- [RFC4787] Audet, F., Ed. and C. Jennings, "Network Address Translation (NAT) Behavioral Requirements for Unicast UDP", BCP 127, RFC 4787, DOI 10.17487/RFC4787, January 2007, <<http://www.rfc-editor.org/info/rfc4787>>.
- [RFC5591] Harrington, D. and W. Hardaker, "Transport Security Model for the Simple Network Management Protocol (SNMP)", STD 78, RFC 5591, DOI 10.17487/RFC5591, June 2009, <<http://www.rfc-editor.org/info/rfc5591>>.
- [RFC5592] Harrington, D., Salowey, J., and W. Hardaker, "Secure Shell Transport Model for the Simple Network Management Protocol (SNMP)", RFC 5592, DOI 10.17487/RFC5592, June 2009, <<http://www.rfc-editor.org/info/rfc5592>>.
- [RFC6333] Durand, A., Droms, R., Woodyatt, J., and Y. Lee, "Dual-Stack Lite Broadband Deployments Following IPv4 Exhaustion", RFC 6333, DOI 10.17487/RFC6333, August 2011, <<http://www.rfc-editor.org/info/rfc6333>>.

- [RFC6353] Hardaker, W., "Transport Layer Security (TLS) Transport Model for the Simple Network Management Protocol (SNMP)", STD 78, RFC 6353, DOI 10.17487/RFC6353, July 2011, <<http://www.rfc-editor.org/info/rfc6353>>.
- [RFC7659] Perreault, S., Tsou, T., Sivakumar, S., and T. Taylor, "Definitions of Managed Objects for Network Address Translators (NATs)", RFC 7659, DOI 10.17487/RFC7659, October 2015, <<http://www.rfc-editor.org/info/rfc7659>>.

11.2. Informative References

- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, DOI 10.17487/RFC3410, December 2002, <<http://www.rfc-editor.org/info/rfc3410>>.

Acknowledgements

The authors would like to thank the following for their valuable comments: Suresh Krishnan, Ian Farrer, Yiu Lee, Qi Sun, Yong Cui, David Harrington, Dave Thaler, Tassos Chatzithomaoglou, Tom Taylor, Hui Deng, Carlos Pignataro, Matt Miller, Terry Manderson, and other members of the Software working group.

Authors' Addresses

Yu Fu
CNNIC
No.4 South 4th Street, Zhongguancun
Hai-Dian District, Beijing 100190
China

Email: fuyu@cnnic.cn

Sheng Jiang
Huawei Technologies Co., Ltd
Q14, Huawei Campus, No.156 Beiqing Road
Hai-Dian District, Beijing 100095
China

Email: jiangsheng@huawei.com

Jiang Dong
Tsinghua University
Department of Computer Science, Tsinghua University
Beijing 100084
China

Email: knight.dongjiang@gmail.com

Yuchi Chen
Tsinghua University
Department of Computer Science, Tsinghua University
Beijing 100084
China

Email: flashfoymx@gmail.com

