

Internet Engineering Task Force (IETF)
Request for Comments: 8983
Updates: 7296
Category: Standards Track
ISSN: 2070-1721

M. Boucadair
Orange
February 2021

Internet Key Exchange Protocol Version 2 (IKEv2) Notification Status
Types for IPv4/IPv6 Coexistence

Abstract

This document specifies new Internet Key Exchange Protocol Version 2 (IKEv2) notification status types to better manage IPv4 and IPv6 coexistence by allowing the responder to signal to the initiator which address families are allowed.

This document updates RFC 7296.

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 7841.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <https://www.rfc-editor.org/info/rfc8983>.

Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction
2. Terminology
3. Why Not INTERNAL_ADDRESS_FAILURE?
4. IP6_ALLOWED and IP4_ALLOWED Status Types
5. Update to RFC 7296
6. Security Considerations
7. IANA Considerations
8. References
 - 8.1. Normative References
 - 8.2. Informative References

Acknowledgements
Author's Address

1. Introduction

As described in [RFC7849], if the subscription data or network configuration allows only one IP address family (IPv4 or IPv6), the

cellular host must not request a second PDP-Context (Section 3.2 of [RFC6459]) to the same Access Point Name (APN) for the other IP address family (AF). The Third Generation Partnership Project (3GPP) network informs the cellular host about allowed Packet Data Protocol (PDP) types by means of Session Management (SM) cause codes. In particular, the following cause codes can be returned:

cause #50 "PDP type IPv4 only allowed": This cause code is used by the network to indicate that only PDP type IPv4 is allowed for the requested Public Data Network (PDN) connectivity.

cause #51 "PDP type IPv6 only allowed": This cause code is used by the network to indicate that only PDP type IPv6 is allowed for the requested PDN connectivity.

cause #52 "single address bearers only allowed": This cause code is used by the network to indicate that the requested PDN connectivity is accepted with the restriction that only single IP version bearers are allowed.

If the requested IPv4v6 PDP-Context is not supported by the network but IPv4 and IPv6 PDP types are allowed, then the cellular host will be configured with an IPv4 address or an IPv6 prefix by the network. It must initiate another PDP-Context activation of the other address family in addition to the one already activated for a given APN. The purpose of initiating a second PDP-Context is to achieve dual-stack connectivity (that is, IPv4 and IPv6 connectivity) by means of two PDP-Contexts.

When the User Equipment (UE) attaches to the 3GPP network using a non-3GPP access network (e.g., Wireless Local Area Network (WLAN)), there are no equivalent IKEv2 capabilities [RFC7296] notification codes for the 3GPP network to inform the UE why an IP address family is not assigned or whether that UE should retry with another address family.

This document fills that void by introducing new IKEv2 notification status types for the sake of deterministic UE behaviors (Section 4).

These notification status types are not specific to 3GPP architectures but can be used in other deployment contexts. Cellular networks are provided as an illustration example.

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

This document makes use of the terms defined in [RFC7296]. In particular, readers should be familiar with "initiator" and "responder" terms used in that document.

3. Why Not INTERNAL_ADDRESS_FAILURE?

The following address assignment failures may be encountered when an initiator requests assignment of IP addresses/prefixes:

- * An initiator asks for IPv_x, but IPv_x address assignment is not supported by the responder.
- * An initiator requests both IPv4 and IPv6 addresses, but only IPv4 address assignment is supported by the responder.
- * An initiator requests both IPv4 and IPv6 addresses, but only IPv6 prefix assignment is supported by the responder.
- * An initiator asks for both IPv4 and IPv6 addresses, but only one address family can be assigned by the responder for policy

reasons.

Section 3.15.4 of [RFC7296] defines a generic notification error type (INTERNAL_ADDRESS_FAILURE) that is related to a failure to handle an address assignment request. The responder sends INTERNAL_ADDRESS_FAILURE only if no addresses can be assigned. This behavior does not explicitly allow an initiator to determine why a given address family is not assigned, nor whether it should try using another address family. INTERNAL_ADDRESS_FAILURE is a catch-all error type when an address-related issue is encountered by an IKEv2 responder.

INTERNAL_ADDRESS_FAILURE does not provide sufficient hints to the IKEv2 initiator to adjust its behavior.

4. IP6_ALLOWED and IP4_ALLOWED Status Types

IP6_ALLOWED and IP4_ALLOWED notification status types (see Section 7) are defined to inform the initiator about the responder's address family assignment support capabilities and to report to the initiator the reason why an address assignment failed. These notification status types are used by the initiator to adjust its behavior accordingly (Section 5).

No data is associated with these notifications.

5. Update to RFC 7296

If the initiator is dual stack (i.e., supports both IPv4 and IPv6), it MUST include configuration attributes for both address families in its configuration request (absent explicit policy/configuration otherwise). More details about IPv4 and IPv6 configuration attributes are provided in Section 3.15 of [RFC7296]. These attributes are used to infer the requested/assigned AFs listed in Table 1.

The responder MUST include the IP6_ALLOWED and/or IP4_ALLOWED notification status type in a response to an address assignment request as indicated in Table 1.

Requested AF(s) (Initiator)	Supported AF(s) (Responder)	Assigned AF(s) (Responder)	Returned Notification Status Type(s) (Responder)
IPv4	IPv6	None	IP6_ALLOWED
IPv4	IPv4	IPv4	IP4_ALLOWED
IPv4	IPv4 and IPv6	IPv4	IP4_ALLOWED, IP6_ALLOWED
IPv6	IPv6	IPv6	IP6_ALLOWED
IPv6	IPv4	None	IP4_ALLOWED
IPv6	IPv4 and IPv6	IPv6	IP4_ALLOWED, IP6_ALLOWED
IPv4 and IPv6	IPv4	IPv4	IP4_ALLOWED
IPv4 and IPv6	IPv6	IPv6	IP6_ALLOWED
IPv4 and IPv6	IPv4 and IPv6	IPv4 and IPv6	IP4_ALLOWED, IP6_ALLOWED
IPv4 and IPv6	IPv4 or IPv6 (policy based)	IPv4 or IPv6	IP4_ALLOWED, IP6_ALLOWED

T., Bajko, G., and K. Iisakkila, "IPv6 in 3rd Generation Partnership Project (3GPP) Evolved Packet System (EPS)", RFC 6459, DOI 10.17487/RFC6459, January 2012, <<https://www.rfc-editor.org/info/rfc6459>>.

[RFC7849] Binet, D., Boucadair, M., Vizdal, A., Chen, G., Heatley, N., Chandler, R., Michaud, D., Lopez, D., and W. Haeffner, "An IPv6 Profile for 3GPP Mobile Devices", RFC 7849, DOI 10.17487/RFC7849, May 2016, <<https://www.rfc-editor.org/info/rfc7849>>.

Acknowledgements

Many thanks to Christian Jacquenet for the review.

Thanks to Paul Wouters, Yaov Nir, Valery Smyslov, Daniel Migault, Tero Kivinen, and Michael Richardson for the comments and review.

Thanks to Benjamin Kaduk for the AD review.

Thanks to Murray Kucherawy, Å\211ric Vyncke, and Robert Wilton for the IESG review.

Author's Address

Mohamed Boucadair
Orange
35000 Rennes
France

Email: mohamed.boucadair@orange.com