

## A YANG Data Model for DHCPv6 Configuration

### Abstract

This document describes YANG data models for the configuration and management of Dynamic Host Configuration Protocol for IPv6 (DHCPv6) (RFC 8415) servers, relays, and clients.

### Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 7841.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <https://www.rfc-editor.org/info/rfc9243>.

### Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

### Table of Contents

1. Introduction
  - 1.1. Scope
  - 1.2. Extensibility of the DHCPv6 Server YANG Module
    - 1.2.1. DHCPv6 Option Definitions
2. Terminology
  - 2.1. Requirements Language
3. DHCPv6 Tree Diagrams
  - 3.1. DHCPv6 Server Tree Diagram
  - 3.2. DHCPv6 Relay Tree Diagram
  - 3.3. DHCPv6 Client Tree Diagram
4. DHCPv6 YANG Modules
  - 4.1. DHCPv6 Common YANG Module
  - 4.2. DHCPv6 Server YANG Module
  - 4.3. DHCPv6 Relay YANG Module
  - 4.4. DHCPv6 Client YANG Module
5. Security Considerations
6. IANA Considerations
  - 6.1. URI Registration
  - 6.2. YANG Module Name Registration
7. References
  - 7.1. Normative References
  - 7.2. Informative References

## Appendix A. Data Tree Examples

A.1. DHCPv6 Server Configuration Examples

A.2. DHCPv6 Relay Configuration Example

A.3. DHCPv6 Client Configuration Example

## Appendix B. Example of Augmenting Additional DHCPv6 Option Definitions

## Appendix C. Example Vendor-Specific Server Configuration Module

## Appendix D. Example Definition of Class-Selector Configuration

## Acknowledgments

## Contributors

## Author's Address

### 1. Introduction

DHCPv6 [RFC8415] is used for supplying configuration and other relevant parameters to clients in IPv6 networks. This document defines YANG [RFC7950] modules for the configuration and management of DHCPv6 'elements' (servers, relays, and clients), using the Network Configuration Protocol (NETCONF) [RFC6241] or RESTCONF [RFC8040].

Separate modules are defined for each element. Additionally, a 'common' module contains typedefs and groupings used by all of the element modules. Appendix A provides XML examples for each of the element modules and shows their interaction.

The relay and client modules provide configuration that is applicable to devices' interfaces. This is done by importing the 'ietf-interfaces' YANG module [RFC8343] and using interface-refs to the relevant interface(s).

It is worth noting that as DHCPv6 is itself a client configuration protocol, it is not the intention of this document to provide a replacement for the allocation of DHCPv6-assigned addressing and parameters by using NETCONF/YANG. The DHCPv6 client module is intended for the configuration and monitoring of the DHCPv6 client function and does not replace DHCPv6 address and parameter configuration.

The YANG modules in this document adopt the Network Management Datastore Architecture (NMDA) [RFC8342].

#### 1.1. Scope

[RFC8415] describes the current version of the DHCPv6 base protocol specification. A large number of additional specifications have also been published, extending DHCPv6 element functionality and adding new options. The YANG modules contained in this document do not attempt to capture all of these extensions and additions; rather, they model the DHCPv6 functions and options covered in [RFC8415]. A focus has also been given on the extensibility of the modules so that they are easy to augment to add additional functionality as required by a particular implementation or deployment scenario.

#### 1.2. Extensibility of the DHCPv6 Server YANG Module

The modules in this document only attempt to model DHCPv6-specific behavior and do not cover the configuration and management of functionality relevant for specific server implementations. The level of variance between implementations is too great to attempt to standardize them in a way that is useful without being restrictive.

However, it is recognized that implementation-specific configuration and management is also an essential part of DHCP deployment and operations. To resolve this, Appendix C contains an example YANG module for the configuration of implementation-specific functions, illustrating how this functionality can be augmented into the main 'ietf-dhcpv6-server.yang' module.

In DHCPv6, the concept of 'class selection' for messages received by the server is common. This is the identification and classification

of messages based on a number of parameters so that the correct provisioning information can be supplied, for example, by allocating a prefix from the correct pool or supplying a set of options relevant for a specific vendor's client implementation. During the development of this document, implementations were researched and the findings were that while this function is common to all, the method for configuring and implementing this function differs greatly. Therefore, configuration of the class selection function has been omitted from the DHCPv6 server module to allow implementors to define their own suitable YANG modules. Appendix D provides an example of this, which demonstrates how this can be integrated with the main 'ietf-dhcpv6-server.yang' module.

### 1.2.1. DHCPv6 Option Definitions

A large number of DHCPv6 options have been created in addition to those defined in [RFC8415]. As implementations differ widely as to which DHCPv6 options they support, the following approach has been taken to defining options: only the DHCPv6 options defined in [RFC8415] are included in this document.

Of these, only the options that require operator configuration are modeled. For example, OPTION\_IA\_NA (3) is created by the DHCP server when requested by the client. The contents of the fields in the option are based on a number of input configuration parameters that the server will apply when it receives the request (e.g., the T1/T2 timers that are relevant for the pool of addresses). As a result, there are no fields that are directly configurable for the option, so it is not modeled.

The following table shows the DHCPv6 options that are modeled, the element(s) they are modeled for, and the relevant YANG module names:

Name	Server	Relay	Client	Module Name
OPTION_ORO (6) Option Request Option			X	ietf-dhcpv6-client.yang
OPTION_PREFERENCE (7) Preference Option	X			ietf-dhcpv6-server.yang
OPTION_AUTH (11) Authentication Option	X	X		ietf-dhcpv6-common.yang
OPTION_UNICAST (12) Server Unicast Option	X			ietf-dhcpv6-server.yang
OPTION_RAPID_COMMIT (14) Rapid Commit Option	X		X	ietf-dhcpv6-common.yang
OPTION_USER_CLASS (15) User Class Option			X	ietf-dhcpv6-client.yang
OPTION_VENDOR_CLASS (16) Vendor Class Option			X	ietf-dhcpv6-client.yang
OPTION_VENDOR_OPTS (17) Vendor-specific Information Option	X		X	ietf-dhcpv6-common.yang
OPTION_INTERFACE_ID (18) Interface-Id Option		X		ietf-dhcpv6-relay.yang
OPTION_RECONF_MSG (19) Reconfigure Message Option	X			ietf-dhcpv6-server.yang

OPTION_RECONF_ACCEPT (20) Reconfigure Accept Option	X		X	ietf-dhcpv6-client.yang
OPTION_INFORMATION _REFRESH_TIME (32) Information Refresh Time Option	X			ietf-dhcpv6-server.yang
OPTION_SOL_MAX_RT (82) sol max rt Option	X			ietf-dhcpv6-server.yang
OPTION_INF_MAX_RT (83) inf max rt Option	X			ietf-dhcpv6-server.yang

Table 1: Modeled DHCPv6 Options

Further option definitions can be added using additional YANG modules via augmentation of the relevant element modules from this document. Appendix B contains an example module showing how the DHCPv6 option definitions can be extended in this manner. Some guidance on how to write YANG modules for additional DHCPv6 options is also provided.

## 2. Terminology

The reader should be familiar with the YANG data modeling language defined in [RFC7950].

The YANG modules in this document adopt NMDA [RFC8342]. The meanings of the symbols used in tree diagrams are defined in [RFC8340].

The reader should be familiar with DHCPv6-relevant terminology defined in [RFC8415] and other relevant documents.

### 2.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

## 3. DHCPv6 Tree Diagrams

### 3.1. DHCPv6 Server Tree Diagram

The tree diagram in Figure 1 provides an overview of the DHCPv6 server module. The tree also includes the common functions module defined in Section 4.1.

```

module: ietf-dhcpv6-server
  +--rw dhcpv6-server
    +--rw enabled?                boolean
    +--rw server-duid?            dhc6:duid
    +--rw vendor-config
    +--rw option-sets
      +--rw option-set* [option-set-id]
        +--rw option-set-id      string
        +--rw description?       string
        +--rw preference-option
          +--rw pref-value?      uint8
        +--rw auth-option
          +--rw algorithm?        uint8
          +--rw rdm?              uint8
          +--rw replay-detection? uint64
          +--rw (protocol)?
            +--:(conf-token)

```

```

|         | +--rw token-auth-information?  binary
|         | +---:(rkap)
|         |   +--rw datatype?           uint8
|         |   +--rw auth-info-value?  binary
+--rw server-unicast-option
| +--rw server-address?  inet:ipv6-address
+--rw rapid-commit-option!
+--rw vendor-specific-information-options
| +--rw vendor-specific-information-option*
|   [enterprise-number]
|   +--rw enterprise-number      uint32
|   +--rw vendor-option-data* [sub-option-code]
|     +--rw sub-option-code      uint16
|     +--rw sub-option-data?     binary
+--rw reconfigure-message-option
| +--rw msg-type?  uint8
+--rw reconfigure-accept-option!
+--rw info-refresh-time-option
| +--rw info-refresh-time?  dhcp6:timer-seconds32
+--rw sol-max-rt-option
| +--rw sol-max-rt-value?  dhcp6:timer-seconds32
+--rw inf-max-rt-option
| +--rw inf-max-rt-value?  dhcp6:timer-seconds32
+--rw class-selector
+--rw allocation-ranges
  +--rw option-set-id*      leafref
  +--rw valid-lifetime?    dhcp6:timer-seconds32
  +--rw renew-time?        dhcp6:timer-seconds32
  +--rw rebind-time?       dhcp6:timer-seconds32
  +--rw preferred-lifetime? dhcp6:timer-seconds32
  +--rw rapid-commit?      boolean
  +--rw allocation-range* [id]
    +--rw id                string
    +--rw description?      string
    +--rw network-prefix    inet:ipv6-prefix
    +--rw option-set-id*    leafref
    +--rw valid-lifetime?   dhcp6:timer-seconds32
    +--rw renew-time?       dhcp6:timer-seconds32
    +--rw rebind-time?      dhcp6:timer-seconds32
    +--rw preferred-lifetime? dhcp6:timer-seconds32
    +--rw rapid-commit?     boolean
    +--rw address-pools {na-assignment}?
      +--rw address-pool* [pool-id]
        +--rw pool-id                string
        +--rw pool-prefix
        |   inet:ipv6-prefix
        +--rw start-address
        |   inet:ipv6-address-no-zone
        +--rw end-address
        |   inet:ipv6-address-no-zone
        +--rw max-address-utilization?  dhcp6:threshold
        +--rw option-set-id*            leafref
        +--rw valid-lifetime?
        |   dhcp6:timer-seconds32
        +--rw renew-time?
        |   dhcp6:timer-seconds32
        +--rw rebind-time?
        |   dhcp6:timer-seconds32
        +--rw preferred-lifetime?
        |   dhcp6:timer-seconds32
        +--rw rapid-commit?            boolean
        +--rw host-reservations
          +--rw host-reservation* [reserved-addr]
            +--rw client-duid?      dhcp6:duid
            +--rw reserved-addr
            |   inet:ipv6-address
            +--rw option-set-id*     leafref
            +--rw valid-lifetime?
            |   dhcp6:timer-seconds32
            +--rw renew-time?
            |   dhcp6:timer-seconds32

```

```

    +--rw rebind-time?
    |   dhcp6:timer-seconds32
    +--rw preferred-lifetime?
    |   dhcp6:timer-seconds32
    +--rw rapid-commit?          boolean
+--ro active-leases
  +--ro total-count             uint64
  +--ro allocated-count        uint64
  +--ro active-lease* [leased-address]
    +--ro leased-address
    |   inet:ipv6-address
    +--ro client-duid?         dhcp6:duid
    +--ro ia-id                 uint32
    +--ro allocation-time?
    |   yang:date-and-time
    +--ro last-renew-rebind?
    |   yang:date-and-time
    +--ro preferred-lifetime?
    |   dhcp6:timer-seconds32
    +--ro valid-lifetime?
    |   dhcp6:timer-seconds32
    +--ro lease-t1?
    |   dhcp6:timer-seconds32
    +--ro lease-t2?
    |   dhcp6:timer-seconds32
    +--ro status
    |   +--ro code?            uint16
    |   +--ro message?       string
+--rw prefix-pools {prefix-delegation}?
  +--rw prefix-pool* [pool-id]
    +--rw pool-id               string
    +--rw pool-prefix
    |   inet:ipv6-prefix
    +--rw client-prefix-length  uint8
    +--rw max-pd-space-utilization? dhcp6:threshold
    +--rw option-set-id*       leafref
    +--rw valid-lifetime?
    |   dhcp6:timer-seconds32
    +--rw renew-time?
    |   dhcp6:timer-seconds32
    +--rw rebind-time?
    |   dhcp6:timer-seconds32
    +--rw preferred-lifetime?
    |   dhcp6:timer-seconds32
    +--rw rapid-commit?        boolean
+--rw host-reservations
  +--rw prefix-reservation* [reserved-prefix]
    |   +--rw client-duid?     dhcp6:duid
    |   +--rw reserved-prefix
    |   |   inet:ipv6-prefix
    |   +--rw reserved-prefix-len?  uint8
    +--rw option-set-id*       leafref
    +--rw valid-lifetime?
    |   dhcp6:timer-seconds32
    +--rw renew-time?
    |   dhcp6:timer-seconds32
    +--rw rebind-time?
    |   dhcp6:timer-seconds32
    +--rw preferred-lifetime?
    |   dhcp6:timer-seconds32
    +--rw rapid-commit?       boolean
+--ro active-leases
  +--ro total-count             uint64
  +--ro allocated-count        uint64
  +--ro active-lease* [leased-prefix]
    +--ro leased-prefix
    |   inet:ipv6-prefix
    +--ro client-duid?         dhcp6:duid
    +--ro ia-id                 uint32
    +--ro allocation-time?
    |   yang:date-and-time

```

```

|         +--ro last-renew-rebind?
|         |         yang:date-and-time
+--ro preferred-lifetime?
|         dhc6:timer-seconds32
+--ro valid-lifetime?
|         dhc6:timer-seconds32
+--ro lease-t1?
|         dhc6:timer-seconds32
+--ro lease-t2?
|         dhc6:timer-seconds32
+--ro status
|         +--ro code?         uint16
|         +--ro message?      string
+--rw statistics
+--rw discontinuity-time?         yang:date-and-time
+--ro solicit-count?             yang:counter32
+--ro advertise-count?          yang:counter32
+--ro request-count?            yang:counter32
+--ro confirm-count?            yang:counter32
+--ro renew-count?              yang:counter32
+--ro rebind-count?             yang:counter32
+--ro reply-count?              yang:counter32
+--ro release-count?            yang:counter32
+--ro decline-count?            yang:counter32
+--ro reconfigure-count?        yang:counter32
+--ro information-request-count? yang:counter32
+--ro discarded-message-count?   yang:counter32

```

#### rpcs:

```

+---x delete-address-lease {na-assignment}?
| +---w input
| | +---w lease-address-to-delete leafref
| +--ro output
| | +--ro return-message? string
+---x delete-prefix-lease {prefix-delegation}?
+---w input
| +---w lease-prefix-to-delete leafref
+--ro output
| +--ro return-message? string

```

#### notifications:

```

+---n address-pool-utilization-threshold-exceeded
| {na-assignment}?
| +--ro pool-id leafref
| +--ro total-pool-addresses uint64
| +--ro max-allocated-addresses uint64
| +--ro allocated-address-count uint64
+---n prefix-pool-utilization-threshold-exceeded
| {prefix-delegation}?
| +--ro pool-id leafref
| +--ro total-pool-prefixes uint64
| +--ro max-allocated-prefixes uint64
| +--ro allocated-prefixes-count uint64
+---n invalid-client-detected
| +--ro message-type? enumeration
| +--ro duid? dhc6:duid
| +--ro description? string
+---n decline-received {na-assignment}?
+--ro duid? dhc6:duid
+--ro declined-resources* []
| +--ro (resource-type)?
| | +--:(declined-address)
| | | +--ro address? inet:ipv6-address
| | +--:(declined-prefix)
| | +--ro prefix? inet:ipv6-prefix
+---n non-success-code-sent
+--ro duid? dhc6:duid
+--ro status
| +--ro code? uint16
| +--ro message? string

```

Figure 1: DHCPv6 Server Data Module Structure

Descriptions of important nodes:

**enabled:** This enables/disables the function of the DHCPv6 server.

**dhcpv6-server:** This container holds the server's DHCPv6-specific configuration.

**server-duid:** Each server must have a DHCP Unique Identifier (DUID) to identify itself to clients. A DUID consists of a 2-octet type field and an arbitrary length (of no more than 128 octets) content field. Currently, there are four DUID types defined in [RFC8415] and [RFC6355]. The DUID may be configured using the format for one of these types or using the 'unstructured' format. The DUID type definitions are imported from the 'ietf-dhcpv6-common.yang' module. [IANA-HARDWARE-TYPES] and [IANA-PEN] are referenced for the relevant DUID types.

**vendor-config:** This container is provided as a location for additional implementation-specific YANG nodes for the configuration of the device to be augmented. See Appendix C for an example of such a module.

**option-sets:** The server can be configured with multiple option-sets. These are groups of DHCPv6 options with common parameters that may be supplied to clients on request. The 'option-set-id' field is used to reference an option-set elsewhere in the server's configuration.

**option-set:** This holds configuration parameters for DHCPv6 options. The initial set of applicable option definitions are defined here, and additional options that are also relevant to the relay and/or client are imported from the 'ietf-dhcpv6-common' module. Where needed, other DHCPv6 option modules can be augmented as they are defined. The complete list of DHCPV6 options is located at [IANA-DHCPV6-OPTION-CODES].

**class-selector:** This is provided as a location for additional implementation-specific YANG nodes for vendor-specific class selector nodes to be augmented. See Appendix D for an example of this.

**allocation-ranges:** A hierarchical model is used for the allocation of addresses and prefixes. The top-level 'allocation-ranges' container holds global configuration parameters. Under this, the 'allocation-range' list is used for specifying IPv6 prefixes and additional prefix-specific parameters.

**address-pools:** This is used for Identity Association for Non-temporary Addresses (IA\_NA) and Identity Association for Temporary Addresses (IA\_TA) pool allocations with a container for defining host reservations. State information about active leases from each pool is also located here.

**prefix-pools:** This defines pools to be used for prefix delegation to clients. Static host reservations can also be configured. As prefix delegation is not supported by all DHCPv6 server implementations, it is enabled by a feature statement.

Information about RPCs:

**delete-address-lease:** This allows the deletion of a lease for an individual IPv6 address from the server's lease database. Per [BCP18], if available, a language identifier should be included in the output message.

**delete-prefix-lease:** This allows the deletion of a lease for an individual IPv6 prefix from the server's lease database. Per [BCP18], if available, a language identifier should be included



in the output message.

Information about notifications:

address/prefix-pool-utilization-threshold-exceeded: This is raised when the number of leased addresses or prefixes in a pool exceeds the configured usage threshold.

invalid-client-detected: This is raised when the server detects an invalid client. A description of the error and message type that has generated the notification can be included.

decline-received: This is raised when a DHCPv6 Decline message is received from a client.

non-success-code-sent: This is raised when there is a status message for a failure. Status codes are drawn from [IANA-DHCPV6-STATUS-CODES].

### 3.2. DHCPv6 Relay Tree Diagram

The tree diagram in Figure 2 provides an overview of the DHCPv6 relay module. The tree also includes the common functions module defined in Section 4.1.

The RPCs in the module are taken from requirements defined in [RFC8987].

```
module: ietf-dhcpv6-relay
  +--rw dhcpv6-relay
    +--rw enabled?          boolean
    +--rw relay-if* [if-name]
      +--rw if-name          if:interface-ref
      +--rw enabled?        boolean
      +--rw destination-address*  inet:ipv6-address
      +--rw link-address?      inet:ipv6-address
      +--rw relay-options
        +--rw auth-option
          +--rw algorithm?      uint8
          +--rw rdm?            uint8
          +--rw replay-detection?  uint64
          +--rw (protocol)?
            +--:(conf-token)
              +--rw token-auth-information?  binary
            +--:(rkap)
              +--rw datatype?      uint8
              +--rw auth-info-value?  binary
        +--rw interface-id-option
          +--rw interface-id?  binary
    +--rw statistics
      +--rw discontinuity-time?
        | yang:date-and-time
      +--ro solicit-received-count?
        | yang:counter32
      +--ro advertise-sent-count?
        | yang:counter32
      +--ro request-received-count?
        | yang:counter32
      +--ro confirm-received-count?
        | yang:counter32
      +--ro renew-received-count?
        | yang:counter32
      +--ro rebind-received-count?
        | yang:counter32
      +--ro reply-sent-count?
        | yang:counter32
      +--ro release-received-count?
        | yang:counter32
      +--ro decline-received-count?
        | yang:counter32
      +--ro reconfigure-sent-count?
        | yang:counter32
```

```

| | | +--ro information-request-received-count?
| | | | yang:counter32
| | +--ro unknown-message-received-count?
| | | yang:counter32
| | +--ro unknown-message-sent-count?
| | | yang:counter32
| | +--ro discarded-message-count?
| | | yang:counter32
+--rw prefix-delegation! {prefix-delegation}?
| +--ro pd-leases* [ia-pd-prefix]
| | +--ro ia-pd-prefix          inet:ipv6-prefix
| | +--ro last-renew?          yang:date-and-time
| | +--ro client-peer-address? inet:ipv6-address
| | +--ro client-duid?         dhcp6:duid
| | +--ro server-duid?         dhcp6:duid
+--rw statistics
| +--ro relay-forward-sent-count?
| | yang:counter32
+--ro relay-forward-received-count?
| | yang:counter32
+--ro relay-reply-received-count?
| | yang:counter32
+--ro relay-forward-unknown-sent-count?
| | yang:counter32
+--ro relay-forward-unknown-received-count?
| | yang:counter32
+--ro discarded-message-count?
| yang:counter32

```

rpcs:

```

+---x clear-prefix-entry {prefix-delegation}?
| +---w input
| | +---w lease-prefix    leafref
| +--ro output
| | +--ro return-message? string
+---x clear-client-prefixes {prefix-delegation}?
| +---w input
| | +---w client-duid     dhcp6:duid
| +--ro output
| | +--ro return-message? string
+---x clear-interface-prefixes {prefix-delegation}?
| +---w input
| | +---w interface      -> /dhcpv6-relay/relay-if/if-name
| +--ro output
| | +--ro return-message? string

```

notifications:

```

+---n relay-event
| +--ro topology-change
| | +--ro relay-if-name?
| | | -> /dhcpv6-relay/relay-if/if-name
| +--ro last-ipv6-addr? inet:ipv6-address

```

Figure 2: DHCPv6 Relay Data Module Structure

Descriptions of important nodes:

`enabled`: This globally enables/disables all DHCPv6 relay functions.

`dhcpv6-relay`: This container holds the relay's DHCPv6-specific configuration.

`relay-if`: As a relay may have multiple client-facing interfaces, they are configured in a list. The 'if-name' leaf is the key and is an interface-ref to the applicable interface defined by the 'ietf-interfaces' YANG module.

`enabled`: This enables/disables all DHCPv6 relay functions for the specific interface.

`destination-addresses`: This defines a list of IPv6 addresses that

client messages will be relayed to, which may include unicast or multicast addresses.

link-address: This configures the value that the relay will put into the link-address field of Relay-Forward messages.

prefix-delegation: As prefix delegation is not supported by all DHCPv6 relay implementations, it is enabled by this feature statement where required.

pd-leases: This contains read-only nodes for holding information about active delegated prefix leases.

relay-options: This holds configuration parameters for DHCPv6 options that can be sent by the relay. The initial set of applicable option definitions are defined here, and additional options that are also relevant to the server and/or client are imported from the 'ietf-dhcpv6-common' module. Information for the Authentication Option (OPTION\_AUTH (11)) is drawn from [IANA-DHCPV6-AUTH-NAMESPACES] and [RFC3118]. Where needed, other DHCPv6 option modules can be augmented as they are defined. The complete list of DHCPV6 options is located at [IANA-DHCPV6-OPTION-CODES].

Information about RPCs:

clear-prefix-entry: This allows the removal of a delegated lease entry from the relay. Per [BCP18], if available, a language identifier should be included in the output message.

clear-client-prefixes: This allows the removal of all of the delegated lease entries for a single client (referenced by client DUID) from the relay. Per [BCP18], if available, a language identifier should be included in the output message.

clear-interface-prefixes: This allows the removal of all of the delegated lease entries from an interface on the relay. Per [BCP18], if available, a language identifier should be included in the output message.

Information about notifications:

topology-change: This is raised when the topology of the relay agent is changed, e.g., a client-facing interface is reconfigured.

### 3.3. DHCPv6 Client Tree Diagram

The tree diagram in Figure 3 provides an overview of the DHCPv6 client module. The tree also includes the common functions module defined in Section 4.1.

```
module: ietf-dhcpv6-client
+--rw dhcpv6-client
  +--rw enabled?          boolean
  +--rw client-if* [if-name]
    +--rw if-name          if:interface-ref
    +--rw enabled?        boolean
    +--rw interface-duid?  dhc6:duid
    |   { (non-temp-addr or prefix-delegation or temp-addr)
    |   and anon-profile}?
  +--rw client-configured-options
    +--rw option-request-option
    |   +--rw oro-option*  uint16
    +--rw rapid-commit-option!
    +--rw user-class-option!
    |   +--rw user-class-data-instance*
    |   |   [user-class-data-id]
    |   |   +--rw user-class-data-id  uint8
    |   |   +--rw user-class-data?    binary
    +--rw vendor-class-option
    |   +--rw vendor-class-option-instances*
    |   |   [enterprise-number]
```

```

    +--rw enterprise-number          uint32
    +--rw vendor-class-data-element*
        [vendor-class-data-id]
        +--rw vendor-class-data-id    uint8
        +--rw vendor-class-data?      binary
+--rw vendor-specific-information-options
    +--rw vendor-specific-information-option*
        [enterprise-number]
        +--rw enterprise-number      uint32
        +--rw vendor-option-data* [sub-option-code]
            +--rw sub-option-code    uint16
            +--rw sub-option-data?    binary
+--rw reconfigure-accept-option!
+--rw ia-na* [ia-id] {non-temp-addr}?
    +--rw ia-id          uint32
    +--rw ia-na-options
    +--ro lease-state
        +--ro ia-na-address?    inet:ipv6-address
        +--ro lease-t1?         dhcp6:timer-seconds32
        +--ro lease-t2?         dhcp6:timer-seconds32
        +--ro preferred-lifetime? dhcp6:timer-seconds32
        +--ro valid-lifetime?   dhcp6:timer-seconds32
        +--ro allocation-time?  yang:date-and-time
        +--ro last-renew-rebind? yang:date-and-time
        +--ro server-duid?      dhcp6:duid
        +--ro status
            +--ro code?          uint16
            +--ro message?       string
+--rw ia-ta* [ia-id] {temp-addr}?
    +--rw ia-id          uint32
    +--rw ia-ta-options
    +--ro lease-state
        +--ro ia-ta-address?    inet:ipv6-address
        +--ro preferred-lifetime? dhcp6:timer-seconds32
        +--ro valid-lifetime?   dhcp6:timer-seconds32
        +--ro allocation-time?  yang:date-and-time
        +--ro last-renew-rebind? yang:date-and-time
        +--ro server-duid?      dhcp6:duid
        +--ro status
            +--ro code?          uint16
            +--ro message?       string
+--rw ia-pd* [ia-id] {prefix-delegation}?
    +--rw ia-id          uint32
    +--rw prefix-length-hint? uint8
    +--rw ia-pd-options
    +--ro lease-state
        +--ro ia-pd-prefix?     inet:ipv6-prefix
        +--ro lease-t1?         dhcp6:timer-seconds32
        +--ro lease-t2?         dhcp6:timer-seconds32
        +--ro preferred-lifetime? dhcp6:timer-seconds32
        +--ro valid-lifetime?   dhcp6:timer-seconds32
        +--ro allocation-time?  yang:date-and-time
        +--ro last-renew-rebind? yang:date-and-time
        +--ro server-duid?      dhcp6:duid
        +--ro status
            +--ro code?          uint16
            +--ro message?       string
+--rw statistics
    +--rw discontinuity-time?    yang:date-and-time
    +--ro solicit-count?        yang:counter32
    +--ro advertise-count?      yang:counter32
    +--ro request-count?        yang:counter32
    +--ro confirm-count?        yang:counter32
    +--ro renew-count?          yang:counter32
    +--ro rebind-count?         yang:counter32
    +--ro reply-count?          yang:counter32
    +--ro release-count?        yang:counter32
    +--ro decline-count?        yang:counter32
    +--ro reconfigure-count?    yang:counter32
    +--ro information-request-count? yang:counter32
    +--ro discarded-message-count? yang:counter32

```

```

notifications:
+---n invalid-ia-address-detected
|   {non-temp-addr or temp-addr}?
|   +--ro ia-id                uint32
|   +--ro ia-na-t1-timer?      uint32
|   +--ro ia-na-t2-timer?      uint32
|   +--ro invalid-address?     inet:ipv6-address
|   +--ro preferred-lifetime?  uint32
|   +--ro valid-lifetime?      uint32
|   +--ro ia-options?          binary
|   +--ro description?         string
+---n transmission-failed
|   +--ro failure-type          enumeration
|   +--ro description?          string
+---n unsuccessful-status-code
|   +--ro server-duid           dhc6:duid
|   +--ro status
|       +--ro code?             uint16
|       +--ro message?         string
+---n server-duid-changed
|   {non-temp-addr or prefix-delegation or temp-addr}?
|   +--ro new-server-duid       dhc6:duid
|   +--ro previous-server-duid  dhc6:duid
|   +--ro lease-ia-na?
|       |   -> /dhcpv6-client/client-if/ia-na/ia-id
|       |   {non-temp-addr}?
+--ro lease-ia-ta?
|       |   -> /dhcpv6-client/client-if/ia-ta/ia-id
|       |   {temp-addr}?
+--ro lease-ia-pd?
|       |   -> /dhcpv6-client/client-if/ia-pd/ia-id
|       |   {prefix-delegation}?

```

Figure 3: DHCPv6 Client Data Module Structure

Descriptions of important nodes:

**enabled:** This globally enables/disables all DHCPv6 client functions.

**dhcpv6-client:** This container holds the client's DHCPv6-specific configuration.

**client-if:** As a client may have multiple interfaces requesting configuration over DHCP, they are configured in a list. The 'if-name' leaf is the key and is an interface-ref to the applicable interface defined by the 'ietf-interfaces' YANG module.

**enabled:** This enables/disables all DHCPv6 client function for the specific interface.

**client-duid/interface-duid:** The DUID is used to identify the client to servers and relays. A DUID consists of a 2-octet type field and an arbitrary length (1-128 octets) content field. Currently, there are four DUID types defined in [RFC8415] and [RFC6355]. The DUID may be configured using the format for one of these types or using the 'unstructured' format. The DUID type definitions are imported from the 'ietf-dhcpv6-common.yang' module. [IANA-HARDWARE-TYPES] and [IANA-PEN] are referenced for the relevant DUID types. A DUID only needs to be configured if the client is requesting addresses and/or prefixes from the server. Presence of the 'client-duid' or 'interface-duid' leaves is conditional on at least one of the 'non-temp-addr', 'temp-addr', or 'prefix-delegation' features being enabled. Additionally, if the 'anon-profile' [RFC7844] feature is enabled, a unique DUID can be configured per a DHCP-enabled interface using the 'interface-duid' leaf; otherwise, there is a global 'client-duid' leaf.

client-configured-options: This holds configuration parameters for DHCPv6 options that can be sent by the client. The initial set of applicable option definitions are defined here, and additional options that are also relevant to the relay and/or server are imported from the 'ietf-dhcpv6-common' module. Where needed, other DHCPv6 option modules can be augmented as they are defined. The complete list of DHCPV6 options is located at [IANA-DHCPV6-OPTION-CODES].

ia-na, ia-ta, ia-pd: These contain configuration nodes relevant for requesting one or more of each of the lease types. Read-only nodes related to the active leases for each type are also located here, drawing the status codes from [IANA-DHCPV6-STATUS-CODES]. As these lease types may not be supported by all DHCPv6 client implementations, they are enabled via individual feature statements. Stateless DHCP (Section 6.1 of [RFC8415]) is configured when all address and prefix features are disabled.

Information about notifications:

invalid-ia-detected: This is raised when the identity association of the client can be proved to be invalid. Possible conditions include duplicated address, illegal address, etc.

retransmission-failed: This is raised when the retransmission mechanism defined in [RFC8415] has failed.

## 4. DHCPv6 YANG Modules

### 4.1. DHCPv6 Common YANG Module

```
<CODE BEGINS> file "ietf-dhcpv6-common@2022-06-20.yang"
module ietf-dhcpv6-common {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-dhcpv6-common";
  prefix dhc6;

  organization
    "IETF Dynamic Host Configuration (DHC) Working Group";
  contact
    "WG Web: <https://datatracker.ietf.org/wg/dhc/>
    WG List: <mailto:dhcwg@ietf.org>
    Author: Yong Cui <yong@csnet1.cs.tsinghua.edu.cn>
    Author: Linhui Sun <lh.sunlinh@gmail.com>
    Editor: Ian Farrer <ian.farrer@telekom.de>
    Author: Sladjana Zeichlin <sladjana.zechlin@telekom.de>
    Author: Zihao He <hezihao9512@gmail.com>
    Author: Michal Nowikowski <godfryd@isc.org>";
  description
```

```
"This YANG module defines common components used for the
configuration and management of DHCPv6.
```

```
The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL',
'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED',
'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document
are to be interpreted as described in BCP 14 (RFC 2119)
(RFC 8174) when, and only when, they appear in all
capitals, as shown here.
```

```
Copyright (c) 2022 IETF Trust and the persons identified as
authors of the code. All rights reserved.
```

```
Redistribution and use in source and binary forms, with or
without modification, is permitted pursuant to, and subject to
the license terms contained in, the Revised BSD License set
forth in Section 4.c of the IETF Trust's Legal Provisions
Relating to IETF Documents
(https://trustee.ietf.org/license-info).
```

```
This version of this YANG module is part of RFC 9243
(https://www.rfc-editor.org/info/rfc9243); see the RFC itself
```

```

    for full legal notices.";

revision 2022-06-20 {
    description
        "Initial revision.";
    reference
        "RFC 9243: A YANG Data Model for DHCPv6 Configuration";
}

typedef threshold {
    type uint8 {
        range "1..100";
    }
    description
        "Threshold value in percent.";
}

typedef timer-seconds32 {
    type uint32;
    units "seconds";
    description
        "Timer value type in seconds (32-bit range).";
}

typedef duid-base {
    type string {
        pattern '([0-9a-fA-F]{2}){3,130}';
    }
    description
        "Each DHCP server and client has a DHCP Unique Identifier
        (DUID). The DUID consists of a 2-octet type field
        and an arbitrary length (1-128 octets) content field.
        The duid-base type is used by other duid types with
        additional pattern constraints.

        Currently, there are four defined types of DUIDs
        in RFCs 8415 and 6355 -- DUID-LLT, DUID-EN, DUID-LL, and
        DUID-UUID. DUID-unstructured represents DUIDs that do not
        follow any of the defined formats.

        Type 'string' is used to represent the hexadecimal DUID value
        so that pattern constraints can be applied.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 11
        RFC 6355: Definition of the UUID-Based DHCPv6 Unique
        Identifier (DUID-UUID), Section 4";
}

typedef duid-llt {
    type duid-base {
        pattern '0001'
            + '[0-9a-fA-F]{12,}';
    }
    description
        "DUID type 1, based on Link-Layer Address Plus Time
        (DUID-LLT). Constructed with a 2-octet hardware type assigned
        by IANA, 4 octets containing the time the DUID is generated
        (represented in seconds since midnight (UTC), January 1, 2000,
        modulo 2^32), and a link-layer address. The address is encoded
        without separator characters. For example:

        +-----+-----+-----+-----+
        | 0001 | 0006 | 28490058 | 00005E005300 |
        +-----+-----+-----+-----+

        This example includes the 2-octet DUID type of 1 (0x01); the
        hardware type is 0x06 (IEEE Hardware Types), and the creation
        time is 0x28490058 (constructed as described above). Finally,
        the link-layer address is 0x5E005300 (EUI-48 address
        00-00-5E-00-53-00).";

```

```

reference
    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Section 11.2
    IANA 'Hardware Types' registry
    <https://www.iana.org/assignments/arp-parameters>";
}

typedef duid-en {
    type duid-base {
        pattern '0002'
            + '[0-9a-fA-F]{8,}';
    }
    description
        "DUID type 2, assigned by vendor based on Enterprise
        Number (DUID-EN). This DUID consists of the 4-octet vendor's
        registered Private Enterprise Number, as maintained by IANA,
        followed by a unique identifier assigned by the vendor. For
        example:

        +-----+-----+-----+
        | 0002 | 00007ED9 | 0CC084D303000912 |
        +-----+-----+-----+

        This example includes the 2-octet DUID type of 2 (0x02),
        4 octets for the Enterprise Number (0x7ED9), followed by
        8 octets of identifier data (0x0CC084D303000912).";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 11.3
        IANA 'Private Enterprise Numbers' registry
        <https://www.iana.org/assignments/enterprise-numbers>";
}

typedef duid-ll {
    type duid-base {
        pattern '0003'
            + '([0-9a-fA-F]){4,}';
    }
    description
        "DUID type 3, based on Link-Layer Address (DUID-LL).
        Constructed with a 2-octet hardware type assigned
        by IANA and a link-layer address. The address is encoded
        without separator characters. For example:

        +-----+-----+-----+
        | 0003 | 0006 | 00005E005300 |
        +-----+-----+-----+

        This example includes the 2-octet DUID type of 3 (0x03); the
        hardware type is 0x06 (IEEE Hardware Types), and the
        link-layer address is 0x5E005300 (EUI-48 address
        00-00-5E-00-53-00).";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 11.4
        IANA 'Hardware Types' registry
        <https://www.iana.org/assignments/arp-parameters>";
}

typedef duid-uuid {
    type duid-base {
        pattern '0004'
            + '[0-9a-fA-F]{32}';
    }
    description
        "DUID type 4, based on Universally Unique Identifier
        (DUID-UUID). This type of DUID consists of 16 octets
        containing a 128-bit UUID. For example:

        +-----+-----+-----+
        | 0004 | 9f03b182705747e38a1e422910078642 |

```



```

+-----+-----+
This example includes the 2-octet DUID type of 4 (0x04) and
the UUID 9f03b182-7057-47e3-8a1e-422910078642.";
reference
"RFC 8415: Dynamic Host Configuration Protocol for
IPv6 (DHCPv6), Section 11.5
RFC 6355: Definition of the UUID-Based DHCPv6 Unique
Identifier (DUID-UUID)";
}

typedef duid-unstructured {
type duid-base {
pattern '(000[1-4].*)' {
modifier "invert-match";
}
}
description
"Used for DUIDs following any formats other than DUID
types 1-4. For example:

+-----+
| 7b6a164d325946539dc540fb539bc430 |
+-----+

Here, an arbitrary 16-octet value is used. The only
constraint placed on this is that the first 2 octets
are not 0x01-0x04 to avoid collision with the other
defined DUID types (duid-llt, duid-en, duid-ll,
or duid-uuid).";
reference
"RFC 8415: Dynamic Host Configuration Protocol for
IPv6 (DHCPv6), Section 11";
}

typedef duid {
type union {
type duid-llt;
type duid-en;
type duid-ll;
type duid-uuid;
type duid-unstructured;
}
description
"Represents the DUID and is neutral to the DUID's construction
format.";
reference
"RFC 8415: Dynamic Host Configuration Protocol for
IPv6 (DHCPv6), Section 11";
}

/*
* Groupings
*/

grouping status {
description
"Holds information about the most recent status code that
has been sent by the server or received by the client.";
reference
"RFC 8415: Dynamic Host Configuration Protocol
for IPv6 (DHCPv6), Section 7.5.";
container status {
description
"Status code information, relating to the success or failure
of operations requested in messages.";
leaf code {
type uint16;
description
"The numeric code for the status encoded in this option.
See the 'Status Codes' registry at

```

```

        <https://www.iana.org/assignments/dhcpv6-parameters>
        for the current list of status codes.";
    }
    leaf message {
        type string;
        description
            "A UTF-8-encoded text string suitable for display to an
            end user. It MUST NOT be null terminated.";
    }
}

grouping auth-option-group {
    description
        "OPTION_AUTH (11) Authentication Option.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol
        for IPv6 (DHCPv6), Section 21.11
        RFC 3118: Authentication for DHCP Messages
        IANA 'Dynamic Host Configuration Protocol (DHCP)
        Authentication Option Name Spaces' registry
        <https://www.iana.org/assignments/auth-namespaces>";
    container auth-option {
        description
            "OPTION_AUTH (11) Authentication Option.";
        leaf algorithm {
            type uint8;
            description
                "The algorithm used in the authentication protocol.";
        }
        leaf rdm {
            type uint8;
            description
                "The Replay Detection Method (RDM) used in this
                Authentication option.";
        }
        leaf replay-detection {
            type uint64;
            description
                "The replay detection information for the RDM.";
        }
        choice protocol {
            description
                "The authentication protocol used in the option. Protocol
                Namespace Values 1 (delayed authentication) and 2 (Delayed
                Authentication (Obsolete)) are not applicable and so are
                not modeled.";
            case conf-token {
                leaf token-auth-information {
                    type binary;
                    description
                        "Protocol Namespace Value 0. The authentication
                        information, as specified by the protocol and
                        algorithm used in this Authentication option.";
                }
            }
            case rkap {
                description
                    "Protocol Namespace Value 3. The Reconfigure Key
                    Authentication Protocol (RKAP) provides protection
                    against misconfiguration of a client caused by a
                    Reconfigure message sent by a malicious DHCP
                    server.";
                leaf datatype {
                    type uint8 {
                        range "1 .. 2";
                    }
                    description
                        "Type of data in the Value field carried in this
                        option.
                        1 Reconfigure key value (used in the Reply

```

```

        message).
    2  HMAC-MD5 digest of the message (used in
        the Reconfigure message).";
}
leaf auth-info-value {
    type binary {
        length "16";
    }
    description
        "Data, as defined by the Type field.  A 16-octet
        field.";
}
}
}
}
}

grouping rapid-commit-option-group {
    description
        "OPTION_RAPID_COMMIT (14) Rapid Commit Option.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 21.14";
    container rapid-commit-option {
        presence "Enable sending of this option";
        description
            "OPTION_RAPID_COMMIT (14) Rapid Commit Option.";
    }
}

grouping vendor-specific-information-option-group {
    description
        "OPTION_VENDOR_OPTS (17) Vendor-specific Information
        Option.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol
        for IPv6 (DHCPv6), Section 21.17";
    container vendor-specific-information-options {
        description
            "OPTION_VENDOR_OPTS (17) Vendor-specific Information
            Option.";
        list vendor-specific-information-option {
            key "enterprise-number";
            description
                "The Vendor-specific Information option allows for
                multiple instances in a single message.  Each list entry
                defines the contents of an instance of the option.";
            leaf enterprise-number {
                type uint32;
                description
                    "The vendor's registered Enterprise Number, as
                    maintained by IANA.";
                reference
                    "IANA 'Private Enterprise Numbers' registry
                    <https://www.iana.org/assignments/enterprise-numbers>";
            }
            list vendor-option-data {
                key "sub-option-code";
                description
                    "Vendor options, interpreted by vendor-specific
                    client/server functions.";
                leaf sub-option-code {
                    type uint16;
                    description
                        "The code for the sub-option.";
                }
            }
            leaf sub-option-data {
                type binary;
                description
                    "The data area for the sub-option.";
            }
        }
    }
}
}

```

```

    }
  }
}

grouping reconfigure-accept-option-group {
  description
    "OPTION_RECONF_ACCEPT (20) Reconfigure Accept Option.
    A client uses the Reconfigure Accept option to announce to
    the server whether or not the client is willing to accept
    Reconfigure messages, and a server uses this option to tell
    the client whether or not to accept Reconfigure messages. In
    the absence of this option, the default behavior is that the
    client is unwilling to accept Reconfigure messages. The
    presence node is used to enable the option.";
  reference
    "RFC 8415: Dynamic Host Configuration Protocol
    for IPv6 (DHCPv6), Section 21.20";
  container reconfigure-accept-option {
    presence "Enable sending of this option";
    description
      "OPTION_RECONF_ACCEPT (20) Reconfigure Accept Option.";
  }
}
}
<CODE ENDS>

```

#### 4.2. DHCPv6 Server YANG Module

This module imports typedefs from [RFC6991] and the module defined in [RFC8343].

```

<CODE BEGINS> file "ietf-dhcpv6-server@2022-06-20.yang"
module ietf-dhcpv6-server {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-dhcpv6-server";
  prefix dhc6-srv;

  import ietf-inet-types {
    prefix inet;
    reference
      "RFC 6991: Common YANG Data Types";
  }
  import ietf-yang-types {
    prefix yang;
    reference
      "RFC 6991: Common YANG Data Types";
  }
  import ietf-dhcpv6-common {
    prefix dhc6;
    reference
      "RFC 9243: A YANG Data Model for DHCPv6 Configuration";
  }
  import ietf-netconf-acm {
    prefix nacm;
    reference
      "RFC 8341: Network Configuration Access Control Model";
  }

  organization
    "IETF Dynamic Host Configuration (DHC) Working Group";
  contact
    "WG Web: <https://datatracker.ietf.org/wg/dhc/>
    WG List: <mailto:dhcwg@ietf.org>
    Author: Yong Cui <yong@csnet1.cs.tsinghua.edu.cn>
    Author: Linhui Sun <lh.sunlinh@gmail.com>
    Editor: Ian Farrer <ian.farrer@telekom.de>
    Author: Sladjana Zeichlin <sladjana.zechlin@telekom.de>
    Author: Zihao He <hezihao9512@gmail.com>
    Author: Michal Nowikowski <godfryd@isc.org>";
  description

```

"This YANG module defines components for the configuration and management of DHCPv6 servers.

Copyright (c) 2022 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Revised BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC 9243 (<https://www.rfc-editor.org/info/rfc9243>); see the RFC itself for full legal notices.";

```
revision 2022-06-20 {
  description
    "Initial revision.";
  reference
    "RFC 9243: A YANG Data Model for DHCPv6 Configuration";
}

/*
 * Features
 */

feature na-assignment {
  description
    "Denotes that the server implements DHCPv6 non-temporary
    address assignment.";
  reference
    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Section 6.2";
}

feature prefix-delegation {
  description
    "Denotes that the server implements DHCPv6 prefix
    delegation.";
  reference
    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Section 6.3";
}

/*
 * Groupings
 */

grouping resource-config {
  description
    "Nodes that are reused at multiple levels in the DHCPv6
    server's addressing hierarchy.";
  leaf-list option-set-id {
    type leafref {
      path "/dhcpv6-server/option-sets/option-set/option-set-id";
    }
    description
      "The ID field of the relevant set of DHCPv6 options
      (option-set) to be provisioned to clients using the
      allocation-range.";
  }
  leaf valid-lifetime {
    type dhc6:timer-seconds32;
    description
      "Valid lifetime for the Identity Association (IA).";
    reference
      "RFC 8415: Dynamic Host Configuration Protocol for
      IPv6 (DHCPv6), Section 12.1";
  }
}
```

```

leaf renew-time {
  type dhcp6:timer-seconds32;
  description
    "Renew (T1) time.";
  reference
    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Section 4.2";
}
leaf rebind-time {
  type dhcp6:timer-seconds32;
  description
    "Rebind (T2) time.";
  reference
    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Section 4.2";
}
leaf preferred-lifetime {
  type dhcp6:timer-seconds32;
  description
    "Preferred lifetime for the IA.";
  reference
    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Section 12.1";
}
leaf rapid-commit {
  type boolean;
  description
    "When set to 'true', specifies that client-server exchanges
    involving two messages is supported.";
  reference
    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Section 5.1";
}
}

grouping lease-information {
  description
    "Binding information for each client that has been allocated
    an IPv6 address or prefix.";
  leaf client-duid {
    type dhcp6:duid;
    description
      "Client DUID.";
    reference
      "RFC 8415: Dynamic Host Configuration Protocol for
      IPv6 (DHCPv6), Section 11";
  }
  leaf ia-id {
    type uint32;
    mandatory true;
    description
      "Client's Identity Association Identifier (IAID).";
    reference
      "RFC 8415: Dynamic Host Configuration Protocol for
      IPv6 (DHCPv6), Section 12";
  }
  leaf allocation-time {
    type yang:date-and-time;
    description
      "Time and date that the lease was made.";
    reference
      "RFC 8415: Dynamic Host Configuration Protocol for
      IPv6 (DHCPv6), Section 18";
  }
  leaf last-renew-rebind {
    type yang:date-and-time;
    description
      "Time of the last successful renew or rebind.";
    reference
      "RFC 8415: Dynamic Host Configuration Protocol for
      IPv6 (DHCPv6), Section 18";
  }
}

```

```

}
leaf preferred-lifetime {
    type dhcp6:timer-seconds32;
    description
        "The preferred lifetime expressed in seconds.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 6";
}
leaf valid-lifetime {
    type dhcp6:timer-seconds32;
    description
        "The valid lifetime for the lease expressed in seconds.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 6";
}
leaf lease-t1 {
    type dhcp6:timer-seconds32;
    description
        "The time interval after which the client should contact
        the server from which the addresses in the IA_NA were
        obtained to extend the lifetimes of the addresses assigned
        to the Identity Association for Prefix Delegation (IA_PD).";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 4.2";
}
leaf lease-t2 {
    type dhcp6:timer-seconds32;
    description
        "The time interval after which the client should contact
        any available server to extend the lifetimes of the
        addresses assigned to the IA_PD.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 4.2";
}
uses dhcp6:status;
}

grouping message-statistics {
    description
        "Counters for DHCPv6 messages.";
    leaf discontinuity-time {
        type yang:date-and-time;
        description
            "The time on the most recent occasion at which any one or
            more of DHCPv6 server's counters suffered a discontinuity.
            If no such discontinuities have occurred since the last
            re-initialization of the local management subsystem, then
            this node contains the time the local management subsystem
            re-initialized itself.";
    }
    leaf solicit-count {
        type yang:counter32;
        config false;
        description
            "Number of Solicit (1) messages received.";
    }
    leaf advertise-count {
        type yang:counter32;
        config false;
        description
            "Number of Advertise (2) messages sent.";
    }
    leaf request-count {
        type yang:counter32;
        config false;
        description
            "Number of Request (3) messages received.";
    }
}

```

```

}
leaf confirm-count {
    type yang:counter32;
    config false;
    description
        "Number of Confirm (4) messages received.";
}
leaf renew-count {
    type yang:counter32;
    config false;
    description
        "Number of Renew (5) messages received.";
}
leaf rebind-count {
    type yang:counter32;
    config false;
    description
        "Number of Rebind (6) messages received.";
}
leaf reply-count {
    type yang:counter32;
    config false;
    description
        "Number of Reply (7) messages sent.";
}
leaf release-count {
    type yang:counter32;
    config false;
    description
        "Number of Release (8) messages received.";
}
leaf decline-count {
    type yang:counter32;
    config false;
    description
        "Number of Decline (9) messages received.";
}
leaf reconfigure-count {
    type yang:counter32;
    config false;
    description
        "Number of Reconfigure (10) messages sent.";
}
leaf information-request-count {
    type yang:counter32;
    config false;
    description
        "Number of Information-request (11) messages
        received.";
}
leaf discarded-message-count {
    type yang:counter32;
    config false;
    description
        "Number of messages that have been discarded for any
        reason.";
}
}

grouping preference-option-group {
    description
        "OPTION_PREFERENCE (7) Preference Option.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 21.8";
    container preference-option {
        description
            "OPTION_PREFERENCE (7) Preference Option.";
        leaf pref-value {
            type uint8;
            description

```



```

        "The preference value for the server in this message. A
        1-octet unsigned integer.";
    }
}

grouping server-unicast-option-group {
    description
        "OPTION_UNICAST (12) Server Unicast Option.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 21.12";
    container server-unicast-option {
        description
            "OPTION_UNICAST (12) Server Unicast Option.";
        leaf server-address {
            type inet:ipv6-address;
            description
                "The 128-bit address to which the client should send
                messages delivered using unicast.";
        }
    }
}

grouping reconfigure-message-option-group {
    description
        "OPTION_RECONF_MSG (19) Reconfigure Message Option.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 21.19";
    container reconfigure-message-option {
        description
            "OPTION_RECONF_MSG (19) Reconfigure Message Option.";
        leaf msg-type {
            type uint8;
            description
                "5 for Renew message, 6 for Rebind message, and 11 for
                Information-request message.";
        }
    }
}

grouping info-refresh-time-option-group {
    description
        "OPTION_INFORMATION_REFRESH_TIME (32) Information Refresh
        Time Option.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 21.23";
    container info-refresh-time-option {
        description
            "OPTION_INFORMATION_REFRESH_TIME (32) Information Refresh
            Time Option.";
        leaf info-refresh-time {
            type dhc6:timer-seconds32;
            description
                "Time duration specifying an upper bound for how long a
                client should wait before refreshing information retrieved
                from a DHCP server.";
        }
    }
}

grouping sol-max-rt-option-group {
    description
        "OPTION_SOL_MAX_RT (82) SOL_MAX_RT Option (Max Solicit timeout
        value).";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 21.24";
    container sol-max-rt-option {

```

```

description
  "OPTION_SOL_MAX_RT (82) SOL_MAX_RT Option.";
leaf sol-max-rt-value {
  type dhcp6:timer-seconds32;
  description
    "Maximum Solicit timeout value.";
}
}
}

grouping inf-max-rt-option-group {
description
  "OPTION_INF_MAX_RT (83) INF_MAX_RT Option (Max
  Information-request timeout value).";
reference
  "RFC 8415: Dynamic Host Configuration Protocol for
  IPv6 (DHCPv6), Section 21.25";
container inf-max-rt-option {
description
  "OPTION_INF_MAX_RT (83) INF_MAX_RT Option.";
leaf inf-max-rt-value {
  type dhcp6:timer-seconds32;
  description
    "Maximum Information-request timeout value.";
}
}
}

/*
 * Data Nodes
 */

container dhcpv6-server {
description
  "Configuration nodes for the DHCPv6 server.";
reference
  "RFC 8415: Dynamic Host Configuration Protocol for
  IPv6 (DHCPv6), Section 18.3";
leaf enabled {
  type boolean;
  description
    "Enables the DHCP server function.";
}
leaf server-duid {
  type dhcp6:duid;
  description
    "DUID of the server.";
reference
  "RFC 8415: Dynamic Host Configuration Protocol for
  IPv6 (DHCPv6), Section 11";
}
container vendor-config {
description
  "This container provides a location for augmenting vendor
  or implementation-specific configuration nodes.";
}
container option-sets {
description
  "A server may allow different option sets to be configured
  for clients matching specific parameters, such as
  topological location or client type. The 'option-set' list
  is a set of options and their contents that will be
  returned to clients.";
reference
  "RFC 8415: Dynamic Host Configuration Protocol for
  IPv6 (DHCPv6), Section 21";
list option-set {
  key "option-set-id";
  description
    "YANG definitions for DHCPv6 options are contained in
    separate YANG modules and augmented to this container as

```

```

        required.";
leaf option-set-id {
    type string;
    description
        "Option set identifier.";
}
leaf description {
    type string;
    description
        "An optional field for storing additional information
        relevant to the option set.";
}
uses preference-option-group;
uses dhcp6:auth-option-group;
uses server-unicast-option-group;
uses dhcp6:rapid-commit-option-group;
uses dhcp6:vendor-specific-information-option-group;
uses reconfigure-message-option-group;
uses dhcp6:reconfigure-accept-option-group;
uses info-refresh-time-option-group;
uses sol-max-rt-option-group;
uses inf-max-rt-option-group;
}
}
container class-selector {
    description
        "DHCPv6 servers use a 'class-selector' function in order
        to identify and classify incoming client messages
        sothat they can be given the correct configuration.
        The mechanisms used for implementing this function vary
        greatly between different implementations; as such, it is
        not possible to include them in this module. This container
        provides a location for server implementors to augment their
        own class-selector YANG.";
}
container allocation-ranges {
    description
        "This model is based on an address and parameter
        allocation hierarchy. The top level is 'global' -- which
        is defined as the container for all allocation-ranges.
        Under this are the individual allocation-ranges.";
    uses resource-config;
    list allocation-range {
        key "id";
        description
            "Network ranges are identified by the 'id' key.";
        leaf id {
            type string;
            mandatory true;
            description
                "Unique identifier for the allocation range.";
        }
        leaf description {
            type string;
            description
                "Description for the allocation range.";
        }
        leaf network-prefix {
            type inet:ipv6-prefix;
            mandatory true;
            description
                "Network prefix.";
        }
    }
    uses resource-config;
    container address-pools {
        if-feature "na-assignment";
        description
            "Configuration for the DHCPv6 server's
            address pools.";
        list address-pool {
            key "pool-id";

```

```

description
  "List of address pools for allocation to clients,
  distinguished by 'pool-id'.";
leaf pool-id {
  type string;
  mandatory true;
  description
    "Unique identifier for the pool.";
}
leaf pool-prefix {
  type inet:ipv6-prefix;
  mandatory true;
  description
    "IPv6 prefix for the pool. Should be contained
    within the network-prefix if configured.";
}
leaf start-address {
  type inet:ipv6-address-no-zone;
  mandatory true;
  description
    "Starting IPv6 address for the pool.";
}
leaf end-address {
  type inet:ipv6-address-no-zone;
  mandatory true;
  description
    "Ending IPv6 address for the pool.";
}
leaf max-address-utilization {
  type dhcp6:threshold;
  description
    "Maximum amount of the addresses in the
    pool that can be simultaneously allocated,
    calculated as a percentage of the available
    addresses (end-address minus start-address plus
    one), and rounded up. Used to set the value for
    the address-pool-utilization-threshold-exceeded
    notification.";
}
uses resource-config;
container host-reservations {
  description
    "Configuration for host reservations from the
    address pool.";
  list host-reservation {
    key "reserved-addr";
    description
      "List of host reservations.";
    leaf client-duid {
      type dhcp6:duid;
      description
        "Client DUID for the reservation.";
    }
    leaf reserved-addr {
      type inet:ipv6-address;
      description
        "Reserved IPv6 address.";
    }
  }
  uses resource-config;
}
container active-leases {
  config false;
  description
    "Holds state related to active client
    leases.";
  leaf total-count {
    type uint64;
    mandatory true;
    description
      "The total number of addresses in the pool.";
  }
}

```

```

}
leaf allocated-count {
    type uint64;
    mandatory true;
    description
        "The number of addresses or prefixes in the pool
        that are currently allocated.";
}
list active-lease {
    key "leased-address";
    description
        "List of active address leases.";
    leaf leased-address {
        type inet:ipv6-address;
        description
            "Active address lease entry.";
    }
    uses lease-information;
}
}
}
}
}
container prefix-pools {
    if-feature "prefix-delegation";
    description
        "Configuration for the DHCPv6 server's prefix pools.";
    list prefix-pool {
        key "pool-id";
        description
            "List of prefix pools for allocation to clients,
            distinguished by 'pool-id'.";
        leaf pool-id {
            type string;
            mandatory true;
            description
                "Unique identifier for the pool.";
        }
        leaf pool-prefix {
            type inet:ipv6-prefix;
            mandatory true;
            description
                "IPv6 prefix for the pool. Should be contained
                within the network-prefix if configured.";
        }
        leaf client-prefix-length {
            type uint8 {
                range "1 .. 128";
            }
            mandatory true;
            description
                "Length of the prefixes that will be delegated
                to clients.";
        }
        leaf max-pd-space-utilization {
            type dhc6:threshold;
            description
                "Maximum amount of the prefixes in the pool that
                can be simultaneously allocated, calculated as a
                percentage of the available prefixes, and rounded
                up. Used to set the value for the
                prefix-pool-utilization-threshold-exceeded
                notification.";
        }
    }
    uses resource-config;
    container host-reservations {
        description
            "Configuration for host reservations from the
            prefix pool.";
        list prefix-reservation {
            key "reserved-prefix";
            description

```

```

        "Reserved prefix reservation.";
    leaf client-duid {
        type dhcp6:duid;
        description
            "Client DUID for the reservation.";
    }
    leaf reserved-prefix {
        type inet:ipv6-prefix;
        description
            "Reserved IPv6 prefix.";
    }
    leaf reserved-prefix-len {
        type uint8;
        description
            "Reserved IPv6 prefix length.";
    }
}
uses resource-config;
}
container active-leases {
    config false;
    description
        "Holds state related to active client prefix
        leases.";
    leaf total-count {
        type uint64;
        mandatory true;
        description
            "The total number of prefixes in the pool.";
    }
    leaf allocated-count {
        type uint64;
        mandatory true;
        description
            "The number of prefixes in the pool that are
            currently allocated.";
    }
    list active-lease {
        key "leased-prefix";
        description
            "List of active prefix leases.";
        leaf leased-prefix {
            type inet:ipv6-prefix;
            description
                "Active leased prefix entry.";
        }
        uses lease-information;
    }
}
}
}
}
}
container statistics {
    description
        "DHCPv6 message counters for the server.";
    uses message-statistics;
}
}
}
}
}
/*
 * RPCs
 */

rpc delete-address-lease {
    nacm:default-deny-all;
    if-feature "na-assignment";
    description
        "Deletes a client's active address lease from the server's
        lease database. Note that this will not cause the address
        to be revoked from the client, and the lease may be refreshed

```

```

    or renewed by the client.";
input {
  leaf lease-address-to-delete {
    type leafref {
      path "/dhcpv6-server/allocation-ranges/"
        + "allocation-range/address-pools/address-pool"
        + "/active-leases/active-lease/leased-address";
    }
    mandatory true;
    description
      "IPv6 address of an active lease that will be
      deleted from the server.";
  }
}
output {
  leaf return-message {
    type string;
    description
      "Response message from the server.  If available, a
      language identifier should be included in the message.";
    reference
      "BCP 18 (RFC 2277) IETF Policy on Character Sets
      and Languages, Section 4.2";
  }
}
}

rpc delete-prefix-lease {
  nacm:default-deny-all;
  if-feature "prefix-delegation";
  description
    "Deletes a client's active prefix lease from the server's
    lease database.  Note that this will not cause the prefix
    to be revoked from the client, and the lease may be refreshed
    or renewed by the client.";
  input {
    leaf lease-prefix-to-delete {
      type leafref {
        path "/dhcpv6-server/allocation-ranges/"
          + "allocation-range/prefix-pools/prefix-pool"
          + "/active-leases/active-lease/leased-prefix";
      }
      mandatory true;
      description
        "IPv6 prefix of an active lease that will be deleted
        from the server.";
    }
  }
  output {
    leaf return-message {
      type string;
      description
        "Response message from the server.  If available, a
        language identifier should be included in the message.";
      reference
        "BCP 18 (RFC 2277) IETF Policy on Character Sets
        and Languages, Section 4.2";
    }
  }
}

/*
 * Notifications
 */

notification address-pool-utilization-threshold-exceeded {
  if-feature "na-assignment";
  description
    "Notification sent when the address pool
    utilization exceeds the threshold configured in
    max-address-utilization.";
}

```

```

leaf pool-id {
  type leafref {
    path "/dhcpv6-server/allocation-ranges/"
      + "allocation-range/address-pools/address-pool"
      + "/pool-id";
  }
  mandatory true;
  description
    "Leafref to the address pool that the notification is being
    generated for.";
}
leaf total-pool-addresses {
  type uint64;
  mandatory true;
  description
    "Total number of addresses in the pool (end-address minus
    start-address plus one).";
}
leaf max-allocated-addresses {
  type uint64;
  mandatory true;
  description
    "Maximum number of addresses that can be simultaneously
    allocated from the pool. This value may be less than the
    count of total addresses. Calculated as the
    max-address-utilization (percentage) of the
    total-pool-addresses and rounded up.";
}
leaf allocated-address-count {
  type uint64;
  mandatory true;
  description
    "Number of addresses allocated from the pool.";
}
}

notification prefix-pool-utilization-threshold-exceeded {
  if-feature "prefix-delegation";
  description
    "Notification sent when the prefix pool utilization
    exceeds the threshold configured in
    max-pd-space-utilization.";
  leaf pool-id {
    type leafref {
      path "/dhcpv6-server/allocation-ranges"
        + "/allocation-range/prefix-pools/prefix-pool/pool-id";
    }
    mandatory true;
    description
      "Unique identifier for the pool.";
  }
  leaf total-pool-prefixes {
    type uint64;
    mandatory true;
    description
      "Total number of prefixes in the pool.";
  }
  leaf max-allocated-prefixes {
    type uint64;
    mandatory true;
    description
      "Maximum number of prefixes that can be simultaneously
      allocated from the pool. This value may be less than
      the count of total prefixes. Calculated as the
      max-prefix-utilization (percentage) of the
      total-pool-prefixes and rounded up.";
  }
  leaf allocated-prefixes-count {
    type uint64;
    mandatory true;
    description

```



```

        "Number of prefixes allocated from the pool.";
    }
}

notification invalid-client-detected {
    description
        "Notification sent when the server detects an invalid
        client.";
    leaf message-type {
        type enumeration {
            enum solicit {
                description
                    "Solicit (1) message.";
            }
            enum request {
                description
                    "Request (3) message.";
            }
            enum confirm {
                description
                    "Confirm (4) message.";
            }
            enum renew {
                description
                    "Renew (5) message.";
            }
            enum rebind {
                description
                    "Rebind (6) message.";
            }
            enum release {
                description
                    "Release (8) message.";
            }
            enum decline {
                description
                    "Decline (9) message.";
            }
            enum info-request {
                description
                    "Information request (11) message.";
            }
        }
    }
    description
        "The message type received by the server that has caused
        the error.";
    leaf duid {
        type dhcp6:duid;
        description
            "Client DUID.";
    }
    leaf description {
        type string;
        description
            "Description of the event (e.g., an error code or log
            message).";
    }
}

notification decline-received {
    if-feature "na-assignment";
    description
        "Notification sent when the server has received a Decline (9)
        message from a client.";
    leaf duid {
        type dhcp6:duid;
        description
            "Client DUID.";
    }
    list declined-resources {

```

```

description
  "List of declined addresses and/or prefixes.";
choice resource-type {
  description
    "Type of resource that has been declined.";
  case declined-address {
    leaf address {
      type inet:ipv6-address;
      description
        "Address that has been declined.";
    }
  }
  case declined-prefix {
    leaf prefix {
      type inet:ipv6-prefix;
      description
        "Prefix that has been declined.";
    }
  }
}
}
}

notification non-success-code-sent {
  description
    "Notification sent when the server responded to a client with
    a non-success status code.";
  leaf duid {
    type dhcp6:duid;
    description
      "Client DUID.";
  }
  uses dhcp6:status;
}
}
<CODE ENDS>

```

#### 4.3. DHCPv6 Relay YANG Module

This module imports typedefs from [RFC6991] and modules defined in [RFC8341] and [RFC8343].

```

<CODE BEGINS> file "ietf-dhcpv6-relay@2022-06-20.yang"
module ietf-dhcpv6-relay {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-dhcpv6-relay";
  prefix dhcp6-rly;

  import ietf-inet-types {
    prefix inet;
    reference
      "RFC 6991: Common YANG Data Types";
  }
  import ietf-yang-types {
    prefix yang;
    reference
      "RFC 6991: Common YANG Data Types";
  }
  import ietf-dhcpv6-common {
    prefix dhcp6;
    reference
      "RFC 9243: A YANG Data Model for DHCPv6 Configuration";
  }
  import ietf-interfaces {
    prefix if;
    reference
      "RFC 8343: A YANG Data Model for Interface Management";
  }
  import ietf-netconf-acm {
    prefix nacm;
    reference

```

```

    "RFC 8341: Network Configuration Access Control Model";
}

organization
  "IETF Dynamic Host Configuration (DHC) Working Group";
contact
  "WG Web: <https://datatracker.ietf.org/wg/dhc/>
  WG List: <mailto:dhcwg@ietf.org>
  Author: Yong Cui <yong@csnet1.cs.tsinghua.edu.cn>
  Author: Linhui Sun <lh.sunlinh@gmail.com>
  Editor: Ian Farrer <ian.farrer@telekom.de>
  Author: Sladjana Zeichlin <sladjana.zechlin@telekom.de>
  Author: Zihao He <hezihao9512@gmail.com>
  Author: Michal Nowikowski <godfryd@isc.org>";
description
  "This YANG module defines components necessary for the
  configuration and management of DHCPv6 relays.

  The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL
  NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED',
  'MAY', and 'OPTIONAL' in this document are to be interpreted as
  described in BCP 14 (RFC 2119) (RFC 8174) when, and only when,
  they appear in all capitals, as shown here.

  Copyright (c) 2022 IETF Trust and the persons identified as
  authors of the code. All rights reserved.

  Redistribution and use in source and binary forms, with or
  without modification, is permitted pursuant to, and subject to
  the license terms contained in, the Revised BSD License set
  forth in Section 4.c of the IETF Trust's Legal Provisions
  Relating to IETF Documents
  (https://trustee.ietf.org/license-info).

  This version of this YANG module is part of RFC 9243
  (https://www.rfc-editor.org/info/rfc9243); see the RFC itself
  for full legal notices.";

revision 2022-06-20 {
  description
    "Initial revision.";
  reference
    "RFC 9243: A YANG Data Model for DHCPv6 Configuration";
}

/*
 * Features
 */

feature prefix-delegation {
  description
    "Enable if the relay functions as a delegating router for
    DHCPv6 prefix delegation.";
  reference
    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Section 6.3";
}

/*
 * Groupings
 */

grouping pd-lease-state {
  description
    "State data for the relay.";
  list pd-leases {
    key "ia-pd-prefix";
    config false;
    description
      "Information about an active IA_PD prefix delegation.";
    leaf ia-pd-prefix {

```

```

    type inet:ipv6-prefix;
    description
        "Prefix that is delegated.";
}
leaf last-renew {
    type yang:date-and-time;
    description
        "Time of the last successful refresh or renew of the
        delegated prefix.";
}
leaf client-peer-address {
    type inet:ipv6-address;
    description
        "Peer-address of the leasing client.";
}
leaf client-duid {
    type dhcp6:duid;
    description
        "DUID of the leasing client.";
}
leaf server-duid {
    type dhcp6:duid;
    description
        "DUID of the delegating server.";
}
}
}

grouping message-statistics {
    description
        "Contains counters for the different DHCPv6 message types.";
    leaf discontinuity-time {
        type yang:date-and-time;
        description
            "The time on the most recent occasion at which any one or
            more of DHCPv6 relay's counters suffered a discontinuity.
            If no such discontinuities have occurred since the last
            re-initialization of the local management subsystem, then
            this node contains the time the local management subsystem
            re-initialized itself.";
    }
    leaf solicit-received-count {
        type yang:counter32;
        config false;
        description
            "Number of Solicit (1) messages received.";
    }
    leaf advertise-sent-count {
        type yang:counter32;
        config false;
        description
            "Number of Advertise (2) messages sent.";
    }
    leaf request-received-count {
        type yang:counter32;
        config false;
        description
            "Number of Request (3) messages received.";
    }
    leaf confirm-received-count {
        type yang:counter32;
        config false;
        description
            "Number of Confirm (4) messages received.";
    }
    leaf renew-received-count {
        type yang:counter32;
        config false;
        description
            "Number of Renew (5) messages received.";
    }
}

```

```

leaf rebind-received-count {
    type yang:counter32;
    config false;
    description
        "Number of Rebind (6) messages received.";
}
leaf reply-sent-count {
    type yang:counter32;
    config false;
    description
        "Number of Reply (7) messages sent.";
}
leaf release-received-count {
    type yang:counter32;
    config false;
    description
        "Number of Release (8) messages received.";
}
leaf decline-received-count {
    type yang:counter32;
    config false;
    description
        "Number of Decline (9) messages received.";
}
leaf reconfigure-sent-count {
    type yang:counter32;
    config false;
    description
        "Number of Reconfigure (10) messages sent.";
}
leaf information-request-received-count {
    type yang:counter32;
    config false;
    description
        "Number of Information-request (11) messages
        received.";
}
leaf unknown-message-received-count {
    type yang:counter32;
    config false;
    description
        "Number of messages of unknown type that have
        been received.";
}
leaf unknown-message-sent-count {
    type yang:counter32;
    config false;
    description
        "Number of messages of unknown type that have
        been sent.";
}
leaf discarded-message-count {
    type yang:counter32;
    config false;
    description
        "Number of messages that have been discarded
        for any reason.";
}
}

grouping global-statistics {
    description
        "Global statistics for the device.";
    leaf relay-forward-sent-count {
        type yang:counter32;
        config false;
        description
            "Number of Relay-forward (12) messages sent.";
    }
    leaf relay-forward-received-count {
        type yang:counter32;
    }
}

```

```

    config false;
    description
        "Number of Relay-forward (12) messages received.";
}
leaf relay-reply-received-count {
    type yang:counter32;
    config false;
    description
        "Number of Relay-reply (13) messages received.";
}
leaf relay-forward-unknown-sent-count {
    type yang:counter32;
    config false;
    description
        "Number of Relay-forward (12) messages containing
        a message of unknown type sent.";
}
leaf relay-forward-unknown-received-count {
    type yang:counter32;
    config false;
    description
        "Number of Relay-forward (12) messages containing
        a message of unknown type received.";
}
leaf discarded-message-count {
    type yang:counter32;
    config false;
    description
        "Number of messages that have been discarded
        for any reason.";
}
}

grouping interface-id-option-group {
    description
        "OPTION_INTERFACE_ID (18) Interface-Id Option.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 21.18";
    container interface-id-option {
        description
            "OPTION_INTERFACE_ID (18) Interface-Id Option.";
        leaf interface-id {
            type binary;
            description
                "An opaque value of arbitrary length generated by the
                relay agent to identify one of the relay agent's
                interfaces.";
        }
    }
}

/*
 * Data Nodes
 */

container dhcpv6-relay {
    description
        "This container contains the configuration data nodes
        for the relay.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 19";
    leaf enabled {
        type boolean;
        description
            "Globally enables the DHCP relay function.";
    }
    list relay-if {
        key "if-name";
        description

```

```

    "List of interfaces configured for DHCPv6 relaying.";
leaf if-name {
    type if:interface-ref;
    description
        "interface-ref to the relay interface.";
}
leaf enabled {
    type boolean;
    description
        "Enables the DHCP relay function for this interface.";
}
leaf-list destination-address {
    type inet:ipv6-address;
    description
        "Each DHCPv6 relay agent may be configured with a list
        of destination addresses for relayed messages.
        The list may include unicast addresses, multicast
        addresses, or other valid addresses.";
}
leaf link-address {
    type inet:ipv6-address;
    description
        "An address that may be used by the server to identify
        the link on which the client is located.";
}
container relay-options {
    description
        "Definitions for DHCPv6 options that can be sent
        by the relay are augmented to this location from other
        YANG modules as required.";
    uses dhc6:auth-option-group;
    uses interface-id-option-group;
}
container statistics {
    description
        "DHCPv6 message counters for the relay's interface.";
    uses message-statistics;
}
container prefix-delegation {
    if-feature "prefix-delegation";
    presence "Enables prefix delegation for this interface.";
    description
        "Controls and holds state information for prefix
        delegation.";
    uses pd-lease-state;
}
}
container statistics {
    description
        "Global DHCPv6 message counters for the relay.";
    uses global-statistics;
}
}

/*
 * RPCs
 */

rpc clear-prefix-entry {
    nacm:default-deny-all;
    if-feature "prefix-delegation";
    description
        "Clears an entry for an active delegated prefix
        from the relay.";
    reference
        "RFC 8987: DHCPv6 Prefix Delegating Relay Requirements,
        Section 4.4";
    input {
        leaf lease-prefix {
            type leafref {
                path "/dhcpv6-relay/relay-if/prefix-delegation"
            }
        }
    }
}

```

```

        + "/pd-leases/ia-pd-prefix";
    }
    mandatory true;
    description
        "IPv6 prefix of an active lease entry that will
        be deleted from the relay.";
    }
}
output {
    leaf return-message {
        type string;
        description
            "Response message from the server.  If available, a
            language identifier should be included in the message.";
        reference
            "BCP 18 (RFC 2277) IETF Policy on Character Sets
            and Languages, Section 4.2";
    }
}
}

rpc clear-client-prefixes {
    nacm:default-deny-all;
    if-feature "prefix-delegation";
    description
        "Clears all active prefix entries for a single client.";
    reference
        "RFC 8987: DHCPv6 Prefix Delegating Relay Requirements,
        Section 4.4";
    input {
        leaf client-duid {
            type dhcp6:duid;
            mandatory true;
            description
                "DUID of the client.";
        }
    }
    output {
        leaf return-message {
            type string;
            description
                "Response message from the server.  If available, a
                language identifier should be included in the message.";
            reference
                "BCP 18 (RFC 2277) IETF Policy on Character Sets
                and Languages, Section 4.2";
        }
    }
}

rpc clear-interface-prefixes {
    nacm:default-deny-all;
    if-feature "prefix-delegation";
    description
        "Clears all delegated prefix bindings from an
        interface on the relay.";
    reference
        "RFC 8987: DHCPv6 Prefix Delegating Relay Requirements,
        Section 4.4";
    input {
        leaf interface {
            type leafref {
                path "/dhcpv6-relay/relay-if/if-name";
            }
            mandatory true;
            description
                "Reference to the relay interface that will have all
                active prefix delegation bindings deleted.";
        }
    }
    output {

```



```

    leaf return-message {
        type string;
        description
            "Response message from the server.  If available, a
            language identifier should be included in the message.";
        reference
            "BCP 18 (RFC 2277) IETF Policy on Character Sets
            and Languages, Section 4.2";
    }
}
}

/*
 * Notifications
 */

notification relay-event {
    description
        "DHCPv6 relay event notifications.";
    container topology-change {
        description
            "Raised if the entry for an interface with DHCPv6-related
            configuration or state is removed from if:interface-refs.";
        leaf relay-if-name {
            type leafref {
                path "/dhcpv6-relay/relay-if/if-name";
            }
            description
                "Name of the interface that has been removed.";
        }
        leaf last-ipv6-addr {
            type inet:ipv6-address;
            description
                "Last IPv6 address configured on the interface.";
        }
    }
}
}
<CODE ENDS>

```

#### 4.4. DHCPv6 Client YANG Module

This module imports typedefs from [RFC6991] and the module defined in [RFC8343].

```

<CODE BEGINS> file "ietf-dhcpv6-client@2022-06-20.yang"
module ietf-dhcpv6-client {
    yang-version 1.1;
    namespace "urn:ietf:params:xml:ns:yang:ietf-dhcpv6-client";
    prefix dhc6-clnt;

    import ietf-inet-types {
        prefix inet;
        reference
            "RFC 6991: Common YANG Data Types";
    }
    import ietf-yang-types {
        prefix yang;
        reference
            "RFC 6991: Common YANG Data Types";
    }
    import ietf-dhcpv6-common {
        prefix dhc6;
        reference
            "RFC 9243: A YANG Data Model for DHCPv6 Configuration";
    }
    import ietf-interfaces {
        prefix if;
        reference
            "RFC 8343: A YANG Data Model for Interface Management";
    }
}

```

```

organization
  "IETF Dynamic Host Configuration (DHC) Working Group";
contact
  "WG Web:  <https://datatracker.ietf.org/wg/dhc/>
  WG List:  <mailto:dhcwg@ietf.org>
  Author:   Yong Cui <yong@csnet1.cs.tsinghua.edu.cn>
  Author:   Linhui Sun <lh.sunlinh@gmail.com>
  Editor:   Ian Farrer <ian.farrer@telekom.de>
  Author:   Sladjana Zeichlin <sladjana.zechlin@telekom.de>
  Author:   Zihao He <hezihao9512@gmail.com>
  Author:   Michal Nowikowski <godfryd@isc.org>";
description
  "This YANG module defines components necessary for the
  configuration and management of DHCPv6 clients.

  The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL',
  'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED',
  'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document
  are to be interpreted as described in BCP 14 (RFC 2119)
  (RFC 8174) when, and only when, they appear in all
  capitals, as shown here.

  Copyright (c) 2022 IETF Trust and the persons identified as
  authors of the code.  All rights reserved.

  Redistribution and use in source and binary forms, with or
  without modification, is permitted pursuant to, and subject to
  the license terms contained in, the Revised BSD License set
  forth in Section 4.c of the IETF Trust's Legal Provisions
  Relating to IETF Documents
  (https://trustee.ietf.org/license-info).

  This version of this YANG module is part of RFC 9243
  (https://www.rfc-editor.org/info/rfc9243); see the RFC itself
  for full legal notices."";

revision 2022-06-20 {
  description
    "Initial revision.";
  reference
    "RFC 9243: A YANG Data Model for DHCPv6 Configuration";
}

/*
 * Features
 */

feature non-temp-addr {
  description
    "Denotes that the client supports DHCPv6 non-temporary address
    allocations.";
  reference
    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Section 6.2";
}

feature temp-addr {
  description
    "Denotes that the client supports DHCPv6 temporary address
    allocations.";
  reference
    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Section 6.5";
}

feature prefix-delegation {
  description
    "Denotes that the client implements DHCPv6 prefix
    delegation.";
  reference

```

```

    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Section 6.3";
}

feature anon-profile {
    description
        "Denotes that the client supports DHCP anonymity profiles.";
    reference
        "RFC 7844: Anonymity Profiles for DHCP Clients";
}

/*
 * Groupings
 */

grouping message-statistics {
    description
        "Counters for DHCPv6 messages.";
    leaf discontinuity-time {
        type yang:date-and-time;
        description
            "The time on the most recent occasion at which any one or
            more of DHCPv6 client's counters suffered a discontinuity.
            If no such discontinuities have occurred since the last
            re-initialization of the local management subsystem, then
            this node contains the time the local management subsystem
            re-initialized itself.";
    }
    leaf solicit-count {
        type yang:counter32;
        config false;
        description
            "Number of Solicit (1) messages sent.";
    }
    leaf advertise-count {
        type yang:counter32;
        config false;
        description
            "Number of Advertise (2) messages received.";
    }
    leaf request-count {
        type yang:counter32;
        config false;
        description
            "Number of Request (3) messages sent.";
    }
    leaf confirm-count {
        type yang:counter32;
        config false;
        description
            "Number of Confirm (4) messages sent.";
    }
    leaf renew-count {
        type yang:counter32;
        config false;
        description
            "Number of Renew (5) messages sent.";
    }
    leaf rebind-count {
        type yang:counter32;
        config false;
        description
            "Number of Rebind (6) messages sent.";
    }
    leaf reply-count {
        type yang:counter32;
        config false;
        description
            "Number of Reply (7) messages received.";
    }
    leaf release-count {

```

```

    type yang:counter32;
    config false;
    description
        "Number of Release (8) messages sent.";
}
leaf decline-count {
    type yang:counter32;
    config false;
    description
        "Number of Decline (9) messages sent.";
}
leaf reconfigure-count {
    type yang:counter32;
    config false;
    description
        "Number of Reconfigure (10) messages received.";
}
leaf information-request-count {
    type yang:counter32;
    config false;
    description
        "Number of Information-request (11) messages sent.";
}
leaf discarded-message-count {
    type yang:counter32;
    config false;
    description
        "Number of messages that have been discarded for any
        reason.";
}
}

grouping lease-state {
    description
        "Information about the active IA_NA lease.";
    leaf preferred-lifetime {
        type dhcp6:timer-seconds32;
        description
            "The preferred lifetime for the leased address
            expressed in seconds.";
    }
    leaf valid-lifetime {
        type dhcp6:timer-seconds32;
        description
            "The valid lifetime for the leased address expressed
            in seconds.";
    }
    leaf allocation-time {
        type yang:date-and-time;
        description
            "Time and date that the address was first leased.";
    }
    leaf last-renew-rebind {
        type yang:date-and-time;
        description
            "Time of the last successful renew or rebind of the
            leased address.";
    }
    leaf server-duid {
        type dhcp6:duid;
        description
            "DUID of the leasing server.";
    }
    uses dhcp6:status;
}

grouping option-request-option-group {
    description
        "OPTION_ORO (6) Option Request Option. A client MUST include
        an Option Request option in a Solicit, Request, Renew,
        Rebind, or Information-request message to inform the server

```

```

    about options the client wants the server to send to the
    client.";
reference
    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Sections 21.23, 21.24, 21.25, & 21.7";
container option-request-option {
    description
        "OPTION_ORO (6) Option Request Option.";
    leaf-list oro-option {
        type uint16;
        description
            "List of options that the client is requesting,
            identified by option code. This list MUST include the
            code for option SOL_MAX_RT (82) when included in a
            Solicit message. If this option is being sent in an
            Information-request message, then the code for option
            OPTION_INFORMATION_REFRESH_TIME (32) and INF_MAX_RT (83)
            MUST be included.";
    }
}
}
}

grouping user-class-option-group {
    description
        "OPTION_USER_CLASS (15) User Class Option";
reference
    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Section 21.15";
container user-class-option {
    presence "Configures the option";
    description
        "OPTION_USER_CLASS (15) User Class Option.";
    list user-class-data-instance {
        key "user-class-data-id";
        min-elements 1;
        description
            "The user classes of which the client is a member.";
        leaf user-class-data-id {
            type uint8;
            description
                "User class data ID.";
        }
        leaf user-class-data {
            type binary;
            description
                "Opaque field representing a User Class of which the
                client is a member.";
        }
    }
}
}

grouping vendor-class-option-group {
    description
        "OPTION_VENDOR_CLASS (16) Vendor Class Option.";
reference
    "RFC 8415: Dynamic Host Configuration Protocol
    for IPv6 (DHCPv6), Section 21.16";
container vendor-class-option {
    description
        "OPTION_VENDOR_CLASS (16) Vendor Class Option.";
    list vendor-class-option-instances {
        key "enterprise-number";
        description
            "The vendor class option allows for multiple instances
            in a single message. Each list entry defines the contents
            of an instance of the option.";
        leaf enterprise-number {
            type uint32;
            description
                "The vendor's registered Enterprise Number, as

```



```

reference
  "RFC 7844: Anonymity Profiles for DHCP Clients,
  Section 3";
}
container client-configured-options {
  description
    "Definitions for DHCPv6 options that can be sent by
    the client. Additional option definitions can be
    augmented to this location from other YANG modules as
    required.";
  uses option-request-option-group;
  uses dhc6:rapid-commit-option-group;
  uses user-class-option-group;
  uses vendor-class-option-group;
  uses dhc6:vendor-specific-information-option-group;
  uses dhc6:reconfigure-accept-option-group;
}
list ia-na {
  if-feature "non-temp-addr";
  key "ia-id";
  description
    "Configuration relevant for an Identity Association
    for Non-temporary Addresses (IA_NA).";
  reference
    "RFC 8415: Dynamic Host Configuration Protocol
    for IPv6 (DHCPv6), Section 13.1";
  leaf ia-id {
    type uint32;
    description
      "A unique identifier for this IA_NA.";
    reference
      "RFC 8415: Dynamic Host Configuration Protocol
      for IPv6 (DHCPv6), Section 12";
  }
  container ia-na-options {
    description
      "An augmentation point for additional options
      that the client may send in the IA_NA-options field
      of OPTION_IA_NA.";
  }
  container lease-state {
    config false;
    description
      "Information about the active IA_NA lease.";
    leaf ia-na-address {
      type inet:ipv6-address;
      description
        "Address that is currently leased.";
    }
    leaf lease-t1 {
      type dhc6:timer-seconds32;
      description
        "The time interval after which the client should
        contact the server from which the addresses in the
        IA_NA were obtained to extend the lifetimes of the
        addresses assigned to the IA_NA.";
    }
    leaf lease-t2 {
      type dhc6:timer-seconds32;
      description
        "The time interval after which the client should
        contact any available server to extend the lifetimes
        of the addresses assigned to the IA_NA.";
    }
  }
  uses lease-state;
}
}
list ia-ta {
  if-feature "temp-addr";
  key "ia-id";
  description

```

```

    "Configuration relevant for an Identity Association
    for Temporary Addresses (IA_TA).";
reference
    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Section 13.2";
leaf ia-id {
    type uint32;
    description
        "The unique identifier for this IA_TA.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol
        for IPv6 (DHCPv6), Section 12";
}
container ia-ta-options {
    description
        "An augmentation point for additional options
        that the client may send in the IA_TA-options field
        of OPTION_IA_TA.";
}
container lease-state {
    config false;
    description
        "Information about an active IA_TA lease.";
    leaf ia-ta-address {
        type inet:ipv6-address;
        description
            "Address that is currently leased.";
    }
    uses lease-state;
}
}
list ia-pd {
    if-feature "prefix-delegation";
    key "ia-id";
    description
        "Configuration relevant for an Identity Association
        for Prefix Delegation (IA_PD).";
reference
    "RFC 8415: Dynamic Host Configuration Protocol for
    IPv6 (DHCPv6), Section 13.3";
leaf ia-id {
    type uint32;
    description
        "The unique identifier for this IA_PD.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol
        for IPv6 (DHCPv6), Section 12";
}
leaf prefix-length-hint {
    type uint8 {
        range "1..128";
    }
    description
        "Prefix-length hint value included in the messages sent
        to the server to indicate a preference for the size of
        the prefix to be delegated.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol
        for IPv6 (DHCPv6), Section 18.2.1";
}
container ia-pd-options {
    description
        "An augmentation point for additional options that the
        client will send in the IA_PD-options field of
        OPTION_IA_TA.";
}
container lease-state {
    config false;
    description
        "Information about an active IA_PD-delegated prefix.";
    leaf ia-pd-prefix {

```



```

    type inet:ipv6-prefix;
    description
        "Delegated prefix that is currently leased.";
}
leaf lease-t1 {
    type dhc6:timer-seconds32;
    description
        "The time interval after which the client should
        contact the server from which the addresses in the
        IA_NA were obtained to extend the lifetimes of the
        addresses assigned to the IA_PD.";
}
leaf lease-t2 {
    type dhc6:timer-seconds32;
    description
        "The time interval after which the client should
        contact any available server to extend the lifetimes
        of the addresses assigned to the IA_PD.";
}
uses lease-state;
}
}
container statistics {
    description
        "DHCPv6 message counters for the client.";
    uses message-statistics;
}
}
}
/*
 * Notifications
 */

notification invalid-ia-address-detected {
    if-feature "non-temp-addr or temp-addr";
    description
        "Notification sent when an address received in an identity
        association option is determined invalid. Possible conditions
        include a duplicate or otherwise illegal address.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 18.2.10.1";
    leaf ia-id {
        type uint32;
        mandatory true;
        description
            "IAID.";
    }
    leaf ia-na-t1-timer {
        type uint32;
        description
            "The value of the T1 time field for non-temporary address
            allocations (OPTION_IA_NA).";
    }
    leaf ia-na-t2-timer {
        type uint32;
        description
            "The value of the preferred-lifetime field for non-temporary
            address allocations (OPTION_IA_NA).";
    }
    leaf invalid-address {
        type inet:ipv6-address;
        description
            "The IP address that has been detected to be invalid.";
    }
    leaf preferred-lifetime {
        type uint32;
        description
            "The value of the preferred-lifetime field in
            OPTION_IAADDR.";
    }
}

```

```

}
leaf valid-lifetime {
    type uint32;
    description
        "The value of the valid-lifetime field in OPTION_IAADDR.";
}
leaf ia-options {
    type binary;
    description
        "A copy of the contents of the IAaddr-options field.";
}
leaf description {
    type string;
    description
        "Description of the invalid Identity Association (IA)
        detection error.";
}
}

notification transmission-failed {
    description
        "Notification sent when the transmission or retransmission
        of a message fails.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 7.6";
    leaf failure-type {
        type enumeration {
            enum solicit-timeout {
                description
                    "Max Solicit timeout value (SOL_MAX_RT) exceeded.";
            }
            enum request-timeout {
                description
                    "Max Request timeout value (REQ_MAX_RT) exceeded.";
            }
            enum request-retries-exceeded {
                description
                    "Max Request retry attempts (REC_MAX_RC) exceeded.";
            }
            enum confirm-duration-exceeded {
                description
                    "Max Confirm duration (CNF_MAX_RD) exceeded.";
            }
            enum renew-timeout {
                description
                    "Max Renew timeout value (REN_MAX_RT) exceeded.";
            }
            enum rebind-timeout {
                description
                    "Max Rebind timeout value (REB_MAX_RT)
                    exceeded.";
            }
            enum info-request-timeout {
                description
                    "Max Information-request timeout value (INF_MAX_RT)
                    exceeded.";
            }
            enum release-retries-exceeded {
                description
                    "Max Release retry attempts (REL_MAX_RC) exceeded.";
            }
            enum decline-retries-exceeded {
                description
                    "Max Decline retry attempts (DEC_MAX_RT) exceeded.";
            }
        }
    }
    mandatory true;
    description
        "Description of the failure.";
}

```

```

leaf description {
    type string;
    description
        "Information related to the failure, such as number of
        retries and timer values.";
}
}

notification unsuccessful-status-code {
    description
        "Notification sent when the client receives a message that
        includes an unsuccessful Status Code option.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 21.13";
    leaf server-duid {
        type dhcp6:duid;
        mandatory true;
        description
            "DUID of the server sending the unsuccessful error code.";
    }
    uses dhcp6:status;
}

notification server-duid-changed {
    if-feature "non-temp-addr or prefix-delegation or "
        + "temp-addr";
    description
        "Notification sent when the client receives a lease from a
        server with different DUID to the one currently stored by the
        client, e.g., in response to a Rebind message.";
    reference
        "RFC 8415: Dynamic Host Configuration Protocol for
        IPv6 (DHCPv6), Section 18.2.5";
    leaf new-server-duid {
        type dhcp6:duid;
        mandatory true;
        description
            "DUID of the new server.";
    }
    leaf previous-server-duid {
        type dhcp6:duid;
        mandatory true;
        description
            "DUID of the previous server.";
    }
    leaf lease-ia-na {
        if-feature "non-temp-addr";
        type leafref {
            path "/dhcpv6-client/client-if/ia-na/ia-id";
        }
        description
            "Reference to the IA_NA lease.";
    }
    leaf lease-ia-ta {
        if-feature "temp-addr";
        type leafref {
            path "/dhcpv6-client/client-if/ia-ta/ia-id";
        }
        description
            "Reference to the IA_TA lease.";
    }
    leaf lease-ia-pd {
        if-feature "prefix-delegation";
        type leafref {
            path "/dhcpv6-client/client-if/ia-pd/ia-id";
        }
        description
            "Reference to the IA_PD lease.";
    }
}
}

```

```
}  
<CODE ENDS>
```

## 5. Security Considerations

The YANG modules specified in this document define schemas for data that is designed to be accessed via network management protocols such as NETCONF [RFC6241] or RESTCONF [RFC8040]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [RFC6242]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [RFC8446].

The Network Configuration Access Control Model (NACM) [RFC8341] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in these YANG modules that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes in the 'ietf-dhcpv6-server.yang' module and their sensitivity/vulnerability:

- \* Denial-of-Service (DoS) attacks, such as disabling the DHCP server service or removing address/prefix pool configuration:

```
(dhcp6-srv/vendor-config)  
(dhcp6-srv/allocation-ranges)
```

- \* Various attacks based on reconfiguring the contents of DHCPv6 options, leading to several types of security or privacy threats. These options could redirect clients to services under an attacker's control, for example, by changing the address of a DNS server supplied in a DHCP option to point to a rogue server.

```
(dhcp6-srv/option-sets)
```

These are the subtrees and data nodes in the 'ietf-dhcpv6-relay.yang' module and their sensitivity/vulnerability:

- \* DoS attacks, based on disabling the DHCP relay function or modifying the relay's "destination-address" to a non-existent address.

```
(dhcp6-rly/relay-if)
```

- \* Modifying the relay's "destination-address" to send messages to a rogue DHCPv6 server.

```
(dhcp6-rly/relay-if)
```

Some of the RPC operations in these YANG modules may be considered sensitive or vulnerable in some network environments. It is thus important to control access to these operations. These RPCs use 'nacm:default-deny-all'.

These are the operations in the 'ietf-dhcpv6-relay.yang' module and their sensitivity/vulnerability:

- \* Deleting/clearing active address and prefix leases causing a DoS attack, as traffic will no longer be routed to the client.

```
(dhcp6-rly/clear-prefix-entry)  
(dhcp6-rly/clear-client-prefixes)  
(dhcp6-rly/clear-interface-prefixes)
```

An attacker sending DHCPv6 messages that cause the server to generate

'invalid-client-detected' and 'decline-received' notifications could result in a DoS attack. Such an attack could be mitigated by the NETCONF client unsubscribing from the affected notifications.

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

The following subtrees and data nodes can be misused to track the activity or fingerprint the device type of the host:

\* Information the server holds about clients with active leases:

(dhc6-srv/allocation-ranges/allocation-range/address-pools/  
address-pool/active-leases)

\* Information the relay holds about clients with active leases:

(dhc6-rly/relay-if/prefix-delegation/)

Information about a server's configured address and prefix pools may be used by an attacker for network reconnaissance [RFC7707]. The following subtrees and data nodes could be used for this purpose:

\* Information about client address allocation ranges:

(dhc6-srv/allocation-ranges/allocation-range/address-pools/  
address-pool/pool-prefix)

\* Information about client prefix allocation ranges:

(dhc6-srv/allocation-ranges/allocation-range/prefix-pools/  
prefix-pool/pool-prefix)

[RFC7844] describes anonymity profiles for DHCP clients. These can be used to prevent client tracking on a visited network. Support for this can be enabled by implementing the 'anon-profile' feature in the client module.

[RFC7824] covers privacy considerations for DHCPv6 and is applicable here.

Security considerations related to DHCPv6 are discussed in [RFC8415].

Security considerations given in [RFC7950] are also applicable here.

## 6. IANA Considerations

This document registers four URIs and four YANG modules.

### 6.1. URI Registration

Per this document, IANA has registered the following four URIs in the "ns" subregistry within the "IETF XML Registry" [RFC3688]:

URI: urn:ietf:params:xml:ns:yang:ietf-dhcpv6-server  
Registrant Contact: The IESG.  
XML: N/A; the requested URI is an XML namespace.

URI: urn:ietf:params:xml:ns:yang:ietf-dhcpv6-relay  
Registrant Contact: The IESG.  
XML: N/A; the requested URI is an XML namespace.

URI: urn:ietf:params:xml:ns:yang:ietf-dhcpv6-client  
Registrant Contact: The IESG.  
XML: N/A; the requested URI is an XML namespace.

URI: urn:ietf:params:xml:ns:yang:ietf-dhcpv6-common  
Registrant Contact: The IESG.

XML: N/A; the requested URI is an XML namespace.

## 6.2. YANG Module Name Registration

Per this document, IANA has registered the following four YANG modules in the "YANG Module Names" subregistry [RFC6020] within the "YANG Parameters" registry.

name: ietf-dhcpv6-server  
namespace: urn:ietf:params:xml:ns:yang:ietf-dhcpv6-server  
maintained by IANA: N  
prefix: dhcp6-srv  
reference: RFC 9243

name: ietf-dhcpv6-relay  
namespace: urn:ietf:params:xml:ns:yang:ietf-dhcpv6-relay  
maintained by IANA: N  
prefix: dhcp6-rly  
reference: RFC 9243

name: ietf-dhcpv6-client  
namespace: urn:ietf:params:xml:ns:yang:ietf-dhcpv6-client  
maintained by IANA: N  
prefix: dhcp6-clnt  
reference: RFC 9243

name: ietf-dhcpv6-common  
namespace: urn:ietf:params:xml:ns:yang:ietf-dhcpv6-common  
maintained by IANA: N  
prefix: dhcp6  
reference: RFC 9243

## 7. References

### 7.1. Normative References

- [BCP18] Alvestrand, H., "IETF Policy on Character Sets and Languages", BCP 18, RFC 2277, January 1998.  
<<https://www.rfc-editor.org/info/bcp18>>
- [IANA-DHCPV6-AUTH-NAMESPACES]  
IANA, "Dynamic Host Configuration Protocol (DHCP) Authentication Option Name Spaces",  
<<https://www.iana.org/assignments/auth-namespaces>>.
- [IANA-DHCPV6-OPTION-CODES]  
IANA, "Option Codes",  
<<https://www.iana.org/assignments/dhcpv6-parameters>>.
- [IANA-DHCPV6-STATUS-CODES]  
IANA, "DHCPv6 Status Codes",  
<<https://www.iana.org/assignments/dhcpv6-parameters>>.
- [IANA-HARDWARE-TYPES]  
IANA, "Hardware Types",  
<<https://www.iana.org/assignments/arp-parameters>>.
- [IANA-PEN] IANA, "Private Enterprise Numbers",  
<<https://www.iana.org/assignments/enterprise-numbers>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997,  
<<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3118] Droms, R., Ed. and W. Arbaugh, Ed., "Authentication for DHCP Messages", RFC 3118, DOI 10.17487/RFC3118, June 2001,  
<<https://www.rfc-editor.org/info/rfc3118>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688,

DOI 10.17487/RFC3688, January 2004,  
<<https://www.rfc-editor.org/info/rfc3688>>.

- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", RFC 6242, DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC6355] Narten, T. and J. Johnson, "Definition of the UUID-Based DHCPv6 Unique Identifier (DUID-UUID)", RFC 6355, DOI 10.17487/RFC6355, August 2011, <<https://www.rfc-editor.org/info/rfc6355>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", RFC 6991, DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC7844] Huitema, C., Mrugalski, T., and S. Krishnan, "Anonymity Profiles for DHCP Clients", RFC 7844, DOI 10.17487/RFC7844, May 2016, <<https://www.rfc-editor.org/info/rfc7844>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, RFC 8341, DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", RFC 8342, DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [RFC8343] Bjorklund, M., "A YANG Data Model for Interface Management", RFC 8343, DOI 10.17487/RFC8343, March 2018, <<https://www.rfc-editor.org/info/rfc8343>>.
- [RFC8415] Mrugalski, T., Siodelski, M., Volz, B., Yourtchenko, A., Richardson, M., Jiang, S., Lemon, T., and T. Winters, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)", RFC 8415, DOI 10.17487/RFC8415, November 2018, <<https://www.rfc-editor.org/info/rfc8415>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

[RFC8987] Farrer, I., Kottapalli, N., Hunek, M., and R. Patterson, "DHCPv6 Prefix Delegating Relay Requirements", RFC 8987, DOI 10.17487/RFC8987, February 2021, <<https://www.rfc-editor.org/info/rfc8987>>.

## 7.2. Informative References

### [GROUPINGS-TLS]

Watsen, K., "YANG Groupings for TLS Clients and TLS Servers", Work in Progress, Internet-Draft, draft-ietf-netconf-tls-client-server-28, 24 May 2022, <<https://datatracker.ietf.org/doc/html/draft-ietf-netconf-tls-client-server-28>>.

[RFC3319] Schulzrinne, H. and B. Volz, "Dynamic Host Configuration Protocol (DHCPv6) Options for Session Initiation Protocol (SIP) Servers", RFC 3319, DOI 10.17487/RFC3319, July 2003, <<https://www.rfc-editor.org/info/rfc3319>>.

[RFC7707] Gont, F. and T. Chown, "Network Reconnaissance in IPv6 Networks", RFC 7707, DOI 10.17487/RFC7707, March 2016, <<https://www.rfc-editor.org/info/rfc7707>>.

[RFC7824] Krishnan, S., Mrugalski, T., and S. Jiang, "Privacy Considerations for DHCPv6", RFC 7824, DOI 10.17487/RFC7824, May 2016, <<https://www.rfc-editor.org/info/rfc7824>>.

## Appendix A. Data Tree Examples

This section contains XML examples of data trees for the different DHCPv6 elements.

### A.1. DHCPv6 Server Configuration Examples

The following example shows a basic configuration for a server. The configuration defines:

- \* enabling the DHCP server function,
- \* the server's DUID,
- \* an option set (id=1) with configuration for the Solicit Max Retry Timeout (SOL\_MAX\_RT (82)) option,
- \* a single network range (2001:db8::/32), and
- \* a single address pool, with start and end addresses, relevant lease timers, and an 'option-set-id' of "1" referencing the option set configured above.

```
<dhcpv6-server
  xmlns="urn:ietf:params:xml:ns:yang:ietf-dhcpv6-server">
  <enabled>true</enabled>
  <server-duid>000200090CC084D303000912</server-duid>
  <vendor-config/>
  <option-sets>
    <option-set>
      <option-set-id>1</option-set-id>
      <description>Example DHCP option set</description>
      <sol-max-rt-option>
        <sol-max-rt-value>3600</sol-max-rt-value>
      </sol-max-rt-option>
    </option-set>
  </option-sets>
  <class-selector/>
  <allocation-ranges>
    <valid-lifetime>54000</valid-lifetime>
    <renew-time>7200</renew-time>
    <rebind-time>32400</rebind-time>
    <preferred-lifetime>43200</preferred-lifetime>
```



```

<allocation-range>
  <id>1</id>
  <description>example-allocation-range</description>
  <network-prefix>2001:db8::/32</network-prefix>
  <option-set-id>1</option-set-id>
  <address-pools>
    <address-pool>
      <pool-id>1</pool-id>
      <pool-prefix>2001:db8:1:1::/64</pool-prefix>
      <start-address>2001:db8:1:1::1000</start-address>
      <end-address>2001:db8:1:1::2000</end-address>
      <max-address-utilization>50</max-address-utilization>
      <option-set-id>1</option-set-id>
    </address-pool>
  </address-pools>
</allocation-range>
</allocation-ranges>
</dhcpv6-server>

```

Figure 4: Basic Server Configuration Example XML

The following example configuration snippet shows a static host reservation within an address pool. The host's lease timers are configured to be longer than hosts from the pool with dynamically assigned addresses.

```

<address-pools>
  <address-pool>
    <pool-id>1</pool-id>
    <pool-prefix>2001:db8:1:1::/64</pool-prefix>
    <start-address>2001:db8:1:1::1000</start-address>
    <end-address>2001:db8:1:1::2000</end-address>
    <max-address-utilization>50</max-address-utilization>
    <option-set-id>1</option-set-id>
    <host-reservations>
      <host-reservation>
        <reserved-addr>2001:db8:1:1::1001</reserved-addr>
        <client-duid>00052001db81</client-duid>
        <option-set-id>1</option-set-id>
        <valid-lifetime>604800</valid-lifetime>
        <renew-time>86400</renew-time>
        <rebind-time>172800</rebind-time>
        <preferred-lifetime>345600</preferred-lifetime>
      </host-reservation>
    </host-reservations>
  </address-pool>
</address-pools>

```

Figure 5: Server Host Reservation Configuration Example XML Snippet

The following example configuration snippet shows a network range and pool to be used for delegating prefixes to clients. In this example, each client will receive a /56 prefix.

The 'max-pd-space-utilization' is set to 80 percent so that a 'prefix-pool-utilization-threshold-exceeded' notification will be raised if the number of prefix allocations exceeds this.

```

<allocation-ranges>
  <allocation-range>
    <id>1</id>
    <description>prefix-pool-example</description>
    <network-prefix>2001:db8::/32</network-prefix>
    <prefix-pools>
      <valid-lifetime>54000</valid-lifetime>
      <renew-time>7200</renew-time>
      <rebind-time>32400</rebind-time>
      <preferred-lifetime>43200</preferred-lifetime>
    <prefix-pool>
      <pool-id>0</pool-id>
      <option-set-id>1</option-set-id>
    </prefix-pool>
  </prefix-pools>
</allocation-range>
</allocation-ranges>

```

```

    <pool-prefix>2001:db8:1::/48</pool-prefix>
    <client-prefix-length>56</client-prefix-length>
    <max-pd-space-utilization>80</max-pd-space-utilization>
  </prefix-pool>
</prefix-pools>
</allocation-range>
</allocation-ranges>

```

Figure 6: Server Prefix Delegation Configuration Example XML Snippet

The next example configuration snippet shows a set of options that may be returned to clients, depending on the contents of a received DHCP request message. The option set ID is '1', which will be referenced by other places in the configuration (e.g., address pool configuration) as the available options for clients that request them.

The example shows how the option definitions can be extended via augmentation. In this case, "OPTION\_SIP\_SERVER\_D (21) SIP Servers Domain-Name List" from the example module in Appendix B has been augmented to the server's option set.

```

<option-sets>
  <option-set>
    <option-set-id>1</option-set-id>
    <description>Example DHCP option set</description>
    <vendor-specific-information-options>
      <vendor-specific-information-option>
        <enterprise-number>32473</enterprise-number>
        <vendor-option-data>
          <sub-option-code>01</sub-option-code>
          <sub-option-data>1234abcd</sub-option-data>
        </vendor-option-data>
        <vendor-option-data>
          <sub-option-code>02</sub-option-code>
          <sub-option-data>abcd1234</sub-option-data>
        </vendor-option-data>
      </vendor-specific-information-option>
    </vendor-specific-information-options>
    <sol-max-rt-option>
      <sol-max-rt-value>3600</sol-max-rt-value>
    </sol-max-rt-option>
    <sip-server-domain-name-list-option
      xmlns="https://example.com/ns/example-dhcpv6-opt-sip-serv">
      <sip-server>
        <sip-serv-id>0</sip-serv-id>
        <sip-serv-domain-name>sip1.example.org</sip-serv-domain-name>
      </sip-server>
      <sip-server>
        <sip-serv-id>1</sip-serv-id>
        <sip-serv-domain-name>sip2.example.org</sip-serv-domain-name>
      </sip-server>
    </sip-server-domain-name-list-option>
  </option-set>
</option-sets>

```

Figure 7: Server Option Set Configuration Example XML Snippet

## A.2. DHCPv6 Relay Configuration Example

The following example shows a basic configuration for a single DHCP relay interface and its interaction with the `ietf-interfaces` module. The configuration shows two XML documents, one for `ietf-interfaces` and a second for `ietf-dhcpv6-relay`, defining:

- \* configuring an interface using the `ietf-interfaces` module that the relay configuration will be applied to,
- \* enabling the DHCP relay function globally and for the relevant interface,

- \* referencing the interface that the relay configuration is relevant for via an interface-ref to the ietf-interfaces module,
- \* defining two destination addresses that incoming DHCP messages will be relayed to,
- \* configuring the link-address value that will be sent in the relay-forward message, and
- \* configuring a value for the Interface ID Option (OPTION\_INTERFACE\_ID (18)), which will be included in the relay forward message.

```

<interfaces xmlns="urn:ietf:params:xml:ns:yang:ietf-interfaces"
  xmlns:ianaift="urn:ietf:params:xml:ns:yang:iana-if-type">
  <interface>
    <name>eth0</name>
    <type>ianaift:ethernetCsmacd</type>
    <description>DHCPv6 Relay Interface</description>
    <enabled>true</enabled>
  </interface>
</interfaces>

<dhcpv6-relay xmlns="urn:ietf:params:xml:ns:yang:ietf-dhcpv6-relay">
  <enabled>true</enabled>
  <relay-if>
    <if-name>eth0</if-name>
    <enabled>true</enabled>
    <destination-address>2001:db8:2::1</destination-address>
    <destination-address>2001:db8:2::2</destination-address>
    <link-address>2001:db8:3::1</link-address>
    <relay-options>
      <interface-id-option>
        <interface-id>EXAMPLEINTERFACEID01</interface-id>
      </interface-id-option>
    </relay-options>
  </relay-if>
</dhcpv6-relay>

```

Figure 8: Basic Relay Configuration Example XML

### A.3. DHCPv6 Client Configuration Example

The following example shows a basic configuration for a DHCP client and its interaction with the ietf-interfaces module. The configuration shows two XML documents, one for ietf-interfaces and a second for ietf-dhcpv6-client, defining:

- \* configuring an interface using the ietf-interfaces module that the client configuration will be applied to,
- \* enabling the DHCP client function globally and for the relevant interface,
- \* referencing the interface that the client configuration is relevant for via an interface-ref to the ietf-interfaces module,
- \* setting the DUID for the DHCPv6-enabled interface,
- \* configuring a list of option codes that will be requested by the client in its Option Request Option (OPTION\_ORO (6)),
- \* configuring a single instance of the Vendor-specific Information Option (OPTION\_VENDOR\_OPTS (17)) with a single sub-option data item,
- \* requesting a non-temporary IPv6 address (IA\_NA) with an identity association interface identifier of 1, and
- \* requesting an IPv6 delegated prefix address (IA\_PD) with an identity association interface identifier of 2.

```

<interfaces xmlns="urn:ietf:params:xml:ns:yang:ietf-interfaces"
  xmlns:ianaift="urn:ietf:params:xml:ns:yang:iana-if-type">
  <interface>
    <name>eth0</name>
    <type>ianaift:ethernetCsmacd</type>
    <description>DHCPv6 Relay Interface</description>
    <enabled>true</enabled>
  </interface>
</interfaces>

<dhcpv6-client
  xmlns="urn:ietf:params:xml:ns:yang:ietf-dhcpv6-client">
  <enabled>true</enabled>
  <client-if>
    <if-name>eth0</if-name>
    <enabled>true</enabled>
    <interface-duid>000200090CC084D303000913</interface-duid>
    <client-configured-options>
      <option-request-option>
        <oro-option>17</oro-option>
        <oro-option>23</oro-option>
        <oro-option>24</oro-option>
        <oro-option>82</oro-option>
      </option-request-option>
      <vendor-specific-information-options>
        <vendor-specific-information-option>
          <enterprise-number>32473</enterprise-number>
          <vendor-option-data>
            <sub-option-code>1</sub-option-code>
            <sub-option-data>abcd1234</sub-option-data>
          </vendor-option-data>
        </vendor-specific-information-option>
      </vendor-specific-information-options>
    </client-configured-options>
    <ia-na>
      <ia-id>1</ia-id>
    </ia-na>
    <ia-pd>
      <ia-id>2</ia-id>
    </ia-pd>
  </client-if>
</dhcpv6-client>

```

Figure 9: Basic Client Configuration Example XML

## Appendix B. Example of Augmenting Additional DHCPv6 Option Definitions

The following section provides an example of how the DHCPv6 option definitions can be extended to include additional options. It is expected that additional specification documents will be published for this in the future.

The example defines YANG modules for OPTION\_SIP\_SERVER\_D (21) and OPTION\_SIP\_SERVER\_D (22) as specified in [RFC3319]. An example XML configuration, showing the interworking with other modules, is provided in Figure 7.

The module is constructed as follows:

- \* The module is named using a meaningful, shortened version of the document name in which the DHCP option format is specified.
- \* A separate grouping is used to define each option.
- \* The name of the option is taken from the registered IANA name for the option, with an '-option' suffix added.
- \* The description field is taken from the relevant option code name and number.

- \* The reference section is the number and name of the RFC in which the DHCPv6 option is defined.
- \* The remaining fields match the fields in the DHCP option. They are in the same order as defined in the DHCP option. Wherever possible, the format that is defined for the DHCP field should be matched by the relevant YANG type.
- \* Fields that can have multiple entries or instances are defined using list or leaf-list nodes.

Below the groupings for option definitions, augment statements are used to add the option definitions for use in the relevant DHCP element's module (server, relay, and/or client).

<CODE BEGINS>

```

module example-dhcpv6-opt-sip-serv {
  yang-version 1.1;
  namespace "https://example.com/ns/"
    + "example-dhcpv6-opt-sip-serv";
  prefix sip-srv;

  import ietf-inet-types {
    prefix inet;
  }
  import ietf-dhcpv6-server {
    prefix dhc6-srv;
  }

  organization
    "IETF Dynamic Host Configuration (DHC) Working Group";
  contact
    "WG Web: <https://datatracker.ietf.org/wg/dhc/>
    WG List: <mailto:dhcwg@ietf.org>
    Author: Yong Cui <yong@csnet1.cs.tsinghua.edu.cn>
    Author: Linhui Sun <lh.sunlinh@gmail.com>
    Editor: Ian Farrer <ian.farrer@telekom.de>
    Author: Sladjana Zeichlin <sladjana.zechlin@telekom.de>
    Author: Zihao He <hezihao9512@gmail.com>
    Author: Michal Nowikowski <godfryd@isc.org>";
  description
    "This YANG module contains DHCPv6 options defined in RFC 8415
    that can be used by DHCPv6 servers.

    Copyright (c) 2022 IETF Trust and the persons identified as
    authors of the code. All rights reserved.

    Redistribution and use in source and binary forms, with or
    without modification, is permitted pursuant to, and subject to
    the license terms contained in, the Revised BSD License set
    forth in Section 4.c of the IETF Trust's Legal Provisions
    Relating to IETF Documents
    (https://trustee.ietf.org/license-info).

    This version of this YANG module is part of RFC 9243
    (https://www.rfc-editor.org/info/rfc9243); see the RFC itself
    for full legal notices.";

  revision 2022-06-20 {
    description
      "Initial revision.";
    reference
      "RFC 9243: A YANG Data Model for DHCPv6 Configuration";
  }

  /*
  * Groupings
  */

  grouping sip-server-domain-name-list-option-group {
    description

```

```

"OPTION_SIP_SERVER_D (21) SIP Servers Domain-Name List.";
reference
"RFC 3319: Dynamic Host Configuration Protocol
(DHCPv6) Options for Session Initiation Protocol (SIP)
Servers";
container sip-server-domain-name-list-option {
description
"OPTION_SIP_SERVER_D (21) SIP Servers Domain Name List
Option.";
list sip-server {
key "sip-serv-id";
description
"SIP server information.";
leaf sip-serv-id {
type uint8;
description
"SIP server list identifier.";
}
leaf sip-serv-domain-name {
type inet:domain-name;
description
"SIP server domain name.";
}
}
}
}

grouping sip-server-address-list-option-group {
description
"OPTION_SIP_SERVER_A (22) SIP Servers IPv6 Address List.";
reference
"RFC 3319: Dynamic Host Configuration Protocol
(DHCPv6) Options for Session Initiation Protocol (SIP)
Servers";
container sip-server-address-list-option {
description
"OPTION_SIP_SERVER_A (22) SIP Servers IPv6 Address List
Option.";
list sip-server {
key "sip-serv-id";
description
"SIP server information.";
leaf sip-serv-id {
type uint8;
description
"SIP server list entry identifier.";
}
leaf sip-serv-addr {
type inet:ipv6-address;
description
"SIP server IPv6 address.";
}
}
}
}

/*
* Augmentations
*/

augment "/dhc6-srv:dhcpv6-server/dhc6-srv:option-sets/"
+ "dhc6-srv:option-set" {
description
"Augment the option definition groupings to the server
module.";
uses sip-server-domain-name-list-option-group;
uses sip-server-address-list-option-group;
}
}
<CODE ENDS>

```

The correct location to augment the new option definition(s) will vary according to the specific rules defined for the use of that specific option. For example, for options that will be augmented into the `ietf-dhcpv6-server` module, in many cases, these will be augmented to:

```
'/dhc6-srv:dhc6-srv/dhc6-srv:option-sets/dhc6-srv:option-set'
```

so that they can be defined within option sets. However, there are some options that are only applicable for specific deployment scenarios, and in these cases, it may be more logical to augment the option group to a location relevant for the option.

One example for this could be `OPTION_PD_EXCLUDE` (67). This option is only relevant in combination with a delegated prefix that contains a specific prefix. In this case, the following location for the augmentation may be more suitable:

```
'/dhc6-srv:dhc6-srv/dhc6-srv:allocation-ranges/dhc6-srv:allocation-range/dhc6-srv:prefix-pools/dhc6-srv:prefix-pool'
```

## Appendix C. Example Vendor-Specific Server Configuration Module

This section shows how to extend the server YANG module defined in this document with vendor-specific configuration nodes, e.g., configuring access to a lease storage database.

The example module defines additional server attributes, such as name and description. Storage for leases is configured using a lease-storage container. It allows storing leases in one of three options: memory (`memfile`), MySQL, and PostgreSQL. For each case, the necessary configuration parameters are provided.

For simplicity, this example module assumes that the DHCPv6 server is colocated with the MySQL or PostgreSQL database server and can serve traffic securely on the localhost without additional cryptographic protection. In a production deployment, these functions would likely not be colocated and thus use TLS to secure the database connection between the DHCPv6 server and database server. A YANG module for configuring TLS is defined in `[GROUPINGS-TLS]`.

At the end, there is an `augment` statement that adds the vendor-specific configuration defined in `"dhcpv6-server-config:config"` under the `"/dhcpv6-server:config/dhcpv6-server:vendor-config"` mount point.

<CODE BEGINS>

```
module example-dhcpv6-server-conf {
  yang-version 1.1;
  namespace "https://example.com/ns/"
    + "example-dhcpv6-server-conf";
  prefix dhc6-srv-conf;

  import ietf-inet-types {
    prefix inet;
  }
  import ietf-interfaces {
    prefix if;
  }
  import ietf-dhcpv6-server {
    prefix dhc6-srv;
  }

  organization
    "IETF Dynamic Host Configuration (DHC) Working Group";
  contact
    "WG Web: <https://datatracker.ietf.org/wg/dhc/>
    WG List: <mailto:dhcwg@ietf.org>
    Author: Yong Cui <yong@csnet1.cs.tsinghua.edu.cn>
    Author: Linhui Sun <lh.sunlinh@gmail.com>
    Editor: Ian Farrer <ian.farrer@telekom.de>
    Author: Sladjana Zeichlin <sladjana.zechlin@telekom.de>
```

Author: Zihao He <hezihao9512@gmail.com>  
Author: Michal Nowikowski <godfryd@isc.org>;

description

"This YANG module defines components for the configuration and management of vendor-/implementation-specific DHCPv6 server functionality. As this functionality varies greatly between different implementations, the module is provided as an example only.

Copyright (c) 2022 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Revised BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC 9243 (<https://www.rfc-editor.org/info/rfc9243>); see the RFC itself for full legal notices.";

revision 2022-06-20 {

description

"Initial revision.";

reference

"RFC 9243: A YANG Data Model for DHCPv6 Configuration";

}

/\*

\* Groupings

\*/

grouping config {

description

"Parameters necessary for the configuration of a DHCPv6 server.";

container serv-attributes {

description

"Contains basic attributes necessary for running a DHCPv6 server.";

leaf name {

type string;

description

"Name of the DHCPv6 server.";

}

leaf description {

type string;

description

"Description of the DHCPv6 server.";

}

leaf ipv6-listen-port {

type uint16;

default "547";

description

"UDP port that the server will listen on.";

}

choice listening-interfaces {

default "all-interfaces";

description

"Configures which interface or addresses the server will listen for incoming messages on.";

case all-interfaces {

container all-interfaces {

presence "true";

description

"Configures the server to listen for incoming messages on all IPv6 addresses (unicast and multicast) on all of its network interfaces.";

}

}



```

}
case interface-list {
  leaf-list interfaces {
    type if:interface-ref;
    description
      "List of interfaces on which the server will listen
      for incoming messages. Messages addressed to any
      valid IPv6 address (unicast and multicast) will be
      received.";
  }
}
case address-list {
  leaf-list address-list {
    type inet:ipv6-address;
    description
      "List of IPv6 address(es) on which the server will
      listen for incoming DHCPv6 messages.";
  }
}
}
leaf-list interfaces-config {
  type if:interface-ref;
  default "if:interfaces/if:interface/if:name";
  description
    "A leaf list of interfaces on which the server should
    listen.";
}
container lease-storage {
  description
    "Configures how the server will store leases.";
  choice storage-type {
    description
      "The type of storage that will be used for lease
      information.";
    case memfile {
      description
        "Configuration for storing leases information in a
        Comma-Separated Value (CSV) file.";
      leaf memfile-name {
        type string;
        description
          "Specifies the absolute location of the lease file.
          The format of the string follows the semantics of
          the relevant operating system.";
      }
      leaf memfile-lfc-interval {
        type uint64;
        description
          "Specifies the interval in seconds, at which the
          server will perform a lease file cleanup (LFC).";
      }
    }
  }
}
case mysql {
  leaf mysql-name {
    type string;
    description
      "Name of the MySQL database, running on the
      localhost.";
  }
  leaf mysql-username {
    type string;
    description
      "User name of the account under which the server
      will access the database.";
  }
  leaf mysql-password {
    type string;
    description
      "Password of the account under which the server
      will access the database.";
  }
}

```



```

description
  "Augment the server-specific YANG module to the
  ietf-dhcpv6-server module.";
uses config;
}
}
<CODE ENDS>

```

#### Appendix D. Example Definition of Class-Selector Configuration

The module "ietf-example-dhcpv6-class-selector" provides an example of how vendor-specific class selection configuration can be modeled and integrated with the "ietf-dhcpv6-server" module defined in this document.

The example module defines "client-class-names" with associated matching rules. A client can be classified based on the "client-id", "interface-id" (ingress interface of the client's messages), packet's source or destination address, relay link address, relay link interface-id, and more. Actually, there are endless methods for classifying clients. So this standard does not try to provide full specification for class selection; it only shows an example of how it could be defined.

At the end of the example, augment statements are used to add the defined class selector rules into the overall DHCPv6 addressing hierarchy. This is done in two main parts:

- \* the augmented class-selector configuration in the main DHCPv6 Server configuration
- \* client-class leafrefs augmented to "allocation-range", "address-pool", and "pd-pool", pointing to the "client-class-name" that is required

The mechanism is as follows: class is associated to a client based on rules, and then a client is allowed to get an address(es) or a prefix(es) from a given allocation-range/pool if the class name matches.

```

<CODE BEGINS>
module example-dhcpv6-class-select {
  yang-version 1.1;
  namespace "https://example.com/ns/"
    + "example-dhcpv6-class-select";
  prefix dhc6-class-sel;

  import ietf-inet-types {
    prefix inet;
  }
  import ietf-interfaces {
    prefix if;
  }
  import ietf-dhcpv6-common {
    prefix dhc6;
  }
  import ietf-dhcpv6-server {
    prefix dhc6-srv;
  }

  organization
    "IETF Dynamic Host Configuration (DHC) Working Group";
  contact
    "WG Web: <https://datatracker.ietf.org/wg/dhc/>
    WG List: <mailto:dhcwg@ietf.org>
    Author: Yong Cui <yong@csnet1.cs.tsinghua.edu.cn>
    Author: Linhui Sun <lh.sunlinh@gmail.com>
    Editor: Ian Farrer <ian.farrer@telekom.de>
    Author: Sladjana Zeichlin <sladjana.zechlin@telekom.de>
    Author: Zihao He <hezihao9512@gmail.com>
    Author: Michal Nowikowski <godfryd@isc.org>";

```

description

"This YANG module defines components for the definition and configuration of the client class selector function for a DHCPv6 server. As this functionality varies greatly between different implementations, the module provided as an example only.

Copyright (c) 2022 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Revised BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC 9243 (<https://www.rfc-editor.org/info/rfc9243>); see the RFC itself for full legal notices.";

revision 2022-06-20 {

description

"Initial revision.";

reference

"RFC 9243: A YANG Data Model for DHCPv6 Configuration";

}

/\*

\* Groupings

\*/

grouping client-class-id {

description

"Definitions of client message classification for authorization and assignment purposes.";

leaf client-class-name {

type string;

mandatory true;

description

"Unique identifier for client class identification list entries.";

}

choice id-type {

mandatory true;

description

"Definitions for different client identifier types.";

case client-id-id {

leaf client-id {

type string;

mandatory true;

description

"String literal client identifier.";

}

description

"Client class selection based on a string literal client identifier.";

}

case received-interface-id {

description

"Client class selection based on the incoming interface of the DHCPv6 message.";

leaf received-interface {

type if:interface-ref;

description

"Reference to the interface entry for the incoming DHCPv6 message.";

}

}

case packet-source-address-id {

description

```

    "Client class selection based on the source address of
    the DHCPv6 message.";
leaf packet-source-address {
    type inet:ipv6-address;
    mandatory true;
    description
        "Source address of the DHCPv6 message.";
}
}
case packet-destination-address-id {
    description
        "Client class selection based on the destination address
        of the DHCPv6 message.";
leaf packet-destination-address {
    type inet:ipv6-address;
    mandatory true;
    description
        "Destination address of the DHCPv6 message.";
}
}
case relay-link-address-id {
    description
        "Client class selection based on the prefix of the
        link-address field in the relay agent message header.";
leaf relay-link-address {
    type inet:ipv6-prefix;
    mandatory true;
    description
        "Prefix of the link-address field in the relay agent
        message header.";
}
}
case relay-peer-address-id {
    description
        "Client class selection based on the value of the
        peer-address field in the relay agent message header.";
leaf relay-peer-address {
    type inet:ipv6-prefix;
    mandatory true;
    description
        "Prefix of the peer-address field in the relay agent
        message header.";
}
}
case relay-interface-id {
    description
        "Client class selection based on a received instance of
        OPTION_INTERFACE_ID (18).";
leaf relay-interface {
    type string;
    description
        "An opaque value of arbitrary length generated by the
        relay agent to identify one of the relay agent's
        interfaces.";
}
}
case user-class-option-id {
    description
        "Client class selection based on the value of the
        OPTION_USER_CLASS (15) and its user-class-data field.";
leaf user-class-data {
    type string;
    mandatory true;
    description
        "User Class value to match.";
}
}
case vendor-class-present-id {
    description
        "Client class selection based on the presence of
        OPTION_VENDOR_CLASS (16) in the received message.";
}
}

```

```

    leaf vendor-class-present {
        type boolean;
        mandatory true;
        description
            "Presence of OPTION_VENDOR_CLASS (16) in the received
            message.";
    }
}
case vendor-class-option-enterprise-number-id {
    description
        "Client class selection based on the value of the
        enterprise-number field in OPTION_VENDOR_CLASS (16).";
    leaf vendor-class-option-enterprise-number {
        type uint32;
        mandatory true;
        description
            "Value of the enterprise-number field.";
    }
}
case vendor-class-option-data {
    description
        "Client class selection based on the value of a data
        field within a vendor-class-data entry for a matching
        enterprise-number field in OPTION_VENDOR_CLASS (16).";
    container vendor-class-option-data {
        description
            "Vendor class option data container.";
        leaf enterprise-number {
            type uint32;
            description
                "The vendor's registered Enterprise Number, as
                maintained by IANA.";
        }
        leaf vendor-class-data-id {
            type uint8;
            description
                "Vendor class data ID.";
        }
        leaf vendor-class-data {
            type string;
            description
                "Opaque field for matching the client's vendor class
                data.";
        }
    }
}
case client-duid-id {
    description
        "Client class selection based on the value of the
        received client DUID.";
    leaf duid {
        type dhcp6:duid;
        description
            "Client DUID.";
    }
}
}
}
}
/*
 * Augmentations
 */

augment "/dhcp6-srv:dhcpv6-server/dhcp6-srv:class-selector" {
    description
        "Augment class selector functions to the DHCPv6 server
        module.";
    container client-classes {
        description
            "Client classes to augment.";
        list class {

```



Beijing,  
100084  
China  
Email: cuiyong@tsinghua.edu.cn

Linhui Sun  
Tsinghua University  
Beijing,  
100084  
China  
Email: lh.sunlinh@gmail.com

Sladjana Zechlin  
Deutsche Telekom AG  
CTO-IPT, Landgrabenweg 151  
53227, Bonn  
Germany  
Email: sladjana.zechlin@telekom.de

Zihao He  
Tsinghua University  
Beijing,  
100084  
China  
Email: hezihao9512@gmail.com

Michal Nowikowski  
Internet Systems Consortium  
Gdansk  
Poland  
Email: godfryd@isc.org

#### Author's Address

Ian Farrer (editor)  
Deutsche Telekom AG  
S&TI, Landgrabenweg 151  
53227 Bonn  
Germany  
Email: ian.farrer@telekom.de