                         The SIP INFO Method

Status of this Memo

Copyright Notice

Abstract

   This document proposes an extension to the Session Initiation
   Protocol (SIP). This extension adds the INFO method to the SIP
   protocol. The intent of the INFO method is to allow for the carrying
   of session related control information that is generated during a
   session. One example of such session control information is ISUP and
   ISDN signaling messages used to control telephony call services.

   This and other example uses of the INFO method may be standardized in
   the future.

Table of Contents

1. Introduction

   The SIP protocol described in [1] defines session control messages
   used during the setup and tear down stages of a SIP controlled
   session.

   In addition, the SIP re-INVITE can be used during a session to change
   the characteristics of the session. This is generally to change the
   properties of media flows related to the session or to update the SIP
   session timer.

   However, there is no general-purpose mechanism to carry session
   control information along the SIP signaling path during the session.

   The purpose of the INFO message is to carry application level
   information along the SIP signaling path.

   The INFO method is not used to change the state of SIP calls, or the
   parameters of the sessions SIP initiates. It merely sends optional
   application layer information, generally related to the session.

   It is necessary that the mid-session signaling information traverse
   the post session setup SIP signaling path. This is the path taken by
   SIP re-INVITEs, BYEs and other SIP requests that are tied to an
   individual session. This allows SIP proxy servers to receive, and
   potentially act on, the mid-session signaling information.

   This document proposes an extension to SIP by defining the new INFO
   method. The INFO method would be used for the carrying of mid-call
   signaling information along the session signaling path.

   1.1 Example Uses

      The following are a few of the potential uses of the INFO message:

      - Carrying mid-call PSTN signaling messages between PSTN
        gateways.

      - Carrying DTMF digits generated during a SIP session.

      - Carrying wireless signal strength information in support of
        wireless mobility applications.

      - Carrying account balance information.

      - Carrying images or other non streaming information between the
        participants of a session.

      These are just potential uses; this document does not specify such
      uses nor does it necessarily recommend them.

      It can also be envisioned that there will be other telephony and
      non-telephony uses of the INFO method.

2. INFO Method

   The INFO method is used for communicating mid-session signaling
   information along the signaling path for the call.

   The INFO method is not used to change the state of SIP calls, nor
   does it change the state of sessions initiated by SIP. Rather, it
   provides additional optional information which can further enhance
   the application using SIP.

   The signaling path for the INFO method is the signaling path
   established as a result of the call setup. This can be either direct
   signaling between the calling and called user agents or a signaling
   path involving SIP proxy servers that were involved in the call setup
   and added themselves to the Record-Route header on the initial INVITE
   message.

   The mid-session information can be communicated in either an INFO
   message header or as part of a message body. The definition of the
   message body and/or message headers used to carry the mid-session
   information is outside the scope of this document.

   There are no specific semantics associated with INFO. The semantics
   are derived from the body or new headers defined for usage in INFO.

   2.1 Header Field Support for INFO Method

      Tables 1 and 2 add a column to tables 4 and 5 in the [1]. Refer
      to Section 6 of [1] for a description of the content of the
      tables. Note that the rules defined in the enc. and e-e columns
      in tables 4 and 5 in [1] also apply to use of the headers in the
      INFO request and responses to the INFO request.

   2.2 Responses to the INFO Request Method

      If a server receives an INFO request it MUST send a final
      response.

      A 200 OK response MUST be sent by a UAS for an INFO request with
      no message body if the INFO request was successfully received for
      an existing call. Beyond that, no additional operations are
      required.

```
         Header                    Where   INFO
         ------                    -----   ----
         Accept                      R      o
         Accept-Encoding             R      o
         Accept-Language             R      o
         Allow                      200     -
         Allow                      405     o
         Authorization               R      o
         Call-ID                    gc      m
         Contact                     R      o
         Contact                    1xx     -
         Contact                    2xx     -
         Contact                    3xx     -
         Contact                    485     -
         Content-Encoding            e      o
         Content-Length              e      o
         Content-Type                e      *
         CSeq                       gc      m
         Date                        g      o
         Encryption                  g      o
         Expires                     g      o
         From                       gc      m
         Hide                        R      o
         Max-Forwards                R      o
         Organization                g      o
```

      Table 1 Summary of header fields, A-0

   Handling of INFO messages that contain message bodies is outside
   the scope of this document. The documents defining the message
   bodies will also need to define the SIP protocol rules associated
   with those message bodies.

   A 481 Call Leg/Transaction Does Not Exist message MUST be sent by
   a UAS if the INFO request does not match any existing call leg.

If a server receives an INFO request with a body it understands,
but it has no knowledge of INFO associated processing rules for
the body, the body MAY be rendered and displayed to the user. The
INFO is responded to with a 200 OK.

If the INFO request contains a body that the server does not
understand then, in the absence of INFO associated processing
rules for the body, the server MUST respond with a 415 Unsupported
Media Type message.

Header	Where	INFO
Priority	R	o
Proxy-Authenticate	407	o
Proxy-Authorization	R	o
Proxy-Require	R	o
Require	R	o
Retry-After	R	-
Retry-After	404,480,486	o
Retry-After	503	o
Retry-After	600,603	o
Response-Key	R	o
Record-Route	R	o
Record-Route	2xx	o
Route	R	o
Server	r	o
Subject	R	o
Timestamp	g	o
To	gc(1)	m
Unsupported	420	o
User-Agent	g	o
Via	gc(2)	m
Warning	r	o
WWW-Authenticate	401	o

Table 2 Summary of header fields, P-Z

Bodies which imply a change in the SIP call state or the sessions
initiated by SIP MUST NOT be sent in an INFO message.

Other request failure (4xx), Server Failure (5xx) and Global
Failure (6xx) responses MAY be sent for the INFO Request.

2.3 Message Body Inclusion

The INFO request MAY contain a message body.

2.4 Behavior of SIP User Agents

   Unless stated otherwise, the protocol rules for the INFO request
   governing the usage of tags, Route and Record-Route,
   retransmission and reliability, CSeq incrementing and message
   formatting follow those in [1] as defined for the BYE request.

   An INFO request MAY be cancelled. A UAS receiving a CANCEL for an
   INFO request SHOULD respond to the INFO with a "487 Request
   Cancelled" response if a final response has not been sent to the
   INFO and then behave as if the request were never received.

   However, the INFO message MUST NOT change the state of the SIP
   call, or the sessions initiated by SIP.

2.5 Behavior of SIP Proxy and Redirect Servers

   2.5.1 Proxy Server

      Unless stated otherwise, the protocol rules for the INFO
      request at a proxy are identical to those for a BYE request as
      specified in [1].

   2.5.2 Forking Proxy Server

      Unless stated otherwise, the protocol rules for the INFO
      request at a proxy are identical to those for a BYE request as
      specified in [1].

   2.5.3 Redirection Server

      Unless stated otherwise, the protocol rules for the INFO
      request at a proxy are identical to those for a BYE request as
      specified in [1].

3. INFO Message Bodies

   The purpose of the INFO message is to carry mid-session information
   between SIP user agents. This information will generally be carried
   in message bodies, although it can be carried in headers in the INFO
   message.

   The definition of the message bodies or any new headers created for
   the INFO method is outside the scope of this document. It is
   expected that separate documents will be created to address
   definition of these entities.

   In addition, the INFO method does not define additional mechanisms
   for ensuring in-order delivery. While the CSeq header will be
   incremented upon the transmission of new INFO messages, this should
   not be used to determine the sequence of INFO information. This is
   due to the fact that there could be gaps in the INFO message CSeq
   count caused by a user agent sending re-INVITES or other SIP
   messages.

4. Guidelines for extensions making use of INFO

   The following are considerations that should be taken into account
   when defining SIP extensions that make use of the INFO method.

   - Consideration should be taken on the size of message bodies to be
     carried by INFO messages. The message bodies should be kept small
     due to the potential for the message to be carried over UDP and the
     potential for fragmentation of larger messages.

   - There is potential that INFO messages could be forked by a SIP
     Proxy Server. The implications of this forking of the information
     in the INFO message need to be taken into account.

   - The use of multi-part message bodies may be helpful when defining
     the message bodies to be carried by the INFO message.

   - The extensions that use the INFO message MUST NOT rely on the
     INFO message to do anything that effects the SIP call state or the
     state of related sessions.

   - The INFO extension defined in this document does not depend on
     the use of the Require or Proxy-Require headers. Extensions using
     the INFO message may need the use of these mechanisms. However,
     the use of Require and Proxy-Require should be avoided, if
     possible, in order to improve interoperability between SIP
     entities.

5. Security Considerations

   If the contents of the message body are private then end-to-end
   encryption of the message body can be used to prevent unauthorized
   access to the content.

   There are no other security issues specific to the INFO method.
   The security requirements specified in the SIP specification apply
   to the INFO method.

6. References

   [1] Handley, M., Schulzrinne, H., Schooler, E. and J. Rosenberg,
       "SIP: Session Initiation Protocol", RFC 2543, March 1999.

7. Acknowledgements

8. Author's Address

   Steve Donovan
   dynamicsoft
   5100 Tennyson Parkway, Suite 200
   Plano, Texas 75024

   Email: sdonovan@dynamicsoft.com

9. Full Copyright Statement

Acknowledgement