

Internet Engineering Task Force (IETF)  
Request for Comments: 6339  
Category: Standards Track  
ISSN: 2070-1721

S. Josefsson  
SJD AB  
L. Hornquist Astrand  
Apple, Inc.  
August 2011

Context Token Encapsulate/Decapsulate and OID Comparison Functions for  
the Generic Security Service Application Program Interface (GSS-API)

#### Abstract

This document describes three abstract Generic Security Service Application Program Interface (GSS-API) interfaces used to encapsulate/decapsulate context tokens and compare OIDs. This document also specifies C bindings for the abstract interfaces.

#### Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc6339>.

#### Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	2
2. Conventions Used in This Document . . . . .	2
3. GSS_Encapsulate_token Call . . . . .	3
3.1. gss_encapsulate_token . . . . .	3
4. GSS_Decapsulate_token Call . . . . .	4
4.1. gss_decapsulate_token . . . . .	5
5. GSS_OID_equal Call . . . . .	6
5.1. gss_oid_equal . . . . .	6
6. Test Vector . . . . .	7
7. Acknowledgements . . . . .	7
8. Security Considerations . . . . .	7
9. References . . . . .	7
9.1. Normative References . . . . .	7
9.2. Informative Reference . . . . .	8

## 1. Introduction

The Generic Security Service Application Program Interface (GSS-API) [RFC2743] is a framework that provides security services to applications using a variety of authentication mechanisms. There are widely implemented C bindings [RFC2744] for the abstract interface.

For initial context tokens, a mechanism-independent token format may be used (see Section 3.1 of [RFC2743]). Some protocols, e.g., Simple Authentication and Security Layer (SASL) GS2 [RFC5801], need the ability to add and remove this token header, which contains some ASN.1 tags, a length, and the mechanism OID to and from context tokens. This document adds two GSS-API interfaces (GSS\_Encapsulate\_token and GSS\_Decapsulate\_token) so that GSS-API libraries can provide this functionality.

Being able to compare OIDs is useful, for example, when validating that a negotiated mechanism matches the requested one. This document adds one GSS-API interface (GSS\_OID\_equal) for this purpose.

Text from this specification can be used as implementation documentation, and for this reason, Sections 3, 4, 5, 6, and 8 should be considered code components.

## 2. Conventions Used in This Document

The document uses terms from, and is structured in a similar way as, [RFC2743] and [RFC2744]. The normative reference to [RFC5587] is for the C types "gss\_const\_buffer\_t" and "gss\_const\_OID"; nothing else from that document is required to implement this document.

### 3. GSS\_Encapsulate\_token Call

#### Inputs:

- o `input_token` OCTET STRING -- buffer with token data to encapsulate
- o `token_oid` OBJECT IDENTIFIER -- object identifier of mechanism for the token

#### Outputs:

- o `major_status` INTEGER
- o `output_token` OCTET STRING -- Encapsulated token data; caller must release with `GSS_Release_buffer()`

#### Return `major_status` codes:

- o `GSS_S_COMPLETE` indicates that completion was successful and that output parameters hold correct information.
- o `GSS_S_FAILURE` indicates that encapsulation failed for reasons unspecified at the GSS-API level.

`GSS_Encapsulate_token()` is used to add the mechanism-independent token header to GSS-API context token data.

#### 3.1. `gss_encapsulate_token`

```
OM_uint32 gss_encapsulate_token (
    gss_const_buffer_t input_token,
    gss_const_OID token_oid,
    gss_buffer_t output_token)
```

#### Purpose:

Add the mechanism-independent token header to GSS-API context token data.

#### Parameters:

<code>input_token</code>	buffer, opaque, read Buffer with GSS-API context token data.
<code>token_oid</code>	Object ID, read Object identifier of token.

output_token	buffer, opaque, modify Encapsulated token data; caller must release with gss_release_buffer().
Function values:	GSS status codes
GSS_S_COMPLETE	Indicates that completion was successful and that output parameters hold correct information.
GSS_S_FAILURE	Indicates that encapsulation failed for reasons unspecified at the GSS-API level.

#### 4. GSS\_Decapsulate\_token Call

##### Inputs:

- o input\_token OCTET STRING -- buffer with token to decapsulate
- o token\_oid OBJECT IDENTIFIER -- expected object identifier of token

##### Outputs:

- o major\_status INTEGER
- o output\_token OCTET STRING -- Decapsulated token data; caller must release with GSS\_Release\_buffer()

##### Return major\_status codes:

- o GSS\_S\_COMPLETE indicates that completion was successful and that output parameters hold correct information.
- o GSS\_S\_DEFECTIVE\_TOKEN means that the token failed consistency checks (e.g., OID mismatch or ASN.1 DER length errors).
- o GSS\_S\_FAILURE indicates that decapsulation failed for reasons unspecified at the GSS-API level.

GSS\_Decapsulate\_token() is used to remove the mechanism-independent token header from an initial GSS-API context token.

## 4.1. gss\_decapsulate\_token

```

OM_uint32
gss_decapsulate_token (
    gss_const_buffer_t input_token,
    gss_const_OID token_oid,
    gss_buffer_t output_token)

```

## Purpose:

Remove the mechanism-independent token header from an initial GSS-API context token.

## Parameters:

input_token	buffer, opaque, read Buffer with GSS-API context token.
token_oid	Object ID, read Expected object identifier of token.
output_token	buffer, opaque, modify Decapsulated token data; caller must release with gss_release_buffer().

Function values: GSS status codes

GSS_S_COMPLETE	Indicates that completion was successful and that output parameters hold correct information.
GSS_S_DEFECTIVE_TOKEN	Means that the token failed consistency checks (e.g., OID mismatch or ASN.1 DER length errors).
GSS_S_FAILURE	Indicates that decapsulation failed for reasons unspecified at the GSS-API level.

## 5. GSS\_OID\_equal Call

## Inputs:

- o first\_oid OBJECT IDENTIFIER -- first object identifier to compare
- o second\_oid OBJECT IDENTIFIER -- second object identifier to compare

## Return codes:

- o non-0 when neither OID is GSS\_C\_NO\_OID and the two OIDs are equal.
- o 0 when the two OIDs are not identical or either OID is equal to GSS\_C\_NO\_OID.

GSS\_OID\_equal() is used to add compare two OIDs for equality. The value GSS\_C\_NO\_OID will not match any OID, including GSS\_C\_NO\_OID itself.

## 5.1. gss\_oid\_equal

```
extern int
gss_oid_equal (
    gss_const_OID first_oid,
    gss_const_OID second_oid
)
```

## Purpose:

Compare two OIDs for equality. The value GSS\_C\_NO\_OID will not match any OID, including GSS\_C\_NO\_OID itself.

## Parameters:

first_oid	Object ID, read First object identifier to compare.
second_oid	Object ID, read Second object identifier to compare.

Function values: GSS status codes

non-0	Neither OID is GSS_C_NO_OID, and the two OIDs are equal.
0	The two OIDs are not identical, or either OID is equal to GSS_C_NO_OID.

## 6. Test Vector

For the GSS\_Encapsulate\_token function, if the "input\_token" buffer is the 3-byte octet sequence "foo" and the "token\_oid" OID is 1.2.840.113554.1.2.2, which encoded corresponds to the 9-byte-long octet sequence (using C notation) "\x2a\x86\x48\x86\xf7\x12\x01\x02\x02", the output should be the 16-byte-long octet sequence (again in C notation) "\x60\x0e\x06\x09\x2a\x86\x48\x86\xf7\x12\x01\x02\x02\x66\x6f\x6f". These values may also be used to test the GSS\_Decapsulate\_token interface.

## 7. Acknowledgements

Greg Hudson pointed out the 'const' problem with the C bindings in earlier versions of this document, and Luke Howard suggested to resolve it by using the [RFC5587] types. Stephen Farrell suggested several editorial improvements and the security consideration regarding absent security features of the encapsulation function. Chris Lonvick suggested some improvements.

## 8. Security Considerations

The security considerations of the base GSS-API specification ([RFC2743]) and the base C bindings ([RFC2744]) are inherited.

Encapsulation of data does not provide any kind of integrity or confidentiality.

Implementations need to treat input as potentially untrustworthy for purposes of dereferencing memory objects to avoid security vulnerabilities. In particular, ASN.1 DER length fields are a common source of mistakes.

## 9. References

### 9.1. Normative References

- [RFC2743] Linn, J., "Generic Security Service Application Program Interface Version 2, Update 1", RFC 2743, January 2000.
- [RFC2744] Wray, J., "Generic Security Service API Version 2 : C-bindings", RFC 2744, January 2000.
- [RFC5587] Williams, N., "Extended Generic Security Service Mechanism Inquiry APIs", RFC 5587, July 2009.

## 9.2. Informative Reference

[RFC5801] Josefsson, S. and N. Williams, "Using Generic Security Service Application Program Interface (GSS-API) Mechanisms in Simple Authentication and Security Layer (SASL): The GS2 Mechanism Family", RFC 5801, July 2010.

## Authors' Addresses

Simon Josefsson  
SJD AB  
Hagagatan 24  
Stockholm 113 47  
SE

E-Mail: [simon@josefsson.org](mailto:simon@josefsson.org)  
URI: <http://josefsson.org/>

Love Hornquist Astrand  
Apple, Inc.

E-Mail: [lha@apple.com](mailto:lha@apple.com)



