

Internet Engineering Task Force (IETF)  
Request for Comments: 7697  
Category: Standards Track  
ISSN: 2070-1721

P. Pan  
Infinera  
S. Aldrin  
Google, Inc.  
M. Venkatesan  
Dell, Inc.  
K. Sampath  
Redeem  
T. Nadeau  
Brocade  
S. Boutros  
VMware, Inc.  
January 2016

MPLS Transport Profile (MPLS-TP) Operations, Administration, and  
Maintenance (OAM) Identifiers Management Information Base (MIB)

#### Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects to configure the Operations, Administration, and Maintenance (OAM) identifiers for Multiprotocol Label Switching (MPLS) and the MPLS-based Transport Profile (TP).

#### Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc7697>.

## Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction .....	3
2. The Internet-Standard Management Framework .....	3
3. Overview .....	3
3.1. Conventions Used in This Document .....	3
3.2. Terminology .....	4
3.3. Acronyms .....	4
4. Feature List .....	5
5. Brief Description of MIB Objects .....	5
5.1. mplsOamIdMegTable .....	5
5.2. mplsOamIdMeTable .....	5
6. MPLS OAM Identifier Configuration for MPLS LSP: Example .....	6
7. MPLS OAM Identifiers MIB Definitions .....	8
8. Security Considerations .....	31
9. IANA Considerations .....	32
9.1. IANA Considerations for MPLS-OAM-ID-STD-MIB .....	32
10. References .....	32
10.1. Normative References .....	32
10.2. Informative References .....	34
Acknowledgments .....	35
Authors' Addresses .....	36

## 1. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects for modeling a Transport Profile (TP) based on Multiprotocol Label Switching (MPLS) [RFC3031].

This MIB module should be used for performing the OAM (Operations, Administration, and Maintenance) operations for MPLS Tunnel LSPs (Label Switched Paths), Pseudowires, and Sections.

At the time of this writing, SNMP SET is no longer recommended as a way to configure MPLS networks as was described in [RFC3812]. However, since the MIB modules specified in this document are intended to work in parallel with the MIB modules for MPLS specified in [RFC3812], certain objects defined here are specified with a MAX-ACCESS of read-write or read-create so that specifications of the base tables in [RFC3812] and the new MIB modules in this document are consistent. Although the example described in Section 6 specifies means to configure OAM identifiers for MPLS-TP Tunnels, this should be seen as indicating how the MIB values would be returned in the specified circumstances having been configured by alternative means.

## 2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIv2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

## 3. Overview

### 3.1. Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

### 3.2. Terminology

This document uses terminology from the Multiprotocol Label Switching Architecture [RFC3031], the MPLS Traffic Engineering (TE) MIB [RFC3812], the MPLS Label Switching Router (LSR) MIB [RFC3813], the OAM Framework for MPLS-Based Transport Networks [RFC6371], "MPLS Transport Profile (MPLS-TP) Identifiers" [RFC6370], MPLS-TP Identifiers Following ITU-T Conventions [RFC6923], and OAM in MPLS Transport Networks [RFC5860].

### 3.3. Acronyms

BFD: Bidirectional Forwarding Detection

ICC: ITU Carrier Code

IP: Internet Protocol

LSP: Label Switched Path

LSR: Label Switching Router

ME: Maintenance Entity

MEG: Maintenance Entity Group

MEP: Maintenance Entity Group End Point

MIB: Management Information Base

MIP: Maintenance Entity Group Intermediate Point

MP: Maintenance Point

MPLS: Multiprotocol Label Switching

MPLS-TP: MPLS Transport Profile

PW: Pseudowire

TE: Traffic Engineering

TP: Transport Profile

#### 4. Feature List

The MPLS transport profile OAM identifiers MIB module is designed to satisfy the following requirements and constraints:

- The MIB module supports configuration of OAM identifiers for MPLS point-to-point Tunnels, point-to-multipoint LSPs, co-routed bidirectional LSPs, associated bidirectional LSPs, and Pseudowires.

#### 5. Brief Description of MIB Objects

The objects described in this section support the functionality described in [RFC5654] and [RFC6370]. The tables support both IP-compatible and ICC-based OAM identifiers configurations for MPLS Tunnels, LSPs, and Pseudowires.

##### 5.1. mplsOamIdMegTable

The mplsOamIdMegTable is used to manage one or more Maintenance Entities (MEs) that belong to the same transport path.

When a new entry is created with mplsOamIdMegOperatorType set to ipCompatible (1), then as per [RFC6370] (MEG\_ID for an LSP is LSP\_ID, and MEG\_ID for a PW is PW\_Path\_ID), MEP\_ID can be automatically formed.

For an ICC-based transport path, the user is expected to configure the ICC identifier explicitly in this table for MPLS Tunnels, LSPs, and Pseudowires.

##### 5.2. mplsOamIdMeTable

The mplsOamIdMeTable defines a relationship between two points (source and sink) of a transport path to which maintenance and monitoring operations apply. The two points that define an ME are called Maintenance Entity Group End Points (MEPs).

In between MEPs, there are zero or more intermediate points, called Maintenance Entity Group Intermediate Points (MIPs). MEPs and MIPs are associated with the MEG and can be shared by more than one ME in a MEG.

## 6. MPLS OAM Identifier Configuration for MPLS LSP: Example

In this section, we provide an example of the OAM identifier configuration for an MPLS co-routed bidirectional LSP.

This example provides usage of MEG and ME tables for management and monitoring operations of an MPLS LSP.

This example considers the OAM identifiers configuration on a head-end LSR to manage and monitor an MPLS LSP. Only relevant objects that are applicable for IP-based OAM identifiers of MPLS co-routed bidirectional LSPs are illustrated here.

In the `mplsOamIdMegTable`:

```
{
  -- MEG index (Index to the table)
  mplsOamIdMegIndex          = 1,
  mplsOamIdMegName           = "MEG1",
  mplsOamIdMegOperatorType   = ipCompatible (1),
  mplsOamIdMegServicePointerType = lsp (1),
  mplsOamIdMegMpLocation     = perNode (1),
  -- Mandatory parameters needed to activate the row go here

  mplsOamIdMegRowStatus      = createAndGo (4),
  mplsOamIdMegPathFlow       = coRoutedBidirectionalPointToPoint (2)
}
```

This will create an entry in the `mplsOamIdMegTable` to manage and monitor the MPLS Tunnel.

The following ME table is used to associate the path information to a MEG.

In the mplsOamIdMeTable:

```
{
-- ME index (Index to the table)
  mplsOamIdMeIndex          = 1,

-- MP index (Index to the table)
  mplsOamIdMeMpIndex        = 1,
  mplsOamIdMeName           = "ME1",
  mplsOamIdMeMpIfIndex      = 0,
-- The source MEP ID is derived from the IP-compatible MPLS LSP
  mplsOamIdMeSourceMepIndex = 0,
-- The sink MEP ID is derived from the IP-compatible MPLS LSP
  mplsOamIdMeSinkMepIndex   = 0,
  mplsOamIdMeMpType         = mep (1),
  mplsOamIdMeMepDirection   = down (2),
-- RowPointer MUST point to the first accessible column of an
-- MPLS LSP
  mplsOamIdMeServicePointer = mplsTunnelName.1.1.10.20,
-- Mandatory parameters needed to activate the row go here
  mplsOamIdMeRowStatus      = createAndGo (4)
}
```

## 7. MPLS OAM Identifiers MIB Definitions

```
MPLS-OAM-ID-STD-MIB DEFINITIONS ::= BEGIN

IMPORTS
    MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,
    Unsigned32
        FROM SNMPv2-SMI -- RFC 2578
    MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
        FROM SNMPv2-CONF -- RFC 2580
    RowStatus, RowPointer, StorageType
        FROM SNMPv2-TC -- RFC 2579
    SnmpAdminString
        FROM SNMP-FRAMEWORK-MIB -- RFC 3411
    IndexIntegerNextFree
        FROM DIFFSERV-MIB -- RFC 3289
    mplsStdMIB
        FROM MPLS-TC-STD-MIB -- RFC 3811
    InterfaceIndexOrZero, ifGeneralInformationGroup,
    ifCounterDiscontinuityGroup
        FROM IF-MIB; -- RFC 2863

mplsOamIdStdMIB MODULE-IDENTITY
    LAST-UPDATED
        "201601070000Z" -- January 07, 2016
    ORGANIZATION
        "Multiprotocol Label Switching (MPLS) Working Group"
    CONTACT-INFO
        "Sam Aldrin
        Google, Inc.
        1600 Amphitheatre Parkway
        Mountain View, CA 94043
        USA
        Email: aldrin.ietf@gmail.com

        Thomas D. Nadeau
        Email: tnadeau@lucidvision.com

        Venkatesan Mahalingam
        Dell, Inc.
        5450 Great America Parkway
        Santa Clara, CA 95054
        USA
        Email: venkat.mahalingams@gmail.com
```



Kannan KV Sampath  
 Redeem  
 India  
 Email: kannankvs@gmail.com

Ping Pan  
 Infinera

Sami Boutros  
 VMware, Inc.  
 3401 Hillview Ave.  
 Palo Alto, CA 94304  
 USA  
 Email: sboutros@vmware.com"

## DESCRIPTION

"Copyright (c) 2016 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This MIB module contains generic object definitions for MPLS OAM identifiers."

-- Revision history

## REVISION

"201601070000Z" -- January 07, 2016

## DESCRIPTION

"MPLS OAM Identifiers MIB objects for Tunnels, LSPs, Pseudowires, and Sections."

::= { mplsStdMIB 21 }

-- Top-level components of this MIB module

-- notifications

mplsOamIdNotifications

OBJECT IDENTIFIER ::= { mplsOamIdStdMIB 0 }

-- tables, scalars

mplsOamIdObjects OBJECT IDENTIFIER ::= { mplsOamIdStdMIB 1 }

```

-- conformance
mplsOamIdConformance
    OBJECT IDENTIFIER ::= { mplsOamIdStdMIB 2 }

-- Start of MPLS Transport Profile MEG table

mplsOamIdMegIndexNext OBJECT-TYPE
    SYNTAX      IndexIntegerNextFree (0..4294967295)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object contains an unused value for
        mplsOamIdMegIndex, or a zero to indicate
        that none exist. Negative values are not allowed,
        as they do not correspond to valid values of
        mplsOamIdMegIndex."
    ::= { mplsOamIdObjects 1 }

mplsOamIdMegTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF MplsOamIdMegEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains information about the Maintenance
        Entity Groups (MEGs).

        A MEG, as mentioned in the MPLS-TP OAM framework, defines
        a set of one or more Maintenance Entities (MEs).
        MEs define a relationship between any two points of a
        transport path in an OAM domain to which maintenance and
        monitoring operations apply."
    ::= { mplsOamIdObjects 2 }

mplsOamIdMegEntry OBJECT-TYPE
    SYNTAX      MplsOamIdMegEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry in this table represents an MPLS-TP MEG.
        An entry can be created by a network administrator
        or by an SNMP agent as instructed by an MPLS-TP OAM
        framework.

        When a new entry is created with
        mplsOamIdMegOperatorType set to ipCompatible (1),
        then as per RFC 6370 (MEG_ID for an LSP is LSP_ID, and
        MEG_ID for a PW is PW_Path_ID), MEP_ID can be
        automatically formed."

```

For a co-routed bidirectional LSP, MEG\_ID is  
 A1-`{Global_ID::Node_ID::Tunnel_Num}`::Z9-`{Global_ID::Node_ID::Tunnel_Num}`::LSP\_Num.

For an associated bidirectional LSP, MEG\_ID is  
 A1-`{Global_ID::Node_ID::Tunnel_Num::LSP_Num}`::  
 Z9-`{Global_ID::Node_ID::Tunnel_Num::LSP_Num}`.

For an LSP, MEP\_ID is formed using  
 Global\_ID::Node\_ID::Tunnel\_Num::LSP\_Num.

For a PW, MEG\_ID is formed using AGI::  
 A1-`{Global_ID::Node_ID::AC_ID}`::  
 Z9-`{Global_ID::Node_ID::AC_ID}`.

For a PW, MEP\_ID is formed using  
 AGI::Global\_ID::Node\_ID::AC\_ID.

MEP\_ID is retrieved from the `mplsOamIdMegServicePointer` object based on the `mplsOamIdMegServicePointerType` value. The ICC MEG\_ID for an LSP and a PW is formed using the objects `mplsOamIdMegIdIcc` and `mplsOamIdMegIdUmc`.

MEP\_ID can be formed using `MEG_ID::MEP_Index`."

#### REFERENCE

1. RFC 5860: Requirements for Operations, Administration, and Maintenance (OAM) in MPLS Transport Networks, May 2010.
2. RFC 6371: Operations, Administration, and Maintenance Framework for MPLS-Based Transport Networks, September 2011, Section 3.
3. RFC 6370: MPLS Transport Profile (MPLS-TP) Identifiers, September 2011.
4. RFC 6923: MPLS Transport Profile (MPLS-TP) Identifiers Following ITU-T Conventions, May 2013."

INDEX { `mplsOamIdMegIndex` }  
 ::= { `mplsOamIdMegTable 1` }

```

MplsOamIdMegEntry ::= SEQUENCE {
    mplsOamIdMegIndex          Unsigned32,
    mplsOamIdMegName           SnmpAdminString,
    mplsOamIdMegOperatorType   INTEGER,
    mplsOamIdMegIdCc           SnmpAdminString,
    mplsOamIdMegIdIcc          SnmpAdminString,
    mplsOamIdMegIdUmc          SnmpAdminString,
    mplsOamIdMegServicePointerType INTEGER,
    mplsOamIdMegMpLocation     INTEGER,
    mplsOamIdMegPathFlow       INTEGER,
    mplsOamIdMegOperStatus     INTEGER,
    mplsOamIdMegSubOperStatus   BITS,
    mplsOamIdMegRowStatus      RowStatus,
    mplsOamIdMegStorageType     StorageType
}

mplsOamIdMegIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "Index for the conceptual row identifying a MEG within
         this MEG table. Managers should obtain new values for row
         creation in this table by reading mplsOamIdMegIndexNext."
    ::= { mplsOamIdMegEntry 1 }

mplsOamIdMegName OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(0..48))
    MAX-ACCESS   read-create
    STATUS      current
    DESCRIPTION
        "Each MEG has a unique name amongst all those used or
         available to a service provider or operator. It
         facilitates easy identification of administrative
         responsibility for each MEG."
    ::= { mplsOamIdMegEntry 2 }

```

```

mplsOamIdMegOperatorType OBJECT-TYPE
    SYNTAX          INTEGER {
                        ipCompatible (1),
                        iccBased (2)
                    }
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "Indicates the operator type for the MEG. Conceptual rows
        having 'iccBased' as the operator type MUST have valid
        values for the objects mplsOamIdMegIdIcc and
        mplsOamIdMegIdUmc when the row status is active."
    REFERENCE
        "1. RFC 6370: MPLS Transport Profile (MPLS-TP) Identifiers,
        September 2011.
        2. RFC 6923: MPLS Transport Profile (MPLS-TP) Identifiers
        Following ITU-T Conventions, May 2013, Section 3.1."
    DEFVAL { ipCompatible }
    ::= { mplsOamIdMegEntry 3 }

mplsOamIdMegIdCc OBJECT-TYPE
    SYNTAX          SnmpAdminString (SIZE(0..2))
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "Global uniqueness is assured by concatenating the ICC
        with a Country Code (CC). The Country Code (alpha-2)
        is a string of two alphabetic characters represented
        with uppercase letters (i.e., A-Z).

        This object MUST contain a non-null value if
        the MplsOamIdMegOperatorType value is iccBased (2);
        otherwise, a null value with octet size 0
        should be assigned."
    REFERENCE
        "RFC 6923: MPLS Transport Profile (MPLS-TP) Identifiers
        Following ITU-T Conventions, May 2013, Section 3."
    DEFVAL { "" }
    ::= { mplsOamIdMegEntry 4 }

```

```
mplsOamIdMegIdIcc OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(0..6))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Unique code assigned to a network operator or service
        provider; maintained by the ITU-T. This is the
        ITU Carrier Code used to form the MEGID.

        This object MUST contain a non-null value if
        the MplsOamIdMegOperatorType value is iccBased (2);
        otherwise, a null value with octet size 0
        should be assigned."
    REFERENCE
        "RFC 6923: MPLS Transport Profile (MPLS-TP) Identifiers
        Following ITU-T Conventions, May 2013, Section 3.1."
    DEFVAL     {""}
    ::= { mplsOamIdMegEntry 5 }

mplsOamIdMegIdUmc OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(0..7))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Unique code assigned by a network operator or service
        provider. This code is appended to mplsOamIdMegIdIcc to
        form the MEGID.
        This object MUST contain a non-null value if
        the MplsOamIdMegOperatorType value is iccBased (2);
        otherwise, a null value with octet size 0
        should be assigned."
    REFERENCE
        "RFC 6923: MPLS Transport Profile (MPLS-TP) Identifiers
        Following ITU-T Conventions, May 2013, Section 7.1."
    DEFVAL     {""}
    ::= { mplsOamIdMegEntry 6 }
```

mplsOamIdMegServicePointerType OBJECT-TYPE

```
SYNTAX          INTEGER {
                tunnel (1),
                lsp (2),
                pseudowire (3),
                section (4)
                }
```

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"Indicates the service type for the MEG.

If the service type indicates tunnel (1), the service pointer in the mplsOamIdMeTable points to an entry in the point-to-point mplsTunnelTable (RFC 3812).

If the service type indicates lsp (2), the service pointer in the mplsOamIdMeTable points to an entry in the co-routed or associated bidirectional mplsTunnelTable.

If the value is the pseudowire (3) service type, the service pointer in the mplsOamIdMeTable points to an entry in the pwTable (RFC 5601).

If the value is the section (4) service type, the service pointer in the mplsOamIdMeTable points to an entry in the mplsTunnelTable (RFC 3812)."

REFERENCE

1. RFC 3812: Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB), June 2004.
2. RFC 5601: Pseudowire (PW) Management Information Base (MIB), July 2009."

DEFVAL { lsp }

::= { mplsOamIdMegEntry 7 }

## mplsOamIdMegMpLocation OBJECT-TYPE

```
SYNTAX          INTEGER {
                    perNode (1),
                    perInterface (2)
                  }
```

```
MAX-ACCESS      read-create
```

```
STATUS          current
```

## DESCRIPTION

"Indicates the MP location type for this MEG.

If the value is perNode, then the MEG in the LSR supports only perNode MEPs/MIPs, i.e., only one MEP/MIP in an LSR.

If the value is perInterface, then the MEG in the LSR supports perInterface MEPs/MIPs, i.e., two MEPs/MIPs in an LSR."

## REFERENCE

"RFC 6371: Operations, Administration, and Maintenance Framework for MPLS-Based Transport Networks, September 2011."

```
DEFVAL { perNode }
```

```
::= { mplsOamIdMegEntry 8 }
```

## mplsOamIdMegPathFlow OBJECT-TYPE

```
SYNTAX          INTEGER {
                    unidirectionalPointToPoint (1),
                    coRoutedBidirectionalPointToPoint (2),
                    associatedBidirectionalPointToPoint (3),
                    unidirectionalPointToMultiPoint (4)
                  }
```

```
MAX-ACCESS      read-create
```

```
STATUS          current
```

## DESCRIPTION

"Indicates the transport path flow for this MEG.

In the case of a unidirectional point-to-point transport path, a single unidirectional ME is defined to monitor it.

In the case of associated bidirectional point-to-point transport paths, two independent unidirectional MEs are defined to independently monitor each direction.

In the case of co-routed bidirectional point-to-point transport paths, a single bidirectional ME is defined to monitor both directions congruently.

In the case of unidirectional point-to-multipoint transport paths, a single unidirectional ME for each leaf is defined to monitor the transport path from the root to that leaf."



## REFERENCE

"RFC 6371: Operations, Administration, and Maintenance Framework for MPLS-Based Transport Networks, September 2011."

```
DEFVAL { coRoutedBidirectionalPointToPoint }
 ::= { mplsOamIdMegEntry 9 }
```

## mplsOamIdMegOperStatus OBJECT-TYPE

```
SYNTAX      INTEGER {
                up (1),
                down (2)
            }
```

```
MAX-ACCESS  read-only
```

```
STATUS      current
```

## DESCRIPTION

"This object specifies the operational status of the Maintenance Entity Group (MEG). This object is used to send the notification to the SNMP manager about the MEG.

The value up (1) indicates that the MEG and its monitored path are operationally up. The value down (2) indicates that the MEG is operationally down.

When the value of mplsOamIdMegOperStatus is up (1), all the bits of mplsOamIdMegSubOperStatus must be cleared. When the value of mplsOamIdMegOperStatus is down (2), at least one bit of mplsOamIdMegSubOperStatus must be set."

```
 ::= { mplsOamIdMegEntry 10 }
```

## mplsOamIdMegSubOperStatus OBJECT-TYPE

```
SYNTAX      BITS {
                megDown (0),
                meDown (1),
                oamAppDown (2),
                pathDown (3)
            }
```

```
MAX-ACCESS  read-only
```

```
STATUS      current
```

## DESCRIPTION

"This object specifies the reason why the MEG operational status, as indicated by the object mplsOamIdMegOperStatus, is down. This object is used to send the notification to the SNMP manager about the MEG.

The bit 0 (megDown) indicates that the MEG is down.  
 The bit 1 (meDown) indicates that the ME table is down.  
 The bit 2 (oamAppDown) indicates that the OAM application (LSP or PW) monitored by this MEG is down. Currently, BFD

is the only supported OAM application.  
 The bit 3 (pathDown) indicates that the underlying  
 LSP or PW is down."

```
::= { mplsOamIdMegEntry 11 }
```

```
mplsOamIdMegRowStatus OBJECT-TYPE
```

```
SYNTAX      RowStatus
MAX-ACCESS  read-create
STATUS      current
```

```
DESCRIPTION
```

"This variable is used to create, modify, and/or delete  
 a row in this table. When a row in this table is in the  
 active(1) state, no objects in that row can be modified  
 by the agent except mplsOamIdMegRowStatus."

```
::= { mplsOamIdMegEntry 12 }
```

```
mplsOamIdMegStorageType OBJECT-TYPE
```

```
SYNTAX      StorageType
MAX-ACCESS  read-create
STATUS      current
```

```
DESCRIPTION
```

"This variable indicates the storage type for this  
 object.  
 Conceptual rows having the value 'permanent'  
 need not allow write access to any columnar  
 objects in the row."

```
DEFVAL { volatile }
```

```
::= { mplsOamIdMegEntry 13 }
```

```
-- End of MPLS Transport Profile MEG table
```

```
-- Start of MPLS Transport Profile ME table
```

```
mplsOamIdMeIndexNext OBJECT-TYPE
```

```
SYNTAX      IndexIntegerNextFree (0..4294967295)
MAX-ACCESS  read-only
STATUS      current
```

```
DESCRIPTION
```

"This object contains an unused value for  
 mplsOamIdMeIndex, or a zero to indicate  
 that none exist. Negative values are not allowed,  
 as they do not correspond to valid values of  
 mplsOamIdMeIndex."

```
::= { mplsOamIdObjects 3 }
```

```
mplsOamIdMeMpIndexNext OBJECT-TYPE
    SYNTAX      IndexIntegerNextFree (0..4294967295)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object contains an unused value for
        mplsOamIdMeMpIndex, or a zero to indicate
        that none exist. Negative values are not allowed,
        as they do not correspond to valid values of
        mplsOamIdMeMpIndex."
    ::= { mplsOamIdObjects 4 }
```

```
mplsOamIdMeTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF MplsOamIdMeEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains MPLS-TP ME information.

        The ME is some portion of a transport path that requires
        management bounded by two points (called MEPs), and the
        relationship between those points to which maintenance
        and monitoring operations apply.

        This table is generic enough to handle MEP and MIP
        information within a MEG."
    ::= { mplsOamIdObjects 5 }
```

```
mplsOamIdMeEntry OBJECT-TYPE
    SYNTAX      MplsOamIdMeEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry in this table represents an MPLS-TP ME. This
        entry represents the ME if the source and sink MEPs are
        defined.

        An ME is a point-to-point entity. One ME has two such
        MEPs. A MEG is a group of one or more MEs. One MEG can
        have two or more MEPs.

        For a point-to-point LSP, one MEG has one ME, and this ME
        is associated with two MEPs (source and sink MEPs) within
        a MEG. Each mplsOamIdMeIndex value denotes the ME within
        a MEG."
```

In the case of unidirectional point-to-point transport paths, a single unidirectional ME is defined to monitor it, and `mplsOamIdMeServicePointer` points to a unidirectional point-to-point path.

In the case of associated bidirectional point-to-point transport paths, two independent unidirectional MEs are defined to independently monitor each direction, and each `mplsOamIdMeServicePointer` MIB object points to a unique unidirectional transport path. This has implications for transactions that terminate at or query a MIP, as a return path from a MIP to a source MEP does not necessarily exist within the MEG.

In the case of co-routed bidirectional point-to-point transport paths, a single bidirectional ME is defined to monitor both directions congruently, and the `mplsOamIdMeServicePointer` MIB object points to a co-routed bidirectional point-to-point transport path.

In the case of unidirectional point-to-multipoint transport paths, a single unidirectional ME for each leaf is defined to monitor the transport path from the root to that leaf, and each leaf has different transport path information in the `mplsOamIdMeServicePointer` MIB object. Note that the `MplsOamIdMeEntry` should be created manually once the MEG is configured for OAM operations."

```
INDEX { mplsOamIdMegIndex,
        mplsOamIdMeIndex,
        mplsOamIdMeMpIndex
      }
 ::= { mplsOamIdMeTable 1 }
```

```
MplsOamIdMeEntry ::= SEQUENCE {
  mplsOamIdMeIndex          Unsigned32,
  mplsOamIdMeMpIndex       Unsigned32,
  mplsOamIdMeName          SnmpAdminString,
  mplsOamIdMeMpIfIndex     InterfaceIndexOrZero,
  mplsOamIdMeSourceMepIndex Unsigned32,
  mplsOamIdMeSinkMepIndex  Unsigned32,
  mplsOamIdMeMpType        INTEGER,
  mplsOamIdMeMepDirection  INTEGER,
  mplsOamIdMeServicePointer RowPointer,
  mplsOamIdMeRowStatus     RowStatus,
  mplsOamIdMeStorageType   StorageType
}
```

```

mplsOamIdMeIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Uniquely identifies an ME index within a MEG. Managers
         should obtain new values for row creation in this table by
         reading mplsOamIdMeIndexNext."
    ::= { mplsOamIdMeEntry 1 }

mplsOamIdMeMpIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Indicates the Maintenance Point (MP) index that is used to
         create multiple MEPs in a node of a single ME. The value
         of this object can be the MEP index or the MIP index.
         Managers should obtain new values for row creation in this
         table by reading mplsOamIdMeMpIndexNext."
    ::= { mplsOamIdMeEntry 2 }

mplsOamIdMeName OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(1..48))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This object denotes the ME name. Each ME has a unique
         name within a MEG."
    ::= { mplsOamIdMeEntry 3 }

mplsOamIdMeMpIfIndex OBJECT-TYPE
    SYNTAX      InterfaceIndexOrZero
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Indicates the MP interface.
         If the mplsOamIdMegMpLocation object value
         is perNode (1), the MP interface index should point
         to the incoming interface or outgoing interface, or
         be zero (to indicate that the MP OAM packets are initiated
         from the forwarding engine).

         If the mplsOamIdMegMpLocation object value is
         perInterface (2), the MP interface index should point to
         the incoming interface or outgoing interface."

```

## REFERENCE

1. RFC 6371: Operations, Administration, and Maintenance Framework for MPLS-Based Transport Networks, September 2011.
2. RFC 2863: The Interfaces Group MIB, June 2000."

```
DEFVAL { 0 }
 ::= { mplsOamIdMeEntry 4 }
```

## mplsOamIdMeSourceMepIndex OBJECT-TYPE

```
SYNTAX      Unsigned32
MAX-ACCESS  read-create
STATUS      current
```

## DESCRIPTION

"Indicates the source MEP index of the ME. This object should be configured if the mplsOamIdMegOperatorType object in the mplsOamIdMegEntry is configured as iccBased (2). If the MEG is configured for an IP-based operator, the value of this object should be set to zero, and the MEP ID will be automatically derived from the service identifiers (MPLS-TP LSP/PW Identifier)."

```
DEFVAL { 0 }
 ::= { mplsOamIdMeEntry 5 }
```

## mplsOamIdMeSinkMepIndex OBJECT-TYPE

```
SYNTAX      Unsigned32
MAX-ACCESS  read-create
STATUS      current
```

## DESCRIPTION

"Indicates the sink MEP index of the ME. This object should be configured if the mplsOamIdMegOperatorType object in the mplsOamIdMegEntry is configured as iccBased (2). If the MEG is configured for an IP-based operator, the value of this object should be set to zero, and the MEP ID will be automatically derived from the service identifiers (MPLS-TP LSP/PW Identifier)."

```
DEFVAL { 0 }
 ::= { mplsOamIdMeEntry 6 }
```

```

mplsOamIdMeMpType OBJECT-TYPE
    SYNTAX          INTEGER {
                    mep (1),
                    mip (2)
                    }
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "Indicates the MP type within the MEG.

        The object should have the value mep (1) only in the
        ingress or egress nodes of the transport path.

        The object can have the value mip (2) in the
        intermediate nodes and possibly in the egress nodes
        of the transport path."
    DEFVAL { mep }
    ::= { mplsOamIdMeEntry 7 }

mplsOamIdMeMepDirection OBJECT-TYPE
    SYNTAX          INTEGER {
                    up (1),
                    down (2),
                    notApplicable (3)
                    }
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "Indicates the direction of the MEP. This object
        should be configured if mplsOamIdMeMpType is configured
        as mep (1); otherwise, notApplicable (3) is set."
    DEFVAL { down }
    ::= { mplsOamIdMeEntry 8 }

mplsOamIdMeServicePointer OBJECT-TYPE
    SYNTAX          RowPointer
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "This variable represents a pointer to the MPLS-TP
        transport path. This value MUST point at an entry in the
        mplsTunnelEntry if mplsOamIdMegServicePointerType
        is configured as tunnel (1), lsp (2), or section (4),
        or at an entry in the pwEntry if
        mplsOamIdMegServicePointerType is configured
        as pseudowire (3).

```

Note: This service pointer object is placed in the ME table instead of the MEG table, since it will be useful in the point-to-multipoint case, where each ME will point to different branches of a point-to-multipoint tree."  
 ::= { mplsOamIdMeEntry 9 }

mplsOamIdMeRowStatus OBJECT-TYPE

SYNTAX RowStatus  
 MAX-ACCESS read-create  
 STATUS current  
 DESCRIPTION

"This variable is used to create, modify, and/or delete a row in this table. When a row in this table is in the active(1) state, no objects in that row can be modified by the agent except mplsOamIdMeRowStatus."

::= { mplsOamIdMeEntry 10 }

mplsOamIdMeStorageType OBJECT-TYPE

SYNTAX StorageType  
 MAX-ACCESS read-create  
 STATUS current  
 DESCRIPTION

"This variable indicates the storage type for this object. Conceptual rows having the value 'permanent' need not allow write access to any columnar objects in the row."

DEFVAL { volatile }

::= { mplsOamIdMeEntry 11 }

-- End of MPLS Transport Profile ME table

-- End of MPLS-TP OAM tables



```

-- Notification definitions of MPLS-TP identifiers

mplsOamIdDefectCondition NOTIFICATION-TYPE
  OBJECTS      {
    mplsOamIdMegName,
    mplsOamIdMeName,
    mplsOamIdMegOperStatus,
    mplsOamIdMegSubOperStatus
  }
  STATUS      current
  DESCRIPTION
    "This notification is sent whenever the operational
    status of the MEG is changed."
  ::= { mplsOamIdNotifications 1 }

-- End of notifications

-- Module compliance

mplsOamIdCompliances
  OBJECT IDENTIFIER ::= { mplsOamIdConformance 1 }

mplsOamIdGroups
  OBJECT IDENTIFIER ::= { mplsOamIdConformance 2 }

-- Compliance requirement for fully compliant implementations

mplsOamIdModuleFullCompliance MODULE-COMPLIANCE
  STATUS      current
  DESCRIPTION "Compliance statement for agents that provide full
    support for the MPLS-TP-OAM-STD-MIB. Such devices
    can then be monitored and also be configured
    using this MIB module."

  MODULE IF-MIB -- The Interfaces Group MIB, RFC 2863
  MANDATORY-GROUPS {
    ifGeneralInformationGroup,
    ifCounterDiscontinuityGroup
  }

  MODULE -- this module
  MANDATORY-GROUPS {
    mplsOamIdMegGroup,
    mplsOamIdMeGroup
  }

```

```

GROUP          mplsOamIdNotificationObjectsGroup
DESCRIPTION    "This group is only mandatory for those
                implementations that can efficiently implement
                the notifications contained in this group."

GROUP          mplsOamIdNotificationGroup
DESCRIPTION    "This group is only mandatory for those
                implementations that can efficiently implement
                the notifications contained in this group."

 ::= { mplsOamIdCompliances 1 }

-- Compliance requirement for read-only implementations

mplsOamIdModuleReadOnlyCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "Compliance statement for agents that only provide
        read-only support for the MPLS-TP-OAM-STD-MIB module."

    MODULE -- this module

MANDATORY-GROUPS {
    mplsOamIdMegGroup,
    mplsOamIdMeGroup
}

GROUP          mplsOamIdNotificationObjectsGroup
DESCRIPTION    "This group is only mandatory for those
                implementations that can efficiently implement
                the notifications contained in this group."

GROUP          mplsOamIdNotificationGroup
DESCRIPTION    "This group is only mandatory for those
                implementations that can efficiently implement
                the notifications contained in this group."

```

```
-- mplsOamIdMegTable

OBJECT      mplsOamIdMegName
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMegOperatorType
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMegIdCc
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMegIdIcc
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMegIdUmc
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMegServicePointerType
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMegMpLocation
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMegPathFlow
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMegRowStatus
SYNTAX      RowStatus { active(1) }
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."
```

```
OBJECT      mplsOamIdMegStorageType
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

-- mplsOamIdMeTable

OBJECT      mplsOamIdMeName
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMeMpIfIndex
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMeSourceMepIndex
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMeSinkMepIndex
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMeMpType
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMeMepDirection
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMeServicePointer
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."

OBJECT      mplsOamIdMeRowStatus
SYNTAX      RowStatus { active(1) }
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."
```

```
OBJECT      mplsOamIdMeStorageType
MIN-ACCESS  read-only
DESCRIPTION
    "Write access is not required."
```

```
::= { mplsOamIdCompliances 2 }
```

```
-- Units of conformance
```

```
mplsOamIdMegGroup OBJECT-GROUP
```

```
OBJECTS {
    mplsOamIdMegIndexNext,
    mplsOamIdMegName,
    mplsOamIdMegOperatorType,
    mplsOamIdMegIdCc,
    mplsOamIdMegIdIcc,
    mplsOamIdMegIdUmc,
    mplsOamIdMegServicePointerType,
    mplsOamIdMegMpLocation,
    mplsOamIdMegOperStatus,
    mplsOamIdMegSubOperStatus,
    mplsOamIdMegPathFlow,
    mplsOamIdMegRowStatus,
    mplsOamIdMegStorageType
}
```

```
STATUS current
```

```
DESCRIPTION
```

```
    "Collection of objects needed for MPLS MEG information."
```

```
::= { mplsOamIdGroups 1 }
```

```
mplsOamIdMeGroup OBJECT-GROUP
  OBJECTS {
    mplsOamIdMeIndexNext,
    mplsOamIdMeMpIndexNext,
    mplsOamIdMeName,
    mplsOamIdMeMpIfIndex,
    mplsOamIdMeSourceMepIndex,
    mplsOamIdMeSinkMepIndex,
    mplsOamIdMeMpType,
    mplsOamIdMeMepDirection,
    mplsOamIdMeServicePointer,
    mplsOamIdMeRowStatus,
    mplsOamIdMeStorageType
  }
  STATUS current
  DESCRIPTION
    "Collection of objects needed for MPLS ME information."
  ::= { mplsOamIdGroups 2 }

mplsOamIdNotificationObjectsGroup OBJECT-GROUP
  OBJECTS {
    mplsOamIdMegOperStatus,
    mplsOamIdMegSubOperStatus
  }
  STATUS current
  DESCRIPTION
    "Collection of objects needed to implement notifications."
  ::= { mplsOamIdGroups 3 }

mplsOamIdNotificationGroup NOTIFICATION-GROUP
  NOTIFICATIONS {
    mplsOamIdDefectCondition
  }
  STATUS current
  DESCRIPTION
    "Set of notifications implemented in this module."
  ::= { mplsOamIdGroups 4 }

END
```

## 8. Security Considerations

This MIB relates to a system that will provide network connectivity and packet forwarding services. As such, improper manipulation of the objects represented by this MIB may result in denial of service to a large number of end-users.

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection opens devices to attack.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

- The mplsOamIdMegTable and the mplsOamIdMeTable collectively show the MPLS OAM characteristics. If an administrator does not want to reveal this information, then these tables should be considered sensitive/vulnerable.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

Implementations SHOULD provide the security features described by the SNMPv3 framework (see [RFC3410]), and implementations claiming compliance to the SNMPv3 standard MUST include full support for authentication and privacy via the User-based Security Model (USM) [RFC3414] with the AES cipher algorithm [RFC3826]. Implementations MAY also provide support for the Transport Security Model (TSM) [RFC5591] in combination with a secure transport such as SSH [RFC5592] or TLS/DTLS [RFC6353].

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

## 9. IANA Considerations

As described in [RFC4221] and [RFC6639], and as requested in the MPLS-TC-STD-MIB [RFC3811], MPLS-related Standards Track MIB modules should be rooted under the mplsStdMIB subtree. The following subsection lists a new assignment that has been made by IANA under the mplsStdMIB subtree for the MPLS-OAM-ID-STD-MIB module defined in this document. New assignments can only be made via a Standards Action as specified in [RFC5226].

### 9.1. IANA Considerations for MPLS-OAM-ID-STD-MIB

IANA has to assign the OID { mplsStdMIB 21 } to the MPLS-OAM-ID-STD-MIB module specified in this document.

## 10. References

### 10.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, DOI 10.17487/RFC2578, April 1999, <<http://www.rfc-editor.org/info/rfc2578>>.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, RFC 2579, DOI 10.17487/RFC2579, April 1999, <<http://www.rfc-editor.org/info/rfc2579>>.
- [RFC2580] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Conformance Statements for SMIv2", STD 58, RFC 2580, DOI 10.17487/RFC2580, April 1999, <<http://www.rfc-editor.org/info/rfc2580>>.
- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", RFC 2863, DOI 10.17487/RFC2863, June 2000, <<http://www.rfc-editor.org/info/rfc2863>>.
- [RFC3031] Rosen, E., Viswanathan, A., and R. Callon, "Multiprotocol Label Switching Architecture", RFC 3031, DOI 10.17487/RFC3031, January 2001, <<http://www.rfc-editor.org/info/rfc3031>>.



- [RFC3289] Baker, F., Chan, K., and A. Smith, "Management Information Base for the Differentiated Services Architecture", RFC 3289, DOI 10.17487/RFC3289, May 2002, <<http://www.rfc-editor.org/info/rfc3289>>.
- [RFC3411] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", STD 62, RFC 3411, DOI 10.17487/RFC3411, December 2002, <<http://www.rfc-editor.org/info/rfc3411>>.
- [RFC3414] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", STD 62, RFC 3414, DOI 10.17487/RFC3414, December 2002, <<http://www.rfc-editor.org/info/rfc3414>>.
- [RFC3826] Blumenthal, U., Maino, F., and K. McCloghrie, "The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model", RFC 3826, DOI 10.17487/RFC3826, June 2004, <<http://www.rfc-editor.org/info/rfc3826>>.
- [RFC5591] Harrington, D. and W. Hardaker, "Transport Security Model for the Simple Network Management Protocol (SNMP)", STD 78, RFC 5591, DOI 10.17487/RFC5591, June 2009, <<http://www.rfc-editor.org/info/rfc5591>>.
- [RFC5592] Harrington, D., Salowey, J., and W. Hardaker, "Secure Shell Transport Model for the Simple Network Management Protocol (SNMP)", RFC 5592, DOI 10.17487/RFC5592, June 2009, <<http://www.rfc-editor.org/info/rfc5592>>.
- [RFC5601] Nadeau, T., Ed., and D. Zelig, Ed., "Pseudowire (PW) Management Information Base (MIB)", RFC 5601, DOI 10.17487/RFC5601, July 2009, <<http://www.rfc-editor.org/info/rfc5601>>.
- [RFC6353] Hardaker, W., "Transport Layer Security (TLS) Transport Model for the Simple Network Management Protocol (SNMP)", STD 78, RFC 6353, DOI 10.17487/RFC6353, July 2011, <<http://www.rfc-editor.org/info/rfc6353>>.

## 10.2. Informative References

- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, DOI 10.17487/RFC3410, December 2002, <<http://www.rfc-editor.org/info/rfc3410>>.
- [RFC3811] Nadeau, T., Ed., and J. Cucchiara, Ed., "Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management", RFC 3811, DOI 10.17487/RFC3811, June 2004, <<http://www.rfc-editor.org/info/rfc3811>>.
- [RFC3812] Srinivasan, C., Viswanathan, A., and T. Nadeau, "Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)", RFC 3812, DOI 10.17487/RFC3812, June 2004, <<http://www.rfc-editor.org/info/rfc3812>>.
- [RFC3813] Srinivasan, C., Viswanathan, A., and T. Nadeau, "Multiprotocol Label Switching (MPLS) Label Switching Router (LSR) Management Information Base (MIB)", RFC 3813, DOI 10.17487/RFC3813, June 2004, <<http://www.rfc-editor.org/info/rfc3813>>.
- [RFC4221] Nadeau, T., Srinivasan, C., and A. Farrel, "Multiprotocol Label Switching (MPLS) Management Overview", RFC 4221, DOI 10.17487/RFC4221, November 2005, <<http://www.rfc-editor.org/info/rfc4221>>.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", BCP 26, RFC 5226, DOI 10.17487/RFC5226, May 2008, <<http://www.rfc-editor.org/info/rfc5226>>.
- [RFC5654] Niven-Jenkins, B., Ed., Brungard, D., Ed., Betts, M., Ed., Sprecher, N., and S. Ueno, "Requirements of an MPLS Transport Profile", RFC 5654, DOI 10.17487/RFC5654, September 2009, <<http://www.rfc-editor.org/info/rfc5654>>.
- [RFC5860] Vigoureux, M., Ed., Ward, D., Ed., and M. Betts, Ed., "Requirements for Operations, Administration, and Maintenance (OAM) in MPLS Transport Networks", RFC 5860, DOI 10.17487/RFC5860, May 2010, <<http://www.rfc-editor.org/info/rfc5860>>.

- [RFC6370] Bocci, M., Swallow, G., and E. Gray, "MPLS Transport Profile (MPLS-TP) Identifiers", RFC 6370, DOI 10.17487/RFC6370, September 2011, <<http://www.rfc-editor.org/info/rfc6370>>.
- [RFC6371] Busi, I., Ed., and D. Allan, Ed., "Operations, Administration, and Maintenance Framework for MPLS-Based Transport Networks", RFC 6371, DOI 10.17487/RFC6371, September 2011, <<http://www.rfc-editor.org/info/rfc6371>>.
- [RFC6639] King, D., Ed., and M. Venkatesan, Ed., "Multiprotocol Label Switching Transport Profile (MPLS-TP) MIB-Based Management Overview", RFC 6639, DOI 10.17487/RFC6639, June 2012, <<http://www.rfc-editor.org/info/rfc6639>>.
- [RFC6923] Winter, R., Gray, E., van Helvoort, H., and M. Betts, "MPLS Transport Profile (MPLS-TP) Identifiers Following ITU-T Conventions", RFC 6923, DOI 10.17487/RFC6923, May 2013, <<http://www.rfc-editor.org/info/rfc6923>>.

#### Acknowledgments

We wish to thank Muly Ilan, Adrian Farrel, Joan Cucchiara, Weiyang Cheng, Mach Chen, Peter Yee, and Tina TSOU for their valuable comments on this document.

The coauthors of this document, the working group chairs, the document shepherd, the responsible AD, and the MPLS Working Group wish to dedicate this RFC to the memory of our friend and colleague Ping Pan, in recognition for his devotion and hard work at the IETF.

## Authors' Addresses

Ping Pan  
Infinera

Sam Aldrin  
Google, Inc.  
1600 Amphitheatre Parkway  
Mountain View, CA 94043  
United States

Email: aldrin.ietf@gmail.com

Venkatesan Mahalingam  
Dell, Inc.  
5450 Great America Parkway  
Santa Clara, CA 95054  
United States

Email: venkat.mahalingams@gmail.com

Kannan KV Sampath  
Redeem  
India

Email: kannankvs@gmail.com

Thomas D. Nadeau  
Brocade

Email: tnadeau@lucidvision.com

Sami Boutros  
VMware, Inc.  
3401 Hillview Ave.  
Palo Alto, CA 94304  
United States

Email: sboutros@vmware.com

