

Internet Engineering Task Force (IETF)  
Request for Comments: 7570  
Category: Standards Track  
ISSN: 2070-1721

C. Margaria, Ed.  
Juniper  
G. Martinelli  
Cisco  
S. Balls  
B. Wright  
Metaswitch  
July 2015

## Label Switched Path (LSP) Attribute in the Explicit Route Object (ERO)

### Abstract

RFC 5420 extends RSVP-TE to specify or record generic attributes that apply to the whole of the path of a Label Switched Path (LSP). This document defines an extension to the RSVP Explicit Route Object (ERO) and Record Route Object (RRO) to allow them to specify or record generic attributes that apply to a given hop.

### Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc7570>.

### Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	2
1.1. Requirements Language . . . . .	3
2. ERO Hop Attributes Subobject . . . . .	3
2.1. Encoding . . . . .	3
2.2. Hop Attributes TLVs . . . . .	4
2.3. Procedures . . . . .	4
3. RRO Hop Attributes Subobject . . . . .	6
3.1. Encoding . . . . .	6
3.2. Procedures . . . . .	6
3.2.1. Subobject Presence Rule . . . . .	6
3.2.2. Reporting Compliance with ERO Hop Attributes . . . . .	7
3.2.3. Compatibility with RRO Attributes Subobject . . . . .	7
4. IANA Considerations . . . . .	8
4.1. ERO Hop Attributes Subobject . . . . .	8
4.2. RRO Hop Attributes Subobject . . . . .	8
4.3. Existing Attribute Flags . . . . .	8
4.4. Existing LSP Attribute TLVs . . . . .	10
5. Security Considerations . . . . .	10
6. References . . . . .	11
6.1. Normative References . . . . .	11
6.2. Informative References . . . . .	13
Acknowledgments . . . . .	14
Authors' Addresses . . . . .	15

## 1. Introduction

Generalized MPLS (GMPLS) Traffic Engineering (TE) Label Switched Paths (LSPs) can be route constrained by making use of the Explicit Route Object (ERO) and related subobjects as defined in [RFC3209], [RFC3473], [RFC3477], [RFC4873], [RFC4874], [RFC5520], and [RFC5553]. Several documents have identified the need for attributes that can be targeted at specific hops in the path of an LSP, including [RFC6163], [WSO-SIG], [RFC7571], or [OBJ-FUN]. This document provides a generic mechanism for use by these other documents.

RSVP already supports generic extension of LSP attributes in [RFC5420]. In order to support current and future ERO constraint extensions, this document provides a mechanism to define per-hop attributes.

The document describes a generic mechanism for carrying information related to specific nodes when signaling an LSP. This document does not restrict what that information can be used for. The defined approach builds on LSP attributes defined in [RFC5420] and enables

attributes to be expressed in ERO and Secondary Explicit Route Objects (SEROs). A new ERO subobject is defined, containing a list of generic per-hop attributes.

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].


2. ERO Hop Attributes Subobject

The ERO Hop Attributes subobject is OPTIONAL. If used, it is carried in the ERO or SERO. The subobject uses the standard format of an ERO subobject.

2.1. Encoding

The length is variable and content is a list of Hop Attributes TLVs defined in Section 2.2. The size of the ERO subobject limits the size of the Hop Attributes TLV to 250 bytes. The typical size of currently defined and forthcoming LSP\_ATTRIBUTE TLVs applicable to a specific hop (WSON\_SIGNALING, Objective Function (OF), and Metric) is not foreseen to exceed this limit.

The ERO Hop Attributes subobject is defined as follows:



The L, Type, and Length parameters are as defined in [RFC3209], Section 4.3.3. The L bit MUST be set to 0. The Type for the ERO Hop Attributes subobject is 35. The Hop Attributes TLVs are encoded as defined in Section 2.2.

Reserved: Reserved MUST be set to 0 when the subobject is inserted in the ERO, MUST NOT be changed when a node processes the ERO, and MUST be ignored on the node addressed by the preceding ERO subobjects.

R: This bit reflects the LSP\_REQUIRED\_ATTRIBUTE and LSP\_ATTRIBUTE semantic defined in [RFC5420]. When set, it indicates required hop attributes to be processed by the node. When cleared, it indicates that the hop attributes are not required as described in Section 2.3.

Hop Attributes TLVs: The TLVs as defined in Section 2.2.

## 2.2. Hop Attributes TLVs

ERO attributes carried by the new objects defined in this document are encoded within TLVs. Each object MAY contain one or more TLVs. There are no ordering rules for TLVs, and interpretation SHOULD NOT be placed on the order in which TLVs are received. The TLV format is defined in [RFC5420], Section 3.

The Attribute Flags TLV defined in [RFC5420] is carried in an ERO Hop Attributes subobject. Flags set in the Attribute Flags TLV [RFC5420] carried in an ERO Hop Attributes subobject SHALL be interpreted in the context of the received ERO. Only a subset of defined flags are defined as valid for use in Attribute Flags TLV carried in an ERO Hop Attributes subobject. Invalid flags SHALL be silently ignored. Unknown flags SHOULD trigger the generation of a PathErr with Error Code "Unknown Attributes Bit" as defined in [RFC5420], Section 5.2. The set of valid flags are defined in Section 4.3.

The presence and ordering rule of the Attribute Flags TLV in an ERO Hop Attributes subobject is defined by each Flag. A document defining a flag to be used in an Attribute Flags TLV carried in the ERO Hop Attributes subobject has to describe:

- o after which kinds of ERO subobject the flag is valid,
- o if ordering of the flag and other ERO subobjects associated with the same hop (e.g., Label subobjects) is significant,
- o if ordering is significant, how the flag is interpreted in association with the preceding subobjects, and
- o any flag modification rules that might apply.

## 2.3. Procedures

As described in [RFC3209], the ERO is managed as a list of subobjects each identifying a specific entity, an abstract node, or a link that defines a waypoint in the network path. Identifying subobjects of various types are defined in [RFC3209], [RFC3477], [RFC4873], [RFC4874], [RFC5520], and [RFC5553].

[RFC3473] modified the ERO list by allowing one or two Label subobjects to be interposed in the list after a subobject identifying a link. One or more ERO Hop Attributes subobjects applicable to a particular hop MAY be inserted directly after any of the existing identifying subobjects defined in [RFC3209], [RFC3477], [RFC4873], [RFC4874], [RFC5520], and [RFC5553]. If any Label subobjects are present for a hop, the ERO Hop Attributes subobject(s) MAY also be inserted after the Label subobjects.

The attributes specified in an ERO Hop Attributes subobject apply to the immediately preceding subobject(s) in the ERO subobject list.

A document defining a specific Hop Attributes TLV has to describe:

- o after which kinds of ERO subobject they are valid,
- o if ordering of the Hop Attributes subobject and other ERO subobjects associated with the same hop (e.g., Label subobjects) is significant,
- o if ordering is significant, how the attribute is interpreted in association with the preceding ERO subobjects, and
- o any TLV modification rules that might apply.

For instance, subobject presence rules can be defined by describing rules similar to [RFC4990], Section 6.1.

If a node is processing an ERO Hop Attributes subobject and does not support the handling of the subobject, it will behave as described in [RFC3209] when an unrecognized ERO subobject is encountered. This node will return a PathErr with Error Code "Routing Error" and Error Value "Bad EXPLICIT\_ROUTE object" with the EXPLICIT\_ROUTE object included, truncated (on the left) to the offending unrecognized subobject.

When the R bit is set, a node MUST examine the attributes TLV present in the subobject following the rules described in [RFC5420], Section 5.2. When the R bit is not set, a node MUST examine the attributes TLV present in the subobject following the rules described in [RFC5420], Section 4.2.

A node processing an ERO Hop Attributes subobject with a Hop Attributes TLV longer than the ERO subobject SHOULD return a PathErr with Error Code "Routing Error" and Error Value "Bad EXPLICIT\_ROUTE object" with the EXPLICIT\_ROUTE object included, truncated (on the left) to the offending malformed subobject. A processing node MUST

NOT originate a Hop Attributes TLV longer than the ERO Hop Attributes subobject. The processing of the Hop Attributes TLVs SHOULD be described in the documents defining them.


3. RRO Hop Attributes Subobject

In some cases, it is important to determine if an OPTIONAL hop attribute has been processed by a node.

3.1. Encoding

The RRO Hop Attributes subobject is OPTIONAL. If used, it is carried in the RECORD\_ROUTE object. The subobject uses the standard format of an RRO subobject.

The RRO Hop Attributes subobject is defined as follows:



The Type and Length parameters are as defined in [RFC3209], Section 4.4.1. The Type for the RRO Hop Attributes subobject is 35. The Hop Attributes TLVs are encoded as defined in Section 2.2.

Reserved: Reserved MUST be set to 0 when the subobject is inserted in the RRO, MUST NOT be changed when a node processes the RRO, and MUST be ignored on the node addressed by the preceding RRO subobjects.

Hop Attributes TLVs: The processed or additional Hop Attributes TLVs, using the format defined in Section 2.2.

3.2. Procedures

3.2.1. Subobject Presence Rule

The RRO rules defined in [RFC3209] are not changed. The RRO Hop Attributes subobject MUST be pushed after the RRO Attributes subobject (if present) as defined in [RFC5420]. The RRO Hop Attributes subobject MAY be present between a pair of subobjects identifying the Label Switching Router (LSR) or links. Unless local

policy applies, all such subobjects SHOULD be forwarded unmodified by transit LSRs.

It is noted that a node (e.g., a domain edge node) MAY edit the RRO to prune/modify the RRO, including the RRO Hop Attributes subobject before forwarding due to confidentiality policy or other reasons (for instance, RRO size reduction).

### 3.2.2. Reporting Compliance with ERO Hop Attributes

To report that an ERO hop attribute has been considered, or to report an additional attribute, an LSR can add a RRO Hop Attributes subobject with the Hop Attributes TLV, which describes the attribute to be reported. The requirement to report compliance MUST be specified in the document that defines the usage of a hop attribute.

### 3.2.3. Compatibility with RRO Attributes Subobject

The RRO Hop Attributes subobject extends the capability of the RRO Attributes subobject defined in [RFC5420], Section 7.2 by allowing the node to report the attribute value. The mechanism defined in this document is compatible with the RRO Attributes subobject using the following procedures.

For LSP attributes signaled in the LSP\_ATTRIBUTES or LSP\_REQUIRED\_ATTRIBUTES objects, a node SHOULD use the RRO Attributes subobject to report processing of those attributes.

For LSP attributes signaled in the ERO Hop Attributes subobject and not in the LSP\_ATTRIBUTES or LSP\_REQUIRED\_ATTRIBUTES objects, if a node desires to report the attributes, it SHOULD use the RRO Hop Attributes subobject and SHOULD NOT use the RRO Attributes subobject. Ingress nodes not supporting the RRO Hop Attributes subobject will drop the information, as described in [RFC3209], Section 4.4.5.

A node can use the RRO Hop Attributes subobject to report an LSP attribute signaled in LSP\_ATTRIBUTES or LSP\_REQUIRED\_ATTRIBUTES only if the following conditions are met:

The attribute and its corresponding flag is allowed on both the LSP\_ATTRIBUTES or LSP\_REQUIRED\_ATTRIBUTES and LSP Hop Attributes subobject.

The reporting of an LSP attribute signaled in LSP\_ATTRIBUTES or LSP\_REQUIRED\_ATTRIBUTES in the RRO Hop Attribute is specified in the document defining that LSP attribute.

## 4. IANA Considerations

### 4.1. ERO Hop Attributes Subobject

IANA manages the "Resource Reservation Protocol (RSVP) Parameters" registry located at <http://www.iana.org/assignments/rsvp-parameters>. Per this document, IANA has made an allocation in the Sub-object type 20 EXPLICIT\_ROUTE - Type 1 Explicit Route registry.

This document introduces a new ERO subobject:

Value	Description	Reference
35	Hop Attributes	This document, Section 2

### 4.2. RRO Hop Attributes Subobject

IANA manages the "Resource Reservation Protocol (RSVP) Parameters" registry located at <http://www.iana.org/assignments/rsvp-parameters>. Per this document, IANA has made an allocation in the Sub-object type 21 ROUTE\_RECORD - Type 1 Route Record registry. This value is the same as that in Section 4.1.

This document introduces a new RRO subobject:

Value	Description	Reference
35	Hop Attributes	This document, Section 3

### 4.3. Existing Attribute Flags

IANA manages the "Attribute Flags" registry as part of the "Resource Reservation Protocol-Traffic Engineering (RSVP-TE) Parameters" registry located at <http://www.iana.org/assignments/rsvp-te-parameters>. A new column in the registry is introduced by this document. This column indicates if the flag is permitted to be used in an Attribute Flags TLV carried in the ERO Hop Attributes subobject. The column uses the heading "ERO" and the registry has been updated as follows:



Bit No.	Name	Attribute Flags	Attribute Path	Attribute Resv	RRO	ERO	Reference
0	End-to-end re-routing	Yes	No	No	No	No	[RFC4920] [RFC5420] This Document
1	Boundary re-routing	Yes	No	No	No	No	[RFC4920] [RFC5420] This Document
2	Segment-based re-routing	Yes	No	No	No	No	[RFC4920] [RFC5420] This Document
3	LSP Integrity Required	Yes	No	No	No	No	[RFC4875]  This Document
4	Contiguous LSP	Yes	No	Yes	No	No	[RFC5151] This Document
5	LSP stitching desired	Yes	No	Yes	No	No	[RFC5150]  This Document
6	Pre-Planned LSP Flag	Yes	No	No	No	No	[RFC6001] This Document
7	Non-PHP behavior flag	Yes	No	Yes	No	No	[RFC6511]  This Document
8	OOB mapping flag	Yes	No	Yes	No	No	[RFC6511] This Document
9	Entropy Label Capability	Yes	Yes	No	No	No	[RFC6790]  This Document
10	OAM MEP entities desired	Yes	Yes	Yes	No	No	[RFC7260]  This Document
11	OAM MIP entities desired	Yes	Yes	Yes	No	No	[RFC7260]  This Document
12	SRLG collection Flag (TEMPORARY - registered 2014-09-11, expires 2015-09-11)	Yes	Yes	Yes	No	No	[SRLG-COLLECT] This Document

New allocation requests to this registry SHALL indicate the value to be used in the ERO column.

#### 4.4. Existing LSP Attribute TLVs

IANA manages the "Resource Reservation Protocol-Traffic Engineering (RSVP-TE) Parameters" registry located at <http://www.iana.org/assignments/rsvp-te-parameters>. The "Attributes TLV Space" registry manages the following attributes, as defined in [RFC5420]:

- o TLV Type (T-field value)
- o TLV Name
- o Whether allowed on LSP\_ATTRIBUTES object
- o Whether allowed on LSP\_REQUIRED\_ATTRIBUTES object

Per this document, IANA has added the following information for each TLV in the RSVP TLV type identifier registry.

- o Whether allowed on LSP Hop Attributes ERO subobject

The existing registry has been modified for existing TLVs as follows. The following abbreviations are used below:

LSP\_A: Whether allowed on LSP\_ATTRIBUTES object.

LSP\_RA: Whether allowed on LSP\_REQUIRED\_ATTRIBUTES object.

HOP\_A: Whether allowed on LSP Hop Attributes subobject.

T Name	LSP_A	LSP_RA	HOP_A	Ref.
1 Attribute Flags	Yes	Yes	Yes	[RFC5420] This Document
2 Service ID TLV	Yes	No	No	[RFC6060] This Document
3 OAM Configuration TLV	Yes	Yes	No	[RFC7260] This Document

#### 5. Security Considerations

This document adds a new subobject in the EXPLICIT\_ROUTE and the ROUTE\_RECORD objects carried in RSVP messages used in MPLS and GMPLS signaling. It builds on mechanisms defined in [RFC3209] and [RFC5420] and does not introduce any new security. The existing security considerations described in [RFC2205], [RFC3209], [RFC3473], and [RFC5420] do apply.

As with any RSVP-TE signaling request, the procedures defined in this document permit the transfer and reporting of functional preferences on a specific node. The mechanism added in this document does allow more control of LSP attributes at a given node. A node SHOULD check the hop attributes against its policies and admission procedures as it does with other inputs. A node MAY reject the message using existing RSVP Error Codes like "Policy Control Failure" or "Admission Control Failure". The node MAY also, depending on the specific TLV procedures, modify the requested attribute. This can reveal information about the LSP request and status to anyone with unauthorized access. The mechanism described in this document does not contribute to this issue, which can be only resolved by encrypting the content of the whole signaling message.

In addition, the reporting of attributes using the RRO can reveal details about the node that the operator wishes to remain confidential. The same strategy and policies that apply to other RRO subobjects also apply to this new mechanism. It is RECOMMENDED that domain boundary policies take the releasing of RRO hop attributes into consideration.

## 6. References

### 6.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC2205] Braden, R., Ed., Zhang, L., Berson, S., Herzog, S., and S. Jamin, "Resource ReSerVation Protocol (RSVP) -- Version 1 Functional Specification", RFC 2205, DOI 10.17487/RFC2205, September 1997, <<http://www.rfc-editor.org/info/rfc2205>>.
- [RFC3209] Awduche, D., Berger, L., Gan, D., Li, T., Srinivasan, V., and G. Swallow, "RSVP-TE: Extensions to RSVP for LSP Tunnels", RFC 3209, DOI 10.17487/RFC3209, December 2001, <<http://www.rfc-editor.org/info/rfc3209>>.
- [RFC3473] Berger, L., Ed., "Generalized Multi-Protocol Label Switching (GMPLS) Signaling Resource ReserVation Protocol-Traffic Engineering (RSVP-TE) Extensions", RFC 3473, DOI 10.17487/RFC3473, January 2003, <<http://www.rfc-editor.org/info/rfc3473>>.

- [RFC3477] Kompella, K. and Y. Rekhter, "Signalling Unnumbered Links in Resource ReSerVation Protocol - Traffic Engineering (RSVP-TE)", RFC 3477, DOI 10.17487/RFC3477, January 2003, <<http://www.rfc-editor.org/info/rfc3477>>.
- [RFC4873] Berger, L., Bryskin, I., Papadimitriou, D., and A. Farrel, "GMPLS Segment Recovery", RFC 4873, DOI 10.17487/RFC4873, May 2007, <<http://www.rfc-editor.org/info/rfc4873>>.
- [RFC4874] Lee, CY., Farrel, A., and S. De Cnodder, "Exclude Routes - Extension to Resource ReserVation Protocol-Traffic Engineering (RSVP-TE)", RFC 4874, DOI 10.17487/RFC4874, April 2007, <<http://www.rfc-editor.org/info/rfc4874>>.
- [RFC4875] Aggarwal, R., Ed., Papadimitriou, D., Ed., and S. Yasukawa, Ed., "Extensions to Resource Reservation Protocol - Traffic Engineering (RSVP-TE) for Point-to-Multipoint TE Label Switched Paths (LSPs)", RFC 4875, DOI 10.17487/RFC4875, May 2007, <<http://www.rfc-editor.org/info/rfc4875>>.
- [RFC4920] Farrel, A., Ed., Satyanarayana, A., Iwata, A., Fujita, N., and G. Ash, "Crankback Signaling Extensions for MPLS and GMPLS RSVP-TE", RFC 4920, DOI 10.17487/RFC4920, July 2007, <<http://www.rfc-editor.org/info/rfc4920>>.
- [RFC5150] Ayyangar, A., Kompella, K., Vasseur, JP., and A. Farrel, "Label Switched Path Stitching with Generalized Multiprotocol Label Switching Traffic Engineering (GMPLS TE)", RFC 5150, DOI 10.17487/RFC5150, February 2008, <<http://www.rfc-editor.org/info/rfc5150>>.
- [RFC5151] Farrel, A., Ed., Ayyangar, A., and JP. Vasseur, "Inter-Domain MPLS and GMPLS Traffic Engineering -- Resource Reservation Protocol-Traffic Engineering (RSVP-TE) Extensions", RFC 5151, DOI 10.17487/RFC5151, February 2008, <<http://www.rfc-editor.org/info/rfc5151>>.
- [RFC5420] Farrel, A., Ed., Papadimitriou, D., Vasseur, JP., and A. Ayyangarps, "Encoding of Attributes for MPLS LSP Establishment Using Resource Reservation Protocol Traffic Engineering (RSVP-TE)", RFC 5420, DOI 10.17487/RFC5420, February 2009, <<http://www.rfc-editor.org/info/rfc5420>>.

- [RFC5520] Bradford, R., Ed., Vasseur, JP., and A. Farrel, "Preserving Topology Confidentiality in Inter-Domain Path Computation Using a Path-Key-Based Mechanism", RFC 5520, DOI 10.17487/RFC5520, April 2009, <<http://www.rfc-editor.org/info/rfc5520>>.
- [RFC5553] Farrel, A., Ed., Bradford, R., and JP. Vasseur, "Resource Reservation Protocol (RSVP) Extensions for Path Key Support", RFC 5553, DOI 10.17487/RFC5553, May 2009, <<http://www.rfc-editor.org/info/rfc5553>>.
- [RFC6001] Papadimitriou, D., Vigoureux, M., Shiimoto, K., Brungard, D., and JL. Le Roux, "Generalized MPLS (GMPLS) Protocol Extensions for Multi-Layer and Multi-Region Networks (MLN/MRN)", RFC 6001, DOI 10.17487/RFC6001, October 2010, <<http://www.rfc-editor.org/info/rfc6001>>.
- [RFC6060] Fedyk, D., Shah, H., Bitar, N., and A. Takacs, "Generalized Multiprotocol Label Switching (GMPLS) Control of Ethernet Provider Backbone Traffic Engineering (PBB-TE)", RFC 6060, DOI 10.17487/RFC6060, March 2011, <<http://www.rfc-editor.org/info/rfc6060>>.
- [RFC6511] Ali, Z., Swallow, G., and R. Aggarwal, "Non-Penultimate Hop Popping Behavior and Out-of-Band Mapping for RSVP-TE Label Switched Paths", RFC 6511, DOI 10.17487/RFC6511, February 2012, <<http://www.rfc-editor.org/info/rfc6511>>.
- [RFC6790] Kompella, K., Drake, J., Amante, S., Henderickx, W., and L. Yong, "The Use of Entropy Labels in MPLS Forwarding", RFC 6790, DOI 10.17487/RFC6790, November 2012, <<http://www.rfc-editor.org/info/rfc6790>>.
- [RFC7260] Takacs, A., Fedyk, D., and J. He, "GMPLS RSVP-TE Extensions for Operations, Administration, and Maintenance (OAM) Configuration", RFC 7260, DOI 10.17487/RFC7260, June 2014, <<http://www.rfc-editor.org/info/rfc7260>>.

## 6.2. Informative References

- [OBJ-FUN] Ali, Z., Swallow, G., Filsfils, C., Fang, L., Kumaki, K., Kunze, R., Ceccarelli, D., and X. Zhang, "Resource ReserVation Protocol-Traffic Engineering (RSVP-TE) Extension for Signaling Objective Function and Metric Bound", Work in Progress, draft-ali-ccamp-rc-objective-function-metric-bound-05, February 2014.

- [RFC4990] Shiomoto, K., Papneja, R., and R. Rabbat, "Use of Addresses in Generalized Multiprotocol Label Switching (GMPLS) Networks", RFC 4990, DOI 10.17487/RFC4990, September 2007, <<http://www.rfc-editor.org/info/rfc4990>>.
- [RFC6163] Lee, Y., Ed., Bernstein, G., Ed., and W. Imajuku, "Framework for GMPLS and Path Computation Element (PCE) Control of Wavelength Switched Optical Networks (WSOs)", RFC 6163, DOI 10.17487/RFC6163, April 2011, <<http://www.rfc-editor.org/info/rfc6163>>.
- [RFC7571] Dong, J., Chen, M., Li, Z., and D. Ceccarelli, "GMPLS RSVP-TE Extensions for Lock Instruct and Loopback", RFC 7571, DOI 10.17487/RFC7571, July 2015, <<http://www.rfc-editor.org/info/rfc7571>>.
- [RSVP-TE-HOPS]  
Kern, A. and A. Takacs, "Encoding of Attributes of LSP intermediate hops using RSVP-TE", Work in Progress, draft-kern-ccamp-rsvpte-hop-attributes-00, October 2009.
- [SRLG-COLLECT]  
Zhang, F., Dios, O., Li, D., Margaria, C., Hartley, M., and Z. Ali, "RSVP-TE Extensions for Collecting SRLG Information", Work in Progress, draft-ietf-teas-rsvp-te-srlg-collect-00, December 2014.
- [WSO-SIG]  
Bernstein, G., Xu, S., Lee, Y., Martinelli, G., and H. Harai, "Signaling Extensions for Wavelength Switched Optical Networks", Work in Progress, draft-ietf-ccamp-wson-signaling-10, March 2015.

#### Acknowledgments

The authors would like to thank Lou Berger for his directions and Attila Takacs for inspiring [RSVP-TE-HOPS]. The authors also thank Dirk Schroetter for his contribution to the initial draft versions of this document.

## Authors' Addresses

Cyril Margaria (editor)  
Juniper  
200 Somerset Corporate Boulevard, Suite 4001  
Bridgewater, NJ 08807  
United States

Email: [cmargaria@juniper.net](mailto:cmargaria@juniper.net)

Giovanni Martinelli  
Cisco  
via Philips 12  
Monza 20900  
Italy

Phone: +39 039 209 2044  
Email: [giomarti@cisco.com](mailto:giomarti@cisco.com)

Steve Balls  
Metaswitch  
100 Church Street  
Enfield EN2 6BQ  
United Kingdom

Phone: +44 208 366 1177  
Email: [steve.balls@metaswitch.com](mailto:steve.balls@metaswitch.com)

Ben Wright  
Metaswitch  
100 Church Street  
Enfield EN2 6BQ  
United Kingdom

Phone: +44 208 366 1177  
Email: [Ben.Wright@metaswitch.com](mailto:Ben.Wright@metaswitch.com)

